AMERICAN JOURNAL OF HYDROPOWER, WATER AND ENVIRONMENT SYSTEMS

Technical Papers

- 06** PUMPED HYDROELECTRIC ENERGY STORAGE SYSTEMS (PHES): CHALLENGES AND PERSPECTIVES IN THE BRAZILIAN ENERGY SCENARIO
Raimundo, Danielle Rodrigues; Filho, Geraldo Lúcio Tiago
- 11** HYDRODYNAMIC BEHAVIOR ON KAPLAN TURBINES: EXPERIMENTAL METHODOLOGY FOR THE EVALUATION OF CAVITATION DEVELOPMENT BASED ON DYNAMIC MEASUREMENTS
Rivetti, Arturo L.; ANGULO Mauricio A.; LUCINO Cecilia V.; BOTERO Francisco.; LISCIA, Sergio O.
- 16** TECHNICAL AND ECONOMIC EVALUATIONS FOR DECISION-MAKING ON THE REPOWERING OF SMALL HYDROPOWER PLANTS AND THE OPTIMUM EXPLOIT OF EXISTING PLANTS IN BRAZIL
Oliveira, Marcos André
- 25** EVALUATION OF HYDROELECTRIC, WIND AND SOLAR POTENTIAL: A CASE STUDY OF EXISTING PLANTS
Filho, Wilson Pereira Barbosa; Silva, Livia Maria Leite da; Silva, Nathan Vinícius Martins da; Oliveira, Karina Aleixo Benetti de; Abreu, Anna Luisa de Oliveira; Swiatovy, Gabriel Hepp
- 33** PREDICTION OF PRESSURE PULSATION IN FRANCIS TURBINES USING RANS SOLUTION: AN APPLIED STUDY OF EFFECTS OF THE TURBULENCE MODELS, MESH, DOMAIN EXTENSION AND MULTIPHASE FLOW
Marra, João M.; Gramani, Liliana M.; Zubeldia, Luiz F.; Kaviski, Eloy

IAHR DIVISION I: HYDRAULICS
TECHNICAL COMMITTEE: HYDRAULIC
MACHINERY AND SYSTEMS

Editors in Chief

Prof. Geraldo Lucio Tiago Fº - UNIFEI
Prof. Eduard Egusquiza - UPC

Executive Editors

Prof. Carlos Martinez - UFMG
Eng. Humberto Gissoni - VOITH

Technical Editors

Prof. Regina Mambeli Barros - UNIFEI
Prof. Cecilia Lucino - UNLP

Journalist in charge

Adriana Barbosa MTb - MG 05984JP

Graphic Project/ Diagramming

Lidiane Silva

Circulation

1,000 copies

Federal University of Itajubá - UNIFEI
Av. BPS, 1303 - Bairro Pinheirinho
Itajubá - MG - Brasil - CEP: 37500-903

Catalographic card prepared by Mauá Library -
Librarian Margareth Ribeiro - CRB_6/1700

R454

American Journal of Hydropower, Water and Environment
Systems, LAWG-IAHR, v.1, 2014 - Itajubá: LAWG-
IAHR, 2015 - v.6, jan. 2018.

Trimestral,
Editors Chief: Geraldo Lúcio Tiago Filho/Eduard Egusquiza
Journalist in Charge: Adriana Barbosa - MTb_MG 05984
ISSN 2317-126X

1. Hydropower. 2. Water. 3. Environment Systems.
II. Latin American Working Group

LAWG-IAHR Executive Secretariat
Lucia Garrido Rios
latinahrsecex@gmail.com

AMERICAN JOURNAL OF HYDROPOWER, WATER AND ENVIRONMENT SYSTEMS

Editorial

Demand for electricity is increasing rapidly in Latin America. Expanding and enhancing the current power generation infrastructure is thus a major concern for the region. In that context, renewable energy is bound to play a relevant role in the coming years and hydroelectric energy especially so in view of its relatively unexploited potential, which is estimated in around 690,000 MW in the region.

Our mission is to contribute to the regional integration by means of the production of knowledge in the field of hydroelectric power generation and hydromechanical systems, with focus on technological advance and the rise of quality standards, but with an eye on the priorities of a region where, well into the XXI century, millions of people find themselves deprived of electricity. That includes the topics such as the evaluation of the development of projects of low environmental impact, the role of hydroelectric powerplants in the face of the diversification of the energy matrix as well as mini- and small-hydro projects to meet the demand of areas with no access to the electrical network.

Three symposia have been held and six editions of this Journal have been published since the creation of this, the Latin Group, in 2012. Added to that are postgraduate courses and exchange programs that are being organized at present. Mexico, Brazil, Ecuador, Colombia, Uruguay and Argentina are the most active members of the Group and it is our goal to get more involved in the future.

We firmly believe in the ability of our universities to conduct the research in the field of hydraulic turbomachinery and that this knowledge will have a beneficial impact on the policy making of our countries, whether on matters related to existing infrastructure as well as the development of long-term projects and strategies.

We understand that keeping and strengthening the link between the nations currently participating is a major challenge in the framework of a constantly evolving reality, seen reflected in the availability of economic resources, the technological tools and the swings of institutional management. May this new edition of the Journal serve as evidence that, however difficult, such challenge is achievable.

Eng. Sergio O. Liscia
Presidente Latin Group 2017-2021

ISSN 2317-126X

INSTRUCTIONS FOR AUTHORS

American Journal of Hydropower, Water and Environment Systems

A publication of Latin American Working Group of the International Association for Hydro-Environment Engineering and Research-IAHR

All papers must be submitted in English. In case the author wants to translate the article through the journal all costs for the translation will be charged on the account of the author.

1. Formatting articles

1.1. Article structure

1.1.1 Subdivision - numbered sections

Divide your article into clearly defined and numbered sections. Subsections should be numbered 1.1 (then 1.1.1, 1.1.2, ...), 1.2, etc. (the abstract is not included in section numbering). Use this numbering also for internal cross-referencing: do not just refer to 'the text'. Any subsection may be given a brief heading. Each heading should appear on its own separate line.

1.1.2 Format

All text of the manuscript must be located within a 170 mm by 252 mm rectangle of a white A4 page or within 170 mm by 240 mm for the letter format. The margins are given in Table 1. An example of the page format is given in Fig. 1

[Table 1]: Page margin for manuscripts.

Margin Position	Top	Bottom	Left	Right
Margin size (cm)	2.0	2.5	2.0	2.0

All text should be single spaced, black and in 12-point type. "Times News Roman" or a similar proportional font should be used. Total length 15 pages in Word.

The terminology given in the *IEC Technical Report for the Nomenclature of Hydraulic Machinery* is recommended.

Introduction

State the objectives of the work and provide an adequate background, avoiding a detailed literature survey or a summary of the results.

Material and methods

Provide sufficient details to allow the work to be reproduced. Methods already published should be indicated by a reference: only relevant modifications should be described.

Theory/calculation

A Theory section should extend, not repeat, the background to the article already dealt with in the Introduction and lay the foundation for further work. In contrast, a Calculation section represents a practical development from a theoretical basis.

Results

Results should be clear and concise.

Discussion

This should explore the significance of the results of the work, not repeat them. A combined Results and Discussion section is often appropriate. Avoid extensive citations and discussion of published literature.

Conclusions

The main conclusions of the study may be presented in a short Conclusions section, which may stand alone or form a subsection of a Discussion or Results and Discussion section.

References

Within the text, references should be cited in numerical order according to their order of appearance. The numbered reference citation within text should be enclosed in brackets.

After the second edition all papers must have at least one reference of the American Journal of Hydropower, Water and Environment Systems.

Example: It was shown by Prusa [1] that the width of the plume decreases under these conditions.

In the case of two citations, the numbers should be separated by a comma [1,2]. In the case of more than two references, the numbers should be separated by a dash [5-7].

List of References. References to original sources for cited material should be listed together at the end of the paper; footnotes should not be used for this purpose. References should be arranged in numerical order according to the sequence of citations within the text. Each reference should include the last name of each author followed by his initials.

(1) Reference to journal articles and papers in serial publications should include:

- last name of each author followed by their initials
- year of publication
- abbreviated title of publication in which it appears
- full title of the cited article in quotes, title capitalization
- volume number (if any) (Do not include the abbreviation, "Vol.")
- issue number (if any) in parentheses (Do not include the abbreviation, "No.")
- inclusive page numbers of the cited article (include "pp.")

(2) Reference to textbooks and monographs should include:

- last name of each author followed by their initials
- year of publication
- titles in examples may be in italic
- publisher
- city of publication
- inclusive page numbers of the work being cited (include "pp.")
- chapter number (if any) at the end of the citation following the abbreviation, "Chap."

(3) Reference to individual conference papers, papers in compiled conference proceedings, or any other collection of works by numerous authors should include:

- last name of each author followed by their initials
- year of publication
- full title of the cited paper in quotes, title capitalization
- individual paper number (if any)
- full title of the publication
- initials followed by last name of editors (if any), followed by the abbreviation, "eds."
- publisher
- city of publication
- volume number (if any) in boldface if a single number, include, "Vol." if part of larger identifier (e.g., "PVP-Vol. 254")
- inclusive page numbers of the work being cited (include "pp.")

(4) Reference to theses and technical reports should include:

- last name of each author followed by their initials
- year of publication
- full title in quotes, title capitalization
- report number (if any)
- publisher or institution name, city

Sample References

- [1] Ning, X., and Lovell, M. R., 2002, "On the Sliding Friction Characteristics of Unidirectional Continuous FRP Composites," *ASME J. Tribol.*, 124(1), pp. 5-13.
- [2] Barnes, M., 2001, "Stresses in Solenoids," *J. Appl. Phys.*, 48(5), pp. 2000-2008.
- [3] Jones, J., 2000, *Contact Mechanics*, Cambridge University Press, Cambridge, UK, Chap. 6.
- [4] Lee, Y., Korpela, S. A., and Horne, R. N., 1982, "Structure of Multi-Cellular Natural Convection in a Tall Vertical Annulus," *Proc. 7th International Heat Transfer Conference*, U. Grigul *et al.*, eds., Hemisphere, Washington, DC, 2, pp. 221-226.
- [5] Hashish, M., 2000, "600 MPa Waterjet Technology Development," *High Pressure Technology*, PVP-Vol. 406, pp. 135-140.
- [6] Watson, D. W., 1997, "Thermodynamic Analysis," *ASME Paper No. 97-GT-288*.
- [7] Tung, C. Y., 1982, "Evaporative Heat Transfer in the Contact Line of a Mixture," Ph.D. thesis, Rensselaer Polytechnic Institute, Troy, NY.
- [8] Kwon, O. K., and Pletcher, R. H., 1981, "Prediction of the Incompressible Flow Over A Rearward-Facing Step," *Technical Report No. HTL-26, CFD-4*, Iowa State Univ., Ames, IA.
- [9] Smith, R., 2002, "Conformal Lubricated Contact of Cylindrical Surfaces Involved in a Non-Steady Motion," Ph.D. thesis, <http://www.cas.phys.unm.edu/rsmith/homepage.html>

1.1.2 Essential title page information

- **Title.** Concise and informative. Titles are often used in information-retrieval systems. Avoid abbreviations and formulae where possible.
- **Author names and affiliations.** Where the family name may be ambiguous (e.g., a double name), please indicate this clearly. Indicate all affiliations with a number immediately after the author's name and in front of the appropriate address. Provide the full postal address of each affiliation, including the country name and, if available, the e-mail address of each author.
- **Author résumé.** The author must inform the graduation degree, post graduation, affiliation and email address. The résumé must not exceed 150 characters.
- **Corresponding author.** Clearly indicate who will handle correspondence at all stages of refereeing and publication, also post-publication. Ensure that e-mail address and the complete postal address are provided. Contact details must be kept up to date by the corresponding author.
- **Present/permanent address.** If an author has moved since the work described in the article was done, or was visiting at the time, a 'Present address' (or 'Permanent address') may be indicated as a footnote to that author's name. The address at which the author actually did the work must be retained as the main, affiliation address. Superscript Arabic numerals are used for such footnotes.

Abstract

A concise and factual abstract is required. The abstract should state briefly the purpose of the research, the principal results and major conclusions. An abstract is often presented separately from the article, so it must be able to stand alone. For this reason, References should be avoided, but if essential, then cite the author(s) and year(s). Also, non-standard or uncommon abbreviations should be avoided, but if essential they must be defined at their first mention in the abstract itself.

Keywords

Immediately after the abstract, provide a maximum of 6 keywords, using American spelling and avoiding general and plural terms and multiple concepts (avoid, for example, 'and',

'of'). Be sparing with abbreviations: only abbreviations firmly established in the field may be eligible. These keywords will be used for indexing purposes.

Abbreviations

Define abbreviations that are not standard in this field in a footnote to be placed on the first page of the article. Such abbreviations that are unavoidable in the abstract must be defined at their first mention there, as well as in the footnote. Ensure consistency of abbreviations throughout the article.

Acknowledgements

Collate acknowledgements in a separate section at the end of the article before the references and do not, therefore, include them on the title page, as a footnote to the title or otherwise. List here those individuals who provided help during the research (e.g., providing language help, writing assistance or proof reading the article, etc.).

Nomenclature and units

Follow internationally accepted rules and conventions: use the international system of units (SI). If other quantities are mentioned, give their equivalent in SI.

Math formulae

Present simple formulae in the line of normal text where possible and use the solidus (/) instead of a horizontal line for small fractional terms, e.g., X/Y. In principle, variables are to be presented in italics. Powers of e are often more conveniently denoted by exp. Number consecutively any equations that have to be displayed separately from the text (if referred to explicitly in the text).

Footnotes

Footnotes should be used sparingly. Number them consecutively throughout the article, using superscript Arabic numbers. Many wordprocessors build footnotes into the text, and this feature may be used. Should this not be the case, indicate the position of footnotes in the text and present the footnotes themselves separately at the end of the article. Do not include footnotes in the Reference list.

Table footnotes

Indicate each footnote in a table with a superscript lowercase letter.

Artwork

Electronic artwork

General points

- Make sure you use uniform lettering and sizing of your original artwork.
- Save text in illustrations as 'graphics' or enclose the font.
- Only use the following fonts in your illustrations: Arial, Courier, Times, Symbol.
- Number the illustrations according to their sequence in the text.
- Use a logical naming convention for your artwork files.
- Provide captions to illustrations separately.
- Produce images near to the desired size of the printed version.
- Submit each figure as a separate file.
- Pictures, graphics and images must be submitted in a JPG or GIF format with 300 dpi.

2 Conducting the Review

2.1 Originality

You might wish to do a quick literature search using tools such as Scopus to see if there are any reviews of the area. If the research has been covered previously, pass on references of those works to the editor.

INSTRUCTIONS FOR AUTHORS

2.2 Structure

Consider each element in turn: Title; Abstract; Introduction (It should describe the experiment, the hypothesis(es) and the general experimental design or method); Method; Results; Conclusion/Discussion; Language: you do not need to correct the English. You should bring this to the attention of the editor, however.

2.3 Previous Research

If the article builds upon previous research does it reference that work appropriately? Are there any important works that have been omitted? Are the references accurate?

2.4 Ethical Issues

Plagiarism: If you suspect that an article is a substantial copy of another work, please let the editor know, citing the previous work in as much detail as possible

Fraud: It is very difficult to detect the determined fraudster, but if you suspect the results in an article to be untrue, discuss it with the editor

AUTHORIZATION FOR PUBLICATION OF PAPERS LICENSE FOR USE OF INTELLECTUAL WORK (Author)

For this private instrument the AUTHOR, below signed authorizes the IAHR Latin American Working Group, to publish its work authorship, without any obligation and in exclusiveness character for the period of six months starting from the publication in the AMERICAN JOURNAL OF HYDROPOWER, WATER AND ENVIRONMENT SYSTEMS, or in another official publication of IAHR.

In case of joint authorship, the first author signs as AUTHOR, assuming before IAHR the commitment of informing the other authors of the granted license.

AUTHOR (full name in form letter):

Title of the Paper:_____

JOINT AUTHORS [full name in form letter]:_____

ADDRESS:_____

Email:_____

IAHR DIVISION I: HYDRAULICS
TECHNICAL COMMITTEE: HYDRAULIC
MACHINERY AND SYSTEMS

Scientific Committee

Alexandre Kepler
André Mesquita
Antonio Brasil Júnior
Arthur Leotta
Augusto Nelson Viana
Benedito Márcio de Oliveira
Carlos Barreira Martinez
Cecilia Lucino
Daniel Fernández
Daniel Rodriguez
Edmundo Koelle
Facundo González
Fernando Zárate
Gabriel Tarnowski
Geraldo Lucio Tiago Filho
Humberto de Camargo Gissoni
Jaime Espinoza
José Carlos Amorim
José Cataldo
José Geraldo P. de Andrade
Juan Carlos Cacciavillani
Lubienska Cristina Lucas Jaquie Ribeiro
Luciano dos Santos
Miguel Tornell
Orlando Anibal Audisio
Rafael Acedo Lopes
Regina Mambeli Barros
Ricardo Vasconcellos
Roque Zanata
Segen Farid Estefen
Sergio Galván
Sergio Liscia
Ticao Siguemoto
Victor Hidalgo
Zulcy de Souza

AMERICAN JOURNAL OF HYDROPOWER, WATER AND ENVIRONMENT SYSTEMS

Number 6

Jan 2018

Technical Papers

- 06** PUMPED HYDROELECTRIC ENERGY STORAGE SYSTEMS (PHES): CHALLENGES AND PERSPECTIVES IN THE BRAZILIAN ENERGY SCENARIO
Raimundo, Danielle Rodrigues; Filho, Geraldo Lúcio Tiago
- 11** HYDRODYNAMIC BEHAVIOR ON KAPLAN TURBINES: EXPERIMENTAL METHODOLOGY FOR THE EVALUATION OF CAVITATION DEVELOPMENT BASED ON DYNAMIC MEASUREMENTS
Rivetti, Arturo; Angulo Mauricio A.; Lucino Cecilia V.; Botero Francisco; Liscia, Sergio O.
- 16** TECHNICAL AND ECONOMIC EVALUATIONS FOR DECISION-MAKING ON THE REPOWERING OF SMALL HYDROPOWER PLANTS AND THE OPTIMUM EXPLOIT OF EXISTING PLANTS IN BRAZIL
Oliveira, Marcos André
- 25** EVALUATION OF HYDROELECTRIC, WIND AND SOLAR POTENTIAL: A CASE STUDY OF EXISTING PLANTS
Filho, Wilson Pereira Barbosa; Silva, Livia Maria Leite da; Silva, Nathan Vinicius Martins da; Oliveira, Karina Aleixo Benetti de; Abreu, Anna Luisa de Oliveira; Swiatovy, Gabriel Hepp
- 33** PREDICTION OF PRESSURE PULSATION IN FRANCIS TURBINES USING RANS SOLUTION: AN APPLIED STUDY OF EFFECTS OF THE TURBULENCE MODELS, MESH, DOMAIN EXTENSION AND MULTIPHASE FLOW
Marra, João M.; Gramani, Liliana M.; Zubeldia, Luiz F.; Kaviski, Eloy

EVALUATION OF HYDROELECTRIC, WIND AND SOLAR POTENTIAL: A CASE STUDY OF EXISTING PLANTS

¹Filho, Wilson Pereira Barbosa; ²Silva, Livia Maria Leite da; ³Silva, Nathan Vinicius Martins da; ⁴Oliveira, Karina Aleixo Benetti de; ⁵Abreu, Anna Luisa de Oliveira; ⁶Swiatovy, Gabriel Hepp

ABSTRACT

The current scenario of electricity generation in Brazil shows a matrix strongly supported by hydroelectricity. Despite being considered a clean source, strong dependence on power from a single source reduces the security of supply and reliability of a system. This was evident in the middle of 2014, when a serious water crisis was installed in the country, which affected drastically the level of reservoirs, requiring the activation of thermal plants to meet demand, causing economic losses to society given the more onerous character of this last type of generation. In this way, this article points to the insertion of renewable sources, namely, solar and wind, as an alternative for the diversification of the national energy matrix and consequent increase of the reliability of the current generation model. A case study was carried out to evaluate the wind and solar potential in two localities where there are hydroelectric plants already functioning, the Emborcação power plant and the small hydroelectric plant of Cachoeira do Brumado, located in the State of Minas Gerais, Brazil, in order to evaluate the potential of combined use of these sources, verifying their gains in terms of seasonal stability of generation. The study was based on the analysis of historical wind speed and solar radiation data recorded in the regions that were the object of study. The achieved results show significant gains in terms of increased energy availability and stabilization of the annual generation. Therefore, it is considered feasible for the state of Minas Gerais to adopt complementary generation models based on the analyzed sources, which may reduce the use of thermal plants during the drought season, which may result in a decrease of carbon emissions rates, given the cleaner generation characteristics of the analyzed sources.

KEYWORDS: Energy, renewable sources, regulatory bases, energy scenario.

1. INTRODUCTION

In the modern world, several human activities have been causing damage to the environment and natural resources. In this sense, segments linked, among others, to the civil society and the academia have sought to draw attention to the urgent need for changes in existing productive models. One of these models is the generation of energy based on fossil sources, which is at the base of the development of the current society [1] and also characterizes one of the main causes of the high emission rates of Greenhouse Gases (GHG) in the terrestrial atmosphere, one of the main damages that civilization has implied to the planet. In this way, we have sought alternatives that can meet the current needs of society by observing the conservation of resources and care for the environment. In this context, renewable energy sources appear, which may play a relevant role in meeting the demands for electricity and have GHG emission levels along their production chain, much lower than those found in sources of fossil origin [2].

According to the National Electric Energy Agency [3], the Brazilian energy matrix is represented by hydroelectricity (64.87%), thermoelectricity (26.97%), thermonuclear generation (1.31%), wind generation (8%) and solar (0.02%). It is observed,

therefore, that the generation of national electricity is strongly supported in hydroelectricity. This guarantees the country less GHG emission indices when compared to other countries that have their generation based on fossil sources, however, hydroelectricity is a resource linked to the country's rainfall regime, which has a stochastic character and seasonal variability. In this way, meeting the demand has always faced the challenge of stabilizing generation during the dry period of the year.

This situation becomes even more difficult in times of rainfall. As a coping strategy, there is a need to diversify the energy supply, where, within the context of environmental concern previously mentioned, the use of renewable sources becomes an increasingly interesting alternative. It is known that Brazil is a country with ample availability of renewable resources.

In terms of wind energy, according to the "Atlas of Brazilian Wind Potential" [4], the wind potential in Brazil reaches 143,000 MW, not including in this calculation offshore potential, and considering only heights up to 50 m. In Brazil, The Wind Atlas of Minas Gerais, completed in May 2010 by Energy Company of Minas Gerais (CEMIG), estimated the seasonal wind potential in the state, in three different dimensions, and the results indicate a potential of 10.6 GW, 24.7 GW and 39.0 GW, at heights of 50 m, 75 m and 100 m, respectively [5].

¹Civil Engineer at PUC Minas, Lawyer at University Salgado de Oliveira, MSc. in Environmental Management and Audit at European University Miguel de Cervantes, PhD student of Program Nuclear Science and Techniques of Department of Nuclear Engineering at UFMG. Environmental Analyst of State Foundation of the Environment (FEAM). Professor of Energy Engineering degree course at the PUC Minas. Curriculum Lattes: <http://lattes.cnpq.br/4241912943857821>.

²Energy Engineer and Master in Electrical Engineering from the Pontifical Catholic University of Minas Gerais. Researcher at the State Foundation of the Environment - FEAM. Curriculum Lattes: <http://lattes.cnpq.br/6661724494856451>.

³Environmental Engineering student at Centro Universitário Newton Paiva. Intern at State Foundation for the Environment in Minas Gerais - FEAM. Lattes resume: <http://lattes.cnpq.br/9519876602254143>.

⁴Student of Energy Engineering at Pontifical Catholic University of Minas Gerais - PUC Minas. Doing internship at the State Foundation of the Environment - FEAM. Conducting Voluntary Scientific Initiation with the State Foundation of the Environment - FEAM.

⁵Student of Energy Engineering at Pontifical Catholic University of Minas Gerais - PUC Minas. Conducting Voluntary Scientific Initiation with the State Foundation of the Environment - FEAM.

⁶Student of Energy Engineering at Pontifical Catholic University of Minas Gerais - PUC Minas. Conducting Voluntary Scientific Initiation with the State Foundation of the Environment - FEAM.

In Brazil, the wind regime tends to reach higher velocities in periods that coincide with low rainfall, which opens space for wind operation in a complementary way to hydroelectric dams that contributes to preserving reservoir water in drought periods [4].

In the case of solar energy, despite the different climatic characteristics observed in Brazil, it can be noticed that the annual average of global irradiation shows good uniformity, with annual averages relatively high in all of the country, varying from 4.25 kWh/m².day to 6.5 kWh/m².day. The values of global solar irradiation in any region of the Brazilian territory (1500-2500 kWh/m²) are higher than in most European Union countries, such as Germany (900-1250 kWh/m²), France (900-1650 kWh/m²) and Spain (1200-1850 kWh/m²), where projects using solar resources, some with strong government incentives, are widely disseminated [6].

In this sense, the present work shows and evaluates the complementarity of hydraulic generation with wind and solar sources as a strategy for the seasonal stabilization of energy supply. Wind and solar resources were evaluated from two localities where two hydroelectric plants are located in operation in the State of Minas Gerais, Brazil, in order to determine the annual generation profile obtained through the joint use of these three sources.

The plants analyzed were the Emborcação Hydroelectric Plant and the Small Hydroelectric Plant of Cachoeira do Brumado. The wind and solar generation were evaluated by means of the theoretical power plant design, carried out through historical series of wind velocities and values of solar radiation recorded in the regions of interest. The results allowed relevant discussions about the characteristics of each source and the strategic role that each one can play in meeting the demands for electricity.

2. MATERIALS AND METHODS

2.1. Characterization of study areas

The plants analyzed are located in the State of Minas Gerais, Brazil. The Emborcação plant is located in the Paranaíba river basin, on the river of the same name, between the States of Minas Gerais and Goiás, more specific in the cities of Catalão (Goiás) and Araguari (Minas Gerais) at the coordinates 47°59'13" W and 18°27'05" S. It has a reservoir with an area of approximately 476 km² and an installed capacity of 1.192 MW.

The Cachoeira do Brumado plant is located in the Paraíba do Sul river basin, on the Peixe river, in the city of Lima Duarte (MG), at the coordinates 43°53'19" W and 21°51'10" S. It has a reservoir with an area of approximately 0,0075 km² and an installed capacity of 2,340 MW.

Figure 1 illustrates the location of the power plants and Figure 2 shows their satellite images.

[Figure 1: Location of the plants analyzed in relation to Brazil (left) And Minas Gerais (right).]

[Figure 2: Satellite image of the Emborcação (up) and Cachoeira do Brumado (below) plants.]

2.2. Stages of the methodology

[Figure 3: Methodological flowchart.]

The methodology used was characterized by the collection of data related to the plants analyzed and the determination of an annual generation curve for the hydraulic, wind and solar sources for each of the plants. The determination of the hydraulic generation was carried out by means of the survey of the historical series of generation of the plants in question, through contact with the responsible owners or organizations. The seasonal water potential was considered as the monthly average of the historical generation raised. The solar generation was determined through the design of a theoretical plant using solar radiation data recorded for the latitude and longitude values of the plants and made available by the Reference Center for Solar and Wind Energy Sérgio Brito (CRESESB) [7].

Wind generation was determined through the design of a theoretical plant, using historical series of wind speeds recorded and made available by the National Institute of Meteorology (INMET) [8].

For sizing of wind and solar generation it was considered that each of the theoretical plants would have 100% of the installed power of the hydroelectric plant. It should be emphasized that this consideration does not take into account the economic viability of wind and solar power plants of the aforementioned size, since this is not the scope of this work. It is only a premise used for the seasonal evaluation of resources.

Figure 3 presents the steps of the methodology used that is described in detail in the next section.

3. THEORIES / CALCULATIONS

3.1. Calculations of seasonal energy generation: Wind energy

The wind potential was calculated from historical measurement series recorded by the INMET measuring stations located in the vicinity of the hydroelectric plants analyzed. With the latitude and longitude data of the plants, it was identified, through Google Earth, the closest station to each hydroelectric plant and, consequently, of the wind power plants. For the Cachoeira do Brumado plant, the Juiz de Fora station was used, and, in the case of the Emborcação plant, the Uberlândia station. The data provided by INMET are wind velocity values in m/s recorded hour per hour during the day, from 2008 to 2013. The figures provided presented, however, two inconsistencies for the purpose used here:

- The occurrence of unmeasured values;
- The fact that the measurements were carried out at 10m, inadequate height to the energy use.

In this way, it was first determined that the last year of measurements would be used for the sizing, and the values of speeds not recorded in that year were replaced by the average values recorded on the same day and hour of previous years. For the calculation of the wind speed for a height of 120 meters, suitable for the energy use, was used the Hellmann Law, given by Equation 1 [9-11]:

$$V_z = V_r \cdot \left(\frac{z}{z_r}\right)^n \quad (1)$$

Where V_z is the velocity for height z ; z is the height to be extrapolated; V_r is the velocity measured at the reference height; z_r is the reference height; n is the soil roughness coefficient [4]. A soil roughness coefficient of 0,20 (mean roughness class) was used, since it was considered that the characteristics of the areas where the hydroelectric plants are located are close to forests, live fences and shrubs.

[Table 1]: Roughness coefficients [12].

Land Type	Coefficient
Lake, ocean and smooth soil	0,10
Florests	0,15
Fences and shrubs	0,20
Small towns with few trees and shrubs	0,25
Large cities with high buildings	0,30

Wind speeds and directions show well-defined seasonal trends within their stochastic character. Therefore, in order to determine the annual energy production, a probabilistic distribution must be analyzed that can represent, as accurately as possible, the behavior of the wind regime in a region.

The Weibull distribution, (v), given by Equation 2, is classified as the most adequate to describe the wind regime of a place and represent the monthly frequencies of its velocity [12].

$$f(v) = \frac{k}{c} \left(\frac{v}{c}\right)^{k-1} e^{-\left(\frac{v}{c}\right)^k} \begin{cases} k > 0 \\ c > 1 \end{cases} \quad (2)$$

Where v is the wind speed recorded in m/s; c is the scaling factor in m/s and k is the (dimensionless) form factor. The scale factor "c" is related to the average local wind speed. On the other hand, the form factor "k" is related to the wind velocity variance around the mean velocity. The scale factor can be estimated by means of Equation 3:

$$c = \frac{v}{\left[\frac{\Gamma}{(1+\frac{1}{k})}\right]} \quad (3)$$

According to Freitas and Volpato [13] many mathematical methods can be used to estimate the parameters of the Weibull distribution, including least squares analysis for an observed distribution, methods of average wind speeds and quartiles, correlation method of "k" with the mean velocity. Still in accordance with these authors, the present work used the least squares analysis to determine the parameter "k".

This method makes an adjustment of this by minimizing the square sum of the differences between the estimated value for the probability distribution and the observed data. The observed values and the monthly probability distributions found for each plant are presented in Appendices A and B. The next step is characterized by the specification of the equipment considered in the design. The chosen wind turbine was the Enercon E-126 EP4 with rotor diameter of 127 m and power of 4,200 kW.

Figure 4 shows the power curve of this wind turbine [14].

[Figure 4: Power curve of the wind turbine.]

The number of turbines used by the plant is characterized by the ratio of turbine power to installed power at the plant. Finally, the monthly generation can be determined by means of Equation 4:

$$G_{MEE} = [\sum(W(v).P(v))] \times 720 \times n \quad (4)$$

Where G_{MEE} is the average monthly generation of wind energy; v is the wind speed in m/s; $W(v)$ is the Weibull distribution for each wind speed; $P(v)$ is the power generated by the turbine for each wind speed; 720 is the number of hours considered in the month; n is the number of turbines [15].

3.2. Calculations of seasonal energy generation: Photovoltaic energy

The potential of solar generation was obtained from information provided by CRESESB, which allows the consulting of data of average monthly solar radiation in kWh/m².day from the geographical coordinates (latitude and longitude) of the desired places. For the sizing of the solar generation the data of solar radiation in the horizontal plane for the latitudes of the analyzed plants were considered.

Note that the radiation values for the horizontal plane are lower than those observed for the radiation in the inclined plane (whose inclination angle can be considered equal to the latitude of the place, in order to optimize the performance of the systems), however, it was decided to use them, adopting a scenario of pessimistic design. In terms of conversion technology, the Canadian MAXPOWER CS6X of 325 W [16] photovoltaic module was adopted. The total number of modules used is characterized by the ratio between the installed power of the plant and the nominal power of the module used. The estimated generation curve was obtained by means of Equation 5.

$$G_{MES} = RS \times AM \times \eta \times d \quad (5)$$

Where G_{MES} is the average monthly generation of solar energy; RS are the average daily solar radiation values in the analyzed locations (in kWh/m².day); AM is the estimated total area of modules, obtained by multiplying the number of modules of the plant with the area of each module; η is the conversion efficiency of solar energy into electric energy obtained by the technology, in this case, 17% [16], and d is the number of days in the month.

4. RESULTS

[Figure 5: Evaluation of resources for the Emborcação plant. Source: INMET (2014) and CRESESB (2017).]

Figure 5 and Figure 6 show the results obtained in terms of the evaluations of the renewable resources in the locations of the plants under study. The mean monthly values of wind speed and annual daily mean values of solar radiation are presented. The wind velocity data were obtained from the Uberlândia (MG) measuring station for the Emborcação plant and the Juiz de Fora (MG) station for the Cachoeira do Brumado plant and are

related to the years 2008 to 2013. It can be seen that, in the case of Emborcação, the wind velocity values range from 2 to 4,5 m/s. The values of solar radiation vary between 4,22 to 5,44 kWh/m².day (horizontal plane). In the case of Cachoeira do Brumado, wind velocity values range from 3,5 to 6 m/s. The values of solar radiation vary between 3,11 to 5,03 kWh/m².day (horizontal plane).

[Figure 6: Evaluation of the resources for the Cachoeira do Brumado plant. Source: INMET (2014) and CRESESB (2017).]

Figure 7 and Figure 8 present the estimated generation profiles for the two plants under analysis. In the case of the Emborcação plant, the dimensioned solar generation is able to supply, annually, about 54% of the hydraulic energy produced.

Wind power is capable of supplying about 10% of this value. For the Cachoeira do Brumado plant, solar generation is able to respond annually to 37% of the hydropower, and the wind power source accounts for 40% of that value.

[Figure 7: Estimated generation profiles for the Emborcação plant.]

[Figure 8: Estimated generation profiles for the Cachoeira do Brumado plant.]

Other important results to be presented are the Capacity Factor of the plants and the area occupied by each one, as shown in Figure 9 and Figure 10. The estimation of the area occupied by the wind turbines was performed as proposed by Garbe, Mello and Tomaselli [17]. Where the authors point out that, in general, a safe distance for the installation of turbines is of the order of 10 times the diameter "D", if installed downstream, and 5 times "D" if installed next to in relation to the prevailing wind.

It is important to note that the values of the Capacity Factors were determined according to the dimensioning done for the wind source and the solar source. For the hydraulic plants, were used the data measured used in the sizing of generation. In the case of the solar photovoltaic source, the losses which such plants are subject were not considered such as: losses by mutual shadowing between rows, soiling losses, mismatch losses, losses by elevation of temperature, etc.

4. CONCLUSIONS

The present work carried out a case study of two existing plants in Minas Gerais, Brazil – Emborcação e Cachoeira do Brumado – evaluating based on their generation profiles, their seasoned complementarity with wind and solar sources. It was observed that the availability of the hydraulic and wind resources has inverse behaviors throughout the year, characterizing a final profile with complementary characteristics. The generation

based on the solar source has lower values of variability, however, presented significant values of generation.

The wind and solar sources have as characteristic their intermittent character. The utilization of large-scale power plants based on these sources requires investments in expanding storage capacities. In the case of hybrid generation (solar + wind + hydropower) it is necessary to analyze the capacity of hydroelectricity in accommodating these plants. However, this was not the objective of this work that sought to realize a evaluation of the potential energy, i.e. of the resources availability

5. BIBLIOGRAPHY

- [1] World Wind Energy Association (WWEA). "Wind energy 2050 on the shape of near 100% re grid". 2015.
- [2] Intergovernmental Panel on Climate Change (IPCC). "Renewable energy sources and climate change mitigation", Cambridge University Press, New York. 2012.
- [3] National Electric Energy Agency (ANEEL). "Generation Information Bank: Generation Capacity of Brazil". 2017.
- [4] Amarante, O. A. C., Zack, M. B. J., SÁ, A. L. "Atlas of Brazilian Wind Potential". MME, Brasília. 2001.
- [5] Energy Company of Minas Gerais (CEMIG). "Wind Atlas of Minas Gerais". Belo Horizonte, Minas Gerais, pp. 43-56, 2010.
- [6] Pereira, E. B. P.; Martins, F. R.; Abreu, S. L. De; Ruther, R. "Brazilian Atlas of Solar Energy". 2006.
- [7] Reference Center for Solar and Wind Energy Sérgio Brito (CRESESB). "Solar Potential - SunData". 2017.
- [8] National Institute of Meteorology (INMET). "Meteorological Data". CD-Room. 2014.
- [9] Đurisić, Z; Mikulović, J. "A model for vertical wind speed data extrapolation for improving wind resource assessment using WAsP." Renewable Energy. V 41. p 407 and 411. 2012.
- [10] Gualtieri, G; Sauro, S. "Comparing methods to calculate atmospheric stability-dependent wind speed profiles: A case study on coastal location". Renewable Energy. V 36. p. 2189 - 2204. 2011.
- [11] Gualtieri, G.; Secci, S. "Methods to extrapolate wind resource to the turbine hub height based on power law: A 1-h wind speed vs. Weibull distribution extrapolation comparison." Renewable Energy. V 43. p. 183-200. 2012.
- [12] Sansigolo, C. A. Distributions of Probability of Speed and Wind Power. Brazilian Journal of Meteorology. V.20, n.2, 207-214, 2005.
- [13] Freitas, T. C.; Volpato, D. C. R. "Methodology to evaluate the viability of windfarm - cases study". Proceedings of ECOS 2016 - the 29th International Conference on Efficiency, Cost, Optimization, Simulation and Environmental Impact of Energy Systems. Slovenia. 2016.
- [14] Enercon. "Enercon E-126 EP4: Overview of technical details". 2017.
- [15] Traveler, G. P; Camacho, J.R.; Andrade, D.A. Estimation of obtaining energy from the wind in a given area. Federal University of Uberlândia. 2014.
- [16] Canadian Solar. "PV Module Product Datasheet - Maxpower CS6X-315 | 320 | 325P". 2016.
- [17] Garbe, E. A.; Mello, R. de; Tomaselli, I. "Conceptual Project and Analysis of Economic Viability of Wind Power Generation Unit in Lagoa dos Patos -RS". Brazilian Journal of Energy. Vol 20. nº 1. 2014.

6. APPENDICES

A. Monthly histograms and distributions of Weibull elaborated for the Emborcação power plant.

B. Monthly histograms and distributions of Weibull elaborated for the Cachoeira do Brumado power plant