DE GRUYTER
OPEN

DOI 10.1515/pesd-2015-0030

PESD, VOL. 9, no. 2, 2015

FLOOD ANALYSIS USING HYDROLOGICAL MODELING. CASE STUDY – THE FLOOD IN THE UPPER CATCHMENT OF RIVER GERU, GALAȚI COUNTY, ROMANIA

Isabela Balan¹, Loredana Crenganiș², Claudiu Pricop³

Key words: hydrological modelling, rainfall, runoff, automatic station, radar

Abstract. This paper analyzes the flood that occurred between 11th and 13th of September 2013 in the upper catchment of the river Geru. The flood was simulated using the program Mike by DHI with the Unitary Hydrograph Method. As input data, we used the precipitation measured at the Automated Hydrological Sensor Station Cudalbi and radar precipitations. We analyzed the importance of accuracy for input data on the simulation results and the direct influence of setting the proper time steps in achieving the simulated discharge hydrograph. It appears that radar precipitations used as input data lead to a discharge hydrograph with low errors for amplitude and phase of the runoff peak.

The model can be used in the future to reproduce the floods produced in the analyzed catchment and to study the influence of physical and geographical characteristics of the hillslopes.

Introduction

To evaluate surface runoff in small catchments that are homogeneous from the physico-geographical point of view, only the processes of rainfall transformation in runoff are modeled, without the study of flood routing through the riverbeds. In the formation of network discharges during high intensity rainfalls, the most important weight is held by surface runoff (*Giurma I., 2003*). These types of hydrological models only study the surface runoff component and assume that the parameters used are constant across the entire catchment, so they are models with global parameters. The models evaluate and then integrate the net rainfall. Evaluation of net rainfall is done through a series of mathematical models (*Serban, 1989*), of

¹Eng. PhD. Stud. “Gheorghe Asachi” Technical University of Iasi, Romania, . isabela.balan@yahoo.co.uk

² Lect. PhD. “Gheorghe Asachi” Technical University of Iasi, Romania,

³Eng. PhD. Water Basinal Administration Prut-Bârlad, Romanian Waters National Administration

which the most widely used model is the model SSAR (Rocwood D., 1981). Integration of net rainfall in surface runoff is performed using a weighted function, called *unit hydrograph* (Drobot R., Giurma R., 1990). The *Unit hydrograph* function is the response of the catchment to a 1 mm net rainfall, uniformly distributed on the surface of the catchment and having the duration Δt ; it is defined by the ordinates:

$$\text{U.H.} = \{u_i = u(i, \Delta t)\}; i = 1, 2, \dots, n_u \quad (1)$$

where u_i is the ordinate of the unit hydrograph at the moment of time i ; n_u is the number of ordinates taken into account, so that:

$$\sum_{i=1}^{n_u} u_i \approx \frac{1}{T} \quad (2)$$

where T is the number of hours of time step Δt .

Mathematical modelling of rainfall-runoff process on the hillslopes, resulting in a runoff hydrograph in the closing section of a catchment can be achieved using MIKE by DHI software, which includes in the hydrological module Rainfall - Runoff, a unit hydrograph model (UHM). The UHM calculates excess rainfall and determines seepage losses by four methods:

- the method using *SCS Curve Number* parameter to characterize the analyzed catchment from the perspective of existing soil type and land use patterns.
- *the constant loss method* that sets an initial fixed value and a constant value during rainfall
- *the rational method* that describes infiltration as a proportional loss - *SCS method* which takes into account the *Curve Number*.
- *SCS method generalised*

Excess rainfall is routed to the river and transited through unit hydrograph method. The model divides the flood generating precipitation in excess rainfall (net rainfall) and losses (infiltration).

In accordance with the principle of superposition, UHM model determines a flow hydrograph corresponding to each step of computation time and excessive rain, according to the method of calculating the losses and then adds the flow generated in the previous step time. The evolution of the runoff can be described in different ways:

- *The triangular hydrograph SCS method* (Soil Conservation Service of USDA), which establish that the moment of occurrence of the maximum flow (peak hydrograph) is considered to be at half the duration of the rain, plus the duration between the nucleus of the rain and the peak of the runoff;

- *Reduced SCS hydrograph* derived from a number of unit hydrograph with different sizes and locations associated with the catchment.

- *User defined hydrograph*. The module includes the possibility of establishing dimensionless hydrographs and facilities for setting up and managing databases with runoff hydrographs basins defined a priori by the user and recorded time series of precipitation and discharges.

During rainfall, a part of the total precipitation infiltrates into the soil, than the infiltration is evaporated or routed as base flow to the river bed, a long period after the end of the rainfall. Hence in event models as the present one, it is reasonable to describe the major part of the infiltration as loss. The amount of rain actually reaching the river (the total amount of rainfall less the los) is termed the excess rainfall.

The *SCS loss method* uses the parameter *AMC* for defining the antecedent moisture condition at the start of the storm. The model operates with three different antecedent moisture conditions namely:

- AMC=1 Dry conditions close to wilting point.
- AMC=2 Average wet conditions close to field capacity.
- AMC=3 Wet conditions close to saturation.

Another parameter used by *SCS loss method* is the parameter *CN* (*Curve number*), which is a dimensionless coefficient whose value varies between 0 and 100. Setting the value of the parameter *CN* requires knowledge of certain specific factors basin: soil type, land use, hydrological conditions, antecedent moisture condition and existing impervious surfaces in the catchment.

To create a valid rainfall-runoff model using MIKE 11 software the following files are required:

- a) time series file with the extension *dfs0 containing the precipitations;
- b) file with the extension *rr11 which is the editor of the rainfall-runoff model;
- c) file with the extension *sim11 which performs the hydrological simulation.

To run a hydrological model the following steps are required:

a) In the file *rr11, in the *catchment* option, the catchment parameters (name, hydrological model and catchment area) are set and then the characteristic parameters of the model are determined.

b) Link the meteorological data (rainfall) from the *dfs0 extension file as INPUT data in the *TIME SERIES* option;

c) Create a file with the extension *dfs0 with hydrological data (significant flow hydrographs registered at the hydrometric stations in the analyzed catchment);

d) Create the simulation file *sim11 where the option *Rainfall-runoff Model* is checked, the file *rr11 is uploaded, the simulation period is set, the path and name for the *Results* are chosen, the simulation is started.

e) The *Results* can be viewed in **MIKE View**.

The model can present the net rainfall and comparison of simulated and measured runoff hydrographs and accumulated volumes for the analyzed flood.

1. Case study

1.1. The characteristics of the analyzed catchment

The model is applied to the upper basin of the river Geru located in Galati county, in the south of the area operated by the Basinal Water Administration Prut - Bârlad. The area of the river Geru catchment is 113.56 km² (river Geru - 99.52

Fig.1. Cartograme of texture soils in the catchment of river Geru

km² and river Gerușița tributary - 14.04 km²). The river Geru is a right tributary of the river Suhu. The upper catchment was chosen for study. The downstream control section is Cudalbi hydrometric station, located at 22.53 km downstream. The confluence of river Gerușița with river Geru is located 5.25 km downstream

from the spring of the river. The river Gerușița is a left tributary, with a length of 7.27 km and a 14.04 km² catchment.

The analyzed catchment is controlled by the hydrometric station located in the village Cudalbi. The daily transmitted data from the classic hydrometric station with vertical hydrometric surprise are doubled since August 2013 with hourly precipitation data from the AHSS (Automated Hydrological Sensor Station) established in the DESWAT program, implemented by the Water Basinal Administration Prut - Bârlad.

Cultivated agricultural lands occupied the largest area in the catchment Geru (45%). As follows meadows (25%), rural localities 15%, and forests (15%).

The catchment of river Geru shows very different soil types: river deposits, carbonate silts, colluvial soils, chernozem soils. Grey forest soils occur on the hillslopes and are formed of loess, sand and marl. Figure 2 presents the textural classes of soils in the catchment of river Geru.

1.2. Significant flood that occurred in September 2013

Between 11th and 13th of September in the upper catchment of river Geru large quantities of precipitation occurred. Following the rapid concentration of runoff on the hillslopes, in the reference period, the defense characteristic threshold DANGER was reached and exceeded on river Geru (Table 1):

Tab. 1. Exceedance of DANGER defense threshold at the hydrometric station Cudalbi

River	Hydrometric station	Maximum Level (cm)	Maximum Discharge (m ³ /s)	Exceedance of DANGER defense threshold (cm) /date	Maximum Hystoric Level (cm)/Year
Geru	Cudalbi	358	118	+ 88 cm On 11 th of September 2013, 23 ⁰⁰	358/2013

Rainfall that occurred between 11th and 13th of September 2013 generated a flow hydrograph with three peaks, with the following maximum discharges: 118.00 m³/s recorded on 12/09/2013 23⁰⁰, then 75.30 m³/s recorded on 13/09/2013 02²⁰, respectively 10.30 m³/s recorded on 13/09/2013 10⁰⁰. The flow hydrograph was extracted from the rating curve calculated by the Hydrology Department of the Basinal Water Administration Prut - Bârlad for the cross section of the river Geru at Cudalbi hydrometric station.

It appears that the flood that occurred 11th and 13th of September 2013 had a maximum discharge of 118.00 m³/s that is very close to the peak of the flood with a 2% probability of exceedance, which is 120.00 m³/s, established by the National Institute of Hydrology and Water Management, for the analyzed section.

1.3. Mike 11-UHM simulations performed with the use of rainfall recorded at AHSS Cudalbi

To simulate the flood that occurred between 11th and 13th of September 2013 we used the hydrological model that was built in the project "Hazard and flood risk maps for the river Bârlad catchment". The model included the river Geru and its tributary, the river Geruşița and it used the unitary hydrograph method the Rainfall – Runoff Module. The model was calibrated and validated for the flood which occurred in May 2008.

UHM parameters used in the model are shown in Figure 2.

Fig.2. Setting the parameters for the model Mike 11 - Unitary Hydrograph Method

Triangular *method* was used to draw the hydrograph and *SCS method* was used to calculate the infiltration.

Mostly clay soil and clay loam, with low infiltration are spread in the river Geru catchment. The soils are classified in the *group C* of hydrological soils. For the analyzed catchment the *CN (Curve Number)* parameter was calculated by the weighted method established in TR - 55 (*Technical Release - 55*) by the *United States Department of Agriculture*. The method is applicable to small basins and *CN* parameter is calculated as a weighted average based on land use and *CN* intermediate surface corresponding to each surface. Table 2 presents the

calculation of the weighted *CN* parameter with detail on both the river Geru and the tributary river Gerușița catchments.

Tab.2. The calculation of weighted coefficient *CN* for the catchments

Area of river Geru catchment = 99.52		Percentage of the catchment	Intermediate area – km ²	CN partial	CN x area	CN
Cultivated agricultural lands		0.45	44.784		3486.88224	
Fallow	Bare soil	0.01	0.44784	91	40.75344	
Row crops	Straight row	0.01	0.44784	88	39.40992	
	Straight row + Crop residue cover	0.02	0.89568	85	76.1328	
	Contoured & terraced	0.10	4.4784	80	358.272	
	Contoured & terraced + Crop residue cover	0.20	8.9568	77	689.6736	
Small grain	Straight row + Crop residue cover	0.10	4.4784	80	358.272	
	Contoured & terraced	0.05	2.2392	78	174.6576	
	Contoured & terraced + Crop residue cover	0.31	13.88304	77	1068.99408	
Close-seeded legumes	Contoured & terraced	0.20	8.9568	76	680.7168	
		0.15	14.928		992.712	
Forrest	Woods	0.30	4.4784	70	313.488	
	Brush	0.70	10.4496	65	679.224	
		0.15	14.928		1138.26	
Localities	Open space (lawns, parks, etc.)	0.45	6.7176	74	497.1024	
	Streets and roads - gravel	0.05	0.7464	89	66.4296	
	Residential districts	0.50	7.464	77	574.728	
Meadow		0.25	24.88	71	1766.48	71.00
CN for the river Geru catchment=74						
Area of river Gerușița catchment = 14.04			km ²			
Forrest		0.75	10.53		705.51	67.00
	Woods	0.40	4.212	70	294.84	
	Brush	0.60	6.318	65	410.67	
Meadow		0.20	2.808	71	199.368	71.00
Cultivated agricultural lands						
Row crops	Contoured & terraced + Crop residue cover	0.05	0.702	77	54.054	77.00
CN for the river Geru catchment=74						

For the initial moisture expressed by *AMC* (*Antecedent Moisture Condition*) parameter we used in first stage the value 1 specific to dry land, with humidity near the wilting coefficient. The *Lag Time* parameter (the time interval between the rain nucleus upon reaching maximum flood flow) was calculated automatically by the software by selecting the Curve Number method formula developed by NRCS (*Natural Resources Conservation Services, USDA*), when provided values for hydraulic length, slope and *CN*. The rainfall recorded by the AHSS Cudalbi with a 10 minutes time step is shown in Figure 3.

For simulation time step it was chosen the time step of 10 minutes, to coincide with rainfall recording accuracy. For the parameter *AMC* it was used the value 1 and for the parameter *area adjustment factor* it was also used the value 1. The comparison between the hydrograph of the discharges measured at AHSS Cudalbi between 11th and 13th of September 2013 and the hydrograph of discharges simulated with Mike Unitary Hydrograph Method is presented in figure 4.

Fig. 3. Precipitation recorded AHSS Cudalbi between 11th and 14th of September 2013

It is found that the maximum simulated discharge was 242.85 m³/s (on 12th of September 2013 06⁰⁰), compared to the maximum measured discharge of 118.00 m³/s (on 11th of September 2013 23⁰⁰), so the peak value is increased by 105 % and appears to show 7 hours later than the measured peak.

The simulated hydrograph does not capture the other 2 peaks recorded on 13th of September 2013, which means that there is a difference between the intensity of the rainfall produced in the catchment and the rainfall records from AHSS Cudalbi.

When using the value 0.71 for the parameter *area adjustment factor* in the setup menu for the parameters used for the simulation, it is found that the maximum simulated discharge is 120.10 m³/s (12th of September 2013 06⁰⁰) compared to the maximum measured discharge of 118.00 m³/s (11th of September 2013 23⁰⁰), so the peak value is increased by 1.8 % and appears to show 7 hours later than the measured peak. (Figure 5).

Fig.4. Discharges measured at AHSS Cudalbi and discharges simulated with Mike 11-UHM (AHSS precipitation, AMC=1, area adjustment factor=1, the simulation time step = 10 minutes)

— Discharges simulated with Mike 11-UHM
 — Discharges measured at AHSS Cudalbi

Fig.5. Discharges measured at AHSS Cudalbi and discharges simulated with Mike 11-UHM (AHSS precipitation, AMC=1, area adjustment factor=0.71, the simulation time step = 10 minutes)

— Discharges simulated with Mike 11-UHM
 — Discharges measured at AHSS Cudalbi

In the *Simulation Result* tab we used a 10 minutes time step for the initial stage of the simulation.

Figure 7 presents a comparison between the hydrograph of the discharges measured at AHSS Cudalbi between 11th and 13th of September 2013 and the hydrograph of discharges simulated with Mike 11- Unitary Hydrograph Method, in terms of value 1 for *AMC* parameter and value 1 for *area adjustment factor*.

Fig.7. Discharges measured at AHSS Cudalbi and discharges simulated with Mike 11-UHM (radar precipitation, AMC=1, area adjustment factor=1, the simulation time step = 10 minutes)

— Discharges simulated with Mike 11-UHM
 — Discharges measured at AHSS Cudalbi

It is found that the first peak of the simulated discharge was 128.25 m³/s (12th of September 2013 05⁰⁰), compared to the first peak of the measured discharge of 118.00 m³/s (11th of September 2013 23⁰⁰), so the peak value is increased by 8.7 % and appears to show 6 hours later than the measured peak.

The second peak of the simulated discharge was 89.82 m³/s (12th of September 2013 07¹⁶), compared to the second peak of the measured discharge of 75.30 m³/s (13th of September 2013 02²⁰), so the value is increased by 19 % and appears to show 5 hours later than the measured peak.

The third peak of the simulated discharge was 7.47 m³/s (14th of September 2013 16³⁰), compared to the third peak of the measured discharge of 10.30 m³/s

(13th of September 2013 10²⁰), so the value is diminished by 27 % and appears to show 30 hours later than the measured peak.

The simulated hydrograph captures the shape of the measured hydrograph with all three discharge peaks with different phase and amplitude errors. The first peak of the hydrograph is captured with acceptable error amplitude and phase.

An hourly time step was chosen for the next stage of the simulation, in order to match the time step of the recorded precipitation used as input data. The simulated discharge hydrograph obtained from the hourly simulation step is shown in figure 8, in comparison with the measured discharge hydrograph at AHSS Cudalbi.

Fig. 8. Discharges measured at AHSS Cudalbi and discharges simulated with Mike 11-UHM (radar precipitation, AMC=1, area adjustment factor=1, the simulation time step = 1 hour)

— Discharges simulated with Mike 11-UHM
 — Discharges measured at AHSS Cudalbi

It is found that the first peak of the simulated discharge was 120.72 m³/s (on 12th of September 2013 02⁰⁰), compared to the first peak of the measured discharge of 118.00 m³/s (on 11th of September 2013 23⁰⁰), so the peak value is increased by 2.3 % and appears to show 3 hours later than the measured peak.

The second peak of the simulated discharge was 85.57 m³/s (on 13th of September 2013 05⁰⁰), compared to the second peak of the measured discharge of

75.30 m³/s (on 13th of September 2013 02⁰⁰), so the value is increased by 13.7 % and appears to show 2.5 hours later than the measured peak.

The third peak of the simulated discharge was 7.04 m³/s (on 14th of September 2013 13⁰⁰), compared to the third peak of the measured discharge of 10.30 m³/s (on 13th of September 2013 10²⁰), so the value is diminished by 31% and appears to show 26.5 hours later than the measured peak.

The comparison between the results obtained with 10 minutes time step and hourly time step highlights that the amplitude errors are smaller when the model uses for simulation the same time step for data input and results. However, phase errors remain at the same value, offset from the actual moments of the maximum discharges measured at AHSS Cudalbi.

Conclusions

This paper analyzes the flood that occurred in the upper catchment of the river Geru between 11th and 13th of September and the simulation results obtained with the use of MIKE 11 – Unitary Hydrograph Method. Precipitation measured by AHSS Cudalbi and radar precipitation were used as input data.

Different time steps for the simulation results were used, in order to analyze the importance of accuracy of the input data on the simulation results and the direct influence of setting the time steps in achieving a close match of the simulated discharge hydrograph with the measured discharge hydrograph.

It appears that the hydrological modeling that used radar precipitation as data input, leads to a discharge hydrograph with low amplitude and phase errors, compared to the measured discharge hydrograph.

The model can be used in the future to reproduce the floods in the analyzed catchment and to study the influence of physical and geographical characteristics of hillslopes.

The results obtained by hydrological modeling can be used as input in hydraulic modeling. Hydraulic modeling and the drawing of flood maps are performed in order to predict the development of a high risk flood event, obtain the potentially flooded areas, the water depth in certain locations on the analyzed river sector.

References

- Alexandrescu (cas. Chevereșan), M.**(2010), *Teză de doctorat – Gestiunea cantitativă a resurselor de apă în bazinul hidrografic Ialomița*, Universitatea Tehnică de Construcții București – Facultatea de Hidrotehnică
- Apostol, A.,** (2011), *Teză de doctorat – Modelarea scurgerii lichide și solide în bazine hidrografice cu activități agrosilvice, aplicații în prognoza hidrologică*, Universitatea Tehnică de Construcții București – Facultatea de Hidrotehnică

- Bîrsan, M.V.**, (2010), *Teză de doctorat - Modelarea proceselor fizice de tip precipitație-scurgere pentru prognoza în timp real a viiturilor*, Universitatea din București – Facultatea de Fizica – Școala Doctorala
- Crăciun, I., Giurma, C.-R.**, (2014), *Hidrologie specială - Aplicații*, Ed. Performantica, Iași
- Ioniță, F.**, (2011), *Teză de doctorat – Formarea viiturilor și delimitarea zonelor inundabile în bazine hidrografice*, Universitatea Tehnică de Construcții București – Facultatea de Hidrotehnică
- Kirkby, M.**, (1971) , *Hillslope process – response models based on the continuity equation. In Slopes form and processes* Instit. British Geography Specifications Pub. No. 3: 15 – 30
- Natural Resources Conservation Services** USDA, (1986), *National Engineering Handbook-Part 630 Hydrology* , chapter 7-12
- Natural Resources Conservation Services** USDA, (1986), *Urban Hydrology for Small Watersheds-Technical Release 55*
- *** (2003), *MIKE 11 – A modelling system for rivers and channels – User guide* – DHI – Agern Alle 5, DK-2970 Horsholm, Denmark
- *** (2003), *MIKE 11 – A modelling system for rivers and channels – Short introduction tutorial* - DHI– Agern Alle 5, DK-2970 Horsholm, Denmark
- *** (2006), *MIKE 11 Users Manual* - DHI water and environment, DK-2970 Horsholm, Denmark DHI
- *** (2011), *MIKE 11 Reference Manual* - DHI water and environment, DK-2970 Horsholm, Denmark DHI
- Administrația Bazinală Prut – Bârlad**, (2014), *Raport anual de sinteză privind activitatea de urmărirea comportării construcțiilor din patrimoniul Administrației Bazinale de Apă Prut – Bârlad în anul 2013*