ISSN 1313 - 8820 (print)
ISSN 1314 - 412X (online)
Volume 9, Number 1
March 2017

AGRICULTURAL SCIENCE AND TECHNOLOGY

2017

An International Journal Published by Faculty of Agriculture,
Trakia University, Stara Zagora, Bulgaria

Editor-in-Chief

Georgi Petkov
Faculty of Agriculture
Trakia University, Stara Zagora
Bulgaria
E-mail: gpetkov@af.uni.sz.bg

Co-Editor-in-Chief

Dimitar Panayotov
Faculty of Agriculture
Trakia University, Stara Zagora
Bulgaria

Editors and Sections

Genetics and Breeding

Tsanko Yablanski (Bulgaria)
Atanas Atanasov (Bulgaria)
Svetlana Georgieva (Bulgaria)
Nikolay Tsenov (Bulgaria)
Max Rothschild (USA)
Ihsan Soysal (Turkey)
Horia Grosu (Romania)
Stoicho Metodiev (Bulgaria)
Bojin Bojinov (Bulgaria)

Nutrition and Physiology

Nikolai Todorov (Bulgaria)
Peter Surai (UK)
Ivan Varlyakov (Bulgaria)
George Zervas (Greece)
Vasil Pirgozliev (UK)

Production Systems

Radoslav Slavov (Bulgaria)
Dimitar Pavlov (Bulgaria)
Bogdan Szostak (Poland)
Banko Banev (Bulgaria)
Georgy Zhelyazkov (Bulgaria)

Agriculture and Environment

Martin Banov (Bulgaria)
Peter Cornish (Australia)
Vladislav Popov (Bulgaria)
Tarek Moussa (Egypt)

Product Quality and Safety

Stefan Denev (Bulgaria)
Vasil Atanasov (Bulgaria)
Roumiana Tsenkova (Japan)

English Editor

Yanka Ivanova (Bulgaria)

Scope and policy of the journal

Agricultural Science and Technology /AST/ – an International Scientific Journal of Agricultural and Technology Sciences is published in English in one volume of 4 issues per year, as a printed journal and in electronic form. The policy of the journal is to publish original papers, reviews and short communications covering the aspects of agriculture related with life sciences and modern technologies. It will offer opportunities to address the global needs relating to food and environment, health, exploit the technology to provide innovative products and sustainable development. Papers will be considered in aspects of both fundamental and applied science in the areas of Genetics and Breeding, Nutrition and Physiology, Production Systems, Agriculture and Environment and Product Quality and Safety. Other categories closely related to the above topics could be considered by the editors. The detailed information of the journal is available at the website. Proceedings of scientific meetings and conference reports will be considered for special issues.

Submission of Manuscripts

There are no submission / handling / publication charges.

All manuscripts written in English should be submitted as MS-Word file attachments via e-mail to editoffice@agriscitech.eu. Manuscripts must be prepared strictly in accordance with the detailed instructions for authors at the website www.agriscitech.eu and the instructions on the last page of the journal. For each manuscript the signatures of all authors are needed confirming their consent to publish it and to nominate on author for correspondence.

They have to be presented by a submission letter signed by all authors. The form of the submission letter is available upon request from the Technical Assistance or could be downloaded from the website of the journal. Manuscripts submitted to this journal are considered if they have submitted only to it, they have not been published already, nor are they under consideration for publication in press elsewhere. All manuscripts are subject to

editorial review and the editors reserve the right to improve style and return the paper for rewriting to the authors, if necessary. The editorial board reserves rights to reject manuscripts based on priorities and space availability in the journal.

The journal is committed to respect high standards of ethics in the editing and reviewing process and malpractice statement. Commitments of authors related to authorship are also very important for a high standard of ethics and publishing. We follow closely the Committee on Publication Ethics (COPE), <http://publicationethics.org/resources/guidelines>

The articles appearing in this journal are indexed and abstracted in: DOI, EBSCO Publishing Inc. and AGRIS (FAO).

The journal is accepted to be indexed with the support of a project № BG051PO001-3.3.05-0001 "Science and business" financed by Operational Programme "Human Resources Development" of EU. The title has been suggested to be included in SCOPUS (Elsevier) and Electronic Journals Submission Form (Thomson Reuters).

The journal is freely available without charge to the user or his/her institution. Users can read, download, copy, distribute, print, search, or link to the full texts of the articles, or use them for any other lawful purpose, without asking prior permission from the publisher or the author.

This issue is printed with the financial support by Contract No DNP 05-21/20.12.2016, financed from Fund 'Scientific Research' grant Bulgarian scientific Periodicals.

Address of Editorial office:

Agricultural Science and Technology
Faculty of Agriculture, Trakia University
Student's campus, 6000 Stara Zagora
Bulgaria
Telephone: +359 42 699330
+359 42 699446
www.agriscitech.eu

Technical Assistance:

Nely Tsvetanova
Telephone: +359 42 699446
E-mail: editoffice@agriscitech.eu

ISSN 1313 - 8820 (print)
ISSN 1314 - 412X (online)

Volume 9, Number 1
March 2017

AGRICULTURAL SCIENCE AND TECHNOLOGY

2017

An International Journal Published by Faculty of Agriculture,
Trakia University, Stara Zagora, Bulgaria

Animal hygiene assessment of microclimate in semi open free-stall barns for dairy cows

D. Dimov^{1*}, Tch. Miteva¹, I. Marinov², Zh. Gergovska², T. Penev¹, A. Enchev³

¹Department of Applied Ecology and Animal Hygiene, Faculty of Agriculture, Trakia University, 6000 Stara Zagora, Bulgaria

²Department of Animal Science – Ruminants and Dairy Farming, Faculty of Agriculture, Trakia University, 6000 Stara Zagora, Bulgaria

³Enfo Agro LTD, Bulgaria

(Manuscript received 2 December 2016; accepted for publication 16 February 2017)

Abstract. The study was conducted in three semi open free-stall barns (B1, B2, and B3) for dairy cows with capacities for 120, 120 and 500 cows, respectively, from three different dairy farms (F-1, F-2 and F-3), situated in Central Southern Bulgaria. The investigated farms had the same production system – loose housing in semi open free-stall dairy barn. For each of the farms the main microclimatic parameters – air temperature, relative humidity and speed of airflow were recorded twice a month at 10.00 h, 12.00 h, 14.00 h, 16.00 h and 18.00 h of the day inside the barns in three main technological zones - above the stalls, above manure and feed alleys and outside the buildings. It was found that: a) Microclimatic parameters (air temperature, air relative humidity and speed of airflow) in technological zones (above the stalls, the manure and feed alleys) of three semi open free-stall dairy barns meet the animal hygienic requirements for all seasons according to Regulation No. 44 (2006). Exceptions are some values of relative humidity in B1 and B2 in the spring, and in B1 in winter and summer, which are lower than the minimum humidity (50%) according to the standard. b) The investigated barns are characterized with poor insulation and do not provide enough isolation from the external ambient temperatures. With the exception of winter, the temperature of the air inside the buildings was lower than that outside, with minor differences for all seasons. The fans in the barns have no effect on the inside air temperature, especially in summer. There was a risk of higher temperatures mainly during the summer period. c) There is no significant difference between the average temperatures, air humidity and speed of airflow in all technological zones of the investigated barns. d) The largest and statistically significant is the difference between the relative air humidity outside and inside the building in Farm 3, followed by buildings in Farm 1 and 2, where the differences are smaller and statistically insignificant. e) Factor analysis revealed a significant effect: of the farm on temperature in the different technological zones in the barns ($P < 0.05-0.01$); of the farm in the zones of manure and feed alleys ($P < 0.001$) and less effect in the zone of stalls ($P < 0.05$) on speed of airflow, the factor season on speed of airflow in all zones ($P < 0.001$), the time of recording in the zone of manure alley on speed of airflow ($P < 0.05$); the farm, season and time of recording on the humidity in the three technological zones ($P < 0.001$).

Keywords: barns, dairy cows, air temperature, relative humidity, speed of airflow

Introduction

Controlling the living environment, according to animal hygienic requirements for rearing dairy cows is a prerequisite for higher productivity, improved feed efficiency, positively affects the reproductive performance and health status, providing better comfort to animals (Harner, 2008; Mijic et al., 2007). One of the main factors with direct influence on the cattle welfare is the microclimate, the main indicators of which are air temperature, relative humidity and speed of airflow (Petkov, 1977; Brouček et al., 2006). According to many authors, the high temperature and humidity in combination with high intensity of solar radiation and low speed of airflow may exceed the stress limit of farm animals, which leads to losses of productivity and even death of some of them (Lefcourt and Adams, 1996; Hahn and Mader, 1997; Mader et al., 1999; Gaughan et al., 2000).

Over the last decades in dairy farming, not only in our country, a tendency of switching from tie to loose housing of dairy cows was observed. The loose housing production systems were preferred to reduce labor input by increasing the size of herds and to meet the requirements for animal welfare. In order to minimize investment costs these buildings have open front walls or even are open from all sides (Erbez et al., 2010). As a result, the cows are exposed to a wide range of climatic conditions, which in some cases can become extreme. This raises the question, whether this type of buildings

provide the perfect environment for living and rearing of animals (Zähner et al., 2004). Given the trend not only in our country but also worldwide, such studies are needed, especially in the time of global warming and climatic changes (Cederberg et al., 2012). This is a serious challenge for dairy farming with regard to its productivity and economic efficiency.

The aim of this study was to determine and make animal hygiene assessment of the main microclimate parameters - air temperature, relative humidity and speed of airflow in different technological areas in semi open free-stall dairy barns and their relation with the same climatic parameters outside the buildings.

Material and methods

Study area

The study was performed for one year in three dairy farms from three different regions of the central part of Southern Bulgaria. In the three farms cows are reared in the same production system - loose housing in semi open free-stall dairy barns.

Farm 1. The farm is located on the territory of Dimitrovgrad Municipality, Haskovo District. Its capacity is for 300 dairy cows. Object of study was a building – B1 (60.00/18.00 m, actual cubic capacity 5205.6 m³) for 120 dairy cows. The longitudinal walls of the building are open, equipped with polyethylene blinds that descend

* e-mail: dimo_1988@abv.bg

automatically under adverse weather conditions (at a speed of airflow over 4 m/s in rain and snowfall and air temperatures below 2 °C). The roof construction is of metal sheets without thermal insulation. In the building there are three rows of stalls, two manure alleys (each with a width of 4.00 m) and one feed alley (width of 4.00 m). The building was equipped with 5 fans (0.55 kW, capacity 60000 L/h) located above the manure alleys. The fans start to work automatically at air temperature over 28 °C.

Farm 2. The farm, with capacity for 500 dairy cows, is located on the territory of Parvomay Municipality, Plovdiv District. Object of study was a building – B2 (66.00/18.00m, actual cubic capacity 5265.6 m³) for 120 dairy cows. The longitudinal walls and the roof construction of that building were similar to B1. In the building there are three rows of stalls, two manure alleys (each with a width of 3.80 m) and one feed alley (width of 4.80 m). The building was equipped with 8 fans (0.55 kW, capacity 17000 L/h) located in two rows above the manure alleys. They start to work manually at the discretion of the seers.

Farm 3. The farm has capacity of 1300 dairy cows and it's located on the territory of Chirpan Municipality, Stara Zagora District. Object of study was a building – B3 (90.00/45.00m, actual cubic capacity 29 362.5 m³) for 500 dairy cows. The longitudinal walls and the roof construction of that building were similar as in B1 and B2. There are 2 feed alleys (one central 5.30 m and one along the longitudinal wall 3.60 m), 5 manure alleys (3.60 m) and 7 rows of free-stalls in the building. The building was equipped with 15 fans located above the stalls which operate automatically according to environmental conditions.

Microclimate/climatic parameters

The following microclimate/climatic parameters were measured twice a month, at a height 1.00 m from the floor/ground surface, at 10.00 h 12.00 h, 14.00 h, 16.00 h and 18.00 h of the day – air temperature, relative humidity and speed of airflow: inside the buildings, in the three main technological zones - above the stalls, above the manure and feed alleys; outside at 10.00 m distance from the buildings.

Methods for microclimate/climatic parameters measured

Air temperature and air humidity were measured by „Lutron MCH-383SDB” with a range of temperature from 0 to 50 °C and for humidity from 10% to 90%. The speed of the airflow was measured by „Lutron EM-9300SD” with range between 0.1 m/s and 25 m/s. Measuring instruments for microclimate indicators were powered by using the energy station LS-856.

Statistical analysis

For basic statistical data processing software package MS Excel and for obtaining average values, errors and analysis of variance, the relevant modules of STATISTICA of StatSoft (Copyright 1990-1995 Microsoft Corp.) were used.

For evaluation of the impact of the factors the following model was used:

$$Y_{ijkl} = \mu + F_i + S_j + H_k + F*S_{ij} + F*H_{ik} + S*H_{jk} + F*S*H_{ijk} + e_{ijkl}$$

where Y_{ijkl} is the dependent variable (temperature, humidity and speed of airflow); μ is the population average; F_i is the fixed effect of the farm; S_j is the fixed effect of the season of measurement; H_k is the fixed effect of the hour of measurement during the day; $F*S_{ij}$ is interactions effect of the farm and the season; $F*H_{ik}$ is interactions effect of the farm and the time of measurement; $S*H_{jk}$ is the interactions effect of the season and the time of measurement; $F*S*H_{ijk}$ is interactions effect of the farm, the season and time of measurement and e_{ijkl} is the effect of uncontrolled factors (the error).

By analysis of variance (ANOVA) for the model are obtained by

classes of fixed factors least squares means (LSM).

Results and discussion

Climatic parameters in the areas of the investigated dairy farms

The farms are relatively distant from one another, which was a prerequisite for the existence of some differences in climatic conditions of the territory where they are located. The climate of the area of Farm 1 is transitional continental to Mediterranean. Farm 2 falls near the mountainous area that was characterized by cool summer (in recent years there were many hot days) and longer winters with very cold days. The climatic conditions in the municipality where Farm 3 is located are influenced by the Balkan Mountains from the North and the Rhodope mountains from the South, which provides protection from winds.

The presented on Table 1 average values for the main climate indicators by location of farms and by season of recording, show that the differences in average temperatures for the various seasons between locations of the three farms were within the range of 2-3 °C. With the greatest deviation was the average daily temperature for autumn in Farm 3 – 21.8 °C versus 17.7 °C and 17.7 °C for the other two farms. These differences, however, were not statistically significant because of the greater variation of the parameter values. The same trend was reported for winter for the location of Farm 3, the average daily temperature was the highest 9.7 °C versus 8.8 °C and 6.7 °C for the locations of the other two farms, as the difference between the temperature in the locations of Farms 1 and 3 was statistically significant at $P < 0.05$.

In terms of speed of airflow, a statistically significant effect of the location of the farm was not reported, although for spring and winter a considerable difference in the speed by location of the farms was observed. A statistically significant difference was established only in spring between the locations of Farms 2 and 3. The difference was larger for the location of Farm 1 (0.28m/s) compared to the other two farms (0.1 m/s and 0.18 m/s), but due to the wide variation these differences were not statistically significant. For the summer in the locations of the three farms, lower than the recommended values (Regulation No. 44, 2006), were recorded, which combined with high air temperatures in the summer was a prerequisite for the occurrence of heat stress among the cows. In this regard Brügemann et al. (2012) reported that solar radiation and wind speed were not of great importance for cows reared year-round in premises.

Air humidity values were significant and consequential differences, particularly between the locations of Farms 1 and 3. The location with the lowest air humidity (below 50%) for almost all seasons was the one of Farm 1, respectively for spring 38.2% = 38.2%, for summer - 45.1% and for winter - 46.9%, with the exception of autumn - 59.1% (Table 1).

In summary, it can be said that the location of Farm 1 is characterized by higher temperature in summer and lower in winter, with more windy conditions during most of the seasons and with a lower humidity in comparison with the locations of the other two farms.

Microclimatic parameters in the barns of the investigated dairy farms

Air temperature. The results for average daily temperatures in different technological zones of the investigated barns from the three farms show that values vary within narrow ranges by technological zones for a barn and by seasons (Table 2). By seasons much smaller

Table 1. Climatic parameters values by farms and seasons

Farm	n	Air temperature		Speed of airflow		Air humidity	
		x ± SE	SD	x ± SE	SD	x ± SE	SD
Summer							
Farm 1	25	29.6±0.67**	3.35	0.31±0.07	0.36	45.1±2.21 ^a	11.03
Farm 2	25	27.8±0.89	7.89	0.21±0.04	0.18	52.5±2.41 ^a	12.04
Farm 3	25	28.8±0.53***	2.63	0.30±0.05*	0.27	50.9±1.85***	9.27
Autumn							
Farm 1	20	17.7±1.69	7.59	0.26±0.04***	0.17	59.1±3.46	15.47
Farm 2	20	17.7±1.76	7.89	0.21±0.02***	0.10	60.3±3.39	15.14
Farm 3	15	21.4±1.97	7.63	0.26±0.09	0.33	59.8±5.74	22.24
Winter							
Farm 1	15	6.7±0.99 ^a	3.86	0.37±0.08***	0.30	46.9±2.80 ^a	10.83
Farm 2	15	8.8±0.71	2.75	0.40±0.11**	0.44	53.9±4.49	17.40
Farm 3	15	9.7±0.91 ^a	3.52	0.23±0.04**	0.17	57.0±3.41 ^a	13.21
Spring							
Farm 1	10	23.9±1.27	4.01	0.28±0.09*	0.30	38.2±2.23 ^a	7.04
Farm 2	10	24.9±0.70*	2.22	0.10±0.00 ^a	0.00	40.6±2.28*	7.20
Farm 3	10	24.6±1.06	3.35	0.18±0.03 ^{a*}	0.10	45.2±1.81 ^{a***}	5.72

Between farms marked with the same letter by seasons a statistically significant difference - $P < 0.05$ was reported. With asterisks is marked the statistical significance of differences between the reported climatic indicators for the location and the microclimatic indicators inside the buildings of the farms (in the zone of stalls). * - significant at $P < 0.05$; ** - significant at $P < 0.01$; *** - significant at $P < 0.001$; ns - no significant effect

Table 2. Average daily temperatures (°C) in different technological zones of the investigated barns by seasons

Barn	n	Free-stalls		Manure alley		Feed alley		
		x ± SE	SD	x ± SE	SD	Number	x ± SE	SD
Summer								
B 1	150	27.4±0.21 ^{ab}	2.55	27.3±0.21 ^{ab}	2.63	75	27.5±0.29 ^{ab}	2.54
B 2	250	26.6±0.23 ^{ac}	3.69	26.5±0.23 ^{ac}	3.59	125	26.3±0.31 ^a	3.47
B 3	250	25.8±0.16 ^{bc}	2.59	25.9±0.18 ^{bc}	2.80	125	26.1±0.22 ^b	2.51
Autumn								
B 1	120	16.3±0.48 ^a	5.25	16.1±0.49 ^a	5.32	60	16.6±0.79 ^a	6.15
B 2	200	16.5±0.43 ^b	6.09	16.4±0.43 ^b	6.08	100	16.1±0.56 ^b	5.82
B 3	150	19.1±0.48 ^{ab}	5.82	19.1±0.49 ^{ab}	6.03	75	19.2±0.63 ^{ab}	5.49
Winter								
B 1	90	7.1±0.33 ^{ab}	3.14	7.2±0.32 ^{ab}	3.05	45	7.1±0.46 ^{ab}	3.08
B 2	150	8.7±0.16 ^{ac}	1.92	8.7±0.17 ^{ac}	2.04	75	8.4±0.23 ^{ac}	1.96
B 3	150	9.8±0.21 ^{bc}	2.61	9.6±0.22 ^{bc}	2.74	75	9.8±0.32 ^{bc}	2.73
Spring								
B 1	60	21.6±0.45 ^a	3.49	21.7±0.45 ^a	3.47	30	21.6±0.66 ^a	3.59
B 2	100	23.2±0.24 ^{ab}	2.42	23.0±0.24 ^{ab}	2.42	50	23.0±0.31 ^{ba}	2.20
B 3	100	21.5±1.45 ^b	14.4	21.5±0.34 ^b	3.38	50	21.9±0.41 ^b	2.88

B1 is investigated barn in Farm 1, B2 – in Farm2 and B3 - in Farm 3, respectively;

Statistically significant difference by seasons between the farms marked with the same letter - $P < 0.05$

are the fluctuations in temperatures between the three technology areas in the same building than between buildings of the surveyed farms. The lowest were the temperatures in almost all technological zones for spring, autumn and winter in B1. Here, however, the

highest summer temperatures were measured. For Farm 3 it can be said that it had the most favorable temperatures inside the building - the lowest in summer and the highest in winter and autumn. This was mainly due to the similar trend reported for the climatic indicators for

the location of this farm, not to a better insulation of the building.

Cows prefer relatively cool environment. The optimal temperature range in the premises of the high-productive dairy cows is between -5 and +15°C. Perissinotto et al. (2006) indicated that thermoneutral zone in lactating cows is within 4 to 26°C. It should be borne in mind that the increase in milk yield from a cow with 10 kg per day leads to a reduction of heat stress threshold by 5°C (Berman, 2005). Lactating, high productive cows have a lower critical temperature than -30°C (van Eerdenburg, 2013). This means that at a temperature higher than -30°C they will not need additional nutrition to maintain their body temperature (Jara et al., 2016).

When comparing this information with the data generated by us (Table 2) it can be seen that the established temperatures are within the thermoneutral zone of the cows in all buildings for all seasons. Exceptions are buildings 1 and 2, where in summer the temperatures slightly exceed the upper limit, thus the cows are exposed to adverse influence of the thermal stress.

According to Bulgarian legislation (Regulation No. 44, 2006), the optimum temperature in the living area of cows must be within 10 to 15°C (min 5°C and max 28°C). The established temperatures in the studied buildings do not deviate from the limit values in the standard. Bulgarian norms for minimum and maximum temperature in buildings for cows are different from those recommended by other authors. This difference indicates the need to review these figures in accordance with the changed requirements of the animals according to their productivity, genetic traits, etc.

There were no significant differences between the average daily temperatures recorded in the different technological zones - above the stalls, above the manure and feed alleys in the barns from the three farms for all seasons. The recorded temperatures over technological zones were higher in the summer, followed by spring, autumn and winter. During the summer at high daytime temperatures in barns, the fans positioned above manure alleys in B1 and B2 and above the stalls in B3, were running, but that did not affected air temperatures. Probably, the reason for this was the improper orientation of the direction of the fans airflow, which have only led to unnecessary energy costs without achieving the desired cooling effect in the areas of the technological zones in the buildings.

There were statistically significant differences between the values of outside air temperature and the temperature inside the barns only for the summer at Farms 1 and 3 and for spring at Farm 3. For the other seasons the differences were minimal and statistically insignificant. The biggest differences between inside and outside

temperatures were restarted in the spring - up to 3.1°C, while the smallest they were for the winter - about 1°C. The lowest difference between indoor and outdoor temperature was in March (0.01°C) and the highest in October (3.48°C). This meant that this type of buildings do not provide any isolation from the outside temperatures of the living environment of the dairy cows.

The buildings for cows with open sidewalls as in our case have maximum air ventilation, but do not maintain a significant difference in temperature between inside and outside the buildings. Such a conclusion is made by Erbez et al. (2010) as well, who established that there was no significant difference in the monthly temperatures inside and outside the buildings.

From the analysis of variance presented on Table 3, a significant effect of the farm on the temperature in the different technological zones by barns was reported ($P < 0.05$ and $P < 0.01$). This effect could be both of climatic and technological nature. A significant effect of the season ($P < 0.001$) and time of recording during the day ($P < 0.001$) was reported as well as of the combined factor „farm and season” ($P < 0.001$) and „season and time of recording” ($P < 0.001$), without the temperature above the feed alley.

The variation in air temperature by technological zone of stalls in buildings by seasons and time of recording during the day for the three farms is presented in Figure 1. Since significant differences in average daily temperatures in the three technological zones by seasons were not found, we present only the variation for the zone of stalls by time of recording of the temperature. This also largely determines the comfort of cows and their desire to rest in stalls.

The variation in temperature in the zone of stalls in B1 from Farm 1 for both summer and winter was with the greatest deviation compared to the other two farms – Farm 1 and Farm 2. In the summer almost throughout the day the temperatures were high, reaching 29°C at noon, and even in the morning not falling below 25°C. Conversely, here, in the winter the lowest temperatures were reported which in the morning and evening fell almost to 6°C and at noon rose to 9°C (Figure 1). Farm 3 was with the most favorable temperature variation at different hours during the day.

The presented variation in temperature during the day by seasons and farms showed no risk of temperatures below the lower limit of the thermoneutral zone in all three farms. There was a risk of higher temperatures mainly during the summer period inside the buildings, resulting in risk of heat stress and negative impact on productivity and animal welfare.

During the last decades, the number of days with extremely

Table 3. Analysis of variance for the influence of the controlled factors on average daily temperatures in the different technological zones inside the buildings

Sources of variation	Degrees of freedom	Free-stalls			Manure alley			Feed alley		
	(n – 1)	MS	F	P	MS	F	P	MS	F	P
Total for the model	59	1475.8	113.41***		1483.78	112.18***		738.66	55.62***	
Farm	2	105.0	8.06***		108.4	8.19***		75.6	5.69**	
Season	3	26431.8	2031.15***		26431.5	1998.38***		13298.5	1001.34***	
Time of recording	4	712.1	54.72***		775.7	58.64***		329.0	24.77***	
Farm*Season	6	234.8	18.04***		211.1	15.96***		114.2	8.60***	
Farm*Time of recording	8	11.3	0.87- ns		15.1	1.14- ns		2.5	0.19- ns	
Season*Time of recording	12	43.5	3.34***		49.1	3.71***		19.4	1.46- ns	
Farm*Season	24	16.8	1.29- ns		15.0	1.13- ns		8.6	0.65- ns	
Error	1710	13.0			13.2			13.3		

* - significant at $P < 0,05$; ** - significant at $P < 0,01$; *** - significant at $P < 0,001$; ns - no significant effect

Figure 1. Air temperature above the stalls in the investigated barns by seasons and time of recording during the day

Table 4. Average daily speed of airflow (m/s) in different technological zones of the investigated barns by seasons

Barn	n	Free-stalls		Manure alley		Feed alley		
		x ± SE	SD	x ± SE	SD	Number	x ± SE	SD
Summer								
B 1	150	0.23±0.019 ^a	0.24	0.37±0.034 ^{ab}	0.41	75	0.24±0.042 ^{ab}	0.37
B 2	250	0.16±0.009 ^{ab}	0.15	0.22±0.016 ^{ac}	0.26	125	0.14±0.008 ^{ac}	0.09
B 3	250	0.20±0.015 ^b	0.24	0.13±0.008 ^{bc}	0.13	125	0.12±0.007 ^{bc}	0.08
Autumn								
B 1	120	0.11±0.003 ^{ab}	0.03	0.11±0.002 ^a	0.03	60	0.13±0.009	0.07
B 2	200	0.10±0.001 ^{ac}	0.02	0.11±0.003	0.04	100	0.13±0.006	0.06
B 3	150	0.19±0.024 ^{bc}	0.30	0.10±0.001 ^a	0.02	75	0.16±0.028	0.24
Winter								
B 1	90	0.10±0.000 ^a	0.00	0.10±0.000 ^a	0.00	45	0.10±0.004	0.03
B 2	150	0.11±0.003 ^{ab}	0.04	0.12±0.007 ^{ab}	0.09	75	0.13±0.011 ^a	0.09
B 3	150	0.10±0.000 ^b	0.00	0.10±0.000 ^b	0.00	75	0.10±0.000 ^a	0.00
Spring								
B 1	60	0.10±0.000	0.00	0.11±0.005	0.05	30	0.22±0.033 ^{ab}	0.18
B 2	100	0.11±0.006	0.06	0.15±0.028	0.28	50	0.12±0.010 ^{ac}	0.07
B 3	100	0.10±0.000	0.00	0.10±0.000	0.00	50	0.10±0.000 ^{bc}	0.00

B1 is investigated barn in Farm 1, B2 – in Farm2 and B3 - in Farm 3, respectively;

Between the farms marked with the same letter by seasons there is a statistically significant difference - $P < 0.05$

high temperatures increased, which affects the animals, and this trend will continue, according to the predictions of meteorologists. This should be taken into account when designing buildings and technology systems in order to ensure an optimal environment for the animals that will reduce this negative effect of climatic extremes (Brouček et al., 2006).

Speed of airflow. The average speed of the airflow (Table 4) was relatively low by farms and by seasons, especially in the zone above stalls of the investigated barns - about 0.10 m/s. A slightly higher speed was measured above the manure alleys and the highest – above the feed alleys. During all the seasons, because of various activities in the buildings during the day (loading diets in cribs, moving the cows to the milking parlor and back, cleaning manure, etc.), the walls on both ends of the feed alleys were often open in all three farms. The result was an air stream, albeit a slight one and a higher speed of airflow above the feed alley compared to the other zones. Only for the summer in all three farms a considerably higher speed of airflow in all three zones of recording was reported. The speed of the air flow measured above the manure alley in B1 was the highest. In the three dairy farms there were running fans, due to this in the summer a higher speed of airflow in all three farms in all three technological zones was reported. From the results shown, it can be seen that in B1 the highest speed of airflow above the manure alley in the summer was observed. Probably this was due to the optimal placement of the fans from one another inside the barn and to the optimal angle at which they were placed towards the manure alley. In B3, although the fans were positioned above the zone of stalls, the highest speed of airflow was not reported compared to the other two barns (B1 and B2).

According to Regulation No. 44 (2006), the speed of airflow in the vital area for the dairy cows during the warmer periods of the year should be in the range of 0.5 to 1 m/s, but for colder periods – up to 0.3 m/s. The results obtained do not exceed these values. Consequently, the values of this index correspond to animal hygienic requirements for cows.

Solan and Jozwik (2009) recommended the speed of the airflow inside the premises for rearing dairy cows should not exceed 0.2 m/s for the winter period and 0.5 m/s for the summer, unless the temperatures are not extremely high. Although these limit values are lower than Bulgarian norms, the results obtained also do not exceed them.

The variation in the speed of airflow depending on the time of

recording in the day during the different seasons by farms was not presented. This indicator had no specific pattern depending on the time of recording. It can be said that a higher speed during the summer season in all three farms was observed. A higher speed of airflow in daytime hours compared to the morning and afternoon was registered, which was related to the work of the fans.

Significant differences in the speed of airflow inside and outside the premises for all farms for most seasons were observed, as the reported from outside were considerably higher. Even for the summer period when fans were working in the different technological zones of the farms, the speed of airflow outside the premises was equal to or higher than inside. This showed that this type of buildings protects dairy cows from airflow.

The temperature stress can be reduced or eliminated by different methods of cooling. Brouček et al. (2006) indicate that there are a number of methods available which can be applied to reduce the air temperature below the outer ambient temperatures. The fans can be used for mechanical ventilation. If they are properly designed, this is a very effective method of providing airflow. However, it can be expensive and may not ensure an adequate relief of heat stress, unless combined with other methods of cooling, for example by mister system (Anderson et al., 2013). If the air is hot, animals do not lose heat. In hot summer conditions dairy cows need more cooling than can be provided by natural or mechanical ventilation (Brouček et al., 2006).

Regarding the average speed of airflow (Table 5) in the different technological zones of the premises statistically significant effect of the farm in the zone of manure and feed alleys was reported ($P < 0.001$) and less effect in the zone of stalls ($P < 0.05$). The factor season influenced significantly ($P < 0.001$) the speed of airflow in the three technological zones. The time of recording had significant effect only in the zone of manure alley ($P < 0.05$). The farm also had significant effect by seasons ($P < 0.001$) in the three technological zones. The time of reporting by seasons had significant effect only above the manure alley ($P < 0.05$). This was so because in Farm 1 and Farm 2 fans were located above the manure alleys, while in Farm 3 they were located above the stalls.

Air relative humidity. The water vapor content in the air is an important animal hygienic indicator, because it affects the speed of evaporation losses through the skin and the lungs of animals. When the average daily temperature is out of the comfort zone of the farm animals, the amount of moisture in the air becomes a considerable

Table 5. Analysis of variance for the effect of controlled factors on the average speed of airflow over the different technological zones in the investigated barns

Sources of variation	Degrees of freedom	Free-stalls			Manure alley			Feed alley		
	(n – 1)	MS	F	P	MS	F	P	MS	F	P
Total for the model	59	0.087	3.62***		0.243	7.93***		0.045	2.17***	
Farm	2	0.098	4.140*		0.520	16.99***		0.177	8.53***	
Season	3	0.930	38.9***		2.190	71.53***		0.120	5.80***	
Time of recording	4	0.030	1.266- ns		0.077	2.53*		0.021	0.99- ns	
Farm*Season	6	0.133	5.585***		0.566	18.49***		0.109	5.24***	
Farm*Time of rec.	8	0.023	0.951- ns		0.052	1.70- ns		0.019	0.93- ns	
Season*Time of rec.	12	0.031	1.295- ns		0.063	2.08*		0.041	1.99*	
Farm*Season*Time of rec.	24	0.023	0.943- ns		0.088	2.87***		0.028	1.37- ns	
Error	1710	0.024			0.031			0.021		

* - significant at $P < 0.05$; ** - significant at $P < 0.01$; *** - significant at $P < 0.001$; ns - no significant effect

element in maintaining the homeostasis of the animal (Bohmanova et al., 2007).

Air humidity average values over the three technological zones of buildings by farms and seasons are presented in Table 6. The lowest humidity over all three technological zones during all seasons was recorded in the barn of Farm 1 (41.5-62.8%), and the highest - in the barn of Farm 3 (55.6-64.0%). These results are in direct relation to established values for the ambient air humidity of the investigated farms (Table 1). The differences between values of air humidity for all technological zones in the barns (B1, B2, B3) by seasons were statistically significant at $P < 0.05$. The highest humidity values were

in the zone of manure alley, which was logical consequence of the high moisture content of manure. In close proximity to this zone was the zone of stalls where the measured humidity was slightly lower. The lowest humidity was reported above the feed alleys in all barns. This corresponded to the highest speed of airflow in that zone. Feed alleys are relatively separated from the zones of manure alleys, which explained the measured lower humidity in that zone, besides the higher speed of airflow contributed to lowering the humidity in the zone. In all three barns the feed alleys were situated toward the open sidewall of the buildings. The adequate speed of airflow (ventilation) contributes to lowering the humidity, harmful gases, temperature

Table 6. Average daily air relative humidity (%) in different technological zones of the investigated barns by seasons

Barn	n	Free-stalls		Manure alley		Feed alley		
		x ± SE	SD	x ± SE	SD	Number	x ± SE	SD
Summer								
B 1	150	49.5±0.79 ^{ab}	9.69	49.9±0.79 ^{ab}	9.72	75	49.0±1.01 ^{ab}	8.72
B 2	250	55.7±0.66 ^{ac}	10.38	55.9±0.64 ^{ac}	10.19	125	54.7±1.00 ^{ac}	11.21
B 3	250	59.3±0.47 ^{bc}	7.50	59.3±0.49 ^{bc}	7.79	125	57.5±0.64 ^{bc}	7.15
Autumn								
B 1	120	64.6±1.25	13.66	65.5±1.24	13.62	60	62.8±1.80	13.92
B 2	200	66.4±0.98	13.85	65.7±0.98	13.83	100	63.5±1.28	12.85
B 3	150	66.2±1.47	18.05	67.0±1.44	17.64	75	64.5±2.05	17.76
Winter								
B 1	90	52.4±1.05 ^{ab}	9.92	52.3±1.01 ^{ab}	9.60	45	49.7±1.47 ^{ab}	9.84
B 2	150	57.5±1.44 ^{ac}	17.63	57.4±1.42 ^{ac}	17.40	75	56.9±2.00 ^a	17.36
B 3	150	62.0±0.86 ^{bc}	10.56	62.4±0.86 ^{bc}	10.54	75	61.2±1.13 ^b	9.82
Spring								
B 1	60	42.7±1.00 ^{ab}	7.76	42.4±0.90 ^{ab}	6.99	30	41.5±1.47 ^a	8.08
B 2	100	45.4±0.64 ^{ac}	6.42	45.7±0.60 ^{ac}	5.98	50	43.9±1.01 ^b	7.12
B 3	100	57.0±0.77 ^{bc}	7.69	57.5±0.78 ^{bc}	7.83	50	55.6±0.98 ^{ab}	6.92

B1 is investigated barn in Farm 1, B2 – in Farm2 and B3 - in Farm 3, respectively;

Between the farms marked with the same letter by seasons there is a statistically significant difference - $P < 0.05$,

and air contamination with microorganisms (Miteva, 2012).

Air humidity inside the buildings in all three farms was higher, compared to that outside the barns. This is explainable, because in the premises the additional moisture from the animals themselves and from the manure was evaporated. In the building of Farm 3 the relative humidity during almost all seasons in the three technological zones was the highest. The main reason for this result is the capacity of the building, which is for 500 cows compared to the other two barns, which have a capacity for 120 cows, each of them. A larger number of cows in B3 is the reason for the release of a larger quantity of water vapor as well as from the animals and from the higher amount of manure in the barn. Another prerequisite is the higher content of water vapor in the air outside Farm 3 compared the air humidity around the other two farms.

The largest and statistically significant difference between the relative humidity outside and inside the building was reported for Farm 3. The smallest was the difference for the winter season - 4.2%, and the greatest for spring - 10.4%. In the other two farms the relative air humidity was also higher in the barns than outside, but the differences were much smaller and not statistically significant - from 2.8% to 3.8%. Erbez et al. (2010) also reported no significant

difference in the monthly values of the relative humidity inside and outside the building. Contradictory to our results reported Šoch et al. (2000), which established that in most of the buildings for cows and heifers, the upper limits (80-85%) of the relative air humidity are exceeded.

Animal hygiene assessment on this indicator showed that all averages relative humidity values by seasons are within the range between 41.5±1.47% (Spring, B1 - feed alley) and 67.0±1.44% (Autumn, B3 - manure alley), i.e. in a range between the minimum allowable (50%) and the lower limit of optimum temperature (70%) under Regulation No. 44 (2006). Exceptions are the values of relative humidity in B1 and B2 for all zones in the spring, in B1 of feed alley in the winter and in B1 in all zones in the summer, which are lower than the minimum humidity according to the standard.

According to Ozhan et al. (2001) (by Sagsoz et al., 2003) optimal relative humidity in livestock premises is between 60 and 70%. Comparing these recommendable rates with the data reported by us, it is obvious that in all three farms the humidity values by seasons and technological zones were around the lower limit of the recommended.

The variations in air humidity above the stalls depending on the

Figure 2. Relative humidity above the stalls in the investigated barns by seasons and time of recording during the day

Table 7. Analysis of variance for the influence of controlled factors on the relative humidity in the different technological zones of the barns

Sources of variation	Degrees of freedom	Free-stalls			Manure alley			Feed alley		
	(n – 1)	MS	F	P	MS	F	P	MS	F	P
Total for the model	59	1998.9	16.43***		2008.5	16.98***		897.9	7.30***	
Farm	2	9256	76.02***		10021	84.32***		4780	38.88***	
Season	3	18417	151.26***		18839	158.52***		8156	66.34***	
Time of recording	4	5258	43.18***		5230	44.01***		2176	17.70***	
Farm*Season	6	1119	9.19***		1139	9.58***		578	4.71***	
Farm* Time of rec.	8	325	2.67**		342	2.88**		147	1.20- ns	
Season * Time of rec.	12	449	3.69***		484	4.07***		258	2.10*	
Farm * Season * Time of rec.	24	283	2.33***		239	2.01**		102	0.83- ns	
Error	1710	122			119			123		

* - significant at $P < 0.05$; ** - significant at $P < 0.01$; *** - significant at $P < 0.001$; ns - no significant effect

time of measuring by seasons are given in Figure 2.

The highest humidity during most of the day for all seasons in Farm 3 was reported. Humidity above the stalls on this farm was the highest right from the morning, as it was around and above 70%. The lowest air humidity above the stalls almost throughout the day was found in Farm 1. The same trend was also registered in the climatic

indicators for the locations of these farms. In Farm 1 the lowest relative humidity both outside and inside the building for all seasons and technological zones was reported.

The difference between the temperature and relative humidity inside and outside the buildings for rearing cows changed with the seasons and also depended on the construction of buildings

(Seedorf et al 1998). Generally, the temperature is higher inside buildings (3-5°C in Northern Europe) and the relative humidity varies, depending on the outdoor temperature (Seedorf et al., 1998; Erbez et al., 2010).

The analysis of variance for the influence of the controlled factors (Table 7) shows that all three factors - farm, season and time of recording had a statistically significant effect on the humidity in the three technological zones ($P < 0.001$), as well as the factors, „farm and season“, „season and time of reporting“, „farm and time of reporting“ as the only exception was air humidity above the feed alley.

Conclusion

It was found that: a) Microclimatic parameters (air temperature, air relative humidity and speed of airflow) in technological zones - above the stalls, the manure and feed alleys, of three semi open free-stall dairy barns (with capacity for 120, 120 and 500 cows) from three farms, situated in different regions of Central South Bulgaria meet the animal hygienic requirements for all seasons according to Regulation No. 44 (2006). Exceptions are some values of relative humidity in B1 and B2 in the spring, in B1 in winter and summer, which are lower than the minimum humidity (50%) according to the standard. b). The investigated barns are characterized with very poor insulation, which does not provide enough isolation from the external ambient temperatures. With the exception of winter, the temperature of the air inside the buildings was lower than that outside, with minor differences for all seasons. The fans in the barns have no effect on the inside air temperature, especially in summer. There was a risk of higher temperatures mainly during the summer period. c) There is no significant difference between the average temperatures, air humidity and speed of airflow in all technological zones. d) The largest and statistically significant is the difference between the relative air humidity outside and inside the building in Farm 3, followed by buildings in Farms 1 and 2, where the differences are smaller and statistically insignificant. e) Factor analysis revealed a significant effect: of the farm on temperature in the different technological zones in the barns ($P < 0.05$ - 0.01); of the farm in the zone of manure and feed alleys ($P < 0.001$) and less effect in the zone of stalls ($P < 0.05$) on speed of airflow, the factor season on speed of airflow in all zones ($P < 0.001$), the time of recording in the zone of manure alley on speed of airflow ($P < 0.05$); the farm, season and time of recording on the humidity in the three technological zones ($P < 0.001$).

References

Anderson S, Bradford B, Harner J, Tucker C, Choi C, Allen J, Hall L, Rungruang S, Collier R and Smith J, 2013. Effects of adjustable and stationary fans with misters on core body temperature and lying behavior of lactating dairy cows in a semiarid climate. *Journal of dairy science*, 96, 4738-50.

Berman AJ, 2005. Estimates of heat stress relief needs for Holstein dairy cows. *Journal of Animal Science*, 83, 1377-1384.

Bohmanova J, Misztal I and Cole JB, 2007. Temperature-Humidity Indices as Indicators of Milk Production. Losses due to Heat Stress. *Journal of Dairy Science*, 90, 1947-1956.

Brouček J, Mihina Š, Ryba Š, Tongel' P, Kišac P, Uhrinčat' M and Hanus A, 2006. Effects of High Air Temperatures on Milk Efficiency

in Dairy Cows. *Czech Journal of Animal Science*, 51, 93-101.

Brügemann K, Gernand E, von Borstel UK and König S, 2012. Defining and evaluating heat stress thresholds in different dairy cow production systems. *Archiv Tierzucht*, 55, 13-24.

Cederberg C, Berglund M, Gustavsson J and Wallman M, 2012. Environmental impacts from livestock production with different animal welfare potentials – a literature review, SIK report 844, Göteborg, Sweden, 19-39.

Erbez M, Falta D and Chládek G, 2010. The relationship between temperature and humidity outside and inside the permanently open-sided cows' barn *Acta Universitatis Agriculturae et Silviculturae Mendelianae Brunensis*, Brno, Česká Republika, LVIII, 91-6.

Gaughan J, Holt S, Hahn G, Mader T and Eigenberg R, 2000. Respiration rate—is it a good measure of heat stress in cattle? *Asian–Australian Journal Animal Science*, 13, (Supp C), 329-332.

Hahn GL and Mader TL, 1997. Heat waves in relation to thermoregulation, feeding behavior and mortality of feedlot cattle. *Proceedings, 5th International Livestock Environment Symposium, American Society Agricultural Engineers, Minneapolis, USA*, 563-571.

Harner PJ, 2008. In the thermoneutral zone: Potential benefits of LPCV buildings. *Western Dairy Management Conf. Reno, Nevada*.

Jara I, Keimb J and Arias R, 2016. Behaviour, tympanic temperature and performance of dairy cows during summer season in southern Chile. *Archivos de medicina veterinaria*, 48, 113-118.

Lefcourt A and Adams W, 1996. Radiotelemetry measurement of body temperatures of feedlot steers during summer. *Journal of Animal Science*, 74, 2633-2640.

Mader T, Dahlquist J, Hahn G and Gaughan J, 1999. Shade and wind barrier effects on summertime feedlot cattle performance. *Journal of Animal Science*, 77, 2065-2072

Mijic P, Knežević I, Matkovic M, Baban M and Ivkic Z, 2007. The milk ability and somatic cell counts of milkcow sinvarious systems of keeping and milking. *Biotehnology in Animal Husbandry*, 23, 209-216.

Miteva Tch, 2012. Hygienic aspects of production activity in loose-housed dairy cows. *Academic Publishing Trakia University, Stara Zagora, Bulgaria*, ISBN 978-954-338-048-0 (Bg).

Ozhan M, Tiizcmen N and Yanar M, 2001. "Buyukbas hayvan yetistirme. Ucuncii baski." *Atatiirk Universitesi Ziraat Fakiiltesi Ofset Tesisi, Erzurum (Tr)*.

Perissinotto M, Moura D, Matarazzo S, Mendes A and Naas I, 2006. Thermal Preference of Dairy Cows Housed in Environmentally Controlled Freestall. *Agricultural Engineering International: the CIGR Ejournal. Manuscript BC 05 016*, 8, March 2006.

Petkov G, 1977. Comparative studies of the microclimate in barns for dairy cows and its dependence on climatic conditions in different regions of Blagoevgrad District, Thesis for PhD, Central Veterinary Research Institute, Sofia, 66-94 (Bg).

Regulation 44, 20.04. 2006. on veterinary requirements for animal holding (Bg).

Sagsoz Y, Tuzemen N, Yanar M, Akbulut O and Aydin R, 2003. Effect of different housing conditions on the milk production and some physiological characteristics of Holstein Friesian cows. *Indian Journal of Animal Sciences*, 73, 104-106.

Seedorf J et al., 1998 Temperature and moisture conditions in livestock buildings in Northern Europe. *Journal of Agricultural Engineering Research*, 70, 49-57.

Šoch M, Matoušková E and Trávníček J, 2000. The Microclimatic conditions in cattle and sheep stables at selected farms in Šumava.

In: Proc. 3rd Int. Scientific Conference Agregion 2000, Zootechnical Section, České Budějovice, 151-152.

Solan M and Jozwik M 2009. The effect of microclimate and management system on welfare of dairy cows. Publikacje i wydawnictwa - Instytut Zootechniki, 1, 25-29 (Po).

van Eerdenburg F, 2013. Lying area design and barn climate

getting it right. Proceedings Cow Longevity Conference. Sweden, August, 2013.

Zahner M, Schrader L, Hauser R, Keck M, Langhans W and Wechsler B, 2004. The influence of climatic conditions on physiological and behavioural parameters in dairy cows kept in open stables. Animal Science 78, 139-147.

Review

- Antimicrobial activity of *Lactobacillus acidophilus* against pathogenic and food spoilage microorganisms: A review** 3
T. Dinev, G. Beev, S. Denev, D. Dermendzhieva, M. Tzanova, E. Valkova

Genetics and Breeding

- Heterosis and degrees of dominance of grain yield and grain yield elements in maize hybrids in different groups of ripeness** 10
M. Ilchovska
- Use of recurrent selection of early flowering in late maize synthetic population. Results of second cycle of breeding.** 16
N. Petrovska, V. Valkova
- Productivity and adaptability of new genotypes field pea (*Pisum sativum* L.) cultivated under environmental condition of Southern Romania** 19
R. Sturzu, A. M. Ene, Cr. Melucă, J. M. Cojocaru
- Nitrogen uptake and expense in durum wheat depending on genotype and nitrogen fertilization** 26
G. Panayotova, M. Almaliev, S. Kostadinova

Nutrition and Physiology

- Haematological investigations upon acute intoxication with carbofuran in dogs** 35
R. Binev, I. Valchev, R. Russenov, Y. Nikolov

Production Systems

- Phytosanitary status and yield of kamut (*Triticum turgidum polonicum* L.) grown in organic and biodynamic farming** 42
V. Maneva, D. Atanasova, T. Nedelcheva
- Hot-water treatment of gladiolus cormels for control of corm-borne fungal diseases** 45
S. Bistrichanov, T. Vatchev, Z. Avramov
- Productivity of common wheat (*Triticum aestivum* L.) grown after various predecessors and nitrogen fertilization rates** 48
M. Gerdzhikova

Agriculture and Environment

- Agro-ecological assessment of manure from different farm animals by content of biogenic elements** 53
D. Dermendzhieva, G. Kostadinova, G. Petkov, D. Dimov, T. Dinev, T. Penev, Ch. Miteva, J. Mitev

Screening of cucurbitaceous rootstocks against root-knot nematodes (<i>Meloidogyne</i> spp.) and soilborne pathogens (<i>Fusarium</i> spp. and <i>Pythium</i> spp.)	62
--	-----------

V. Yankova , D. Markova, N. Velkov, S. Masheva

Animal hygiene assessment of microclimate in semi open free-stall barns for dairy cows	67
---	-----------

D. Dimov, Ch. Miteva, I. Marinov, Zh. Gergovska, T. Penev, A. Enchev

Product Quality and Safety

Accumulation of astaxanthin and canthaxanthin in muscle tissues of Rainbow trout (<i>Oncorhynchus mykiss</i> W.) fed with xanthophyll supplemented feed	77
--	-----------

M. Tzanova

Chemical composition and technological characteristics of wines from red grape varieties, selected in Bulgaria	83
---	-----------

V. Haygarov, T. Yoncheva, Z. Nakov, M. Ivanov, D. Dimitrov

Instruction for authors

Preparation of papers

Papers shall be submitted at the editorial office typed on standard typing pages (A4, 30 lines per page, 62 characters per line). The editors recommend up to 15 pages for full research paper (including abstract, references, tables, figures and other appendices).

The manuscript should be structured as follows: Title, Names of authors and affiliation address, Abstract, List of keywords, Introduction, Material and methods, Results, Discussion, Conclusion, Acknowledgements (if any), References, Tables, Figures.

The title needs to be as concise and informative about the nature of research. It should be written with small letter /bold, 14/ without any abbreviations.

Names and affiliation of authors

The names of the authors should be presented from the initials of first names followed by the family names. The complete address and name of the institution should be stated next. The affiliation of authors are designated by different signs. For the author who is going to be corresponding by the editorial board and readers, an E-mail address and telephone number should be presented as footnote on the first page. Corresponding author is indicated with *.

Abstract should be not more than 350 words. It should be clearly stated what new findings have been made in the course of research. Abbreviations and references to authors are inadmissible in the summary. It should be understandable without having read the paper and should be in one paragraph.

Keywords: Up to maximum of 5 keywords should be selected not repeating the title but giving the essence of study.

The introduction must answer the following questions: What is known and what is new on the studied issue? What necessitated the research problem, described in the paper? What is your hypothesis and goal?

Material and methods: The objects of research, organization of experiments, chemical analyses, statistical and other methods and conditions applied for the experiments should be described in detail. A criterion of sufficient information is to be possible for others to repeat the experiment in order to verify results.

Results are presented in understandable

tables and figures, accompanied by the statistical parameters needed for the evaluation. Data from tables and figures should not be repeated in the text.

Tables should be as simple and as few as possible. Each table should have its own explanatory title and to be typed on a separate page. They should be outside the main body of the text and an indication should be given where it should be inserted.

Figures should be sharp with good contrast and rendition. Graphic materials should be preferred. Photographs to be appropriate for printing. Illustrations are supplied in colour as an exception after special agreement with the editorial board and possible payment of extra costs. The figures are to be each in a single file and their location should be given within the text.

Discussion: The objective of this section is to indicate the scientific significance of the study. By comparing the results and conclusions of other scientists the contribution of the study for expanding or modifying existing knowledge is pointed out clearly and convincingly to the reader.

Conclusion: The most important consequences for the science and practice resulting from the conducted research should be summarized in a few sentences. The conclusions shouldn't be numbered and no new paragraphs be used. Contributions are the core of conclusions.

References:

In the text, references should be cited as follows: single author: Sandberg (2002); two authors: Andersson and Georges (2004); more than two authors: Andersson et al. (2003). When several references are cited simultaneously, they should be ranked by chronological order e.g.: (Sandberg, 2002; Andersson et al., 2003; Andersson and Georges, 2004).

References are arranged alphabetically by the name of the first author. If an author is cited more than once, first his individual publications are given ranked by year, then come publications with one co-author, two co-authors, etc. The names of authors, article and journal titles in the Cyrillic or alphabet different from Latin, should be transliterated into Latin and article titles should be translated into English. The original language of articles and books translated into English is indicated in parenthesis after the bibliographic reference (Bulgarian = Bg, Russian = Ru, Serbian = Sr, if in the Cyrillic, Mongolian =

Mo, Greek = Gr, Georgian = Geor., Japanese = Ja, Chinese = Ch, Arabic = Ar, etc.)

The following order in the reference list is recommended:

Journal articles: Author(s) surname and initials, year. Title. Full title of the journal, volume, pages. Example:

Simm G, Lewis RM, Grundy B and Dingwall WS, 2002. Responses to selection for lean growth in sheep. *Animal Science*, 74, 39-50

Books: Author(s) surname and initials, year. Title. Edition, name of publisher, place of publication. Example:

Oldenbroek JK, 1999. Genebanks and the conservation of farm animal genetic resources, Second edition. DLO Institute for Animal Science and Health, Netherlands.

Book chapter or conference proceedings:

Author(s) surname and initials, year. Title. In: Title of the book or of the proceedings followed by the editor(s), volume, pages. Name of publisher, place of publication. Example:

Mauff G, Pulverer G, Operkuch W, Hummel K and Hidden C, 1995. C3-variants and diverse phenotypes of unconverted and converted C3. In: *Provides of the Biological Fluids* (ed. H. Peters), vol. 22, 143-165, Pergamon Press. Oxford, UK.

Todorov N and Mitev J, 1995. Effect of level of feeding during dry period, and body condition score on reproductive performance in dairy cows. IXth International Conference on Production Diseases in Farm Animals, September 11-14, Berlin, Germany.

Thesis:

Hristova D, 2013. Investigation on genetic diversity in local sheep breeds using DNA markers. Thesis for PhD, Trakia University, Stara Zagora, Bulgaria, (Bg).

The Editorial Board of the Journal is not responsible for incorrect quotes of reference sources and the relevant violations of copyrights.

Animal welfare

Studies performed on experimental animals should be carried out according to internationally recognized guidelines for animal welfare. That should be clearly described in the respective section "Material and methods".

AGRICULTURAL SCIENCE AND TECHNOLOGY

Volume 9, Number 1
March 2017

Journal web site:
www.agriscitech.eu

Publisher:
www.alfamarket.biz