SUBAUTOMATA OF A GENERAL FUZZY AUTOMATON

MOHAMMAD HORRY

Department of Mathematics

Faculty of Chamran

Technical and Vocational University (TVU)

Kerman Branch

Kerman

Iran

e-mail: mhori@tvu.ac.ir

mohhorry@yahoo.com

Abstract

In this paper, we first define the notions of a successor of the state q in a max-min general fuzzy automaton and subautomaton of a max-min general fuzzy automaton. Then define a fuzzy subsystem of a max-min general fuzzy automaton. Finally, we derive the relationships between them.

1. Introduction and Preliminaries

The concept of fuzzy automata was introduced by Wee in 1967 [10].

Let Σ be a non-empty finite set of symbols (alternatively called characters), called the alphabet. A string (or word) over Σ is any finite

2010 Mathematics Subject Classification: 18B20.

Keywords and phrases: (general) fuzzy automata, successor, subautomaton, fuzzy subsystem.

Received November 14, 2018

sequence of symbols from Σ . Λ denotes the empty (or null) string and Σ^* the closure of the alphabet, i.e., the set of all words over Σ . The length $\ell(x)$ of the word $x \in \Sigma^*$ is the number of its letters, so $\ell(\Lambda) = 0$. For a nonempty set X , $\tilde{P}(X)$ will denote the set of all fuzzy sets on X and $P(X)$ will denote the set of all subsets on X .

A deterministic finite-state automaton is a five-tuple denoted as $A = (Q, \Sigma, f, T, s)$, where Q is a finite set of states, Σ is a finite set of input symbols, the function f from $Q \times \Sigma$ into Q is the state transition, T is a subset of Q of accepting states and $s \in Q$ is the initial state.

A word $x = x_1x_2 \dots x_n \in \Sigma^*$ is said to be accepted by A if there exist states $q_0, q_1, \dots, q_n$ satisfying

- (1) $q_0 = s$,
- (2) $f(q_{i-1}, x_i) = q_i$ for $i = 1, 2, \dots, n$,
- (3) $q_n \in T$.

The empty word is accepted by A if and only if $s \in T$.

A nondeterministic finite-state automaton is a five-tuple denoted as $A = (Q, \Sigma, f, T, s)$, where Q is a finite set of states, Σ is a finite set of input symbols, the function f from $Q \times \Sigma$ into $P(Q)$ is the state transition, T is a subset of Q of accepting states and $s \in Q$ is the initial state.

A fuzzy finite-state automaton (FFA) is a six-tuple $\tilde{F} = (Q, \Sigma, R, Z, \delta, \omega)$, where Q is a finite set of states, Σ is a finite set of input symbols, R is the initial state of $\tilde{F}$, Z is a finite set of output symbols,

$\delta : Q \times \sum \times Q \rightarrow [0, 1]$ is the fuzzy transition function which is used to map a state (current state) into another state (next state) upon an input symbol, attributing a value in the interval $[0, 1]$ and $\omega : Q \rightarrow Z$ is the output function. Associated with each fuzzy transition, there is a membership value in $[0, 1]$ called the weight of the transition. The transition from state q_i (current state) to state q_j (next state) upon input a_k is denoted by $\delta(q_i, a_k, q_j)$.

We use $\delta(q_i, a_k, q_j)$ to refer both to a transition and its weight in the sense that whenever $\delta(q_i, a_k, q_j)$ is used as a value, it refers to the weight of the transition, and otherwise, specifies the transition itself. The set of all transitions of $\tilde{F}$ will be denoted by Δ . The above definition is generally accepted as a formal definition of a fuzzy finite-state automaton [2, 3, 6, 7, 8, 9].

In 2004, Doostfatemeleh and Kremer extended the notion of fuzzy automata and introduced the notion of general fuzzy automata [1].

In this paper, by using [1] and [11], we define the notions of a successor of the state q and subautomaton of a max-min general fuzzy automaton. Then define a fuzzy subsystem of a max-min general fuzzy automaton. Finally, we derive the relationships between them.

Definition 1.1 ([1]). A general fuzzy automaton (GFA) is an eight-tuple machine $\tilde{F} = (Q, \sum, \tilde{R}, Z, \tilde{\delta}, \omega, F_1, F_2)$, where

- (i) Q is a finite set of states, $Q = \{q_1, q_2, \dots, q_n\}$,
- (ii) $\sum$ is a finite set of input symbols, $\sum = \{a_1, a_2, \dots, a_m\}$,
- (iii) $\tilde{R}$ is the set of fuzzy start states, $\tilde{R} \in \tilde{P}(Q)$,
- (iv) Z is a finite set of output symbols, $Z = \{b_1, b_2, \dots, b_k\}$,
- (v) $\omega : Q \rightarrow Z$ is the output function,

(vi) $\tilde{\delta} : (Q \times [0, 1]) \times \sum \times Q \rightarrow [0, 1]$ is the augmented transition function,

(vii) $F_1 : [0, 1] \times [0, 1] \rightarrow [0, 1]$ is the membership assignment function,

(viii) $F_2 : [0, 1]^* \rightarrow [0, 1]$ is called the multi-membership resolution function.

We note that the function $F_1(\mu, \delta)$ has two parameters μ and δ , where μ is the membership value of a predecessor and δ is the weight of a transition. In this definition, the process that takes place upon the transition from state q_i to q_j on input a_k is represented as:

$$\mu^{t+1}(q_j) = \tilde{\delta}((q_i, \mu^t(q_i)), a_k, q_j) = F_1(\mu^t(q_i), \delta(q_i, a_k, q_j)).$$

This means that the membership value (mv) of the state q_j at time $t + 1$ is computed by function F_1 using both the membership value of q_i at time t and the weight of the transition.

The usual options for the function $F_1(\mu, \delta)$ are $\max\{\mu, \delta\}$, $\min\{\mu, \delta\}$ and $(\mu + \delta) / 2$.

The multi-membership resolution function resolves the multi-membership active states and assigns a single membership value to them.

Let $Q_{act}(t_i)$ be the fuzzy set of all active states at time t_i , $\forall i \geq 0$. We have $Q_{act}(t_0) = \tilde{R}$ and

$$Q_{act}(t_i) = \{(q, \mu^{t_i}(q)) : \exists q' \in Q_{act}(t_{i-1}), \exists a \in \sum, \delta(q', a, q) \in \Delta\}, \forall i \geq 1.$$

Since $Q_{act}(t_i)$ is a fuzzy set, in order to show that a state q belongs to $Q_{act}(t_i)$ and T is a subset of $Q_{act}(t_i)$, we should write: $q \in \text{Domain}(Q_{act}(t_i))$ and $T \subset \text{Domain}(Q_{act}(t_i))$.

Hereafter, we simply denote them as: $q \in Q_{act}(t_i)$ and $T \subset Q_{act}(t_i)$.

The combination of the operations of functions F_1 and F_2 on a multi-membership state q_j leads to the multi-membership resolution algorithm.

Algorithm 1.2 ([1]) (Multi-membership resolution). If there are several simultaneous transitions to the active state q_j at time $t + 1$, the following algorithm will assign a unified membership value to it:

(1) Each transition weight $\delta(q_i, a_k, q_j)$ together with $\mu^t(q_i)$, will be processed by the membership assignment function F_1 , and will produce a membership value. Call this v_i .

$$v_i = \tilde{\delta}((q_i, \mu^t(q_i)), a_k, q_j) = F_1(\mu^t(q_i), \delta(q_i, a_k, q_j)).$$

(2) These membership values are not necessarily equal. Hence, they need to be processed by the multi-membership resolution function F_2 .

(3) The result produced by F_2 will be assigned as the instantaneous membership value of the active state q_j ,

$$\mu^{t+1}(q_j) = \underset{i=1}{\overset{n}{F_2}}[v_i] = \underset{i=1}{\overset{n}{F_2}}[F_1(\mu^t(q_i), \delta(q_i, a_k, q_j))],$$

where

- n is the number of simultaneous transitions to the active state q_j at time $t + 1$.
- $\delta(q_i, a_k, q_j)$ is the weight of a transition from q_i to q_j upon input a_k .
- $\mu^t(q_i)$ is the membership value of q_i at time t .
- $\mu^{t+1}(q_j)$ is the final membership value of q_j at time $t + 1$.

Definition 1.3 ([11]). Let $\tilde{F} = (Q, \sum, \tilde{R}, Z, \omega, \tilde{\delta}, F_1, F_2)$ be a general fuzzy automaton. We define max-min general fuzzy automata as $\tilde{F}^* = (Q, \sum, \tilde{R}, Z, \omega, \tilde{\delta}^*, F_1, F_2)$ such that:

$$\tilde{\delta}^* : Q_{act} \times \sum^* \times Q \rightarrow [0, 1],$$

where $Q_{act} = \{Q_{act}(t_0), Q_{act}(t_1), Q_{act}(t_2), \dots\}$ and for all $i \geq 0$,

$$\tilde{\delta}^*((q, \mu^{t_i}(q)), \Lambda, p) = \begin{cases} 1, & q = p, \\ 0, & \text{otherwise.} \end{cases}$$

Also, if the input at time t_i be u_i , where $u_i \in \sum$, $\forall 1 \leq i \leq n$, then

$$\begin{aligned} \tilde{\delta}^*((q, \mu^{t_{i-1}}(q)), u_i, p) &= \tilde{\delta}((q, \mu^{t_{i-1}}(q)), u_i, p), \\ \tilde{\delta}^*((q, \mu^{t_{i-1}}(q)), u_i u_{i+1}, p) &= \bigvee_{q' \in Q_{act}(t_i)} (\tilde{\delta}((q, \mu^{t_{i-1}}(q)), u_i, q') \wedge \tilde{\delta}((q', \mu^{t_i}(q')), u_{i+1}, p)), \end{aligned}$$

and recursively

$$\begin{aligned} \tilde{\delta}^*((q, \mu^{t_0}(q)), u_1 u_2 \dots u_n, p) &= \bigvee \{ \tilde{\delta}((q, \mu^{t_0}(q)), u_1, p_1) \wedge \tilde{\delta}((p_1, \mu^{t_1}(p_1)), \\ &u_2, p_2) \wedge \dots \wedge \tilde{\delta}((p_{n-1}, \mu^{t_{n-1}}(p_{n-1})), u_n, p) \mid p_1 \in Q_{act}(t_1), p_2 \in Q_{act}(t_2), \\ &\dots, p_{n-1} \in Q_{act}(t_{n-1}) \}. \end{aligned}$$

If $q \in Q_{act}(t_i)$, we should write q belongs to an element of Q_{act} . Hereafter, we simply denote it as: $q \in Q_{act}$.

2. Subautomata of a General Fuzzy Automaton

Definition 2.1. Let $\tilde{F}^* = (Q, \sum, \tilde{R}, Z, \omega, \tilde{\delta}^*, F_1, F_2)$ be a max-min general fuzzy automaton and $p, q \in Q$. Then q is called a successor of p if there exists $x \in \sum^*$ such that $\tilde{\delta}^*((p, \mu^t(p)), x, q) > 0$.

We denoted $S(p)$ the set of all successors of p . If $T \subseteq Q$, then set of all successors of T denoted by $S(T)$, is defined by the set $S(T) = \bigcup \{S(p) : p \in T\}$.

Example 2.2. Let $\tilde{F}^* = (Q, \sum, \tilde{R}, Z, \omega, \tilde{\delta}^*, F_1, F_2)$ be a max-min general fuzzy automaton, where

$$Q = \{q_0, q_1, q_2\}, \sum = \{a, b\}, Q_{act}(t_0) = \tilde{R} = \{(q_0, \mu^{t_0}(q_0))\} = \{(q_0, 1)\},$$

$$F_1(\mu, \delta) = \text{Min}(\mu, \delta), Z = \emptyset, \omega \text{ and } F_2 \text{ are not applicable, } \delta(q_0, a, q_1) = 0.4, \\ \delta(q_0, b, q_2) = 0.5, \delta(q_1, a, q_2) = 0.3, \delta(q_2, a, q_2) = 0.2.$$

If we choose the input string $x = aa \dots a$, then

$$Q_{act}(t_1) = \{(q_1, \mu^{t_1}(q_1))\}, \quad Q_{act}(t_i) = \{(q_2, \mu^{t_i}(q_2))\}, \forall i \geq 2,$$

$$\mu^{t_1}(q_1) = \tilde{\delta}((q_0, \mu^{t_0}(q_0)), a, q_1) = F_1(\mu^{t_0}(q_0), \delta(q_0, a, q_1)) = F_1(1, 0.4) = 0.4,$$

$$\mu^{t_2}(q_2) = \tilde{\delta}((q_1, \mu^{t_1}(q_1)), a, q_2) = F_1(\mu^{t_1}(q_1), \delta(q_1, a, q_2)) = F_1(0.4, 0.3) = 0.3,$$

$$\mu^{t_3}(q_2) = \tilde{\delta}((q_2, \mu^{t_2}(q_2)), a, q_2) = F_1(\mu^{t_2}(q_2), \delta(q_2, a, q_2)) = F_1(0.3, 0.2) = 0.2,$$

$$\mu^{t_4}(q_2) = \tilde{\delta}((q_2, \mu^{t_3}(q_2)), a, q_2) = F_1(\mu^{t_3}(q_2), \delta(q_2, a, q_2)) = F_1(0.2, 0.2) = 0.2,$$

$$\mu^{t_i}(q_2) = 0.2, \forall i \geq 5,$$

$$\tilde{\delta}^*((q_0, \mu^{t_0}(q_0)), \Lambda, q_0) = 1 \Rightarrow q_0 \in S(q_0),$$

$$\tilde{\delta}^*((q_0, \mu^{t_0}(q_0)), a, q_1) = 0.4 \Rightarrow q_1 \in S(q_0),$$

$$\tilde{\delta}^*((q_0, \mu^{t_0}(q_0)), aa, q_2) = 0.4 \wedge 0.3 = 0.3 \Rightarrow q_2 \in S(q_0),$$

$$\tilde{\delta}^*((q_1, \mu^{t_1}(q_1)), a, q_2) = 0.3 \Rightarrow q_2 \in S(q_1).$$

Definition 2.3. Let $\tilde{F}^* = (Q, \sum, \tilde{R}, Z, \omega, \tilde{\delta}^*, F_1, F_2)$ be a max-min general fuzzy automaton and $\tilde{F}^{*'} = (T, \sum, \tilde{R}, Z, \omega, \tilde{\delta}^{*'}, F_1, F_2)$. Then $\tilde{F}^{*'}$ is called a subautomaton of $\tilde{F}^*$ if $S(T) \subseteq T$, where $\tilde{\delta}^{*'} = \tilde{\delta}^*|_{(Q_{act} \cap T) \times \sum^* \times T}$.

Definition 2.4. Let $\tilde{F}^* = (Q, \sum, \tilde{R}, Z, \omega, \tilde{\delta}^*, F_1, F_2)$ be a max-min general fuzzy automaton and λ be a fuzzy subset on Q . λ is called a fuzzy subsystem of $\tilde{F}^*$, if

$$\lambda(q) \geq \lambda(p) \wedge \tilde{\delta}((p, \mu^t(p)), a, q), \forall p, q \in Q, a \in \sum.$$

Example 2.5. In Example 2.2, let $\lambda(q_0) = 0.3$, $\lambda(q_1) = 0.4$ and $\lambda(q_2) = 0.5$. If we choose the input string $x = aa \dots a$, then

$$Q_{act}(t_1) = \{(q_1, \mu^{t_1}(q_1))\}, \quad Q_{act}(t_i) = \{(q_2, \mu^{t_i}(q_2))\}, \forall i \geq 2,$$

$$\mu^{t_1}(q_1) = \tilde{\delta}((q_0, \mu^{t_0}(q_0)), a, q_1) = F_1(\mu^{t_0}(q_0), \delta(q_0, a, q_1)) = F_1(1, 0.4) = 0.4,$$

$$\mu^{t_2}(q_2) = \tilde{\delta}((q_1, \mu^{t_1}(q_1)), a, q_2) = F_1(\mu^{t_1}(q_1), \delta(q_1, a, q_2)) = F_1(0.4, 0.3) = 0.3,$$

$$\mu^{t_3}(q_2) = \tilde{\delta}((q_2, \mu^{t_2}(q_2)), a, q_2) = F_1(\mu^{t_2}(q_2), \delta(q_2, a, q_2)) = F_1(0.3, 0.2) = 0.2,$$

$$\mu^{t_4}(q_2) = \tilde{\delta}((q_2, \mu^{t_3}(q_2)), a, q_2) = F_1(\mu^{t_3}(q_2), \delta(q_2, a, q_2)) = F_1(0.2, 0.2) = 0.2,$$

$$\mu^{t_i}(q_2) = 0.2, \forall i \geq 5,$$

$$\lambda(q_0) \geq \lambda(q_0) \wedge \tilde{\delta}^*((q_0, \mu^{t_0}(q_0)), \Lambda, q_0) = 0.3 \wedge 1 = 0.3,$$

$$\lambda(q_1) \geq \lambda(q_0) \wedge \tilde{\delta}^*((q_0, \mu^{t_0}(q_0)), a, q_1) = 0.3 \wedge 0.4 = 0.3,$$

$$\lambda(q_2) \geq \lambda(q_1) \wedge \tilde{\delta}^*((q_1, \mu^{t_1}(q_1)), a, q_2) = 0.4 \wedge 0.3 = 0.3.$$

Thus λ is a fuzzy subsystem of $\tilde{F}^*$.

Theorem 2.6. Let $\tilde{F}^* = (Q, \sum, \tilde{R}, Z, \omega, \tilde{\delta}^*, F_1, F_2)$ be a max-min general fuzzy automaton and λ be a fuzzy subset on Q . Then λ is a fuzzy subsystem of $\tilde{F}^*$ if and only if $\lambda(q) \geq \lambda(p) \wedge \tilde{\delta}^*((p, \mu^t(p)), x, q), \forall p, q \in Q, x \in \sum^*$.

Proof. Let λ be a fuzzy subsystem of $\tilde{F}^*$ and $p, q \in Q, x \in \sum^*$. We prove the theorem by mathematical induction on $|x| = n$. If $n = 0$, then $x = \Lambda$. Now if $q = p$, then $\lambda(p) \wedge \tilde{\delta}^*((p, \mu^t(p)), x, q) = \lambda(p) \wedge 1 = \lambda(p) = \lambda(q)$. If $q \neq p$, then $\lambda(p) \wedge \tilde{\delta}^*((p, \mu^t(p)), x, q) = \lambda(p) \wedge 0 = 0 \leq \lambda(q)$.

Assume that the theorem is true for all $u \in \sum^*$ such that $|u| = n - 1, n > 1$. Let $x = au$, where $a \in \sum$ and $|u| = n - 1$. Then we have

$$\begin{aligned} \lambda(p) \wedge \tilde{\delta}^*((p, \mu^t(p)), x, q) &= \lambda(p) \wedge \tilde{\delta}^*((p, \mu^t(p)), au, q) \\ &= \lambda(p) \wedge \left(\bigvee_{r \in Q} \tilde{\delta}^*((p, \mu^t(p)), a, r) \wedge \tilde{\delta}^*((r, \mu^t(r)), u, q) \right) \\ &= \bigvee_{r \in Q} \{ (\lambda(p) \wedge \tilde{\delta}^*((p, \mu^t(p)), a, r)) \wedge \tilde{\delta}^*((r, \mu^t(r)), u, q) \} \\ &\leq \bigvee_{r \in Q} (\lambda(r) \wedge \tilde{\delta}^*((r, \mu^t(r)), u, q)) \leq \lambda(q). \end{aligned}$$

The converse is trivial. □

Theorem 2.7. Let $\tilde{F}^* = (Q, \sum, \tilde{R}, Z, \omega, \tilde{\delta}^*, F_1, F_2)$ be a max-min general fuzzy automaton. Then every constant fuzzy set λ on Q is a fuzzy subsystem of $\tilde{F}^*$.

Proof. Let λ is constant fuzzy set on Q . So for any $p, q \in Q$, we have $\lambda(p) = \lambda(q)$. Then for any $a \in \sum$, clearly $\lambda(q) = \lambda(p) \geq \lambda(p) \wedge \tilde{\delta}((p, \mu^t(p)), a, q)$. Therefore, λ is a fuzzy subsystem of $\tilde{F}^*$. $\square$

Theorem 2.8. Let $\tilde{F}^* = (Q, \sum, \tilde{R}, Z, \omega, \tilde{\delta}^*, F_1, F_2)$ be a max-min general fuzzy automaton, λ_1 and λ_2 be fuzzy subsystems of $\tilde{F}^*$. Then $\lambda_1 \cap \lambda_2$ and $\lambda_1 \cup \lambda_2$ are fuzzy subsystems of $\tilde{F}^*$.

Proof. Since λ_1 and λ_2 are fuzzy subsystems of $\tilde{F}^*$, for $p, q \in Q$, $x \in \sum^*$, we have $\lambda_1(q) \geq \lambda_1(p) \wedge \tilde{\delta}^*((p, \mu^t(p)), x, q)$ and $\lambda_2(q) \geq \lambda_2(p) \wedge \tilde{\delta}^*((p, \mu^t(p)), x, q)$. So

$$(\lambda_1 \cap \lambda_2)(q) = \lambda_1(q) \wedge \lambda_2(q) \geq (\lambda_1(p) \wedge \lambda_2(p)) \wedge \tilde{\delta}^*((p, \mu^t(p)), x, q).$$

Hence, $\lambda_1 \cap \lambda_2$ is a fuzzy subsystem of $\tilde{F}^*$. Also, we have

$$(\lambda_1 \cup \lambda_2)(q) = \lambda_1(q) \vee \lambda_2(q) \geq (\lambda_1(p) \vee \lambda_2(p)) \wedge \tilde{\delta}^*((p, \mu^t(p)), x, q).$$

Hence, $\lambda_1 \cup \lambda_2$ is a fuzzy subsystem of $\tilde{F}^*$. $\square$

Theorem 2.9. Let $\tilde{F}^* = (Q, \sum, \tilde{R}, Z, \omega, \tilde{\delta}^*, F_1, F_2)$ be a max-min general fuzzy automaton and λ be a fuzzy subsystem of $\tilde{F}^*$. Then $\tilde{F}^{*'} = (supp(\lambda), \sum, \tilde{R}, Z, \omega, \tilde{\delta}^{*'}, F_1, F_2)$ is a subautomaton of $\tilde{F}^*$, where $\tilde{\delta}^{*'} = \tilde{\delta}^*|_{(Q_{act} \cap supp(\lambda)) \times \sum^* \times supp(\lambda)}$.

Proof. Let $q \in S(supp(\lambda))$. Then $q \in S(p)$, for some $p \in supp(\lambda)$. So $\lambda(p) > 0$. Since $q \in S(p)$, then there exists $x \in \sum^*$ such that $\tilde{\delta}^*((p, \mu^t(p)), x, q) > 0$. Now, since λ is a fuzzy subsystem of $\tilde{F}^*$, then we have

$$\lambda(q) \geq \lambda(p) \wedge \tilde{\delta}((p, \mu^t(p)), x, q) > 0.$$

Thus $q \in \text{supp}(\lambda)$. Therefore $S(\text{supp}(\lambda)) \subseteq \text{supp}(\lambda)$. Hence $\tilde{F}^*$ is a subautomaton of $\tilde{F}^*$. $\square$

Theorem 2.10. Let $\tilde{F}^* = (Q, \sum, \tilde{R}, Z, \omega, \tilde{\delta}^*, F_1, F_2)$ be a max-min general fuzzy automaton and λ be a fuzzy subset of Q . For $x \in \sum^*$ and $q \in Q$, define the fuzzy subset λx of Q by

$$(\lambda x)(q) = \bigvee_{p \in Q} \{\lambda(p) \wedge \tilde{\delta}^*((p, \mu^t(p)), x, q)\}.$$

Then λ is a fuzzy subsystem of $\tilde{F}^*$ if and only if $\lambda x \subseteq \lambda, \forall x \in \sum^*$.

Proof. Let λ be a fuzzy subsystem of $\tilde{F}^*$ and $x \in \sum^*, q \in Q$. Then

$$(\lambda x)(q) = \bigvee_{p \in Q} \{\lambda(p) \wedge \tilde{\delta}^*((p, \mu^t(p)), x, q)\} \leq \lambda(q).$$

Hence, $\lambda x \subseteq \lambda$.

Conversely, let $x \in \sum^*$ and $q \in Q$. Then for all $p \in Q$, we have

$$\lambda(q) \geq (\lambda x)(q) = \bigvee_{p \in Q} \{\lambda(p) \wedge \tilde{\delta}^*((p, \mu^t(p)), x, q)\} \geq \lambda(p) \wedge \tilde{\delta}^*((p, \mu^t(p)), x, q).$$

Hence, λ is a fuzzy subsystem of $\tilde{F}^*$. $\square$

Theorem 2.11. Let $\tilde{F}^* = (Q, \sum, \tilde{R}, Z, \omega, \tilde{\delta}^*, F_1, F_2)$ be a max-min general fuzzy automaton, $\alpha \in [0, 1]$ and $p, q \in Q$. Define the fuzzy subset $q_\alpha \sum^*$ of Q by

$$(q_\alpha \sum^*)(p) = \bigvee_{x \in \sum^*} \{\alpha \wedge \tilde{\delta}^*((q, \mu^t(q)), x, p)\}, \forall q \in Q.$$

Then $q_\alpha \sum^*$ is a fuzzy subsystem of $\tilde{F}^*$.

Proof. Let $x' \in \sum^*$, then we have

$$\begin{aligned}
 (q_\alpha \sum^*)(p) &\wedge \tilde{\delta}^*((p, \mu^t(p)), x', r) \\
 &= \bigvee_{x \in \sum^*} \{\alpha \wedge \tilde{\delta}^*((q, \mu^t(q)), x, p)\} \wedge \tilde{\delta}^*((p, \mu^t(p)), x', r) \\
 &= \bigvee_{x \in \sum^*} \{\alpha \wedge \tilde{\delta}^*((q, \mu^t(q)), x, p) \wedge \tilde{\delta}^*((p, \mu^t(p)), x', r)\} \\
 &\leq \bigvee_{x \in \sum^*} \{\alpha \wedge \tilde{\delta}^*((q, \mu^t(q)), xx', r)\} \\
 &\leq \bigvee_{u \in \sum^*} \{\alpha \wedge \tilde{\delta}^*((q, \mu^t(q)), u, r)\} \\
 &= (q_\alpha \sum^*)(r).
 \end{aligned}$$

Hence, $q_\alpha \sum^*$ is a fuzzy subsystem of $\tilde{F}^*$. □

Theorem 2.12. Let $\tilde{F}^* = (Q, \sum, \tilde{R}, Z, \omega, \tilde{\delta}^*, F_1, F_2)$ be a max-min general fuzzy automaton, λ is a fuzzy subset of Q , $\alpha \in [0, 1]$, $q \in Q$ and $\alpha \leq \lambda(q)$. Then λ is a fuzzy subsystem of $\tilde{F}^*$ if and only if $q_\alpha \sum^* \subseteq \lambda$.

Proof. Let λ be a fuzzy subsystem of $\tilde{F}^*$. Then for $p \in Q$, we have

$$\begin{aligned}
 (q_\alpha \sum^*)(p) &= \bigvee_{x \in \sum^*} \{\alpha \wedge \tilde{\delta}^*((q, \mu^t(q)), x, p)\} \\
 &\leq \bigvee_{x \in \sum^*} \{\lambda(q) \wedge \tilde{\delta}^*((q, \mu^t(q)), x, p)\} \\
 &\leq \bigvee_{x \in \sum^*} \lambda(p) = \lambda(p).
 \end{aligned}$$

Hence, $q_\alpha \sum^* \subseteq \lambda$.

Conversely, let $q_\alpha \sum^* \subseteq \lambda$, $p \in Q$ and $u \in \sum^*$. If $\lambda(p) = 0$ or $\tilde{\delta}^*((p, \mu^t(p)), x, q) = 0$, then $\lambda(q) \geq \lambda(p) \wedge \tilde{\delta}^*((p, \mu^t(p)), x, q) = 0$.

Suppose $\lambda(p) \neq 0$ and $\tilde{\delta}^*((p, \mu^t(p)), x, q) \neq 0$. Let $\alpha = \lambda(q)$ and $u \in \sum^*$. Thus, by the hypothesis, $q_\alpha \sum^* \subseteq \lambda$. Then we have

$$\begin{aligned} \lambda(p) &\geq (q_\alpha \sum^*)(p) = \bigvee_{x \in \sum^*} \{\alpha \wedge \tilde{\delta}^*((q, \mu^t(q)), x, p)\} \\ &\geq \alpha \wedge \tilde{\delta}^*((q, \mu^t(q)), u, p) \\ &= \lambda(q) \wedge \tilde{\delta}^*((q, \mu^t(q)), u, p). \end{aligned}$$

Hence, λ is a fuzzy subsystem of $\tilde{F}^*$. □

Theorem 2.13. *Let $\tilde{F}^* = (Q, \sum, \tilde{R}, Z, \omega, \tilde{\delta}^*, F_1, F_2)$ be a max-min general fuzzy automaton, $\alpha \in [0, 1]$ and $q \in Q$. Then $\text{supp}(q_\alpha \sum^*) = S(q)$.*

Proof. We have

$$\begin{aligned} p \in S(q) &\Leftrightarrow \exists x \in \sum^* : \tilde{\delta}^*((q, \mu^t(q)), x, p) > 0 \\ &\Leftrightarrow \bigvee_{x \in \sum^*} \{\alpha \wedge \tilde{\delta}^*((q, \mu^t(q)), x, p)\} > 0 \\ &\Leftrightarrow (q_\alpha \sum^*)(p) > 0 \\ &\Leftrightarrow p \in \text{supp}(q_\alpha \sum^*). \end{aligned}$$

Thus $\text{supp}(q_\alpha \sum^*) = S(q)$. □

Definition 2.14. Let $\tilde{F}^* = (Q, \sum, \tilde{R}, Z, \omega, \tilde{\delta}^*, F_1, F_2)$ be a max-min general fuzzy automaton and λ be a fuzzy subsystem of $\tilde{F}^*$. Then λ is called cyclic if there exist $\alpha \in [0, 1]$ and $q \in Q$ with $\alpha \leq \lambda(q)$ such that $\lambda = q_\alpha \sum^*$.

In this case, we call q_α a generator of λ .

Theorem 2.15. Let $\tilde{F}^* = (Q, \sum, \tilde{R}, Z, \omega, \tilde{\delta}^*, F_1, F_2)$ be a max-min general fuzzy automaton, $\alpha \in [0, 1]$, $q \in Q$, $\alpha \leq \lambda(q)$ and λ be a fuzzy subsystem of $\tilde{F}^*$. If λ be cyclic with generator q_α , then $\lambda(q) = \alpha$.

Proof. Since $\lambda = q_\alpha \sum^*$, then we have

$$\begin{aligned} \lambda(q) &= (q_\alpha \sum^*)(q) \\ &= \bigvee_{x \in \sum^*} \{\alpha \wedge \tilde{\delta}^*((q, \mu^t(q)), x, q)\} \\ &= \alpha \wedge \bigvee_{x \in \sum^*} \{\tilde{\delta}^*((q, \mu^t(q)), x, q)\} = \alpha \wedge 1 = \alpha. \end{aligned}$$

□

Theorem 2.16. Let $\tilde{F}^* = (Q, \sum, \tilde{R}, Z, \omega, \tilde{\delta}^*, F_1, F_2)$ be a max-min general fuzzy automaton, $\alpha \in [0, 1]$, $q \in Q$, $\alpha \leq \lambda(q)$ and λ be a fuzzy subsystem of $\tilde{F}^*$. If λ be cyclic with generator q_α , then $\lambda(q) \geq \lambda(p)$, $\forall p \in Q$.

Proof. Let $p \in Q$. Since $\lambda = q_\alpha \sum^*$, then we have

$$\begin{aligned}
 \lambda(p) &= (q_\alpha \sum^*)(p) \\
 &= \bigvee_{x \in \sum^*} \{\alpha \wedge \tilde{\delta}^*((q, \mu^t(q)), x, p)\} \\
 &\leq \bigvee_{x \in \sum^*} \{\lambda(q) \wedge \tilde{\delta}^*((q, \mu^t(q)), x, p)\} \\
 &= \lambda(q) \wedge \bigvee_{x \in \sum^*} \{\tilde{\delta}^*((q, \mu^t(q)), x, p)\} \leq \lambda(q).
 \end{aligned}$$

□

Theorem 2.17. Let $\tilde{F}^* = (Q, \sum, \tilde{R}, Z, \omega, \tilde{\delta}^*, F_1, F_2)$ be a max-min general fuzzy automaton, $\alpha \in [0, 1]$, $q \in Q$, $\alpha \leq \lambda(q)$ and λ be a fuzzy subsystem of $\tilde{F}^*$. If λ be cyclic with generator q_α , then for any fuzzy subsystem λ' of $\tilde{F}^*$ such that $\lambda' \subseteq \lambda$ and $\lambda'(q) \geq \lambda'(r)$, $\forall r \in Q$, we have $\lambda' = q_{\lambda'(q)} \sum^*$.

Proof. Let $p \in Q$. Since $\lambda' \subseteq \lambda$, we have $\lambda'(p) \leq \lambda(p)$. Then $\lambda'(p) = \lambda'(p) \wedge \lambda(p)$. Also, since $\lambda = q_\alpha \sum^*$, then we have

$$\begin{aligned}
 \lambda(p) &= (q_\alpha \sum^*)(p) \\
 &= \bigvee_{x \in \sum^*} \{\alpha \wedge \tilde{\delta}^*((q, \mu^t(q)), x, p)\} \\
 &= \bigvee_{x \in \sum^*} \{\lambda(q) \wedge \tilde{\delta}^*((q, \mu^t(q)), x, p)\} \\
 &= \lambda(q) \wedge \bigvee_{x \in \sum^*} \{\tilde{\delta}^*((q, \mu^t(q)), x, p)\}.
 \end{aligned}$$

Hence

$$\begin{aligned}\lambda'(p) &= \lambda'(p) \wedge \lambda(p) \\ &= (\lambda'(p) \wedge \lambda(q)) \wedge \bigvee_{x \in \Sigma^*} \{\tilde{\delta}^*((q, \mu^t(q)), x, p)\}.\end{aligned}$$

Since $\lambda'(q) \geq \lambda'(p)$, then we have

$$\begin{aligned}\lambda'(p) &\leq (\lambda'(q) \wedge \lambda(q)) \wedge \bigvee_{x \in \Sigma^*} \{\tilde{\delta}^*((q, \mu^t(q)), x, p)\} \\ &= \lambda'(q) \wedge \bigvee_{x \in \Sigma^*} \{\tilde{\delta}^*((q, \mu^t(q)), x, p)\} \\ &= \bigvee_{x \in \Sigma^*} \{\lambda'(q) \wedge \tilde{\delta}^*((q, \mu^t(q)), x, p)\} = (q_{\lambda'(q)} \sum^*)(p).\end{aligned}$$

Therefore $\lambda' \subseteq q_{\lambda'(q)} \sum^*$. By Theorem 2.12, we have $\lambda' = q_{\lambda'(q)} \sum^*$. $\square$

3. Conclusion

In this paper, we have defined the notions of a successor of the state q and subautomaton of a max-min general fuzzy automaton. Then have defined a fuzzy subsystem of a max-min general fuzzy automaton. Finally, we have obtained the relationships between them.

References

- [1] M. Doostfatemeh and S. C. Kremer, New directions in fuzzy automata, International Journal of Approximate Reasoning 38(2) (2005), 175-214.
DOI: <https://doi.org/10.1016/j.ijar.2004.08.001>
- [2] J. Jin, Q. Li and Y. Li, Algebraic properties of L -fuzzy finite automata, Information Sciences 234 (2013), 182-202.
DOI: <https://doi.org/10.1016/j.ins.2013.01.018>

- [3] Y. Li and W. Pedrycz, Fuzzy finite automata and fuzzy regular expressions with membership values in lattice-ordered monoids, *Fuzzy Sets and Systems* 156(1) (2005), 68-92.
DOI: <https://doi.org/10.1016/j.fss.2005.04.004>
- [4] J. N. Mordeson and D. S. Malik, *Fuzzy Automata and Languages: Theory and Applications*, Chapman and Hall/CRC, London/Boca Raton, FL, 2002.
- [5] D. S. Malik, J. N. Mordeson and M. K. Sen, On subsystems of a fuzzy finite state machine, *Fuzzy Sets and Systems* 68(1) (1994), 83-92.
DOI: [https://doi.org/10.1016/0165-0114\(94\)90274-7](https://doi.org/10.1016/0165-0114(94)90274-7)
- [6] M. Mizumoto, J. Toyoda and K. Tanaka, Some considerations on fuzzy automata, *Journal of Computer and System Sciences* 3(4) (1969), 409-422.
DOI: [https://doi.org/10.1016/S0022-0000\(69\)80029-2](https://doi.org/10.1016/S0022-0000(69)80029-2)
- [7] C. L. Giles, C. W. Omlin and K. K. Thornber, Equivalence in knowledge representation: Automata, recurrent neural networks, and dynamical fuzzy systems, *Proceedings of the IEEE* 87(9) (1999), 1623-1640.
DOI: <https://doi.org/10.1109/5.784244>
- [8] C. W. Omlin, K. K. Thornber and C. L. Giles, Fuzzy finite-state automata can be deterministically encoded into recurrent neural networks, *IEEE Transactions on Fuzzy Systems* 6(1) (1998), 76-89.
DOI: <https://doi.org/10.1109/91.660809>
- [9] E. S. Santos, Realizations of fuzzy languages by probabilistic, max-product, and maximin automata, *Information Sciences* 8(1) (1975), 39-53.
DOI: [https://doi.org/10.1016/0020-0255\(75\)90004-3](https://doi.org/10.1016/0020-0255(75)90004-3)
- [10] W. G. Wee, On Generalizations of Adaptive Algorithms and Application of the Fuzzy Sets Concept to Pattern Classification, Ph.D. Dissertation Purdue University, IN, 1967.
- [11] M. M. Zahedi, M. Horry and Kh. Abolpor, Bifuzzy (general) topology on max-min general fuzzy automata, *Advances in Fuzzy Mathematics* 3(1) (2008), 51-68.