Electrochemical Preparation of Sub-micrometer Sn-Sb Alloy powder in ChCl-EG deep eutectic solvent

Zhaolei Su^{1,2}, Cunying Xu^{1,2,*}, Yixin Hua^{1,2}, Jian Li^{1,2}, Juanjian Ru^{1,2}, Mengmeng Wang^{1,2}, Li Xiong^{1,2}, Yadong Zhang^{1,2}

¹Faculty of Metallurgical and Energy Engineering, Kunming University of Science and Technology, Kunming 650093, P. R. China

²State Key Laboratory of Complex Nonferrous Metal Resources Cleaning Utilization, Kunming, 650093, P. R. China

*E-mail: xucunying@foxmail.com, xucunying@kmust.edu.cn

doi: 10.20964/101041

Received: 7 February 2016 / Accepted: 11 March 2016 / Published: 1 April 2016

The sub-micrometer Sn-Sb alloy powders were electrochemically prepared on a titanium substrate in choline chloride-ethylene glycol (ChCl-EG, 1:2 molar ratio) deep eutectic solvent containing 0.2 M SbCl₃ and 0.2 M SnCl₂. The electrochemical behaviors of Sb(III) and Sn(II) were investigated using cyclic voltammetry techniques. It revealed that the reduction of Sb(III) and Sn(II), as well as co-reduction of them in ChCl-EG involved the irreversible process controlled by diffusion. The diffusion coefficients of Sb(III) and Sn(II) species were in the range of 10⁻⁷ and 10⁻⁶ cm² s⁻¹, respectively. Potentiostatically deposited Sn-Sb alloys were characterized by inductively coupled plasma atomic emission spectrometry (ICP-AES), scanning electron microscopic (SEM) and X-ray diffraction (XRD). The deposition potential played an important role in controlling the composition, but had little effect on surface morphology. Depending on the deposition potential, sub-micrometer Sn-Sn alloy powders containing about 2.7–67.4 at.% Sn were obtained.

Keywords: Deep eutectic solvent; Sn-Sb alloy; Electrodeposition; Sub-micrometer.

[FULL TEXT](#)

© 2016 The Authors. Published by ESG (www.electrochemsci.org). This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution license (<http://creativecommons.org/licenses/by/4.0/>).