Comparative Study of Dye-Sensitized Solar Cell Utilizing Seaweed and Rose Bengal Sensitizer: Influence of Dye Concentration

M.J. Jimmy¹, A.M. Harun^{1,*}, M.Y.A. Rahman^{2,*}, N.A. Ludin³

¹ Faculty of Engineering, Universiti Malaysia Sabah, Jalan UMS, 88400, Kota Kinabalu, Sabah

² Institute of Microengineering and Nanoelectronics (IMEN), Universiti Kebangsaan Malaysia, 43600, Bangi, Selangor, Malaysia

³ Solar Energy Research Institute (SERI), Universiti Kebangsaan Malaysia, 43600, Bangi, Selangor, Malaysia

*E-mail: mukifza@ums.edu.my (A.M. Harun); mohd.yusri@ukm.edu.my (M.Y.A. Rahman)

doi: 10.20964/2020.04.44

Received: 6 December 2019 / Accepted: 20 January 2020 / Published: 10 March 2020

This work is concerned with the performance comparison study of dye-sensitized solar cell utilizing seaweed and rose bengal as dye-sensitizer. The influence of concentration of each dye on the optical absorption, photovoltaic performance and electrochemical impedance spectroscopy (EIS) data has been investigated. The 0.3 mM seaweed dye possesses the highest optical absorption. While, the 0.5 mM rose bengal dye exhibits the highest absorption in visible region. The DSSC utilizing the 0.3 mg/l seaweed dye produces the highest J_{sc} of 0.0183 mA cm⁻² due to the highest absorption in visible region and the lowest charge transfer resistance at the interface of Pt/electrolyte (R_{ct}). The device using 0.5 mM rose bengal dye demonstrates the highest J_{sc} that is 0.1436 mA cm⁻² due to the highest absorption in visible region and the lowest charge transfer resistance at the interface of Pt/electrolyte. In conclusions, the performance of the device with rose bengal dye is higher than that of the device using seaweed dye. This is because the charge carrier lifetime of the device with rose bengal dye is longer than that of the device with seaweed dye. The power conversion efficiency of the device using both dyes is low.

Keywords: dye, dye-sensitized solar cell, rose bengal, seaweed, titanium dioxide

[FULL TEXT](#)

© 2020 The Authors. Published by ESG (www.electrochemsci.org). This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution license (<http://creativecommons.org/licenses/by/4.0/>).