iJRASET

International Journal For Research in
Applied Science and Engineering Technology

INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 6 Issue: I Month of publication: January 2018

DOI: <http://doi.org/10.22214/ijraset.2018.1352>

www.ijraset.com

Call: ☎ 08813907089

E-mail ID: ijraset@gmail.com

Fuzzy Matrix with Application in Automata

J. Vimala¹, P. Elavarasi², C.Venkatesan³

¹Assistant Professor, Department of Mathematics, Srinivasan College of Arts and Science, Perambalur.

²Assistant Professor, Department of Mathematics, Dhanalakshmi Srinivasan College of Arts and Science for Woman, Perambalur.

³Associate Professor, Meenakshi Academy of Higher Education and Research, Faculty of Engineering and Technology, Chennai.

Abstract: A sequential machine is a dynamic system operating in discrete time that transforms sequence of input states received at the input of the system to sequence of output states produced at the output of the system. The produce large sequence of fuzzy internal states and output states for any given sequences of fuzzy input states of a fuzzy automation.

Keywords: Fuzzy internal states, Fuzzy automation, Transition relation, Fuzzy input and output state

I. INTRODUCTION

The sequences may be finite (or) count ably infinite. The transformation is accomplished by the concept of the dynamically changing interval state. At the same time, a new internal state is determined, which replaces its predecessor. The new internal state is stored in the system to be used subsequently. A finite state machine is called fuzzy automata when its states are characterized by fuzzy sets, the production of responses and next states is facilitated by suitable fuzzy relations.

II. PRELIMINARIES

A. Definition 3.1 Fuzzy Matrices

Let F_{mn} denote the set of all $m \times n$ matrices over F . If $m = n$, we write F_n . Elements of F_{mn} are called as membership value matrices binary fuzzy relation matrices (or) Fuzzy Matrices. Boolean matrices over the Boolean algebra $\{0,1\}$ are special types of fuzzy matrices.

B. Definition 3.2 Multiplication on Fuzzy Matrices

Let $A = (a_{ij}) \in F_{mp}$ and $B = (b_{ij}) \in F_{pn}$.

The max - min product

$$AB = \left(\sup_k \{ \inf \{ a_{ik}, b_{kj} \} \} \right) \in F_{mn}$$

The product AB is defined if and only if the number of column of A is the same as the number of rows of B ; A and B are said to be conformable for Multiplication.

1) Example

$$\text{Let } A = \begin{bmatrix} 0.8 & 0.1 \\ 0.2 & 0.7 \end{bmatrix} \text{ and } B = \begin{bmatrix} 0.6 & 0.5 \\ 0.4 & 0.3 \end{bmatrix}$$

Find AB .

2) Solution

$$AB = \begin{bmatrix} [0.8 \ 0.1] \begin{bmatrix} 0.6 \\ 0.4 \end{bmatrix} & [0.8 \ 0.1] \begin{bmatrix} 0.5 \\ 0.3 \end{bmatrix} \\ [0.2 \ 0.7] \begin{bmatrix} 0.6 \\ 0.4 \end{bmatrix} & [0.2 \ 0.7] \begin{bmatrix} 0.5 \\ 0.3 \end{bmatrix} \end{bmatrix}$$

$$= \begin{bmatrix} \text{Sup}\{\inf\{0.8,0.6\}, \inf\{0.1,0.4\} & \text{Sup}\{\inf\{0.8,0.5\}, \inf\{0.1,0.3\}\} \\ \text{Sup}\{\inf\{0.2,0.6\}, \inf\{0.7,0.4\} & \text{Sup}\{\inf\{0.2,0.5\}, \inf\{0.7,0.3\}\} \end{bmatrix}$$

$$= \begin{bmatrix} \text{Sup}\{0.6,0.1\} & \text{Sup}\{0.5,0.1\} \\ \text{Sup}\{0.2,0.4\} & \text{Sup}\{0.2,0.3\} \end{bmatrix}$$

$$AB = \begin{bmatrix} 0.6 & 0.5 \\ 0.4 & 0.3 \end{bmatrix}$$

C. Definition 3.3 Fuzzy Automata

A finite fuzzy automation A is a fuzzy relational system defined by the quintuple $A = \langle X, Y, Z, R, S \rangle$

where

X is a non- empty finite set of input states

Y is a non- empty finite set of output states

Z is a non- empty finite set of internal states

R is a fuzzy relation on $X \times Y$

S is a fuzzy relation on $X \times Y \times Z$

III. DERIVATION

Let us consider $X = \{x_1, x_2, \dots, x_{n-1}, x_n\}$, $Y = \{y_1, y_2, \dots, y_{n-1}, y_n\}$ and $Z = \{z_1, z_2, \dots, z_{n-1}, z_n\}$ as the set of input states, output states and internal states respectively. Let A_t, B_t, C_t and E_t denote the fuzzy sets that characterize respectively, the stimulus response, response, current internal state and emerging internal state (next state) of the automation at time t. Given A_t and C_t at some time t, then by using fuzzy relations R and S, we can determine B_t and E_t . Clearly $A_t \in F(X)$, $B_t \in F(Y)$ and $C_t, E_t \in F(Z)$. Where $F(\cdot)$ is the set of fuzzy sets on the set $(\cdot)$. A fuzzy set C_1 which characterizes the initial state must be given to make fuzzy automation operate. Then $C_t = E_{t-1}$ for each time $t \in N - \{1\}$. The equation $C_t = E_{t-1}$ is assumed to be implemented by the block called storage. Its role is to store the produced fuzzy set E_t at time t and release it the next time under the label C_t . Given a sequence $A_1, A_2, \dots$ and an initial characterization C_1 of the internal state, fuzzy response relation R and state transition relation δ allow us to generate the corresponding sequences $B_1, B_2, \dots$ and $C_2=E_1, C_3=E_2$. Now let us describe the operator of a fuzzy automation as follows. For any given fuzzy input state A_t , the ternary state – transition relation δ is converted into a binary relation δ_{A_t} on $Z \times Z$ by the formula

$$\delta_{A_t}(z_i, z_j) = \max_{k \in N_n} (\min[A_t(x_k), \delta_{x_k}(z_i, z_j)]) \quad \dots (1)$$

Then assuming the present fuzzy state C_t is given. The fuzzy next state E_t and the fuzzy output state B_t are determined by the max-min compositions

$$E_t = C_t \delta_{A_t} \text{ and } B_t = C_t R \quad \dots (2)$$

Equations (1) and (2) are sufficient to handle the sequences of fuzzy states. For instance a sequence $A_1, A_2, \dots, A_r$ of r- fuzzy input state applied to a given initial fuzzy state C_1 , the fuzzy automata produces the sequence of fuzzy internal states.

$$E_1 = C_1 \delta_{A_1}, E_2 = E_1 \delta_{A_2} \text{ and } E_r = E_{r-1} \delta_{A_r}$$

Thus $E_r = C_1 \delta_{A_1} \dots \delta_{A_r}$. The corresponding sequence of fuzzy output states

$$B_1 = C_1 R, B_2 = E_1 R \text{ and } B_r = E_{r-1} R$$

$$\text{Thus } B_r = C_1 \delta_{A_1}, \delta_{A_2}, \dots \delta_{A_{r-1}} \cdot R.$$

IV. ILLUSTRATIVE EXAMPLE

Consider a fuzzy automation with $x = \{x_1, x_2\}$, $y = \{y_1, y_2, y_3\}$ and $z = \{z_1, z_2, z_3, z_4\}$ whose output relation

$$y_1 \quad y_2 \quad y_3 R = \begin{matrix} z_1 \\ z_2 \\ z_3 \\ z_4 \end{matrix} \begin{bmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \\ 0.5 & 1 & 0.3 \end{bmatrix}$$

State transition relation δ are defined by the following matrices respectively for the input states x_1 and x_2 .

$$\delta_{A1}(z_i, z_j) = \begin{matrix} z_1 & z_2 & z_3 & z_4 \\ \begin{matrix} z_1 \\ z_2 \\ z_3 \\ z_4 \end{matrix} \end{matrix} \begin{bmatrix} 0 & 0.4 & 0.2 & 1 \\ 0.3 & 1 & 0 & 0.2 \\ 0.5 & 0 & 0 & 1 \\ 0 & 0 & 0 & 1 \end{bmatrix}$$

$$\delta_{A2}(z_i, z_j) = \begin{matrix} z_1 \\ z_2 \\ z_3 \\ z_4 \end{matrix} \begin{bmatrix} 0 & 0 & 1 & 0 \\ 0.2 & 0 & 0 & 1 \\ 0 & 0 & 0 & 1 \\ 1 & 0.3 & 0 & 0.6 \end{bmatrix}$$

Generate sequence of two fuzzy initial states and output states under the following conditions:

The initial fuzzy states is $C_1 = [1, 0.8, 0.6, 0.4]$ the input fuzzy states are $A_1 = [1, 0.4]$ and $A_2 = [0, 1]$.

Solution: Let us assume that the initial state of the automation is $C_1 = [1, 0.8, 0.6, 0.4]$ and fuzzy input $A_1 = [1, 0.4]$ is given.

By using the equation

$$\delta_{At}(z_i, z_j) = \max_{k \in \{1, 2\}} (\min[A_t(x_k), \delta_k(z_i, z_j)])$$

Let us compute the equation δ_{A1}

$$\begin{aligned} \delta_{A1}(z_1, z_1) &= \max\{\min[A_1(x_1), \delta_{x1}(z_1, z_1)], \min[A_1(x_2), \delta_{x2}(z_1, z_1)]\} \\ &= \max\{\min(1, 0), \min(0.4, 0)\} \\ &= 0 \\ \delta_{A1}(z_1, z_2) &= \max\{\min[A_1(x_1), \delta_{x1}(z_1, z_2)], \min[A_1(x_2), \delta_{x2}(z_1, z_2)]\} \\ &= \max\{\min(1, 0.4), \min(0.4, 0)\} \\ &= 0.4 \\ \delta_{A1}(z_1, z_3) &= \max\{\min[A_1(x_1), \delta_{x1}(z_1, z_3)], \min[A_1(x_2), \delta_{x2}(z_1, z_3)]\} \\ &= \max\{\min(1, 0.2), \min(0.4, 1)\} \\ &= 0.4 \\ \delta_{A1}(z_1, z_4) &= \max\{\min[A_1(x_1), \delta_{x1}(z_1, z_4)], \min[A_1(x_2), \delta_{x2}(z_1, z_4)]\} \\ &= \max\{\min(1, 1), \min(0.4, 0)\} \\ &= 1 \end{aligned}$$

Thus the First row of δ_{A1} is $[0 \quad 0.4 \quad 0.4 \quad 1]$

$$\begin{aligned} \delta_{A1}(z_2, z_1) &= \max\{\min[A_1(x_1), \delta_{x1}(z_2, z_1)], \min[A_1(x_2), \delta_{x2}(z_2, z_1)]\} \\ &= \max\{\min(1, 0.3), \min(0.4, 0.2)\} \\ &= 0.3 \\ \delta_{A1}(z_2, z_2) &= \max\{\min[A_1(x_1), \delta_{x1}(z_2, z_2)], \min[A_1(x_2), \delta_{x2}(z_2, z_2)]\} \\ &= \max\{\min(1, 1), \min(0.4, 0)\} \\ &= 1 \\ \delta_{A1}(z_2, z_3) &= \max\{\min[A_1(x_1), \delta_{x1}(z_2, z_3)], \min[A_1(x_2), \delta_{x2}(z_2, z_3)]\} \\ &= \max\{\min(1, 0), \min(0.4, 0)\} \end{aligned}$$

$$\begin{aligned}
 &= 0 \\
 \delta_{A1}(z_2, z_4) &= \max\{\min[A_1(x_1), \delta_{x1}(z_2, z_4)], \min[A_1(x_2), \delta_{x2}(z_2, z_4)]\} \\
 &= \max\{\min(1, 0.2), \min(0.4, 1)\} \\
 &= 0.4
 \end{aligned}$$

Thus the Second row of δ_{A1} is [0.3 1 0 0.4]

$$\begin{aligned}
 \delta_{A1}(z_3, z_1) &= \max\{\min[A_1(x_1), \delta_{x1}(z_3, z_1)], \min[A_1(x_2), \delta_{x2}(z_3, z_1)]\} \\
 &= \max\{\min(1, 0.5), \min(0.4, 0)\} \\
 &= 0.5
 \end{aligned}$$

$$\begin{aligned}
 \delta_{A1}(z_3, z_2) &= \max\{\min[A_1(x_1), \delta_{x1}(z_3, z_2)], \min[A_1(x_2), \delta_{x2}(z_3, z_2)]\} \\
 &= \max\{\min(1, 0), \min(0.4, 0)\} \\
 &= 0
 \end{aligned}$$

$$\begin{aligned}
 \delta_{A1}(z_3, z_3) &= \max\{\min[A_1(x_1), \delta_{x1}(z_3, z_3)], \min[A_1(x_2), \delta_{x2}(z_3, z_3)]\} \\
 &= \max\{\min(1, 0), \min(0.4, 0)\} \\
 &= 0
 \end{aligned}$$

$$\begin{aligned}
 \delta_{A1}(z_3, z_4) &= \max\{\min[A_1(x_1), \delta_{x1}(z_3, z_4)], \min[A_1(x_2), \delta_{x2}(z_3, z_4)]\} \\
 &= \max\{\min(1, 1), \min(0.4, 1)\} \\
 &= 1
 \end{aligned}$$

Thus the Third row of δ_{A1} is [0.5 0 0 1]

$$\begin{aligned}
 \delta_{A1}(z_4, z_1) &= \max\{\min[A_1(x_1), \delta_{x1}(z_4, z_1)], \min[A_1(x_2), \delta_{x2}(z_4, z_1)]\} \\
 &= \max\{\min(1, 0), \min(0.4, 1)\} \\
 &= 0.4
 \end{aligned}$$

$$\begin{aligned}
 \delta_{A1}(z_4, z_2) &= \max\{\min[A_1(x_1), \delta_{x1}(z_4, z_2)], \min[A_1(x_2), \delta_{x2}(z_4, z_2)]\} \\
 &= \max\{\min(1, 0), \min(0.4, 0.3)\} \\
 &= 0.3
 \end{aligned}$$

$$\begin{aligned}
 \delta_{A1}(z_4, z_3) &= \max\{\min[A_1(x_1), \delta_{x1}(z_4, z_3)], \min[A_1(x_2), \delta_{x2}(z_4, z_3)]\} \\
 &= \max\{\min(1, 0), \min(0.4, 0)\} \\
 &= 0
 \end{aligned}$$

$$\begin{aligned}
 \delta_{A1}(z_4, z_4) &= \max\{\min[A_1(x_1), \delta_{x1}(z_4, z_4)], \min[A_1(x_2), \delta_{x2}(z_4, z_4)]\} \\
 &= \max\{\min(1, 1), \min(0.4, 0.6)\} \\
 &= 1
 \end{aligned}$$

Thus the Last row of δ_{A1} is [0.4 0.3 0 1]

The matrix δ_{A1} is

$$\delta_{A1} = \begin{bmatrix} 0 & 0.4 & 0.4 & 1 \\ 0.3 & 1 & 0 & 0.4 \\ 0.5 & 0 & 0 & 1 \\ 0.4 & 0.3 & 0 & 1 \end{bmatrix}$$

To calculate the fuzzy next set E_1 and the fuzzy output state B_1 of the automation

$$E_1 = C_1 \cdot \delta_{A1}$$

$$= [1 \quad 0.8 \quad 0.6 \quad 0.4] \begin{bmatrix} 0 & 0.4 & 0.4 & 1 \\ 0.3 & 1 & 0 & 0.4 \\ 0.5 & 0 & 0 & 1 \\ 0.4 & 0.3 & 0 & 1 \end{bmatrix}$$

$$E_1 = [\max(0, 0.3, 0.5, 0.4) \quad \max(0.4, 0.8, 0, 0.3) \quad \max(0.4, 0, 0, 0) \quad \max(1, 0.4, 0.6, 0.4)]$$

$$E_1 = [0.5 \quad 0.8 \quad 0.4 \quad 1]$$

$$B_1 = C_1 \cdot R$$

$$= [1 \quad 0.8 \quad 0.6 \quad 0.4] \begin{bmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 0 \\ 0.5 & 1 & 0.3 \end{bmatrix}$$

$$= [\max(1, 0, 0, 0.4) \quad \max(0, 0.8, 0, 0.4) \quad \max(0, 0, 0.6, 0.3)]$$

$$B_1 = [1 \ 0.8 \ 0.6]$$

Assume that the next fuzzy input state $A_2 = [0,1]$ is given.

By using the equation

$$\delta_{A_2}(z_i, z_j) = \max_{k \in \{1,2\}} (\min[A_2(x_k), \delta_{xk}(z_i, z_j)])$$

Let us compute the equation

$$\begin{aligned} \delta_{A_2}(z_1, z_1) &= \max\{\min[A_2(x_1), \delta_{x1}(z_1, z_1)], \min[A_2(x_2), \delta_{x2}(z_1, z_1)]\} \\ &= \max\{\min(0,0), \min(1,0)\} \end{aligned}$$

$$= 0$$

$$\begin{aligned} \delta_{A_2}(z_1, z_2) &= \max\{\min[A_2(x_1), \delta_{x1}(z_1, z_2)], \min[A_2(x_2), \delta_{x2}(z_1, z_2)]\} \\ &= \max\{\min(0,0.4), \min(1,0)\} \\ &= \max\{0,0\} \end{aligned}$$

$$= 0$$

$$\begin{aligned} \delta_{A_2}(z_1, z_3) &= \max\{\min[A_2(x_1), \delta_{x1}(z_1, z_3)], \min[A_2(x_2), \delta_{x2}(z_1, z_3)]\} \\ &= \max\{\min(0,0.2), \min(1,1)\} \end{aligned}$$

$$= 1$$

$$\begin{aligned} \delta_{A_2}(z_1, z_4) &= \max\{\min[A_2(x_1), \delta_{x1}(z_1, z_4)], \min[A_2(x_2), \delta_{x2}(z_1, z_4)]\} \\ &= \max\{\min(0,1), \min(1,0)\} \end{aligned}$$

$$= 0$$

Thus the First row of δ_{A_2} is $[0 \ 0 \ 1 \ 0]$

$$\begin{aligned} \delta_{A_2}(z_2, z_1) &= \max\{\min[A_2(x_1), \delta_{x1}(z_2, z_1)], \min[A_2(x_2), \delta_{x2}(z_2, z_1)]\} \\ &= \max\{\min(0,0.3), \min(1,0.2)\} \end{aligned}$$

$$= 0.2$$

$$\begin{aligned} \delta_{A_2}(z_2, z_2) &= \max\{\min[A_2(x_1), \delta_{x1}(z_2, z_2)], \min[A_2(x_2), \delta_{x2}(z_2, z_2)]\} \\ &= \max\{\min(0,1), \min(1,0)\} \end{aligned}$$

$$= 0$$

$$\begin{aligned} \delta_{A_2}(z_2, z_3) &= \max\{\min[A_2(x_1), \delta_{x1}(z_2, z_3)], \min[A_2(x_2), \delta_{x2}(z_2, z_3)]\} \\ &= \max\{\min(0,0), \min(1,0)\} \end{aligned}$$

$$= 0$$

$$\begin{aligned} \delta_{A_2}(z_2, z_4) &= \max\{\min[A_2(x_1), \delta_{x1}(z_2, z_4)], \min[A_2(x_2), \delta_{x2}(z_2, z_4)]\} \\ &= \max\{\min(0,0.2), \min(1,1)\} \end{aligned}$$

$$= 1$$

Thus the Second row of δ_{A_2} is $[0.2 \ 0 \ 0 \ 1]$

$$\begin{aligned} \delta_{A_2}(z_3, z_1) &= \max\{\min[A_2(x_1), \delta_{x1}(z_3, z_1)], \min[A_2(x_2), \delta_{x2}(z_3, z_1)]\} \\ &= \max\{\min(0,0.5), \min(1,0)\} \end{aligned}$$

$$= 0$$

$$\begin{aligned} \delta_{A_2}(z_3, z_2) &= \max\{\min[A_2(x_1), \delta_{x1}(z_3, z_2)], \min[A_2(x_2), \delta_{x2}(z_3, z_2)]\} \\ &= \max\{\min(0,0), \min(1,0)\} \end{aligned}$$

$$= 0$$

$$\begin{aligned} \delta_{A_2}(z_3, z_3) &= \max\{\min[A_2(x_1), \delta_{x1}(z_3, z_3)], \min[A_2(x_2), \delta_{x2}(z_3, z_3)]\} \\ &= \max\{\min(0,0), \min(1,0)\} \end{aligned}$$

$$= 0$$

$$\begin{aligned} \delta_{A_2}(z_3, z_4) &= \max\{\min[A_2(x_1), \delta_{x1}(z_3, z_4)], \min[A_2(x_2), \delta_{x2}(z_3, z_4)]\} \\ &= \max\{\min(0,1), \min(1,1)\} \end{aligned}$$

$$= 1$$

Thus the Third row of δ_{A_2} is $[0 \ 0 \ 0 \ 1]$

$$\begin{aligned}\delta_{A2}(z_4, z_1) &= \max\{\min[A_2(x_1), \delta_{x1}(z_4, z_1)], \min[A_2(x_2), \delta_{x2}(z_4, z_1)]\} \\ &= \max\{\min(0,0), \min(1,1)\} \\ &= 1\end{aligned}$$

$$\begin{aligned}\delta_{A2}(z_4, z_2) &= \max\{\min[A_2(x_1), \delta_{x1}(z_4, z_2)], \min[A_2(x_2), \delta_{x2}(z_4, z_2)]\} \\ &= \max\{\min(0,0), \min(1,0.3)\} \\ &= 0.3\end{aligned}$$

$$\begin{aligned}\delta_{A2}(z_4, z_3) &= \max\{\min[A_2(x_1), \delta_{x1}(z_4, z_3)], \min[A_2(x_2), \delta_{x2}(z_4, z_3)]\} \\ &= \max\{\min(0,0), \min(1,0)\} \\ &= 0\end{aligned}$$

$$\begin{aligned}\delta_{A2}(z_4, z_4) &= \max\{\min[A_2(x_1), \delta_{x1}(z_4, z_4)], \min[A_2(x_2), \delta_{x2}(z_4, z_4)]\} \\ &= \max\{\min(0,1), \min(1,0.6)\} \\ &= 0.6\end{aligned}$$

Thus the Last row of δ_{A2} is [1 0.3 0 0.6]

The matrix δ_{A2} is

$$\delta_{A2} = \begin{bmatrix} 0 & 0 & 1 & 0 \\ 0.2 & 0 & 0 & 1 \\ 0 & 0 & 0 & 1 \\ 1 & 0.3 & 0 & 0.6 \end{bmatrix}$$

To calculate the fuzzy next set E_2 and the fuzzy output state B_2 of the automation

$$E_2 = C_2 \cdot \delta_{A2} = E_1 \cdot \delta_{A2}$$

$$= [0.5 \quad 0.8 \quad 0.4 \quad 1] \begin{bmatrix} 0 & 0 & 1 & 0 \\ 0.2 & 0 & 0 & 1 \\ 0 & 0 & 0 & 1 \\ 1 & 0.3 & 0 & 0.6 \end{bmatrix}$$

$$E_2 = [\max(0,0.2,1) \max(0,0,0,0.3) \max(0.5,0,0,0) \max(0,0.8,0.4,0.6)]$$

$$E_2 = [1 \quad 0.3 \quad 0.5 \quad 0.8]$$

$$B_2 = E_1 \cdot R$$

$$= [0.5 \quad 0.8 \quad 0.4 \quad 1] \begin{bmatrix} 1 & 0 & 1 \\ 0 & 1 & 0 \\ 0 & 0 & 0 \\ 0.5 & 1 & 0.3 \end{bmatrix}$$

$$= [\max(0.5, 0, 0, 0.5) \max(0, 0.8, 0, 1) \max(0, 0, 0.4, 0.3)]$$

$$B_2 = [0.5 \quad 1 \quad 0.4]$$

Similarly we can produce large sequence of fuzzy internal states and output states for any given sequences of fuzzy input states of a fuzzy automation.

V. CONCLUSION

The response of the system depends on the basis of the received stimulus and the internal state of the system, which in-turn results in a new internal state. The fuzzy automaton when characterized by fuzzy sets, the production of responses and next states are facilitated by suitable fuzzy relations.

BIBLIOGRAPHY

- [1] Meenakshi .A.R(2008), "Fuzzy Matrix" Theory and Application, MJP publishers.
- [2] Bellman.R. and Zadeh.L.A. - "Decision making in a fuzzy environment." Management Science.
- [3] George J.Klir/Bo Yuan (2005) - "Fuzzy sets and Fuzzy Logic" Theory and Applications, prentice hall of India Private limited.
- [4] Kim, K.H and Roush, F.W - "Generalized fuzzy matrices." Fuzzy Sets Sys.
- [5] Meenakshmi.A.R. and Sriram,S (2003)- "Some Remakrs on Regular Fuzzy matrices" Annamalai University, Science Journal.
- [6] Mizumoto - Fuzzy Theory and its Applications. Science Publications.
- [7] M. Shimura, Fuzzy sets concept in rank ordering objects, J. Math. Anal.1 Appl., 43 (1973),
- [8] S. Elizabeth and L. Sujatha - Application Of Fuzzy Membership Matrix In Medical Diagnosis And Decision Making.
- [9] M. Shimura(1973) Fuzzy sets concept in rank ordering objects, J. Math. Anal. 1.Appl.,

- [10] Palaniyappan.N2005 - "Fuzzy topology" Second Edition, Narosa publishing house, on Allied Publishers Ltd, New Delhi.
- [11] Vasantha Kandasamy.W.B- "Elementary Fuzzy Matrix" Theory and Fuzzy models for social scientists, University of Microfilm International, USA.
- [12] Vasantha.W.B. Kandasamy "Elementary Fuzzy matrix theory and fuzzy models for social scientist"
- [13] Zimmermann.H.J – "Fuzzy set theory and its Applications", 2nd edition.

10.22214/IJRASET

45.98

IMPACT FACTOR:
7.129

IMPACT FACTOR:
7.429

INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 (24*7 Support on Whatsapp)