iJRASET

International Journal For Research in
Applied Science and Engineering Technology

INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 6 Issue: IV Month of publication: April 2018

DOI: <http://doi.org/10.22214/ijraset.2018.4091>

www.ijraset.com

Call: ☎ 08813907089

E-mail ID: ijraset@gmail.com

Mine Blast Algorithm

Gurasis Singh¹, Prabhdeep Kaur²

¹Department of Computer Science Guru Nanak Dev University College Jalandhar, Punjab

²Department of Computer Science CT Institute of Engineering and Management Technology Jalandhar, Punjab

Abstract: Optimization is technique by which we can do our work in most efficient way as possible. This can be achieved by reducing no. of calculations in particular algorithm or reducing work done in any of the task. Mine blast algorithm is a new optimization algorithm which is population based algorithm for solving constrained engineering problems. Computational effort that is number of evaluating functions are less and the results of the computations are perfect. More than fifteen constrained problems are solved by Mine blast algorithm and results are more accurate. An introduction and detail about the algorithm as well as one application which is using mine blast for optimum results is also described in detail. The name of the application is speed reducer problem in which the mine blast algorithm is used to get the optimal results of the parameters which are optimal if we get as less value as we can. This result is compared with various other algorithms and hence mine blast algorithm proved to be most efficient in giving optimal results.

I. INTRODUCTION

Mine Blast Algorithm is an optimization algorithm that is used to solve many constrained engineering problems. over the period of time many algorithms had been introduced but this algorithms is proven to give the better results then the other algorithms. This algorithm is novel population –based algorithm. Many algorithms had came that uses on the gradient information for the evaluation, less information leads to inaccurate results and more of the function evaluation. The target of optimization technique is to reduce time, computations, inaccuracy, parameters on which algorithms are based upon.

In this algorithm the concept of mine blast explosion is used.

The main concept is that when the mine blast in real world its shrapnel pieces are spread in different direction with different speed and time and the next is exploded when the shrapnel collide with next mine within a specified area. The initial population is produced when the first mine is blasted. Lets assume a situation in which there is a mine field in which there are so many mines plotted under the ground and to clean up the mine field is the main purpose. One optimal point is taken in the starting where the first mine is blasted and the shrapnel of that mine will lead to blast the other mines proceeding in this direction we will get next optimal point. The first optimal point from where the maximum causalities caused is denoted as X^* and the causalities caused are defined by min and max function ($f(x)$) per X^* . Bombs of different sizes and powers are pointed under the ground. When a mine bomb is exploded many of its shrapnel pieces causes the causalities which are calculated as the direction and distance of each shrapnel is different. One shrapnel can cause many causalities that indicates the explosive power of that bomb. These will lead to the clearance of the mine field. The solution domain is field divided into the grids.

II. RELATED WORK

Mine Blast Algorithm provides the accuracy in results and leads to less function evaluations and the work is done in a specified domain.

Algorithm have an initial point is the starting where the first mine is blasted known as the initial point or first shot point.

It is denoted as the X_{f0} .

f is number of first shot points(1,2,3,4...) and it is a user defined parameter.

The population is generated by the first shot explosion which is denoted as the initial population(N_{pop}) and that is number of shrapnel(N_s). In this algorithm have lower and upper bound values which are provided in the problem. Now, the first shot point is calculated by the Equation (1):

$$X_0 = LB + rand * (UB - LB)$$

Where X_0 , LB and UB are first shot point, lower bound, upper bound and rand is uniformly distributed random number between 0 and 1.

Now, the Equation (2):

$$X = \{X_m\}, m=1,2,3,\dots,N_d$$

N_d is search space dimension which is equal to number of independent variables. Now, the location of another mine bomb is given by Equation(3):

$$X_{n+1}^f = X_{e(n+1)}^f + \exp\left(-\sqrt{\frac{m_{n+1}^f}{d_{n+1}^f}}\right) X_n^f, \quad n=0,1,2,3,\dots \quad (3)$$

D is distance, m is distance. now the location of exploding bomb is given by Equation(4):

$$X_{e(n+1)}^f = d_n^f \times \text{rand} \times \cos(\Theta), \quad n=0,1,2,\dots \quad (4)$$

D is the distance to find next optimal point, theta is angle of the shrapnel pieces and is calculated as $360/N_s$. The distance and the direction of the shrapnel is calculated by Equation(5) and Equation(6):

$$d_{n+1}^f = \sqrt{(X_{n+1}^f - X_n^f)^2 + (F_{n+1}^f - F_n^f)^2} \quad n=0,1,2,3 \dots \quad (5)$$

$$m_{n+1}^f = \frac{F_{n+1}^f + F_n^f}{X_{n+1}^f - X_n^f}, \quad n=0,1,2,3,\dots \quad (6)$$

F is the function value for the X . To check the exploration that is the range of the area or space smaller and larger

Fig 1: Exploration area of mines when the mines are blasted.

distances the exploration factor(u) is used. The condition on the exploration factor is checked as:

If($u > k$)

Exploration(Equation(7) and(8))

Else

Exploration(Equation(4)(6) and(9))

End

K is iteration number index. for the solution space the Equation(7)and (8):

$$d_{n+1}^f = d_n^f \times (|\text{randn}|)^2, \quad n=0,1,2,\dots \quad (7)$$

$$X_{e(n+1)}^f = d_{n+1}^f \times \cos(\Theta), \quad n=0,1,2 \dots \quad (8)$$

For the more accurate and rapid search we need to decrease the area is calculated by the Equation(9):

$$d_n^f = \frac{d_{n-1}^f}{\exp\left(\frac{k}{\alpha}\right)}, \quad n=1,2,3,\dots \quad (9)$$

These were the parameters and the equations used in this algorithm. the functions of every equation is given below:

Equation(1): First shot point value.

Equation(2):current location of mine bomb

Equation(3):location of another mine

Equation(4):location of another mine to be used in previous equation

Equation(5):distance of shrapnel

Equation(6):direction of shrapnel pieces

Equation(7):new distance can be smaller or larger

Equation(8):new location of another mine bomb

Rule 4: if there are two infeasible solutions then the solution with smaller sum of constraints is preferred

521

subsystems for this problem, gears and shafts. Stress, geometric and deflection are the various constraints involved. The weight of the speed reducer includes both the weight of the gears as well as the weight of the shafts.

Fig 3. Cylindrical fin heat sink.

IV. PROBLEM DEFINITION

The objective of Golinski's Speed Reducer problem is to find the minimum of a gear box volume f (and, hence, its minimum weight), subject to several constraints. There are seven design variables, $x1 - x7$, which represent

- $x1$ width of the gear face, cm
- $x2$ teeth module, cm
- $x3$ number of pinion teeth
- $x4$ shaft 1 length between bearings, cm
- $x5$ shaft 2 length between bearings, cm
- $x6$ diameter of shaft 1, cm
- $x7$ diameter of shaft 2, cm

Mathematically, the problem is specified as follows:

minimize f , given by:

$$f = c_{f1}x_1x_2^2(c_{f2}x_3^2 + c_{f3}x_3 - c_{f4}) - c_{f5}(x_6^2 + x_7^2)x_1 + c_{f6}(x_6^3 + x_7^3) + c_{f1}(x_4x_6^2 + x_5x_7^2)$$

where the constants are:

$$c_{f1}=0.7854, c_{f2}= 3.333, c_{f3}=14.9334, c_{f4}=43.0934, c_{f5}=1.5079, c_{f6}=7.477$$

and the seven variables with their lower and upper limits are

$$2.6 \leq x_1 \leq 3.6, 0.7 \leq x_2 \leq 0.8, 17 \leq x_3 \leq 28, 7.3 \leq x_4 \leq 8.3,$$

$$7.3 \leq x_5 \leq 8.3, 2.9 \leq x_6 \leq 3.9, 5.0 \leq x_7 \leq 5.5$$

The constraints can be characterized by

- $g1$ upper bound on the bending stress of the gear tooth
- $g2$ upper bound on the contact stress of the gear tooth

- g_3, g_4 upper bounds on the transverse deflection of shafts 1, 2
- g_5, g_6 upper bounds on the stresses in shafts 1, 2
- g_7 - g_{23} dimensional restrictions based on space and experience
- g_{24}, g_{25} dimensional requirements for shafts based on experience

V. RESULTS

The speed reducer problem is used in many other types of applications and is one of the standard benchmark problems in structural optimization. Although many metaheuristic algorithms have been developed to solve this problem, these methods cannot guarantee global optimality of the solution. However, numerous break points are utilized in the linearization process for reaching an approximate global solution with a low error, and much CPU time is required to solve the reformulated model. Therefore, this study also adopts the range reduction technique to enhance the computational efficiency. Compared with metaheuristic methods, this study guarantees the global optimality of the solution. Compared with other deterministic methods, this study obtains a better solution with a lower error in constraint.

Table 2: shows the number of iterations and the corresponding function values.

Fig 4: implementation of the mine blast algorithm in matlab.

Fig 5: Showing the values of the functions.

Fig:6: Showing the values of various functions of number of function evaluation.

Hence the mine blast proved to give most efficient results in this application. As compared to other algorithm most optimum results are given by the mine blast algorithm.

VI. FUTURE SCOPE

A. Specified Domain

The exploration area can improved by making the particular domain for the search and efficient results. The exploration factor (u) having the random variable rand , it can be double so that the more area is covered under the search. It will offer the greater extent for research. When the mine bomb is blasted the shrapnel spread in many directions and reaching to the next optimal point so therefore there are more than one path to reach to the optimal point so the both the distances should be calculated and the distance having the minimum value is chosen to reach to that point and the algorithm's exploration area can be much improved in this manner making the algorithm more accurate.

B. Improve Positioning

The prediction of other mines can be done as the when the distance between two mines are calculated. The distance of other mine can be predicted. The position of the optimal points can be chosen more wisely therefore decreasing the difference and increasing the accuracy of the algorithm as it an optimization algorithm aiming at minimizing the results that is being used in the applications. The optimization means to decrease the work load and get the most optimum results as it can therefore if we improve the positioning of optimal points then the calculations will become easy and the will give more accurate and optimum results for various applications.

VII. CONCLUSION

This paper presents the method and procedure of mine blast algorithm. The algorithm have very less number of function evaluation and the accuracy is more in the results. The basic concept of the algorithm is explosion of the mines in mine field and the main aim is to clear the mine field. Many iterations are carried out in this algorithm so as to get accurate and efficient results. The algorithm consists of 12 steps in which various equations are used which are easy to execute. more than fifteen constrained optimization and engineering problems are being solved and the results obtained by them gives better solutions than other optimizers terms of number of function evaluation (computational cost) and objective function for every problem. The quality of solution and computational efficiency obtained by Mine Blast Algorithm depends on the nature and complexity of underlined problem and is true for most meta heuristic methods.

REFERENCES

- [1] Rajeev S, Krishnamoorthy CS. Discrete optimization of structures using genetic algorithms. J Struct Eng 1992;118(5):1233–50. Krishnamoorthy CS, Venkatesh PP, Sudarshan R. Object-oriented framework for genetic algorithms with application to space truss optimization. J Comput Civil Eng 2002;16(1):66–75
- [2] K.S. Lee, Z.W. Geem, A new meta-heuristic algorithm for continuous engineering optimization: harmony search theory and practice, Computer Methods in Applied Mechanics and Engineering 194 (2005) 3902–3933
- [3] Rahami H, Kaveh A, Gholipour Y. Sizing, geometry and topology optimization of trusses via force method and genetic algorithm. Eng Struct 2008;30:2360–9.
- [4] Kaveh A, Talatahari S. Size optimization of space trusses using Big Bang–Big Crunch algorithm. Comput Struct 2009;87:1129–40.
- [5] Ali sadollah, hadi askander, joong hong kim “Geometric optimization of a cylinder fin heat sink using mine blast algorithm” 2010
- [6] Ali Sadollah, Ardeshtir Bahreininejad, Hadi Eskandar, Mohd Hamdi a Faculty of Engineering, University of Malaya, 50603 Kuala Lumpur, Malaysia Department of Mechanical Engineering, Semnan University, Semnan, Iran (2011) mine blast algorithm for optimization of truss structures with discrete variable
- [7] Sizing optimization of truss structures by method of centers and force formulation Behrooz Farshi *, Ali Alinia-ziazi Department of Mechanical Engineering (2012).
- [8] improved mine blast algorithm for optimal cost design of water distribution systems Ali Sadollaha, Do Guen Yooa & Joong Hoon Kima a School of Civil, Environmental and Architectural Engineering, Korea University, Seoul, South Korea Published online: 21 Nov 201
- [9] Golinski, J.: "Optimal Synthesis Problems Solved by Means of Nonlinear Programming and Random Methods", Journal of Mechanisms, Vol. 5, pp. 287-309, 1970
- [10] Management Optimization, vol. 8, no. 2, pp. 429–455, 2012.
- [11] M. H. Lin and J. F. Tsai, "Optimal design of a speed reducer," Applied Mechanics and Materials, vol. 376, pp. 327–330, 2013
- [12] A. H. Gandomi and X.-S. Yang, "Benchmark problems in structural optimization," in Computational Optimization, Methods and Algorithms, vol. 356 of Studies in Computational Intelligence, pp. 259–281, Springer, Berlin, Germany, 2011
- [13] J.-F. Tsai and M.-H. Lin, "An efficient global approach for posynomial geometric programming problems," INFORMS Journal on Computing, vol. 23, no. 3, pp. 483–492, 2011.

10.22214/IJRASET

45.98

IMPACT FACTOR:
7.129

IMPACT FACTOR:
7.429

INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 (24*7 Support on Whatsapp)