iJRASET

International Journal For Research in
Applied Science and Engineering Technology

INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 7 Issue: XI Month of publication: November 2019

DOI: <http://doi.org/10.22214/ijraset.2019.11120>

www.ijraset.com

Call: ☎ 08813907089

E-mail ID: ijraset@gmail.com

Numerical Investigation on Stress and CFD Analysis of Aircraft Wings for Better Performance

Rajesh Kumar¹, Ch. Shalini²

^{1,2}CVR college of Engineering, Hyderabad

Abstract: *The air foil section is the incarnation of a wing or a lifting surface which is very important in an airplane wing design. While the shape of the air foil changes, their aerodynamic characteristics also change. This investigation deals with a standard symmetrical air foil as reference and the effect of changes in shape due to minor variations in the coordinates. Three new air foil shapes have been produced in this optimisation process. The aerodynamic characteristic results such as the coefficients of lift and drag (C_d , C_l), pressure coefficient (C_p), moment coefficient (C_m) are noted for all three different profiles, produced from the standard NACA 0012. Wortmann fx 63-137 and Clark y air foils are also included in our project. The modus-operandi used in this optimisation process is the Computational Fluid Dynamics (CFD). We have used ANSYS FLUENT and MODAL for flow and stress analysis. Flow changes have been recorded for these air foil shapes and the results are arrived for finding the best air foil that can be advisable.*

Keywords: Airfoil, airfoil shape, aerodynamic characteristics, Fluent, Modal.

I. INTRODUCTION

The wing may be considered as the most important component of an aircraft, since a fixed-wing aircraft is not able to fly without it. It is made up of an airfoil which have some cross sectional area. Since the wing geometry and its features are influencing all other aircraft components, we begin the detail design process by wing design. The primary function of the wing is to generate sufficient lift force or simply lift (L). However, the wing has two other productions, namely drag force or drag (D) and nose-down pitching moment (M). While a wing designer is looking to maximize the lift, the other two (drag and pitching moment) must be minimized. In fact, wing is assumed ad a lifting surface that lift is produced due to the pressure difference between lower and upper surfaces. A wing following the laminar stream has much larger thickness in the middle of the camber line. It represent negative weight slant along the stream. So if we maintain the camber I the center, then a laminar stream with high rate high rate at high speed can be achieved.

II. WING DESIGN

The wing may be considered as the most important component of an aircraft, since a fixed-wing aircraft is not able to fly without it. Since the wing geometry and its features are influencing all other aircraft components, we begin the detail design process by wing design. The primary function of the wing is to generate sufficient lift force or simply lift (L). However, the wing has two other productions, namely drag force or drag (D) and nose-down pitching moment (M). While a wing designer is looking to maximize the lift, the other two (drag and pitching moment) must be minimized. In fact, wing is assumed ad a lifting surface that lift is produced due to the pressure difference between lower and upper surfaces. Aerodynamics textbooks may be studied to refresh your memory about mathematical techniques to calculate the pressure distribution over the wing and how to determine the flow variables. Basically, the principles and methodologies of “systems engineering” are followed in the wing design process. Limiting factors in the wing design approach, originate from design requirements such as performance requirements, stability and control requirements, producibility requirements, operational requirements, cost, and flight safety. Major performance requirements include stall speed, maximum speed, take off run, range and endurance. Primary stability and control requirements include lateral-directional static stability, lateral-directional dynamic stability, and aircraft controllability during probable wing stall. One of the necessary tools in the wing design process is an aerodynamic technique to calculate wing lift, wing drag, and wing pitching moment. With the progress of the science of aerodynamics, there are variety of techniques and tools to accomplish this time consuming job. Variety of tools and software based on aerodynamics and numerical methods have been developed in the past decades. The CFD Software based on the solution of Navier-Stokes equations, vortex lattice method, thin air foil theory, and circulation are available in the market. The application of such software –that are expensive and time-consuming – at this early stage of wing design seems un-necessary. Instead, a simple approach, namely Lifting Line Theory is introduced. Using this theory, one can determine those three wing productions (L , D , and M) with an acceptable accuracy.

III.METHODOLOGY

CFD and CAE are the numerical strategy which are used to reproduce physical issues with use of experiments. This is used to inquire about the arrangement without making physical model. In general numerical simulation consists of the following processes.

- 1) *Modelling*: After the completion of aerofoil selection, we collected aerofoil coordinate data as per the required dimensions from aerofoil tools website. By using CREO software, 2D model is generated by importing the coordinates into it. Then the 2D generated model is extruded into 3D model. After modelling different types of aerofoils, then it is imported in ANSYS WORKBENCH for CFD and MODAL analysis. Even other software XFLR is used to study the various characteristics of the aerofoils. The below figures shows the 3D model of NACA 0012 generated in CREO software and the mesh of one of the aerofoil selected.

Fig A: 3D model of NACA Aerofoil 0012

Fig B: NACA 0040 Mesh part

- 2) *Meshing*: All the different aerofoils were meshed in Ansys default mesher. Minimum five inflation layers were created around the aerofoils to capture the boundary layers. The above figure shows the best mesh around the aerofoils which we obtained by giving it a fine mesh. The below table shows us the structure of mesh elements of various aerofoil.

AIRFOIL	NO. OF NODES	NO. OF ELEMENTS	MESH TYPE
NACA 0012	192663	353937	Triangular
NACA 0015	194248	353441	Triangular
NACA 0030	198568	361220	Triangular
NACA 0040	201320	387756	Triangular
Clark Y	326001	593100	Triangular
Wortmann fx63-137	248640	400882	Triangular

Table 1: No. of nodes and elements of different aerofoils

- 3) *Fluent*: After successfully meshing the aerofoils, then they were imported in Ansys Fluent and boundary conditions were given to start the simulation. Various contours of pressure and velocity were obtained for all the different aerofoils. The various boundary conditions applied here are mentioned below.

S.No	PROPERTIES	VALUES
1	Type of material	Aluminium
2	Chord	300mm
3	Span	1m
4	Velocity	133 m/s
5	Solution method	Standard k-ε

Table 2: Boundary conditions used in Fluent

- 4) *XFLR5*: After getting the various contours of pressure and velocity C_l and C_d values were determined by using a software called XFLR5. Here in this software we can easily get the graphs of C_l and C_d of various aerofoil and can compare them to get the L/D ratio.
- 5) *Modal Analysis*: After successfully iterations of the aerofoils in Fluent it was again imported in Ansys Workbench to find out the natural characteristics or the mode shape and vibration frequencies that are responsible for the vibratory oscillations of the aerofoil. Here self-weight condition was of opted to mainly identify the flutter characteristics of the aerofoil profiles and the means of noise related problems during the flight. Even the structural performance of the aerofoil can be estimated by knowing the modes of the failures.
- 6) *Comparison*: After getting all the output results from various software, all the aerofoils were compared to find out the optimum aerofoil which can give better performance and stability.

IV.RESULT ANALYSIS

From the figures below we can see the different contours of velocity and pressure distribution on different aerofoils. It is clearly seen that there are variations in pressure and velocity on each aerofoil.

Fig C: Pressure distributions on NACA 0030

Fig D: Pressure distribution on Wortmann fx63-137

Fig E: Velocity distribution of Wortmann fx63-137

Fig F: Velocity distribution of NACA 0040

After finding the different contours of velocity and pressure, we have taken different aerofoils and calculated the C_l , C_d and C_m values for those aerofoils. Then a graph was generated comparing those aerofoils and also calculated L/D ratio from the values. The effect of shape on the Lift to drag ratio has been found by the analysis of airfoil shapes for various conditions of Mach number and Angle of attack and it is tabulated as follows. Some of the tabulated results are shown in table 3.

The aerodynamic coefficients are dependent on their body shape (airfoil section chosen), and also on the attitude (angle of attack), Reynolds number, Mach number, surface roughness, and air turbulence. The results tabulated in Table 5.2 shows the (L/D) ratio of Clark Y and Wortmann airfoils at 3° angle of attack.

Mach No.	REF	1	2	3
(L/D) in % of chord at AOA 3°				
	12	15	30	40
0.2	21.9	15.5	23.9	30.3
0.3	21.0	15.0	23.2	29.4
0.4	20.5	14.5	22.6	28.5
0.5	20.5	14.0	22.0	27.1
0.6	19.0	12.9	21.6	27.1

Table 4: (L/D) ratio in % of chord of NACA 0012

Mach no.	Wortmann f*63-137	Clark y
(L/D) in % of chord at 3 AOA		
0.2	61.7	41.5
0.3	60.5	40.3
0.4	59.2	39.1
0.5	58.1	38.0
0.6	56.0	37.5

Table 5: (L/D) ratio in % of chord

The below figures shows the wing design and analysis generated in XFLR5 software. Boundary conditions were applied like Mach number, Angle of Attack, chord length and dihedral angle.

Fig G: XFLR5 model of NACA 0012

Fig H: XFLR5 model of NACA 0015

Fig I: XFLR5 model of NACA 0030

Fig J: XFLR5 model of NACA 0040

Fig K: XFLR5 model of Wortmann fx63-137

Fig L: XFLR5 model of Clark Y airfoil

The following figures shows the stress distribution on each aerofil and the toatl deformation in them.

Fig M: Stress distribution of NACA 0012

Fig N: Stress distribution of NACA 0030

Fig O: Stress distribution of Wortmann fx63-137

Fig P: Stress distribution of Clark Y

V. CONCLUSION

From the investigation, following conclusions have been drawn.

CFD and MODAL analysis was done on various different aerofoils with different thickness in % of chord. It was found that Wortmann fx63-137 at an angle of attack 12° and Mach no. ranging from 0.2 to 0.6 has the best lift to drag values. From the results obtained from ANSYS FLUENT, it has been found that wortmann fx63-137 has the best pressure and velocity distributions over selected airfoils. We plotted graphs between C_l vs C_d , C_l/C_d vs α , C_m vs α using XFLR5 software. Fig shows the comparison between selected airfoils. It was found that Wortmann fx63-137 has the highest C_l value at low C_d . From modal analysis, wortmann and clark y has the best resistance to deformation and stresses

VI. ACKNOWLEDGMENT

I am thankful to Dr. T. Murugan who has spared his valuable time and append novel ideas to guide us. I am thankful to our colleagues for providing us appropriate environment required for the paper to complete. I am also thankful to the whole Mechanical Department for their encouragement and cooperation for the successful completion of the paper

REFERENCES

- [1] Eppler, Richard, Airfoil Design and Data, Springer-Verlag, Berlin, 1990
- [2] Abbott I. H. and Von Donehoff A. F., Theory of Wing Sections, Dover, 1959
- [3] Anderson J. D., Fundamentals of Aerodynamics, McGraw-Hill, Fifth edition, 2010
- [4] Jackson P., Jane's All the World's Aircraft, Jane's information group, Various years
- [5] Blanchard B. S. and Fabrycky W. J., Systems Engineering and Analysis, Prentice Hall, Third edition, 2006
- [6] Shevell R. S., Fundamentals of Flight, Prentice Hall, Second edition, 1989
- [7] Sadraey M., Aircraft Performance Analysis, VDM Verlag Dr. Müller, 2009
- [8] Anderson J. D., Aircraft Performance and Design, McGraw-Hill, 1999
- [9] Hibbeler R. C., Engineering Mechanics, Dynamics, 9th Edition, Prentice Hall, 2001
- [10] Stevens B. L. and Lewis F. L., Aircraft Control and Simulation, Second Edition, Wiley, 2003

10.22214/IJRASET

45.98

IMPACT FACTOR:
7.129

IMPACT FACTOR:
7.429

INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 (24*7 Support on Whatsapp)