iJRASET

International Journal For Research in
Applied Science and Engineering Technology

INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 7 Issue: III Month of publication: March 2019

DOI: <http://doi.org/10.22214/ijraset.2019.3146>

www.ijraset.com

Call: ☎ 08813907089

E-mail ID: ijraset@gmail.com

Bidirectional Full Bridge Configuration for Inductive Wireless Power Transfer

T. Mathumathi¹, L. Geethanjali², A. Kaviya³, S. Swetha⁴

¹Assistant Professor, ^{2,3,4}Student, Prathyusha Engineering College, Thiruvallur

Abstract: The wireless power transfer (WPT) offers a band new way for energy acquisition in electric-driven devices. An active resonance circuit is used to wirelessly transfer power from the transmitter to the receiver. In traditional circuits parallel L-C resonant tank in transmitter circuit is commonly used, where as our project utilizes series-parallel CLC tank circuit. Capacitive WPT is used for low power applications whereas the wireless inductive power transfer (IPT) is used for both low and medium power applications. Various WPT applications are electric vehicles, electronic gadgets, lighting, material handling and biomedical implants. Day by day new technologies are making our life simpler. Wireless charging through resonance could be one of the next technologies that bring the future nearer. In this project it has been shown that it is possible to charge low power devices wirelessly via inductive coupling. It minimizes the complexity that arises for the use of conventional wire system. In addition, the project also opens up new possibilities of wireless systems in our other daily life uses.

Keywords: Wireless power transfer, Transmitter, Receiver, Bidirectional power transfer

I. INTRODUCTION

We live in a world of technological advancement. New technologies emerge each and every day to make our life simpler. The conventional wire system creates a mess when it comes to charging several devices simultaneously. It also takes up a lot of electric sockets and not to mention the fact that each device has its own design for the charging port. The solution to all these dilemma lies with inductive coupling, a simple and effective way of transferring power wirelessly.

Wireless Power Transmission (WPT) is the efficient transmission of electric power from one point to another trough vacuum or an atmosphere without the use of wire or any other substance. This can be used for applications where either an instantaneous amount or a continuous delivery of energy is needed, but where conventional wires are unaffordable, inconvenient, expensive, hazardous, unwanted or impossible. The power can be transmitted using Inductive coupling for short range, Resonant Induction for mid-range and Electromagnetic wave power transfer for high range. WPT is a technology that can transport power to locations, which are otherwise not possible or impractical to reach.

A. Components

Timer 555

Op amp741

Coil copper 22awg

Full wave rectifier

B. Methods

Technology	Energy Transfer	Enabling the Power Transfer
Inductive coupling	Magnetic fields	Coils of wire
Resonant inductive coupling	Magnetic fields	Resonant circuits
Capacitive coupling	Electric fields	Conductive coupling plates
Magnetodynamic coupling	Magnetic fields	Rotating permanent magnets
Microwave radiation	Microwaves	Phased arrays/dishes
Optical radiation	Light/infrared/ultraviolet	Lasers/photocells

C. Existing System

The WPT technique has been taken as an ideal technical solution for energizing electric-driven devices within some specific regions in the near future, especially for smart home applications. The reason why WPT technologies is so crucial is regarding to two fundamental problems of battery-powered devices that limit their popularization - short battery life and high initial cost. Battery-powered devices can harness wireless power from electromagnetic field in air and then charge their batteries cordlessly even in the moving state. Existing older systems mainly use the following types of technology:

- 1) Capacitive Compensation Network
- 2) Magnetic Resonant Coupling
- 3) Capacitive Coupled Power Transfer

D. Proposed System

Our project utilizes Inductive Power Transfer (IPT) to transfer power over a short range. Series – Parallel CLC resonant tank circuit is used, to reduce high voltage stresses and ensure soft switching. Transmission coil is multi-directional in nature, to compensate for misalignment between transmitter and receiver coils. Full wave rectification is used, to improve on the power transmission loss. The power transmission capacity is considerably increased to about a maximum of 1.2Kw.

E. Block Diagram

1) Transmitter

- 2) *Power Supply*: Converts the AC current to DC current.
- 3) *Oscillator Circuit*: An oscillator is an electronic circuit that produces a periodic, oscillating electronic signal, often a sine wave or a square wave. Oscillators convert direct current (DC) from a power supply to an alternating current (AC) signal. They are widely used in many electronic devices.
- 4) *Power Amplifier*: The function of a power amplifier is to raise the power level of input signal. It is required to deliver a large amount of power and has to handle large current. The function of a power amplifier is to raise the power level of input signal. It is required to deliver a large amount of power and has to handle large current.
- 5) *Transmitting Coil*: By driving a sinusoidal alternating current through this loop at the Larmor frequency, an oscillating magnetic field perpendicular to the coil is produced.
- 6) *Receiver*

- 7) *Receiver Coil*: Receiver coil is located near to the magnetic field of the transmitting coil, then the magnetic field can induce an AC current in the receiving coil. Which is supplied to the load.
- 8) *Full Wave Rectifier*: A Full Wave Rectifier is a circuit, ac voltage. which converts an AC voltage into a pulsating dc voltage using both half cycles of the applied ac voltage. It uses two diodes of which one conducts during one half cycle while the other conducts during the other halfcycle of the applied. Depending on the type of alternating current supply and the arrangement of the rectifier circuit, the output voltage may require additional smoothing to produce a uniform steady voltage. Many applications of rectifiers, such as power supplies for radio, television and computer equipment, require a steady constant DC current (as would be produced by a battery). In these applications the output of the rectifier is smoothed by an electronic filter, which may be a capacitor, choke, or set of capacitors, chokes and resistors, possibly followed by a voltage regulator to produce a steady current.

- 9) **Regulator:** A regulator is an electricity regulation device designed to automatically convert voltage into a lower, usually direct current (DC), constant voltage. Voltage regulators or stabilizers are used to compensate for voltage fluctuations in mains power. Large regulators may be permanently installed on distribution lines. Small portable regulators may be plugged in between sensitive equipment and a wall outlet.
- 10) **Load:** A device which is to be powered. Example LED, MOTOR.

Fig. Circuit diagram in Multisim

F. Simulation Output

1) Transmitter Output

Fig. Simulation transmitter output

2) Output

- a) **Oscillator Output:** Channel A of scope gives the output value of the Oscillator circuit.
- b) **Power Amplifier output:** Channel B of the scope gives the output value of the amplifier circuit.

G. Receiver Output

Fig. Simulation receiver output

H. Rectifier Output

The output from the transmitter coil passes through the receiver coil and then rectified by a full wave rectifier. The voltage provided to the load is shown.

II. CONCLUSION

The goal of this project was to design and implement a wireless charger for low power devices via resonant inductive coupling. After analyzing the whole system step by step for optimization, a circuit was designed and implemented. Experimental results showed that significant improvements in terms of power-transfer efficiency have been achieved.

It was described and demonstrated that resonant inductive coupling can be used to deliver power wirelessly from a source coil to a load coil and charge a low power device.

The fundamental aim of this project is to introduce the working mechanism of IPT systems. The key technical issues of WPT systems have been summarized in terms of the efficiency, power, distance, misalignment, bi-directional charging, and energy security. Effective method of power transfer is proposed.

REFERENCES

- [1] Zhen Zhang, Senior Member, IEEE, Hongliang Pang, Student Member, IEEE, Apostolos Georgiadis, Senior Member, IEEE, and Carlo Cecati, Fellow. "Wireless Power Transfer –An Overview", IEEE 2018.
- [2] Ali Abdolkhani, Member, IEEE. "Single-Switch Soft-Switched Power Flow Controller for Wireless Power Transfer Applications", IEEE2017.
- [3] Suvendu Samanta, Student Member, IEEE and Akshay K. Rathore, Senior Member, IEEE, and Duleepa J. Thrimawithana, Member, IEEE. "Analysis and Design of Current-Fed Half-Bridge (C)(LC)-(LC) Resonant Topology for Inductive Wireless Power Transfer Application", IEEE 2016.
- [4] Siliang Zhang, Student Member, IEEE and Xinke Wu, Member "Low Common Mode Noise Half Bridge LLC DC-DC Converter with Asymmetric Center Tapped Rectifier", IEEE Transactions on Power Electronics.
- [5] R Narayanamoorthi, Member, IEEE, A Vimala Juliet, "Capacitor Less High Strength Resonant Wireless Power Transfer Using Open Bifilar spiral Coil", IEEE 2018.
- [6] Guangqi Zhu Robert D. Lorenz Life Fellow, IEEE University of Wisconsin " Surface Spiral Parallel and Antiparallel Winding Designs for High Efficiency, Low Spatial Voltage Stress, Inductive Wireless Power Transfer Systems" ,IEEE 2018.
- [7] Nags F. Ali Mohamed Johnson I Agbinya, Abdanaser Okaf, "Magnetic Field Tuning and Control for Wireless Power Transfer Using Inductive Tuning Plunger and Conical Coils" ,IEEE 2017.
- [8] David Maier, Jörg Heinrich, Marco Zimmer, Marcel Maier, and Nejila Parspour. "Contribution to the System Design of Contactless Energy Transfer Systems" ,IEEE 2015.
- [9] Suvendu Samanta, Student Member IEEE, Akshay K.Rathore, Senior Member IEEE, and Duleepa J.Thrimawithana, Member "Bidirectional Current-Fed-Half-Bridge (C)(LC) –(LC) Configuration for Inductive Wireless Power Transfer System",IEEE 2016.
- [10] Chenyang XIA, Wei WANG, Yuling LIU, Kezhang LIN, Yanhe WANG, Xiaojie WU School of Information & Electrical Engineering, Faculty of Electrical Engineering, China University of Mining and Technology, Xuzhou, P.R "A bidirectional wireless power transfer system for an electric vehicle with a relay circuit" ,IEEE 2014.
- [11] Nobuyuki Nitta, Ning Li, Kento Fujimori, Yasuhiro Sugimoto Department of Electrical, Electronics, and Communication Engineering, Chuo University "A Q-enhancement Method For Resonant Inductive Coupling Wireless Power Transfer System" ,IEEE 2013.

10.22214/IJRASET

45.98

IMPACT FACTOR:
7.129

IMPACT FACTOR:
7.429

INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 (24*7 Support on Whatsapp)