iJRASET

International Journal For Research in
Applied Science and Engineering Technology

INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 8 Issue: XII Month of publication: December 2020

DOI: <https://doi.org/10.22214/ijraset.2020.32660>

www.ijraset.com

Call: 08813907089

E-mail ID: ijraset@gmail.com

Suggested Methodology of Molar Density along X-Ray Diffraction Spectrum for Nano-composite Mixture with Standard Formulae

Rohit Madhukar Nikam¹, Kailas Haribhau Kapadnis², Ratan Yadav Borse³

¹Assistant Professor, Department of Chemistry, M. J. M. A.C.S College, Karanjali, Tal- Peth, Dist-Nashik-422 208,

²Professor, Department of Chemistry, L. V. H. A.C.S College, Panchavati, Dist-Nashik-422 003,

³Principal, Department of Physics, M. J. M. A.C.S College, Karanjali, Tal- Peth, Dist-Nashik-422 208.

Abstract: One of the most important application of x-ray diffraction is to provide the structural details of the material to researchers. This technique is employed on massive scale to interpret the analysis of nano crystalline phases and to determine average crystallite sizes with the aid of diffraction angle or peak position and FWHM values on account of Scherer equation. The phenomenon of XRD can be explained as function of reflection of incident beam from the lattice planes. These results are also tuned for different molar density along XRD planes for any nanomaterial for molar mass and molar volume elaborated in this paper. We have tried to calculate molar density of composite mixture for nanostructured material in terms of molar mass and molar volume using XRD data of Intensity verses peak position and weight assigned for film material in composite form quantitatively.

Keywords: Nano crystalline phases, XRD, peak position, molar density, molar mass, molar volume etc.

I. INTRODUCTION

Material characterization includes different instrumental techniques such as XRD, scanning electron morphology, Fourier transform infra-red spectroscopy, ultra-violet spectrophotometer and Spectro-flurometry. Applications of nanomaterial are electrical [1], gas sensing [2], antimicrobial properties [3], photo catalyst [4], supercapacitors [5], transistors [6], humidity sensing [7] and much more. Different methods of material synthesis are also reported in different articles [8]. In XRD spectra intensity along plane either increases or decreases with peak position, one of the strong reason given to always atomic or molecular density along plane either increases or decreases along the peak. In this paper molar mass is evaluated for mixture using standard equations such as weight fractions in terms of number of moles and molar volume is obtained from PowderX software [9] by refining cell or by reitveld refinement [10] by X'pert highscore software [11].

II. MATERIALS AND METHODS

In this article a method was based on illustration to calculate atomic/molar density along XRD spectrum, for this purpose a screen printed tin oxide (SnO₂) composite for 1% zinc oxide (ZnO) material/sample was under consideration. Molar mass was calculated from mass of substance in grams to number of moles. The number of moles for molar mass was calculated from weights of material to molecular weight.

Fig 1. XRD pattern of 1% ZnO:SnO₂

Molar volume of 1% ZnO:SnO₂ composite material is obtained by considering above XRD pattern(fig 1.) Molar volume can be calculated or obtained from lattice parameters a, b and c. Molar volume is obtained from PowderX software by refining cell or by reitveld refinement by X'pert highscore software.

III. RESULTS AND DISCUSSION

Density of material is the mass to volume ratio. When we consider molar density, it is defined as ratio of molar mass to molar volume. As every material prepared by any method in the form mixtures, composites, additives or doped into one another remain in their molecular state hence molar mass is considered. In mixture state, material remains as probably in compound and molar state not the atomic state (except by EDAX where we obtained values in atomic and weight percentage quantitatively and separately for each atoms of the material/composite material).

A. *Molar mass/Molecular weight of Material can be Calculated from Following Equation*

$$\text{Molar Mass of \% ZnO:SnO}_2 = \frac{\text{Total Mass or weight of \% ZnO:SnO}_2 \text{ in grams}}{\text{Total Number of moles of \% ZnO:SnO}_2}$$

.....(1)

B. *Calculation for total number of moles of \% ZnO:SnO₂*

In 1% ZnO:SnO₂ composite mixture, 99% SnO₂ is present. Let the weight of 99% SnO₂ has 0.665 gm and 1% ZnO:SnO₂ has 0.00665 gm was mixed with tin oxide so as to form a mixture for screen printed film material.

To calculate total number of moles, we have the values of molecular weight of zinc oxide (ZnO) and molecular weight of tin oxide (SnO₂) i.e., 81.38 and 150.7088 respectively. The following formula is used [12].

$$\text{Number of moles} = \frac{\text{Mass of substance}}{\text{Mass of one mole}}$$

$$\text{Number of moles of ZnO} = \frac{\text{Mass of ZnO in grams}}{\text{Molar Mass of ZnO}}$$

$$\text{Number of moles of ZnO} = \frac{0.00665}{81.38}$$

$$\text{Number of moles of ZnO} = 0.000817154 \text{ mol}$$

Similarly

$$\text{Number of moles of Tin oxide} = \frac{\text{Mass of tin oxide in grams}}{\text{Molar Mass of tin oxide}}$$

$$\text{Number of moles of Tin oxide} = \frac{0.665}{150.7088}$$

$$\text{Number of moles of ZnO} = 0.004412 \text{ mol}$$

Total number of moles is the sum of Number of moles of zinc oxide (ZnO) and Number of moles of tin oxide (SnO₂)

$$\text{Total Number of moles of ZnO:SnO}_2 = 0.004412 \text{ mol} + 0.000817154 \text{ mol} = 0.00522912 \text{ mol}$$

C. *Calculation for Total Mass of Mixture*

$$\text{Similarly total mass of ZnO:SnO}_2 = \text{Mass of ZnO} + \text{Mass of SnO}_2$$

$$\text{Total mass of ZnO:SnO}_2 = 0.00665 + 0.665 = 0.67164 \text{ gm}$$

By considering values obtained from part B and Part C, Equation 1, becomes,

$$\text{Molar Mass of \% ZnO:SnO}_2 = \frac{\text{Total Mass of \% ZnO:SnO}_2 \text{ in grams}}{\text{Total Number of moles of \% ZnO:SnO}_2}$$

$$\text{Molar Mass of \% ZnO:SnO}_2 = \frac{0.67164}{0.005229124}$$

$$\text{Molar Mass of \% ZnO:SnO}_2 = 128.44 \text{ gm}$$

Molar mass of 1% ZnO:SnO₂ is 128.44 gms

D. *To Evaluate the Molar Volume*

Molar volume is the product of unit cell parameters a, b, and c along x,y and z axis in crystal lattice obtained from different software's like PowderX software by refining cell or by rut weld refinement or by X'pert highscore software in origin. After refining cell, lattice parameter were evaluated in following table

Table1. Refinement data for 1% ZnO:SnO₂

ZERO	LAMBDA	A	B	C	ALPHA	BETA	GAMMA
-0.026	1.54060	4.73661	4.73661	3.18588	90.000	90.000	90.000
0.002	0.00000	0.00018	0.00018	0.00012	0.002	0.002	0.002
VOLUME (A*B*C) : 71.47671 cc							

Molar volume obtained from refinement data shows value of 71.47671 CC. Cell volume was interpreted for the input of XRD data of 1% ZnO:SnO₂ into PowderX software after subtraction, subjected to baseline correction using different standard methods.

E. To evaluate molar density of 1% ZnO: SnO₂

As we know, from the definition of molar density [13],

$$\text{Density of material} = \frac{\text{Molar Mass of material}}{\text{Molar Volume of material}}$$

$$\text{Molar density of 1\% ZnO: SnO}_2 = \frac{\text{Molar mass of 1\% ZnO: SnO}_2}{\text{Molar Volume of 1\% ZnO: SnO}_2}$$

$$\text{Molar density of 1\% ZnO: SnO}_2 = \frac{128.44}{71.47671}$$

$$\text{Molar density of 1\% ZnO: SnO}_2 = 1.7975 \text{ gm/cc}$$

Thus Molar densities of any nanostructured material can be calculated with above method in terms of molar mass obtained from weights of composite material and molar volume obtained from reitveld refinement using different software.

IV. CONCLUSION

This paper will be our effort to suggest the basic reason behind high or low intensities observed in x-ray diffraction pattern along the planes. The main reason is total number of counts present along peaks. These counts are high for high intensities and low for low intensities. XRD pattern of different composite material may differ in intensities because of strain, dislocation densities, different interplaner spacing. The above values are obtained from different standard mathematical formulae for molar mass is 128.44 gm., molar volume 71.47671 cc and molar density 1.7975 gm/cc for 1% ZnO: SnO₂. The value of molar density for any composite material will be calculated from above standard equation and mathematical formulae. Molar density is directly proportional to molar mass and inversely proportional to molar volume. Molar density of any composite material in different percentage can be calculated with above formulae.

REFERENCES

- [1] Dighavkar C. G., Patil. A. V., Borse. R.Y., Patil. S. J. effect of firing temperature on electrical and structural characteristics of screen printed TiO₂ thick films, Optoelectronics and advanced materials-Rapid communication, Vol-3, No.10, October 2009, p. 1013-1017.
- [2] Borse. R.Y., Salunke. V. T., Synthesis and characterization of nanostructured ZnO thick film gas sensors prepared by screen printing method, Sensors and transducers, Vol.9, special issue, December 2010, pp-161-170.
- [3] Kumari Subham, Jaskirat Kaur, Mouli chakroborty, Suba G. A. manuel, Pradeep N., Green synthesis of zinc oxide nanoparticles, using the extract of CALOTROPIS GIGANTEA, FOENICULUM VULGARE and MURRAYA KOENIGII and their antimicrobial properties, Journal of advanced scientific research, 2020, 11 (3), 183-188.
- [4] Suchithra Padmajan Sasikala, Nibila. T.A., Kunnathaparambil Babu Babitha, Abdul Azeez peer Mohammad, Ananthakumar Solalappan, competitive photodegradation performance of ZnO modified bentonite clay in water containing both organic and inorganic contaminats, Sustainable environment research, (2019) 29:1, <https://doi.org/10.1186/s42834-019-0001-z>
- [5] Purushothaman K.K., Priya Subha V, Sadayappan nagamuthu, Subbukalai Vijay, G. Murlidharan, Synthesizing of ZnO nanopaeatals for`supercapacitors applications, Micro & Nano Letters 6 (8) 668-670, IEEE Xplore.
- [6] Yutava ohya, Tsukasa Niwa, Takayuki ban, Yusutaka Takahashi, Thin film transistor of ZnO fabricated by chemical solution route, Jpan,J. Appl. Phys. Vol. 40, (2001) pp-297-298
- [7] Borse. R. Y., Garde A.S., effect of firing temprature on humidity sensing properties of SnO2 thick film resistor, sensor and transducer, Vol. 111, issue 12, 2009, pp-155-165.

- [8] Ajay Vasudeo rane, Sabu Thomas, method of synthesis of nanoparticles and fabrication of nanocomposites, methods for synthesis of nanoparticles and fabrication of nanocomposites, Micro and nano technologies, 2018, p-121-139, <https://doi.org/10.1016/B978-0-08-101975-7.00005-1>
- [9] C. Dong, PowderX: Windows-95-based program for powder X-ray diffraction data processing, Journal of applied crystallography, 32(4) 838-838, doi:10.1107/s0021889899003039
- [10] Mithun Rani Nath, Aninda Nafis Ahmed, M. A. Gafur, Muhammad Yusuf Miah, Study on the reitveld analysis for synthesized zinc oxide nanoparticles, AIP conference proceeding's, 1980, 030012 (2018) <https://doi.org/10.1063/1.5044291>
- [11] Mohammad A.A, first principles calculation on electronic properties of zinc oxideby zinc-air system, Journal of King saud university-engineering services, 2017, 29, 278-283
- [12] <https://toppr.com>, chemistry formula, Number of moles formula
- [13] <https://toppr.com>, chemistry formula, Molar density formula

10.22214/IJRASET

45.98

IMPACT FACTOR:
7.129

IMPACT FACTOR:
7.429

INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 (24*7 Support on Whatsapp)