iJRASET

International Journal For Research in
Applied Science and Engineering Technology

INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 9 Issue: III Month of publication: March 2021

DOI: <https://doi.org/10.22214/ijraset.2021.33506>

www.ijraset.com

Call: 08813907089

E-mail ID: ijraset@gmail.com

Design and Flow Analysis of Convergent -Divergent Nozzle

Mansi Bhadani¹, Harsh Patel², Tej Patel³, Singh Anup Tejnarayan⁴

^{1, 2, 3}U.G. Students, Department of Aeronautical Engineering, Parul Institute of Engineering & Technology, Vadodara, Gujarat, India

⁴Assistant professor, Department of Aeronautical Engineering

Abstract: A main purpose of nozzle is to increase the velocity or to accelerate the flow at exit of nozzle. Variation of parameters and fluid properties depend on design of that certain nozzle. To achieve better performance with less losses of fluid properties, nozzle should be satisfying better design requirements in every operating conditions. This research paper focuses on design, modelling and flow analysis of Convergent-Divergent nozzle. Objective of our research is to show variation of fluid properties like pressure, Mach number at exit of CD nozzle. Flow in the nozzle is considered as isentropic flow. The design parameters are inlet diameter, outlet diameter, throat diameter, length of convergent section and length of divergent section. Modelling is done in CREO PARAMETRIC 4.0 and fluid flow analysis is done in ANSYS 17.1 FLUENT. We have chosen design of CD nozzle based on literature studies.

Keywords: Convergent-Divergent nozzle, isentropic, mass flow rate, pressure contour, Mach number contour, velocity, boundary conditions, meshing, inlet diameter, exit diameter, throat diameter, area velocity Mach relation, area ratio

I. INTRODUCTION

In this modern time, in every passenger aircraft and military aircraft we are using jet engine or gas turbine. In gas turbine nozzle is placed after turbine. The purpose for using nozzle is to increase velocity of flow at nozzle exit to produce thrust. Types of nozzle depends on application of that and exit velocity.

Nozzle efficiency affects whole system where we put nozzle. Application of nozzle is generally in aerospace and aeronautical field, in mechanical field, in chemical and medical field as well. The one type of nozzle is Convergent-Divergent nozzle or de laval nozzle.

When divergent section or duct is combined with conventional nozzle then it's called Convergent- Divergent nozzle. This nozzle mostly used in rocket engine and in some high-speed missile, which operates at supersonic Mach number. CD nozzles enhance kinetic energy of the fluid which is flowing through it. This is the primary purpose of CD nozzle. Basically, it works on Newton's third law of motion. Cd nozzle should be designed in such a way so it can receive more mass flow of fluid. There are various shapes are available in CD nozzle like rectangular, square, circular etc. We can get more thrust by using de laval nozzle. In convergent section we get subsonic flow, at the throat of CD nozzle there is sonic flow then flow accelerate in divergent section and becomes supersonic.

II. METHODOLOGY

A. Design of CD nozzle

In this study Method of Characteristics is used for designing the CD nozzle. This method is numerical method to solve 2-dimensional flow problem. Flow properties can be calculated by this method like direction and velocity of flow at various point. Supersonic nozzle can be divided into two parts, gradual-expansion, and minimum-length nozzle [1]. Gradual expansion is typically used where we need to

maintain high quality flow at exit of nozzle. (e.g., supersonic wind tunnel) and the second one that is minimum length nozzle, it can be used in rocket engine. We have designed minimum length nozzle.

B. Modelling

Design and modelling of de laval nozzle is done in the CREO PARAMETRIC 4.0. Parameters are inlet diameter, outlet diameter, throat diameter, convergent section length, divergent section length. Table 1 shows the dimensions of CD nozzle.

Table I. Dimension of CD nozzle

Sr. No.	Specifications	Dimensions (mm)
2.	Inlet diameter	3000
3.	Exit diameter	5000
4.	Throat diameter	700
5.	Convergent section length	3000
6.	Divergent section length	5000

Figure 1. Sectional view of CD nozzle

C. Analysis

In this study analysis has been done in ANSYS 17.1 FLUENT. Energy equation and momentum equation are principal equations used in CFD to solve required solution [2]. Geometry which has been done in CREO PARAMETRIC 4.0 is imported to ANSYS WORKBENCH 17.1. There is no need of other domain construction in ANSYS as nozzle flow analysis is an internal flow type[2]. After that meshing has been done for input and output section. Next assigned boundary conditions.

N1= Number of divisions at exit and inlet

N2= Number of divisions on wall

Table II. Boundary Conditions

Boundary zone	Details of fluid properties
Inlet	Gauge total pressure: 3e5 Pa Inlet temperature: 298 K
Outlet	Gauge total pressure: 0.12e5 Pa
Material	Fluid: Air Density: Ideal gas Ratio of specific heat: 1.4

Figure 2. Meshing 1 of CD nozzle

Fig. 3. Meshing 2 of CD nozzle

Here in figure 3 and 4 shows the contour of static pressure and Mach number for two various meshing respectively. From that contour we can conclude some results of flow properties.

Fig. 4. Static pressure contour of CD nozzle

Figure 5. Mach number contour of CD nozzle

From above static pressure contour we can conclude that, red part is showing highest value of pressure that is 2.99×10^5 Pa at inlet, after that pressure is decreasing throughout the length, so we can say that according to Bernoulli's principal as pressure decreases then velocity increases. So, the highest value of pressure is 2.99×10^5 and the lowest value of pressure is -9.75×10^4 at exit.

From Mach number contour we can say that inlet Mach number is 0.0597 that is subsonic, after that Mach number is increasing and it will be close to 1 at throat, in divergent section Mach number increasing again and we get supersonic Mach number at exit of CD nozzle. Mach number is key parameter for the calculation.

D. Numerical Calculations

$$\frac{T_0}{T^*} = \left(1 + \frac{\gamma+1}{2}\right) (M^*)^2$$

$$a^* = \sqrt{\gamma R T^*}$$

$$\frac{P_0}{P^*} = \left(\left(1 + \frac{\gamma+1}{2}\right) (M^*)^2\right)^{\frac{\gamma}{\gamma-1}}$$

$$\text{Exhaust Velocity} = \left(\frac{2\gamma}{\gamma-1} \frac{R T_0}{M} \left(1 - \frac{P_c}{130}\right)^{\frac{\gamma-1}{\gamma}}\right)^{\frac{1}{2}}$$

$$\text{Convergence area in nozzle} = A_c = 3A_t$$

$$\text{Length of divergent section} = \sqrt{\frac{A_c}{\pi} \left(\frac{1}{\tan \theta}\right)}$$

$$\text{Length of convergent section} = \sqrt{\frac{A_c}{\pi} \left(\frac{1}{\tan \beta}\right)}$$

$$\frac{P_2}{P^*} = \left(\frac{\gamma+1}{2+(\gamma-1)Me^2}\right)^{\frac{\gamma}{\gamma-1}}$$

$$\frac{T_0}{T_e} = \left(1 + \frac{\gamma-1}{2}\right) (Me)^2$$

$$\text{Area ratio: } \left(\frac{A_e}{A^*}\right)^2 = \left(\frac{1}{(Me)^2}\right) \left(\left(\frac{2}{\gamma+1}\right) \left(1 + \left(\frac{\gamma-1}{2}\right) (Me)^2\right)\right)^{\frac{\gamma+1}{\gamma-1}}$$

Throat area equation:

$$A^* = \frac{m \dot{V}_1}{C^* (\rho^*)^{\frac{1}{\gamma}}}$$

Critical pressure ratio:

$$r^* = \left(\frac{2}{\gamma+1}\right)^{\frac{\gamma}{\gamma-1}}$$

III. CONCLUSIONS

Nozzle is most important part of the gas turbine engine because its playing vital role to produce thrust. So, by this research we got idea about the internal flow of nozzle, and the loss of energy. When area increase at that time velocity will increase, from that we can say that pressure decrease according to Bernoulli's principle. As velocity increases Mach number Increases. So, we can get more thrust.

IV. ACKNOWLEDGMENT

We are grateful to all who helped us for completing our project. We faced many challenges due to lack of knowledge. We are grateful to Prof. Anup Tejnaryan Singh for his guidance. Thank to Prof. Swati Chauhan for monitoring. Our whole team is very grateful to all faculties and Department of Aeronautical Engineering, PIET.

REFERENCES

- [1] Md. Akhtar Khan, Sanjay Kumar Sardiwal, 'Design of a supersonic nozzle using method of characteristics', Gitam University, Hyderabad. International Journal of Engineering & Technology (IJERT), ISSN:2278-0181, Vol.2 Issue 11, November-2013
- [2] A. Shanthi Swaroopini, M. Ganesh Kumar, 'Numerical simulation and optimization of high-performance supersonic nozzle at different conical', Sanketika Institute of Technology & management, Vizag, International Journal of Research in Engineering & Technology, eISSN:2319-1163
- [3] Muhammad Waqas Khalid, Computational fluid dynamic analysis of compressible flow through a converging-diverging nozzle using k-ε turbulence model, School of chemical and materials engineering, Pakistan, Engineering, Technology & Applied Science Research, Vol 10, No. 1, 2020, 5180-5185
- [4] Andreas K. flock, Ali Gulhan, 'Design of converging-diverging nozzle with constant-radius centerbury', CEAS Space Journal
- [5] Pardhasaradhi natta, 'Flow analysis of rocket nozzle using computational fluid dynamic', International Journal of Engineering research and applications(IJERA)
- [6] Nikhil D, Deshpande, Suyash S. Vidwans, 'Theoretical and CFD analysis of De laval nozzle', International Journal of Mechanical & production Engineering

10.22214/IJRASET

45.98

IMPACT FACTOR:
7.129

IMPACT FACTOR:
7.429

INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 (24*7 Support on Whatsapp)