iJRASET

International Journal For Research in
Applied Science and Engineering Technology

INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 9 Issue: VII Month of publication: July 2021

DOI: <https://doi.org/10.22214/ijraset.2021.37097>

www.ijraset.com

Call: 08813907089

E-mail ID: ijraset@gmail.com

Smart Circuit Breaker

Ankit Aloni¹, Prof. Vishal Mehtre², Yashashwi Raj³

^{1, 2, 3}Bharati Vidhyapeeth College of Engineering Pune

Abstract: This project is to supply single phase home appliances. This project is used for an alternative for MCB. MCB is fault current protective device which trip on fault current which flows in the circuit. MCB are based on the thermal bimetallic trip mechanism which is very slow and tripping time is based upon percentage of overloads MCB having bimetallic trip which gets derated after some mechanical operation and cause unwanted tripping. All the above faults will be overcome by smart circuit breakers which provide all types of protection such as overload, under voltage, high temperature and short circuit protection, this type of protection is necessary because, now days all, appliance such as LCD, Air conditioner, Refrigerator, etc consist of electronic circuitry which is voltage sensitive and get damage at voltage fluctuation. This project also monitors and display fault on LCD and stores the data for further action. Smart circuit breaker is fast acting and sense relay as fast as possible and trips the relay within 100msec. than MCB which takes 1000msec. to 1600msec. In addition to that LM 35 temperature sensor is also interface to microcontroller by if temperature exceed 550C microcontroller will trip the relay. The intention to use temperature sensor is to detect fire hazard in domestic purpose as well as commercial purpose.

Keywords: Circuit Breaker, LCD, MCB, Relay, Sensor

I. INTRODUCTION

A fault in electrical instrumentality is outlined as a defect in its electric circuit because of that this is amused from the supposed path. Faults are usually caused by mechanical failure, accidents, excessive internal and external stresses etc. The fault resistance being low, the fault currents are comparatively high. During the faults, the ability flow is amused towards the fault and therefore the provide to the neighboring zone is affected. Voltages become unbalanced. it's necessary to notice the fault as early as doable that's why a kit is being created exploitation microcontroller to form its method quicker. it'll notice following four major faults and can offer trip signal to relay. The four faults detected by the model are: below voltage Over voltage, Short-circuit, Overload and hot temperature. This project is intended to pack up the ability provide once any higher than fault occur. standard breaker like MCB supported thermal electrical device lever mechanism. it's terribly slow and therefore the trip time depends upon the share of overload. In this project potential electrical device is employed to sense the input voltage across the load and current electrical device is employed to sense this within the circuit and offers command to microcontroller to trip the relay if voltage varies inside set vary. The idea of good breaker came into focus realizing that standard breaker like MCB takes longer time to trip, thus sensitive device injury and therefore it's important to activate the tripping mechanism at the shortest doable time, preferred instant. This project is extraordinarily quick and overcome the drawbacks of the thermal sort.

II. CONSTRUCTION & DESCRIPTION OF HARDWARE MODEL

- A. The concept of the device designed is that it's wont to detect the type of fault and supply its protection that has occurred in an exceedingly single phase home system.
- B. By using PIC Microcontroller, the fault is detected by the designed circuit and it also displays on the LCD screen.
- C. Except for that, relay circuit is additionally attached thereto so as to save lots of the system from being damaged by disconnecting the faulty circuit from the system.
- D. The 230/12V step down transformer converted into 12V dc and is given to transformer
- E. the present transducer and potential transformer is connected to microcontroller to watch this within the circuit and input voltage across the load respectively
- F. The program fed into microcontroller will compare the sign of current transducer and potential transformer and can compare with the given set range of import, if the input is above or below the range of set value, the microcontroller will send a symptom to the relay to trip the circuit and also send a parallel signal to the LCD to display the kind of fault that has occurred.
- G. Thus we finally obtain the tripping additionally as display of the fault at same time.

III. CIRCUIT DIAGRAM AND COMPONENTS

The Components used are as follows:

- A. Transformer 230/12V
- B. Rectifier
- C. Voltage Regulator IC 7805
- D. PIC Microcontroller 18F25K20
- E. Current Transducer ACS712
- F. Potential Transformer
- G. LCD Display
- H. Driver IC ULN2803
- I. S.P.D.T Relay
- J. Crystal Oscillator
- K. Filter
- L. Temperature Sensor LM35
- M. Resistor
- N. Filter Capacitor
- O. Ceramic Capacitor
- P. Toggle Switches
- Q. LED Light

B. When Under Voltage Occurs

Whenever the under-voltage scenario occurs which is below 200V the microcontroller will sense low voltage and will trip the relay and at the same time LCD will display "Low V" and after the delay of 15-sec microcontroller will again check if the fault is gone or not. if the fault is gone it will display ALL OK otherwise it will display "TRIP-V"

C. When Over Voltage Occurs

whenever the under-voltage scenario occurs which is above 260V the microcontroller will sense over-voltage and will trip the relay and at the same time LCD will display "High V" and after the delay of 15-sec microcontroller will again check if the fault is gone or not. if the fault is gone it will display ALL OK otherwise it will display "TRIP-V"

D. When Overload Occurs

whenever the overload scenario occurs which means the current exceeds above 0.8A the microcontroller will sense over-voltage and will trip the relay and at the same time LCD will display "High A" and after the delay of 15-sec microcontroller will again check if the fault is gone or not. if the fault is gone it will display ALL OK otherwise it will display "TRIP-A".

E. When High Temperature Occurs

whenever the high Temperature scenario occurs which means the temperature has exceed 55 C the microcontroller will sense the rise in temperature and will trip the relay and at the same time LCD will display "High Temp' and after the delay of 15-sec microcontroller will again check if the fault is gone or not. if the fault is gone it will display ALL OK otherwise it will display "Hi Temp".

VI. FEATURES

- A. Quick Operation i.e. within 100ms
- B. Multiple Fault Protection
- C. Monitoring as well as Controlling Device
- D. Fault data saving
- E. High Accuracy

VII. ADVANTAGES

A. Fast Acting

It has tripping time of 100msec which is less than MCB (1000 to 1600msec)

B. Auto Reset Circuit

Microcontroller constantly monitors and gives command to switch ON and OFF the relay automatically.

C. Long Life

The life of this circuit breaker is much longer than MCB as there no mechanical contact.

D. No Mechanical Part

It does not have any mechanical part such as bimetallic strip and coil, hence it has high accuracy.

VIII. CONCLUSION

- A. One of the primary objectives of an engineer is to endeavor to deliver the best product or most efficient service at the lowest cost to the end user. The system has been tested and was found to meet the expected result.
- B. This project is designed in form of hardware for protecting single phase home appliance against any fault such as under voltage, over voltage, overload, and high temperature.
- C. The automatic tripping as well as reset of the circuit is achieved through this project.
- D. This project is much more accurate and reliable and fast acting then conventional circuit breaker like MCB and can be used up to rating more than 30 ampere.

IX. FUTURE SCOPES

- A. It also can be used for Protecting Three phase supply Equipments in Industry by using some extra components.
- B. It can be modified by using GSM Module.
- C. It may be connecting with home security system.
- D. By using Power Electronic Application, Voltage Fluctuation can be maintaining to rated voltage
- E. It can also be used for Earth Fault protection, hence eliminating ELCB (Earth Leakage circuit Breaker)

REFERENCES

- [1] Gerd Balzer, Applications of High Voltage Circuit-Breakers and Development of Aging Models, 2007.
- [2] C. D. Nail, "Automated Circuit Breaker Analysis," M.S. thesis, Texas A&M University, College Station, TX, August 2002.
- [3] Saurabh Saxena Maroof Ali Alok Singh Kapil Gandhi, "Various Types of Circuit Breakers used in Power System for Smooth Working of the Transmission Line," MIT International Journal of Electrical and Instrumentation Engineering, Vol. 2, No. 2, Aug. 2012, pp. (106-111)
- [4] S. Tokoyoda, T. Inagaki, K. Tahata, F. Page, K. Kamei, T. Minagawa, H. Ito C. Spallarossa, "DC current interruption tests with HV mechanical DC circuit breaker," 2017
- [5] Om Prakash Regar, Pradeep Kumar, Mr. Gaurav Srivastava, "A Review on HVDC Circuit Breakers," IJTSRD, Volume: 3, Issue: 3, Mar-Apr 2019
- [6] Hui Hwang Goh, Sy yi Sim, Nur Iskandar bin Hamzah, Sulaiman bin Mazlan, Chin Wan Ling, Qing Shi Chua, Kai Chen Goh, "Types of Circuit Breaker and its Application in Substation Protection", Indonesian Journal of Electrical Engineering and Computer Science, Vol. 8, No. 1, October 2017, pp. 213 ~ 220
- [7] Mokhberdoran, A. Carvalho, H. Leite and N. Silva, "A review on HVDC circuit breakers," 3rd Renewable Power Generation Conference (RPG 2014), Naples, 2014, pp. 1-6, doi: 10.1049/cp.2014.0859.
- [8] Y. Kieffel et al., "Characteristics of g3 – an alternative to SF6," in CIREN - Open Access Proceedings Journal, vol. 2017, no. 1, pp. 54-57, 10 2017, doi: 10.1049/oap-cired.2017.0795.
- [9] Y. Du, J. Deng, H. Lin, H. Zheng, K. Xiang and Y. Shen, "Research and experiment of a current-limiting HVDC circuit breaker," in The Journal of Engineering, vol. 2019, no. 16, pp. 2002-2006, 3 201

Biographies

Has completed his master in electrical engineering (power systems) from Bharati Vidyapeeth (deemed to be university) college of engineering, Pune.

He is currently working as assistant professor in department of electrical engineering. He has an industrial experience of about 2 years in Suzlon power. As engineer in power evacuation department and has an teaching experience of more than 5 years. His area of interest is renewable sources of energy specially wind and solar with its analysis, optimization and power quality.

Currently pursuing bachelor of technology degree in electrical engineering from Bharati Vidyapeeth (deemed to be university) college of Engineering, Pune. I have completed my diploma course in electrical stream from Shri Datta Meghe Institute of Polytechnic Nagpur.

Currently pursuing bachelor of technology degree in electrical engineering from Bharati Vidyapeeth (deemed to be university) college of engineering, Pune. he has completed diploma course in electrical stream from Bharati Vidyapeeth Jawaharlal Nehru institute of technology, Pune.

10.22214/IJRASET

45.98

IMPACT FACTOR:
7.129

IMPACT FACTOR:
7.429

INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 (24*7 Support on Whatsapp)