ISBN: 978-1-948012-17-1

Ethics and Information Technology (ETIT)

DOI: <http://doi.org/10.26480/etit.02.2020.151.153>

RECENT DEVELOPMENTS IN LANE DEPARTURE WARNING SYSTEM: AN ANALYSIS

Leeza Panda, Bibhu Prasad Mohanty

Department of Electronics and Communication Engineering, ITER, Siksha 'O' Anusandhan University (Deemed to be University)

*Corresponding Author Email: leezapanda@soa.ac.in; bibhumohanty@soa.ac.in

This is an open access article distributed under the Creative Commons Attribution License CC BY 4.0, which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

ARTICLE DETAILS

Article History:

Received 25 October 2020
Accepted 26 November 2020
Available online 03 December 2020

ABSTRACT

With a rapid evolving India, the transportation facilities are also ramping up in a drastic manner. For instance, subways, pedestrian ways, headways are additionally getting created. The transportation can be positioned as a basic activity in Indian economy. And as the facilities for transportation are getting enhanced, per day happening of the number of accidents are also increasing. It has become important to venture on finding the solution to the accidents. This paper gives a broad analysis of the lane departure strategies and lane recognition approach. Specifically, lane detection becomes challenging when it comes to different road structures. This paper further attempts to make sense of the issues and confinements of the current lane detection and lane departure warning framework.

KEYWORDS

lane detection, pedestrian ways, inverse perspective mapping, Otsu's algorithm, hough transform.

1. INTRODUCTION

There are innumerable road accident cases in India. Possibly this statement is the goal behind the authors still performing research on day's vision based lane recognition. It is a need to have a lane departure warning framework para-mounting the vehicle and finding the bends of the roads. However, while developing this structure the crucial issue is distinguishing the road and lane acknowledgement and recognizing obstacle, for instance vehicle and individual road. ADAS, which cautions the driver in unsafe conditions or plays an important role in the driving, are being integrated into the vehicles. The standard cluster in the enhancement of such structures is the knowledge issue which includes 2 sections: road and lane recognition likewise, obstacle (for instance: motors and observer) detection. The lane detection and departure system has below mentioned bottlenecks:

1. Recognition of stationed and vehicles which are in motion on road.
2. The presence of faint lines on the pavement. So the quality of lines not apt for processing
3. Silhouette of trees, buildings and other motors.
4. Presence of sharp edged curves on the street.
5. Merging of lines at the junctions.
6. Writings on road and other markings present on road.
7. Strange street materials e.g. litter thrown and different slopes.
8. Condition which influences the picture quality like streets secured with snow. Substantial downpours, low perceivability because of reflection on wet street

The introductory footstep of lane recognition system is the evulsion of lane data. The various lane identification strategies incorporate 2 methods: component based lane recognition system and model/counterfeit based lane recognition system. The later one (i.e. model based) require high theoretical computational cost. Such system moreover require the assessment of camera. The component based technique basically aims the nature of the photos. The counterfeit based strategies require the inverse perspective mapping which is hard to move to the implanted condition.

This research study dispense the documentary research of 4 to 6 years development of lane detection and lane variation warning framework.

2. LITERATURE SURVEY

A study created an equivalent strategy for lane markers. Inverse Perspective Mapping is carried out initially. The IPM picture is converted into gray scale picture and then standard cross correlation filter is used in the picture. To find out the straight lines, Randomised Hough Transform is used (Borkar et al., 2011). Lane Recognition strategy is developed by Tan et al. To recognise the lane mark, a linear parabolic model is used. Pixels on the pedestrian lanes are recognised to have lower power than the lane mark pixels. The quantifiable properties between the lane mark pixels and pedestrian pathway pixels are being cleared by the rectangular fix. To perceive five grouping i.e.: dashed, dashed-solid, solid dashed, single solid, double-solid, Binary classifiers are utilized. Previous study proposed a theory for lane detection using learning based method. The lane detection data conceded using a feature descriptor (Gopalan et al., 2012).

A study initiated a scheme for lane recognition in terrible environment conditions as well as in dark night. They have contemplated some crucial parts: 1) they perceived a point considering a map and concede a region of interest (ROI) to lessen calculation intricacy. 2) properties of lane hues are used to finish lighting invariant lane mark locale 3) Finally the authors have found a standard way using a grouping strategy from the lane marker contenders (Son et al., 2015).

Y. Ma et al. [4] have come up with a strategy for lane mark assumption, which utilizes one of the two path markings if there is just a single path mark which can be seen; or even, utilizing path stamping models from past moments if there are no lane markings to be seen at the current moment. Likewise, they had additionally proposed using Deep Neural Network systems (DNN) which basically removes noise at the feature extraction stage. two DNN strategies are utilized: a YOLO tool for identifying and

Quick Response Code	This paper was presented at	Access this article online	
	International Conference on Contemporary Issues in Computing (ICCIC-2020) - Virtual IETE Sector V, Salt Lake, Kolkata From 25th-26th July 2020	Website: www.intelcomp-design.com	DOI: 10.26480/etit.02.2020.151.153

removing vehicles from pictures; a CPN tool for recognizing street surfaces so as to deduct noise that are not on street surfaces. they have tried their technique on a video wherein the streets are mostly bended and the lighting conditions change very quickly.

Other study have proposed a strategy that consolidates the color and edge data to recognize the lanes inside the picture either situated far or close to the machine. the region of interest is separated from the picture (Cáceres et al., 2017). The set of lane marking features are separated by changing the shades among street and marking surface is used along with probability density function for extraction purpose. At last, the Otsu's technique was executed utilizing 10x10 sliding window so as to enhance the exhibition in the background/foreground division. Besides, path markings are identified by utilizing a clustering technique.

A recent study introduced another methodology for street path arrangement utilizing an installed camera. At first, path boundaries are recognized utilizing a direct parabolic path model, and a programmed fly camera adjustment method is applied. At that point, a versatile smoothing technique is applied to diminish noise while keeping close edges isolated, and combination of local maxima-minima of the inclination are utilized as signals to recognize path markings. At last, a Bayesian classifier is applied to characterize the path markings (De Paula et al., 2015).

A previous research have proposed an IPM strategy dependent on street limits called BIRD (Boundary-based IPM for Road Recognition), staying away from basic issues of fixed IPM. Besides, coordinating top-down and base up consideration, a robust method of lane detection approach utilizing BIRD tool is proposed (Ying et al., 2016). A study proposed a unique technique that consolidates two particular shading spaces to decrease obstruction in a pre-handling step. The strategy is versatile to various lighting circumstances. The directional gradient is utilized to distinguish the lane mark edges. The technique can distinguish path markings with various complexities forced by shadows, rain, reflection, solid wellsprings of light, for example, headlights and tail lights (Zarbakh et al., 2018).

And the paper focuses on two bits: lane mark recognition and lane type identification. In the recognition step, we utilize the nearest IPM picture to examine and decide the area of weighted pinnacles. In the later part, they have proposed a particular methodology for recognizing different sorts of path markings (Ding et al. 2015).

Others introduced the calculation of path mark distinguished by a vision sensor for path change choice and its application to path level localisation through confidence assessment. By utilizing recognition consequences of each side of path, confidence assessment calculation dependent on probabilistic data association filter (PDAF) is proposed. And by utilizing estimation results from PDAF, lane change choice calculation is likewise proposed (Kim et al., 2014).

Introduced LDW framework dependent on the Hough transform and Euclidean distance. Histogram equalisation is utilized initially to improve the complexity degree of input picture. They isolated the chosen ROI into two subregions, to improve the speed and precision of the framework. At that point Hough transform is utilized for lane recognition in which left and right path checking are distinguished independent of one another (Bhujbal et al., 2015).

A study proposed technique which utilizes a robust path checking detection technique, just as a proficient shape enrolment technique between the identified path markings and a GPS based lane shape, to improve the power and exactness of global localisation of a street vehicle. they have exploited both the state of the art advancements of visual restriction dependent on lane checking location and the wide accessibility of Global Positioning System (GPS) based accessibility (Cui et al., 2014). Previous study proposed a segmentation-by-detection strategy for lane mark extraction. To diminish the computational intricacy, the street locale will be trimmed by vanishing point technique. To upgrade the sensitivity of network lane markings and to improve the detection precision, they have fused a Siamese consideration module by coordinating with the channel and spatial maps into the system. In the division module, their segmentation technique is based on traditional image morphological calculations, which is less computational and furthermore can accomplish pixel-level exactness. Moreover, the sliding inquiry box and maximum stable external region (MSER) calculations are used to make up for missed recognition and position blunder of bounding boxes (Zhang et al., 2019). Some proposed frameworks which depends on a single 120 degrees fish eye camera and a 180 degrees LIDAR sensor. For the path recognition an improved path checking procedure was utilized which was meant to be the position of the lines. The paper depicts usage of the path identification

framework utilizing Hough transform to identify the line. Based on the recognised path markings, the location of the relative vehicle is resolved concerning whether it is in its path or diverted from the path (Amaradi et al., 2016).

A recent study has proposed an perpendicular traversal linear search technique with combination of color segmentation to address alternatives in lane marking which happens because of different climatic conditions, shadows, and obstructions, for example, traffic on the lanes. robustness of this technique has been tried under different street conditions and tested results have accomplished an exactness of 89% for the general application execution (Yapa et al., 2017). Novel techniques for present and nearby lane recognition for a self-governing vehicle. These strategies depend on discovering current path by utilizing path markings and assessing nearby paths of the test vehicle by some geometric estimation. Moreover when path markings are taken cover behind articles or the input video quality is exceptionally low, another calculation for path coordinating so as to approve the identified paths is recommended. At last a departure warning algorithm is proposed that is exceptionally valuable for impediment avoidance (Kalaki et al., 2014).

A primary point was to distinguish the structured lane, and better recognition impact of path line is acquired. the primary occupation was presenting a strategy for separating path edge pixels by emulating Canny edge identification system to remove edge pixels gradient and section it with threshold determined from OTSU calculation, and afterward path line recognition and following is acknowledged by Hough transform and Kalman filter (Li-Yong et al., 2018). A system of the co-stimulation of intelligent vehicle dependent on visual route is introduced, which is utilized to dissect path keeping of vehicle under crosswind. A rectangular ROI for lane image is set to accelerate image processing, and lane boundation are identified by joining with the edge extraction and the Hough transform. henceforth vehicle model is fabricated in Car Sim, and three kinds of crosswind model are done in MATLAB, which are utilized to co-simulation path keeping of vehicle under crosswind (Li et al., 2018).

An FPGA based real-time lane detection system for automotive applications was proposed (Hwang, 2016). Conventional Canny-Hough lane detection is used for reduction of computational complexity and algorithm is modified for achieving satisfactory results for the real-time processing. By using the FPGA platform the prototype is designed and in comparison to the previous detection algorithm, 41% of processing rate was achieved. Others presented a vigorous lane location and an algorithm to adapt to complex situations and to diminish the impact of threshold. Symmetrical local threshold (SLT) is proposed to improve the feature map and for feature extraction (Ozgunalp et al., 2014).

A study introduced a proficient, powerful Lane Departure Warning System (LDWS) and a frontal impact cautioning framework, which operate at various enlightenment conditions. A monoscopic dashboard camera fitted in the windshield of the vehicle is utilised in this methodology. Inverse Perspective Mapping is used for further calculation. Hough technique is applied on this IPM to discover the paths, lastly RANSAC Bezier spline fitting is done to discover the lanes. To recognize vehicles, Hough technique is applied on the picture to check for level lines made by the vehicle (Vinuchandran et al. 2017).

A novel image processing technique to identify lane markers. So as to improve the precision and hostile to impedance capacity the region of interest for source picture is resolved dependent on spatial positional relationship. A minute size identification window scanner moving in the region of interest to decide if there is a path mark at the actual position as indicated by the traits of the image in recognition window (Zhu et al., 2017). Also proposed a novel methodology of lane estimator with the help of Kalman Filter. The lane estimator is structured with clothoid street model and a presumption dependent on lane width. To confirm the presentation of proposed lane estimator, genuine vehicle test in the open street is done. The test outcome shows the robustness of the proposed path estimator even in disappointment circumstance of front camera. Besides, the outcome additionally demonstrated that exactness and value of path estimation based objective choice (Song et al., 2017).

Other research applied the technique for cubic B-spline bend fitting dependent on discrete binary molecule swarm enhancement in fitting bend path line. As indicated by the qualities of the vertical and transverse width of the line, must be straight for the extraction of lane features. At that point they had chosen the cubic B-spline bend to fit the arched path, first the discrete binary molecule swarm technique to enhance the number of control points, then by the least square technique to compute the control points of B-spline curve (Li et al., 2017).

A strategy for sideward protection for the path location work to address a disappointment of the picture sensor-based computerized driving framework. The proposed calculation comprises of three sections: the initial segment is the ego-motion estimator that appraises the development of a vehicle; the second is a coordinated path identification sensor module, which reacts to failure by assessing path data at the corresponding time; the latter is a path estimator, which tracks path coefficients dependent on constant path widths. A mix of these three modules and the prediction of the path coefficient, C3, in the virtual sensor, empowers an increasingly robust reaction to lane recognition failure (Song et al., 2019).

3. CONCLUSION

Various methodologies of lane detection and lane departure system has been deliberated in this research paper. Different difficulties confronted path identification framework has additionally been researched in this paper. If lane location are exact, at that point lane identification can occur. To guarantee appropriate lane location, different image pre-processing strategies are utilized by authors, for example, histogram adjustment, grayscale change, morphological channels, and so on. For path location, numerous strategies have evolved, for example, B-Snake, quick filtering, local gradient features, Hough change, and so forth.

REFERENCES

- Amaradi P., Sriramoju N., Dang Li, Tewolde G. S. and Kwon J., 2016, Lane following and obstacle detection techniques in autonomous driving vehicles, 2016 IEEE International Conference on Electro Information Technology (EIT), Grand Forks, ND, 0674-0679.
- Bhujbal P. N. and Narote S. P., 2015, Lane departure warning system based on Hough transform and Euclidean distance, 2015 Third International Conference on Image Information Processing (ICIIP), Wanknaghat, 370-373.
- Borkar A., Hayes M., and Smith M.T., 2011, Polar randomized hough transform for lane detection using loose constraints of parallel lines. Acoustics, Speech and Signal Processing (ICASSP), 2011 IEEE International Conference on. IEEE.
- Cáceres Hernández D., Filonenko A., Shahbaz A. and Jo K., 2017, Lane marking detection using image features and line fitting model, 2017 10th International Conference on Human System Interactions (HSI), Ulsan, 234-238.
- Cui D., Xue J., Du S. and Zheng N., 2014, Real-time global localization of intelligent road vehicles in lane-level via lane marking detection and shape registration, 2014 IEEE/RSJ International Conference on Intelligent Robots and Systems, Chicago, IL, 4958-4964
- De Paula M. B. and Jung C. R., 2015, Automatic Detection and Classification of Road Lane Markings Using Onboard Vehicular Cameras, in *IEEE Transactions on Intelligent Transportation Systems*, 16(6), 3160-3169
- Ding D., Yoo J., Jung J., Jin S. and Kwon S., 2015, Various lane marking detection and classification for vision-based navigation system, 2015 IEEE International Conference on Consumer Electronics (ICCE), Las Vegas, NV, 491-492.
- Gopalan R., Hong T., Shneier M., and Chellappa R., 2012, A Learning Approach Towards Detection and Tracking of Lane Markings, *Intelligent Transportation Systems*, IEEE Transactions on, 13(3), 1088- 1098.
- Hwang S. and Lee Y., 2016, FPGA-based real-time lane detection for advanced driver assistance systems, 2016 IEEE Asia Pacific Conference on Circuits and Systems (APCCAS), Jeju, 218-219.
- Kalaki A. S. and Safabakhsh R., 2014, Current and adjacent lanes detection for an autonomous vehicle to facilitate obstacle avoidance using a monocular camera, 2014 Iranian Conference on Intelligent Systems (ICIS), Bam, 1-6.
- Kim H., Kwon O., Song B., Lee H., and Jang H., 2014, Lane confidence assessment and lane change decision for lane-level localization, 2014 14th International Conference on Control, Automation and Systems (ICCAS 2014), Seoul, 1448-1451.
- Li S., Xu J., Wei W. and Qi H., 2017, Curve lane detection based on the binary particle swarm optimization, 2017 29th Chinese Control and Decision Conference (CCDC), Chongqing, 75-80.
- Li Z., Li S., Li Z., Cui G. and Wu X., 2018, Lane Keeping of Intelligent Vehicle under Crosswind Based on Visual Navigation, 2018 5th International Conference on Information Science and Control Engineering (ICISCE), Zhengzhou, 290-294.
- Li-Yong M., Chun-Sheng H., Yu-Qing H., Yun-Jing L. and Pei-Lun Y., 2018, A Lane Detection Technique Based on Adaptive Threshold Segmentation of Lane Gradient Image, 2018 4th Annual International Conference on Network and Information Systems for Computers (ICNISC), Wuhan, China, 182-186.
- Ma Y., Havyarimana V., Bai J. and Xiao Z., 2018, Vision-Based Lane Detection and Lane-Marking Model Inference: A Three-Step Deep Learning Approach, 2018 9th International Symposium on Parallel Architectures, Algorithms and Programming (PAAP), Taipei, Taiwan, 183-190.
- Nguyen T., Tran V. and Huang C., 2018, Lane Detection and Tracking Based on Fully Convolutional Networks and Probabilistic Graphical Models, 2018 IEEE International Conference on Systems, Man, and Cybernetics (SMC), Miyazaki, Japan, 1282-1287.
- Ozgunalp U. and Dahnoun N., 2014, Robust lane detection & tracking based on novel feature extraction and lane categorization, 2014 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), Florence, 8129-8133.
- Son J., Yoo H., Kim S., Sohn K., 2015. Real-time illumination invariant lane detection for lane departure warning system, *Expert Systems with Applications*, 42,1816–1824.
- Song M. et al., 2017, A novel approach to the enhancement of lane estimator by using Kalman filter, 2017 17th International Conference on Control, Automation and Systems (ICCAS), Jeju, 1078-1082.
- Song M., Kim C., Kim M. and K. Yi, 2019, Enhanced Lane Tracking Algorithm Using Ego-Motion Estimator for Fail-Safe Operation, in *IEEE Access*, 7,155158-155170.
- Vinuchandran A. V. and Shanmugasundaram R., 2017, A real-time lane departure warning and vehicle detection system using monoscopic camera, 2017 International Conference on Intelligent Computing, Instrumentation and Control Technologies (ICICT), Kannur, 1565-1569.
- Yapa L. A. N. and Atukorale A. S., 2017, Lane detection using hybrid colour segmentation and perpendicular traversal linear search algorithm, 2017 Seventeenth International Conference on Advances in ICT for Emerging Regions (ICTer), Colombo, 1-5.
- Ying Z. and Li G., 2016, Robust lane marking detection using boundary-based inverse perspective mapping, 2016 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), Shanghai, 1921-1925.
- Zarbakht N. and Zou J. J., 2018, Lane Detection Under Adverse Conditions Based on Dual Color Space, 2018 Digital Image Computing: Techniques and Applications (DICTA), Canberra, Australia, 1-5.
- Zhang W., Mi Z., Zheng Y., Gao Q. and Li W., 2019, Road Marking Segmentation Based on Siamese Attention Module and Maximum Stable External Region, in *IEEE Access*, 7,143710-143720.
- Zhu S., Yu T. and Wang J., 2017, A new approach to lane detection based on pattern recognition technology, 2017 IEEE 2nd Advanced Information Technology, Electronic and Automation Control Conference (IAEAC), Chongqing, 404-408.