RESEARCH ARTICLE

ATTENUATION OF WATER-BOTTOM MULTIPLES: A CASE STUDY FROM SHALLOW MARINE IN THE NIGER DELTA, NIGERIA

Dora B. Umoetok¹, Etim D. Uko², Aminayanasa P. Ngeri²¹Integrated Data Sciences Limited, Nigeria National Petroleum Corporation, Benin City, Nigeria.²Department of Physics, Rivers State University, PMB 5080, Port Harcourt, Nigeria.*Corresponding Author Email: umoetok.dorothy@nnpc-idsl.com, e_uko@yahoo.com, paddyngeri@gmail.com

This is an open access article distributed under the Creative Commons Attribution License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

ARTICLE DETAILS

ABSTRACT

Article History:

Received 10 June 2019
Accepted 15 July 2019
Available online 1 August 2019

ABSTRACT

Three-dimensional (3D) seismic data in the shallow offshore Niger Delta was acquired and processed. The dataset at water-depth of 250m was masked by interbed multiples and water bottom multiples. The major differences exploited for the multiples removal were velocity discrimination, frequency, wavelength, periodicity, and predictability using predictive deconvolution and Radon techniques. The dominant frequency of the primary events varies between 3 and 120Hz having dominant amplitude ranging between -12dB and -45dB. The dominant frequency of the multiples ranges between 8 and 90Hz, while dominant amplitude ranges between -5dB and -45dB. Multiples were predominantly short-period with water bottom reverberation having high-frequency and high-amplitude. With the short-period and high-frequency content, the characteristics of the multiples were quite close to those of the primaries. Water-depth and geology are major generators of the waterbottom and interbed multiple energies in a marine environment. The multiple parameters established in this work would be required as inputs in the multiples-attenuation processing program for a better image of the subsurface geology.

KEYWORDS

Seismic, processing, multiples, attenuation, shallow marine, Niger Delta, Nigeria.

1. INTRODUCTION

The occurrence of strong primary reflections necessarily implies the occurrence of strong multiples. Multiples are delayed reflections that interfere with the primary reflections. The delay occurs because the reflection energy, reverberating between two layers that are highly reflective, has taken a more complex and longer ray path from source to receiver. While any two layers with high reflectivity can create a multiple image, it is energy reverberating between the seafloor and the sea surface that is the most important issue to deal with. The three main methods of multiples removal are: treat the multiple as a long, ringing wavelet, and use signal processing to simplify it; create a model of the multiple and try and subtract it from the data, and use the difference in stacking velocity of the primary and multiple to remove the multiple [1-5].

The modelling approaches, such as SRME (Surface Related Multiple Elimination), usually require the primary seafloor reflection to be the first clear signal. The velocity discrimination method uses the Parabolic Radon Transform (PRT) approach. The Radon transform is a generic mathematical procedure where input data in the frequency domain are decomposed into a series of events in the RADON domain. One of the key elements of the PRT as a demultiple method is that a Normal Moveout (NMO) correction is applied to the data. This helps do two things: (i) target the primaries and multiples – for example we can use water velocity or a picked primary trend, and (ii) approximate the reflections (which are originally hyperbolic) through a series of parabolic curves [6].

In marine areas, the sea-floor (water bottom) and free water surface have large acoustic impedance contrasts and therefore, generate multiples which are recorded together with the desired primary reflections [7- 10]. The presence of multiples often has an obscuring effect in the interpretation of target reflections in the seismic section. Multiples always

reduce the signal-to-noise ratio, interfere with the identification of primaries and lead to difficulties in velocity analysis and in migration. Multiples can present pitfalls for the interpreter and cause problems in seismic data interpretation. Multiples can result in spurious images and amplitudes and interpretation uncertainties. The aim of this research is to attenuate multiples in order to appropriately image the geology and provide appropriate interpretable image of the subsurface, thereby reducing the risk of drilling dry wells.

2. THEORETICAL BACKGROUND

Many different methodologies have been developed based on different characteristics of the multiples in the history of the multiple attenuation research [11-15]. Multiple attenuation methods can be briefly classified into three categories: (1) methods which rely on the natural periodicity of multiples or use a transform to introduce periodicity into the data; (2) methods that discriminate primaries and multiples according to some specific features or properties; (3) methods which predict and then subtract the multiple reflections from input seismic data with wave-equation theories.

Multiple-suppression techniques make use of the different characteristics that distinguish multiple from primary reflections. The characteristics most frequently used are the moveout differences between multiple and primary and the periodic nature of multiples due to the fact that multiples are repetitions of some primary reflection [16-18]. The first characteristic may be exploited to attenuate the multiples by stacking the data or moveout filters [19-21]. Short-period multiples are approximately periodic and may be discriminated using predictive and adaptive deconvolution methods [22,23]. Another common approach is suppression based upon wave-equation methods [24-27].

Radon de-multiple method is one of the methods of multiple attenuation. It generally consists of three stages: decomposition, modelling and subtraction. This scheme usually decomposes data (i.e. both primaries and multiples) into parabolas as this allows the method to operate in the frequency domain. It models the multiples by muting in the Radon domain, and then subtracts the resulting model from the original data. Both the modelling and subtraction are generally performed with least squares algorithms in the frequency domain. The Radon de-multiple method performs well with the correct primary velocity and adequate move-out differences between the primaries and multiples [28-30].

3. THE STUDY AREA AND GEOLOGICAL SETTING

The area of study is within the offshore portion of the Niger Delta Province. It is delineated by the geology of southern Nigeria and south-western Cameroon (Figure 1) in the Gulf of Guinea. The Gulf of Guinea consists of the coastal and offshore areas of Cote d'Ivoire, Ghana, Togo, and Benin, and the western part of the coast of Nigeria, from the Liberian border east to the west edge of the Niger Delta. The province includes the Ivory Coast, Tano, Central, Saltpond, Keta, and Benin basins and the Dahomey Embayment. The Gulf of Guinea formed at the culmination of Late Jurassic to Early Cretaceous tectonism that was characterized by both block and transform faulting superimposed across an extensive Paleozoic basin breakup of the African, North American, and South American paleocontinents [31]. The deep offshore contains Alba, Azurita and Zafiro Canyons [32-34].

Figure 1: Map of Niger Delta showing the area of study [18, 15].

4. MATERIALS AND METHODOLOGY

4.1 Data Acquisition

In the areas under this study, the data are from Shallow Marine (250m deep) in the Gulf of Guinea, off the Niger Delta. Two traverse lines arbitrarily selected - inline and crossline from sample datasets - are taken from the offshore Niger Delta area of southern Nigeria to demonstrate the impact of multiple removal from a seismic data. The data is with water depth of 250meters (shallow marine). Acquisition parameters for datasets are shown in Table 1. Figure 2 shows the raw Stack for dataset for Inline 1001 masked by noise and multiples.

Table 1: Acquisition Parameters for shallow marine

Parameters	Shallow Marine
streamer	
Recording length	6s
Sample rate	2ms
Bin size	12.5 x 18.75m
Far offset	4500m
Coverage (fold)	45
Channels	360
Cables	8
Cable depth	7m
Cable separation	100m
Group interval	12.5
Source	
Source power	2120ci 2000psi
Source depth	5m
Shot point interval	25m

Figure 2: Raw Shots for Dataset for Inline 1001

4.2 Data Processing

The data processing was executed on a 64 bit processing system comprising of a 32-Node pc cluster with 50tb online storage disk. Job submission was done using an RS690 engineering workstation as front end machine. Proprietary software with client-server architecture developed by Information Technology (IT) department of Integrated Data Services Limited was used for the processing. The first multiple attenuation method applied to the data was filtering based on move-out and dip discrimination. This determined the velocities of Multiples energy and separates them from primaries. The common-mid-point (CMP) gathers, semblance and stack response are all placed side by side for quality control purposes. The CMP gathers were NMO-corrected with velocity functions that are between the primary and multiple velocities, such that the overcorrected primaries map into the negative wave numbers plane and the under-corrected multiples map unto the positive wave numbers. By muting the data for the positive wave numbers, multiples were suppressed.

An NMO correction was applied to make the originally hyperbolic events in CMP gathers nearly parabolic in the x-t domain, thereby mapping them into approximately discrete points after the parabolic transform. Yilmaz (1989) improved on Hampson's method by replacing the NMO correction prior to the transform with a stretching of the CMP data. This converts the hyperbolic events to exact parabolas, improving the velocity resolution and hence the primary-multiple discrimination in the transform domain.

5. RESULTS AND DISCUSSION

5.1 Velocity Discrimination

A preliminary 2km by 2km velocity analysis was performed on 8 CMP locations. Inline stack was displayed to validate the result of the velocities. CMP velocity function for dataset and the raw data without velocity applied are shown in Figures 3 - 5. Figure 5 clearly shows the effect of velocity application on dataset. It is clear from results that stack velocity has resolved some of the structures in the dataset. Improvement in the dataset is very pronounced because of the gentle subsurface structures.

Figure 3: Velocity analysis for dataset for Inline 1001.

Figure 4: Inline 1001 stack from dataset after velocity without velocity application

Figure 5: Inline 1001 from dataset stack Application

5.2 Amplitude Analysis of Primaries and Multiples

Spectral analysis was applied on the dataset to see the difference between the primaries and multiples amplitude values. Amplitude response trend indicates that the processing preserved true amplitudes as there was no change in the spectrum (Figure 6). Spectral analysis for the dataset showed that the multiple energies were of higher amplitude than the primaries. This was a major characteristic which was used for its discrimination and attenuation. The amplitudes of primaries and multiples are significantly different as shown in Figures 7 and 8.

Figure 6: Amplitude Response for dataset from inline 1001

Figure 7: Pre-demultiple amplitude for dataset

Figure 8: Overlay of amplitude spectrum for primaries and multiples post demultiple for dataset from inline 1001

5.3 Predictive Deconvolution

Predictive deconvolution was performed on the dataset. Various values of deconvolution operator, operator length, and deconvolution window and frequency range were applied. Figures 9 and 10 show the dataset without and with deconvolution operations.

Figure 9: Inline 1001 stack from dataset (Grey Scale) with events with collapsed diffractions.

Figure 10: Inline 1001 from dataset (Grey Scale) without deconvolution masked by ringing and deconvolution applied: Sharper events with diffractions.

5.4 Radon Transformation

The objective of the Radon transformation process was to establish parameters for the removal of multiples that may be discriminated from primaries through differences in velocity or, more generally, in moveout. A high-resolution Radon transform was applied to the dataset in order to model or remove events based on moveout criteria. Radon parameters for minimum and maximum moveout in t-x (ms) were 2200ms, 3000ms respectively. Figures 11 and 12 are stacks with and without Radon demultiple. Figure 13 is the difference plot, after the removal of the multiple energy from dataset. Radon had a lot of significant improvements on the data.

Figure 11: Before Radon Demultiple

Figure 12: After Radon Demultiple

Figure 13: Difference after Radon Demultiple

5.5 Dominant Characteristics of Multiples

Owing to the dominant characteristics (velocity, frequency wavelength, etc.) of the multiples as compared to those of primaries, Velocity Discrimination and Radon transformation was used to eliminate multiples in shallow marine data. Multiples were observed to be of predominantly short-periods with some water bottom reverberation, and high frequency and high amplitude resulting from short travel time. With the short-period and high-frequency content, multiples were quite close to the primaries and therefore required a lot of care in the attenuation process.

5.6 Velocity Responses of Primaries and Multiples

From the velocity spectrum and semblance stack, it is clear that the velocities of multiples are much lower than those of primary events. This is the reason the multiple energy was significantly attenuated when the dataset was stacked with higher velocities.

6. CONCLUSION

The shallow marine dataset at depth of 250m had predominantly interbedded multiples. The major differences that were exploited for the multiples removal were multiple-attributes of velocity, frequency, wavelength, periodicity, and predictability using predictive deconvolution and Radon techniques. The dominant frequency of the primary events varies between 3 and 120Hz having dominant amplitude ranging between -12dB and -45dB. The dominant frequency of the multiples ranges between 8 and 90Hz, while dominant amplitude ranges between -5dB and -45dB. This work is relevant because when multiples are attenuated from a seismic section, a better image of the subsurface geology is obtained, thereby reducing the risk of drilling dry oil wells.

ACKNOWLEDGEMENT

The authors are grateful to The Nigeria National Petroleum Corporation for provision of data. Wale Adelodun, Ya'u Auwal, Tope Omotoso and Nelson Ebini are also appreciated for provision of processing technical assistance.

REFERENCES

[1] Weglein, A. 1999. Multiple attenuation: an overview of recent advances and the road ahead. *The Leading Edge*, 18 (1), 40 – 44.

[2] Niu, B.H., Sheng, C., Huang, X.W. 2002a. Progress in multiple attenuation techniques based on wave equation. *Progress. Geophysics*, 17 (3), 480-485.

[3] Niu, B.H., Sheng, C., Huang, X.W. 2002b. Multiple attenuation techniques based on wave equation. *Earth Science Frontiers*, 9 (2), 511-517.

[4] Huang, X.W., Wu, L., Niu, B.H. 2003. Reconstruction of seismic traces by parabolic Radon transform. *Journal of China University of Mining Science & Technology*, 32 (5), 534-539.

[5] Ogagarue, D.O., Ebeniro, J.O. 2014. Water Bottom Multiple Elimination and Data Quality Enhancement Using Parabolic Radon Transform: A Case Study of 3D Seismic Data from Offshore Niger Delta. *Journal of Geosciences and Geomatics*, 2 (4) 172-177.

[6] Ogagarue, D.O., Nwankwo, C.N. 2016. A Statistical Amplitude Analysis Method with Application to Streamer Data from the Niger Delta Offshore. *Journal of Applied Geology and Geophysics*, 4 (2), 10-14.

[7] Umoetok, D.B., Uko, E.D. 2015. Characteristics of multiples in shallow and deep marine seismograms in Gulf of Guinea. *Petroleum Technology Development Journal*, 5 (2), 72 – 83.

[8] Meles, G.A., Löer, K., Ravasi, M., Curtis, A., Carlos Alberto da Costa Filho, C.A.C. 2015. Internal multiple prediction and removal using Marchenko autofocusing and seismic interferometry. *Geophysics*, 80 (1), A7-A11.

[9] Wang, J., Wang, S. 2013. Practical implementation of SRME for land multiple attenuation. *GeoConvention Integration*, 1-5.

[10] Umoetok, D.B. 2019. Land multiples prediction and attenuation in Bornu-Chad Basin, Nigeria. Unpublished PhD Thesis, Rivers State University, Port Harcourt, Nigeria.

[11] Hansen, R.F., Johnson, C.H. 1948. Multiple reflections of seismic energy. *Geophysics*, 13, 58-85.

[12] Yilmaz, O. 1987. *Seismic Data Processing*. SEG Tulsa, Oklahoma.

[13] Foster, D.J., Mosher, C.C. 1992. Suppression of multiple reflections using the Radon transform. *Geophysics*, 57 (3), 386 - 395.

[14] Huang, X.W., Sun, C.Y., Niu, B.H., Wang, H.D., Zeng, M.S. 2005. Surface-related multiple prediction and suppression based on data-consistency: a theoretical study and test. *Chinese Journal of Geophysics*, 48 (1), 188-196.

[15] Bruso, J.M., Wallace, R.L. 2004. *Gulf of Guinea geology*. Oil and gas Journal.

[16] Kulke, H. 1995. *Nigeria In Kulke, H. (Ed), Regional Petroleum Geology of the World. Part II: Africa, America, Australia and Antarctica: Berlin, Gebrüder Borntraeger*, 143 - 172.

[17] Klett, T. R., Ahlbrandt, T.S., Schmoker, J.W., Dolton, J.L. 1997. Ranking of the world's oilroleumand gas pr volumes. *U.S. Geological Survey Open-file Report-97-463*, CD-ROM.

[18] Doust, H., Omatsola, E. 1990. *Niger Delta In Edwards, J. D. and Santogrossi, P. A., (Eds), Divergent/passive Margin Basins, AAPG Memoir 48: Tulsa. American Association of Petroleum Geologists*, 239 - 248.

[19] Hospers, J. 1965. Gravity field and structure of the Niger Delta, Nigeria, West Africa. *Geological Society of American Bulletin*, 76, 407 - 422.

[20] Kaplan, A., Lusser, C.U., Norton, I.O. 1994. Tectonic map of the world, panel 10. *American Association of Petroleum Geologists, Tulsa*.

[21] Naija247 News. 2011. Group wants urgent oil Exploration in the North.

[22] Schneider, W., Prince, E., Giles, B. 1965. A new data-processing technique for multiple attenuation exploiting differential moveout. *Geophysics*, 30, 348 – 362.

[23] Hardy, R.J.J., Warner, M.R., Hobbs, R.W. 1989. Labelling long-period multiple reflections. *Geophysics*, 54, 122 – 126.

[24] Yilmaz, O. 1989. Velocity stack processing. *Geophysical Prospecting*, 37, 357 – 382.

[25] Backus, M.M. 1959. Water reverberations, their nature and elimination. *Geophysics*, 55, 1508 – 1511.

[26] Peacock, K., Treitel, S. 1969. Predictive deconvolution – theory and

practice. Geophysics, 34, 155 – 169.

[27] Berryhill, J.R., Kim, Y.C. 1986. Deep water peg-legs and multiples: elimination and suppression. Geophysics, 51, 2177 – 2184.

[28] Fokkema, J., Berg, P.V. 1990. Removal of surface-related wave phenomena: the marine case. 60th SEG meeting, San Francisco, USA, Expanded Abstracts, 983 – 988.

[29] Verschuur, D.J., Berkhout, A.J. 1992. Surface-related multiple eliminations: Practical Aspects. 62nd SEG Meeting, New Orleans, USA, Expanded Abstracts, 1100 – 1103.

[30] Keydar, S., Gelchinhinsky, B., Berkovitch, A. 1996. Common shot-point

stacking and imaging method. Journal of Seismic Exploration, 5, 261 – 274.

[31] Dix, C.H. 1948. The existence of multiple reflections. Geophysics, 13, 49 - 50.

[32] Gutenberg, B., Fu, C.Y. 1948. Remarks on multiple reflections. Geophysics, 13, 45 - 48.

[33] Waterman, J.C. 1948. Multiple-reflection evidence. Geophysics, 13, 41 - 44.

[34] Burg, K.E., Ewing, M., Press, F., Stulken, E.J. 1951. A seismic wave guide phenomenon. Geophysics, 16, 594 - 612.