THE INNOVATIVE DESIGNING OF THE CONNECTING-ROD SWINGROD GEAR-DRIVING INTERNAL-COMBUSTION ENGINES

Yi Fan

Transportation College, Nanning University, Nanning City Guangxi Province, China

*Corresponding Author Email: 64608769@qq.com

This is an open access article distributed under the Creative Commons Attribution License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited

ARTICLE DETAILS

Article History:

Received 02 october 2017

Accepted 06 october 2017

Available online 11 november 2017

Keywords

gear driving, connecting-rod and swing-rod, internal-combustion engine, shaft torsion

ABSTRACT

Aiming at the current problems like short drive arms and low mechanism efficiency existed in the crank connecting rod piston internal-combustion engines, the paper proposes a design of a kind of connecting-rod swing-rod gear-driving internal-combustion engine that can convert two reversal thrusts of the piston linear reciprocating motion into two reversal torques of the swing rod and then into one one-way torque by the gear sets. The maximum piston thrust F are highly converted into the shaft torsion F_t , which makes the connecting-rod swing-rod gear-driving internal-combustion engines' maximum shaft torque increase by about 34% than that of the crank engines. What's more, the effective fuel consumption rate is reduced. The connecting-rod swing-rod gear-driving internal-combustion engines directly use the mature technology of the traditional internal-combustion engines' straight reciprocating piston structure to trial-manufacture the prototypes and produce in enormous quantities. Production difficulty will be less than ever. The internal-combustion engines' environmental performance is improved.

1. Introduction

Nowadays, the internal-combustion engines are widely used in some important areas like industry and agriculture, communications and transportation industry and national defense industry. Due to the world's greatly increasing demand, both the social benefit and the economic benefit of the internal-combustion engines are notable. Some developed countries even consider the industries that take the internal-combustion engines as the core as the most important economic base. Big cities are crowded with automobiles; people suffer from the serious pollution from the internal-combustion engines. Under these background, every country constantly makes stricter and stricter demands and restrictions to the internal-combustion engines, eliminates the backwards, and finally popularizes the environmental protective. Therefore, developing good-performance internal-combustion engines can bring good social benefit and economic benefit. They will have a bright market prospects.

The current cylinder-piston internal-combustion engines use the crankshaft connecting rod and slider conversion mechanism. It is known that the crankshaft connecting rod and slider conversion mechanism has a 0 point, and its theoretical mechanical efficiency is $2/\pi$. Its piston stroke approximately equals to the cylinder diameter, which cannot be lengthened at will. The exhaust gas pressure is around 0.105Mpa to 0.12Mpa. The temperature is between 427°C and 627°C. The piston stroke cannot be lengthening either. Although the turbine converts some exhaust gas pressure into the inlet pressure and improves the power of the internal-combustion engine, the effective thermal efficiency of the practical internal-combustion engine still hovers around 40%, and it is hard to go beyond 50%. The maximum thermal efficiency of the laboratory diesel engines can only reach 52%.

For over a century, people have put the rotor and the eccentric gear as the research direction, thinking the mechanical efficiency may be high by reducing the intermediate links. Felix Wankel in Germany developed the rotary engine and solved the sealing problem in 1957. However, the eccentric gear transmission had two fatal smalls. One was the gas expansion coefficient (the Maximum volume ratio and the minimum volume ratio of gas) small, the other was the arm of force small [1-2]. When the rotary engine decelerates, these two smalls produce backfire and much CH with high exhaust temperature, a high effective fuel consumption rate and a bad low-speed performance. What's more, its effective thermal efficiency and the environmental compatibility is lower than that of the

crank connecting rod reciprocating piston internal-combustion engine (Crank Engine for short), which has no economic and practical significance. Today, the four-stroke crank machine is widely used for its technological maturity.

2. THE INNOVATIVE DESIGNING OF THE CONNECTING-ROD SWING-ROD GEAR-DRIVING INTERNAL-COMBUSTION ENGINES

According to the fundamental law of gearing, the ideal mechanical efficiency of gear driving is 100%, and the gear ratio can equal to the effect of the force transformation. For example, see [3]. From the Line $p-\phi$ of the four-stroke crank machine in Figure 3, the tangential force of the crankshaft is F_t . The crankshaft radius of gyration is r . The crank rotation angle is ϕ , and the swing angle of connecting rod is β . $F_t = F \sin(\phi + \beta) / \cos \beta$. Suppose the connecting rod length L equal to three r , and we can draw the crankshaft torque Line F_t of the four-stroke crank machine as the Line ② $F_t-\phi$ in Figure 3. From Line $F_t-\phi$ in Figure 3, when it is 0 degree or 180 degrees, the value of F_t is 0, and there is a peak value between these two points. The peak value of F_t is at about 25 degrees to 65 degrees in ϕ . $F_t = F \sin(\phi + \beta) / \cos \beta$. The peak value of line F_t is influenced by the peak value of Line ① $F-\phi$. Its peak value removes ahead to 0 degree to 25 degrees of ϕ .

In Figure 3, the peak value of Line F is between 0 and 25°, while Line F_t 's is between 25° and 65°. These two miss each other. The maximum F value of Line $F_t-\phi$ is only about half of Line $F-\phi$'s.

The gear driving can effectively change the peak value F of the early thrust from the gas to the piston into the shaft torsion F_t . At the same time, the piston stroke of the gear driving can be arbitrarily chosen, and the ratio of the piston stroke and the cylinder diameter can be increased. What's more, the exhaust temperature and pressure are close to the outside air and the exhaust gas pressure is working. So, the effective thermal efficiency is enhanced, and the environmental compatibility is improved. Here comes the problem that there may be damaged collision, jamming and interference when using the gear to shift two reversal torques into one one-way torque [4]. This paper proposes a kind of connecting-rod swing-rod gear-driving Internal-combustion Engine which can help to realize the following three aspects. Firstly, two reversal thrusts of the piston linear reciprocating motion are converted into two reversal torques of the swing rod. Secondly, these two reversal torques of the swing rod are converted into one one-way torque by the gear sets. Thirdly, conditions are created

to 0 as in Figure 2. $S=49.38\text{mm}-48.75\text{mm}=0.63\text{mm}$.

Modify the tooth height of the engaging-out gear, and produce an anti-jamming clearance S for the meshing gear. As in Figure 2, the distance from the addendum of Tooth ⑤ to its gear center is $R44.27$, and we can get the value S 0.65mm.

Modify the slope of the engaging-out gear, and make it slowly close to the meshing gear. As in Figure 2, one third of the addendum of Tooth ⑤ is flat, while the other parts are slope. The slope intersects with the profile that is $R43.03$, which makes the meshing gear slides on the slope and makes the engaging-out gear slowly get in touch.

3.4 Cylinder blocks in parallel

Several cylinder blocks should be connected in parallel to work in order to get higher power. The Four-stroke Swing-rod Gear-driving Engine listed here makes two cylinders into one-cylinder block. If all the cylinders are placed in parallel together, one cylinder is one-cylinder block. Several cylinder blocks are connected in parallel to work.

Figure 4: A-A Profile Figure of Two Cylinder Blocks Cooperating

As in Figure 4, two-cylinder blocks are placed in parallel sharing two gears to form a two-cylinder four-stroke swing-rod gear-driving engine. One piston works to drive one stroke, and four cylinders drive four strokes. Two cylinders are connected in parallel, while one piston works in every stroke. Internal-combustion engine's shafts can continuously output the torque. Using this method, several cylinder blocks are in parallel and can work cooperatively. Increasing the piston stroke and fully using the tail gas to drive the piston to work can greatly improve the effective thermal efficiency.

4 CONCLUSION

The connecting-rod swing-rod gear-driving internal-combustion engines directly use the mature technology of the traditional internal-combustion engines' straight reciprocating piston structure to trial-manufacture the prototypes and produce in enormous quantities. Production difficulty will be less than ever.

The maximum piston thrust F are highly converted into the shaft torsion F_t , which makes the connecting-rod swing-rod gear-driving internal-combustion engines' maximum shaft torque increase by about 34% than that of the crank engines. What's more, the effective fuel consumption rate is reduced.

The tail gas is effectively utilized to do useful work, and the effective thermal efficiency of the connecting-rod swing-rod gear-driving internal-combustion engines is heightened. At the same time, the exhaust gas temperature and pressure are diminished, and the noise pollution and thermal pollution are greatly reduced. The internal-combustion engines' environmental performance is improved.

ACKNOWLEDGMENTS

This paper was financially supported by the Basic Ability Promotion Project of Young and Middle-aged Teachers in Guangxi Universities (2017KY1437) and the Professor Foster Project of Nanning University (2016JSGC07).

REFERENCES

- [1] Antonelli, M., Baccioli, A., Francesconi, M., Desideri, U., Martorano, L. 2014. Operating maps of a rotary engine used as an expander for micro-generation with various working fluids. *Applied Energy*, 113 (2), 742-750.
- [2] Fan, B., Pan, J., Yang, W., Zhu, Y., Chen, W. 2016. Effects of hydrogen blending mode on combustion process of a rotary engine fueled with natural gas/hydrogen blends. *International Journal of Hydrogen Energy*, 41 (6), 4039-4053.
- [3] Zhou, L., Liu, Y., Gao, Z. 2005. *Internal combustion engine*. Beijing, China Machine Press.
- [4] Fernández, A., Iglesias, M., DeJuan, A., García, P., Sancibrián, R., Viadero, F. 2014. Gear transmission dynamic: Effects of tooth profile deviations and support flexibility. *Applied Acoustics*, 77 (2), 138-149.
- [5] Chen, B., Liang, D., Gao, Y. 2014. Geometry design and mathematical model of a new kind of gear transmission with circular arc tooth profiles based on curve contact analysis. *Proceedings of the Institution of Mechanical Engineers, Part C: Journal of Mechanical Engineering Science*, 228 (17), 3200-3208.