StuCoSReC

Proceedings
of the 2018
5th Student
Computer
Science
Research
Conference

StuCoSReC

Proceedings of the 2018 5th Student Computer Science Research Conference

Edited by

Iztok Fister jr. and Andrej Brodnik

Reviewers and Programme Committee

Klemen Berkovič • University of Maribor, Slovenia
Lucija Brezočnik • University of Maribor, Slovenia
Patricio Bulić • University of Ljubljana, Slovenia
Zoran Bosnić • University of Ljubljana, Slovenia
Borko Bošković • University of Maribor, Slovenia
Janez Brest • University of Maribor, Slovenia
Andrej Brodnik • University of Primorska and University
of Ljubljana, Slovenia
Haruna Chiroma • Gombe State University, Nigeria
Mojca Ciglarič • University of Ljubljana, Slovenia
Jani Dugonik • University of Maribor, Slovenia
Iztok Fister • University of Maribor, Slovenia
Iztok Fister Jr. • University of Maribor, Slovenia
Matjaž Gams • Jozef Stefan Institute, Slovenia
Tao Gao • North China Electric Power University, China
Andres Iglesias • Universidad de Cantabria, Spain
Branko Kavšek • University of Primorska, Slovenia
Miklos Kresz • University of Szeged, Hungary
Niko Lukač • University of Maribor, Slovenia
Uroš Mlakar • University of Maribor, Slovenia
Marjan Mernik • University of Maribor, Slovenia
Eneko Osaba • University of Deusto, Spain
Vili Podgorelec • University of Maribor, Slovenia
Peter Rogelj • University of Primorska, Slovenia
Xin-She Yang • Middlesex University, United Kingdom
Damjan Vavpotič • University of Ljubljana, Slovenia
Grega Vrbančič • University of Maribor, Slovenia
Aleš Zamuda • University of Maribor, Slovenia
Nikolaj Zimic • University of Ljubljana, Slovenia
Borut Žalik • University of Maribor, Slovenia

Published by

University of Primorska Press
Titov trg 4, SI-6000 Koper

Editor-in-Chief

Jonatan Vinkler

Managing Editor

Alen Ježovnik

Koper, 2018

ISBN 978-961-7055-26-9 (pdf)

www.hippocampus.si/ISBN/978-961-7055-26-9.pdf

ISBN 978-961-7055-27-6 (html)

www.hippocampus.si/ISBN/978-961-7055-27-6/index.html

DOI: <https://doi.org/10.26493/978-961-7055-26-9>

© University of Primorska Press

Kataložni zapis o publikaciji (CIP) pripravili v Narodni in
univerzitetni knjižnici v Ljubljani

COBISS.SI-ID=296769024

ISBN 978-961-7055-26-9 (pdf)

ISBN 978-961-7055-27-6 (html)

Preface

It is no longer necessary to emphasize that computer science is omnipresent today. Terms as digitalization, Industry 4.0 etc. are frequently heard in the mass media and are becoming a part of our everyday life. The rapid advances in computer science require a large investment in research and development. In particular, it is important to educate young scientists, which is one of the objectives of the StuCoSReC conference.

In front of you is the proceedings of the fifth StuCoSReC conference. The StuCoSReC is intended for masters & PhD students to show their research achievements. Socializing is also important and the conference is an excellent opportunity for students to get to know each other. The conference connects students of computer science and goes beyond the invisible limits of faculties. The uniqueness of StuCoSReC conference is that it is organized each year by different higher education institution. The University of Ljubljana - Faculty of Computer and Information Science is proud to host the conference this year.

Twelve papers addressed this conference, covering several topics of the computer science. All the papers were reviewed by two international reviewers and accepted for the oral presentation.

ref. prof. dr. Nikolaj Zimic

Preface

II

Papers

<i>Regulacija plovca v zračnem tunelu (zračna levitacija) na osnovi mehke logike</i> • Primož Bencak, Dominik Sedonja, Andrej Picej, Alen Kolman, Matjaž Bogša	5–13
<i>Razpoznavanje literature v dokumentih in določanje njihovih sklicev v besedilu</i> • Matej Moravec, David Letonja, Jan Tovornik, Borko Boškovič	15–19
<i>Klasifikacija samomorilskih pisem</i> • Dejan Rupnik, Denis Ekart, Gregor Kovačevič, Dejan Orter, Alen Verk, Borko Boškovič	21–25
<i>Načrtovanje poprocesorja za pretvorbo NC/ISO G-kode v translacije za 3/5 osnega robota ACMA ABB XR701</i> • Gregor Germadnik, Timi Karner, Klemen Berkovič, Iztok Fister	27–33
<i>Using constrained exhaustive search vs. greedy heuristic search for classification rule learning</i> • Jamolbek Mattiev, Branko Kavšek	35–38
<i>Real-time visualization of 3D digital Earth</i> • Aljaž Jeromel	39–42
<i>Towards an enhanced inertial sensor-based step length estimation model</i> • Melanija Vežočnik, Matjaž Branko Jurič	43–46
<i>Breast Histopathology Image Clustering using Cuckoo Search Algorithm</i> • Krishna Gopal Dhal, Iztok Fister Jr., Arunita Das, Swarnajit Ray, Sanjoy Das	47–54
<i>Time series classification with Bag-Of-Words approach post-quantum cryptography</i> • Domen Kavran	55–59
<i>The problem of quantum computers in cryptography and post-quantum cryptography</i> • Dino Vlahek	61–64
<i>Named Entity Recognition and Classification using Artificial Neural Network</i> • Luka Bašek, Borko Boškovič	65–70
<i>Context-dependent chaining of heterogeneous data</i> • Rok Gomišček, Tomaž Curk	71

Towards an enhanced inertial sensor-based step length estimation model

Melanija Vežočnik
University of Ljubljana, Faculty of Computer and
Information Science
Ljubljana, Slovenia
mv6082@student.uni-lj.si

Matjaž Branko Jurič
University of Ljubljana, Faculty of Computer and
Information Science
Ljubljana, Slovenia
matjaz.juric@fri.uni-lj.si

ABSTRACT

Inertial sensors found in Internet-of-Things devices such as smartphones and smartwatches can be used to track user's activity as well as step length. In particular, rapidly growing interest in pedestrian dead reckoning – indoor positioning approach that calculates current position as the sum of previous position and vector with step length and heading information – prompts to develop refined step length estimation models to overcome inaccuracy in determining step length. In this work we present our research towards an enhanced inertial sensor-based step length estimation model. For this purpose, we extend an existing step-frequency-based model with acceleration and make it less user-specific. We evaluated the performance of the proposed model for one sensor position and different walking speeds and obtained very promising results comparable to related models. We will further improve the accuracy of the proposed model and modify it, so it will require less time for tuning, and thoroughly address the pre-processing of the sensor data. We will also test the proposed model for different sensor positions and pedestrian-dead-reckoning-based indoor positioning.

Keywords

inertial sensors, pedestrian dead reckoning, step length estimation

1. INTRODUCTION

Over the past few years, user engagement enabling Internet-of-Things (IoT) technologies are emerging. In particular, inertial sensors can be utilized to track user's activity as well as step length since they can be found in smartphones, smartwatches and other IoT devices. They also exhibit advantages such as easy accessibility, inexpensiveness and small-size. Moreover, estimating step length is also applicable in diverse areas, especially in indoor positioning approach called pedestrian dead reckoning [1, 2, 3, 4] that determines the current position by adding vector with step length and heading information to the previous position.

Throughout this work we address inertial sensor-based step length estimation models. According to [5], they can be classified into four categories based on the parameters they require as an input. These parameters are obtained from inertial sensor measurements. The categories are: step-frequency-based [1, 2, 6], acceleration-based [3, 7], angle-based [8] and multiparameter [4, 9]. Step-frequency-based models require step frequency as an input, acceleration-based

models require acceleration, angle-based models require the opening angle of the leg and the input of multiparameter models combines two or all three of the previously listed parameters.

In this work we present our research towards an enhanced inertial sensor-based step length estimation model that increases the accuracy of estimated step length. Section 2 overviews step length estimation models. Section 3 describes the derivation and Section 4 the evaluation of the proposed model. Section 5 presents results, whereas Section 6 discusses them. Finally, Section 7 concludes this work presenting future research directions.

2. OVERVIEW OF STEP LENGTH ESTIMATION MODELS

Step length is determined in several phases. In order to acquire inertial sensor measurements, a sensor has to be set-up on user's body, most commonly in hand, pocket or centre of body mass. Acquired data – usually accelerometer measurements – have to be pre-processed to eliminate errors. Steps are detected before step length is determined using a step length estimation model that often has to be tuned. Next, we briefly present the categories of the models (step-frequency-based, acceleration-based, angle-based and multiparameter).

2.1 Step-frequency-based models

Step-frequency-based models require step frequency as an input. They commonly exploit linear relationship between step length and step frequency and have to be tuned prior to utilization. The following two models include user's height. Renaudin et al. [6] proposed a model based on linear relationship between step length and step frequency, whereas Tian et al. [2] exploited the link between square root of step frequency and step length. On the contrary, Zhang et al. [1] included user's leg length in their model, but based it on the linear relationship between step length and step frequency, similarly as the model proposed by Renaudin et al. [6].

2.2 Acceleration-based models

Acceleration-based models require acceleration as an input. They often exploit the link between step length and acceleration properties such as minimum and maximum acceleration values within the step. Weinberg [7] proposed such model. It calculated step length as the product of a tuneable constant and fourth principal root of the difference between

maximum and minimum vertical acceleration values within a step. Similarly, Do et al. [3] based their model on vertical displacement of the centre of body mass. This model includes user's leg length, but it does not include any tuneable constants.

2.3 Angle-based models

Angle-based models require the opening angle of the leg as an input. They often exploit linear relationship between step length and the opening angle of the leg. Diaz and Gonzales [8] proposed such model. It includes two tuneable constants.

2.4 Multiparameter models

The input of multiparameter models combines two or all three of the previously listed parameters: step frequency, acceleration or the opening angle of the leg. These models usually extend existing models with additional parameters. For example, Mikov et al. [4] included the inverse of step frequency in the Weinberg model [7]. Similarly, Bylemans et al. [9] also based their model on the difference between maximum and minimum acceleration values within a step, but they included step frequency and absolute average acceleration value in walking direction in the model.

3. THE DERIVATION OF THE PROPOSED MODEL

Before we started deriving a new model, we carried out an in-depth analysis and comparison of 13 relevant representative inertial sensor-based step length estimation models [5], where we studied the influence of four typical sensor positions and different walking speeds on their performance. We tuned the models with personalized and universal sets of constants. We also established a benchmark repository for the performance evaluation of inertial sensor-based step length estimation models that includes more than 22 km of gait measurements obtained from 15 adults using off-the-shelf smartphone. This repository is openly available at: <https://github.com/repositoryadmin/SLERepository>.

In [5], we obtained the best overall evaluation results for universal sets of constants for the model proposed by Tian et al. [2] and therefore started deriving our enhanced model from this model. The model proposed by Tian et al. [2] calculates step length as:

$$SL = K \cdot \sqrt{F} \cdot h, \quad (1)$$

where SL represents estimated step length, K tuneable constant, h user's height and F step frequency.

We observed that average walking speed during tests affected the values of tuneable constant in the model as shown in Figure 1. We can see that on average the values of the constant increase with the increased walking speed. We therefore include mean absolute acceleration in walking direction in our model. To make the proposed model less user-specific, we exclude user's height and calculate step length as:

$$SL = K_1 \cdot \sqrt{F} \cdot a_{mean}^{K_2}, \quad (2)$$

where SL represents estimated step length, K_1 and K_2 are tuneable constants, a_{mean} mean absolute acceleration value in walking direction and F step frequency.

Figure 1: Values of tuneable constants in the model proposed by Tian et al. [2] for different walking speeds.

4. EVALUATION

For the evaluation of the proposed model, we used data from the repository described in the previous section that includes measurements acquired in two independent sets of field tests on two straight test paths: 15- and 108-m-long. We used the data collected on the shorter path to tune the models and the data collected on the longer path to evaluate the performance of the models.

To eliminate the impact of smartphone orientation, we only considered hand-reading position as shown in Figure 2, where the user is carrying the smartphone in hand. Smartphone's local coordinate system is considered as follows: y -axis is pointing in the walking direction and z -axis is pointing in the opposite direction of the floor. Smartphone's position is fixed. Three steady walking speeds were tested: slow, normal and fast. Participants self-selected walking speeds to their preference, but they were asked to maintain the walking speed as similar as possible for the time of the experiment. One person always monitored the execution of the experiments and counted the number of participants' steps. Despite the fact that persons self-selected slow, normal and fast walking speeds to their preference, we observed that average walking speeds ranged from 0.45 m/s to 1.25 m/s for slow walking speed, 0.90 m/s to 1.65 m/s for normal walking speed and 1.40 m/s to 2.00 m/s for fast walking speed [5].

Measurements were acquired using off-the-shelf Samsung Galaxy S7 edge smartphone. Sampling frequency was 100 Hz with standard deviation of 8 Hz. Therefore, acquired measurements were resampled to 100 Hz by employing linear interpolation. We used peak detection algorithm for step detection and determined personalized constants of the proposed model and the models selected for the comparison using optimization analysis on the data collected on the shorter path. We employed personalized sets of constants to evaluate the performance of the models on the data collected on the longer path. For every test, we have calculated the

Figure 2: Hand-reading position.

performance as:

$$e = \frac{|d - d^*|}{d^*} \cdot 100\% \quad (3)$$

where e is error, d is the estimated distance of walked path and d^* the real distance of walked path.

5. RESULTS

Table 1 shows the performance of the models. It includes mean errors and standard deviations of the models with respect to total walked distance. Mean errors range from 3.76 % to 16.84 % and standard deviations from 2.41 % to 7.56 %.

Table 1: The performance of the models.

Models	Mean errors [%]	Standard deviations [%]
Tian et al. [2]	4.35	2.78
Zhang et al. [1]	8.91	6.86
Renaudin et al. [6]	8.91	6.86
Do et al. [3]	16.84	7.56
Weinberg [7]	4.36	3.80
Diaz and Gonzales [8]	5.25	4.54
Mikov et al. [4]	7.44	5.93
Bylemans et al. [9]	5.68	4.61
Proposed model	3.76	2.41

6. DISCUSSION

Overall, the proposed model slightly outperformed all the other models. Quite similar performance achieved the models proposed by the Tian et al. [2], Weinberg [7], Diaz and Gonzales [8], Bylemans et al. [9] and Mikov et al. [4]. Even though the model proposed by Mikov et al. [4] extends the Weinberg model [7] it did not perform better on average. The models proposed by Zhang et al. [1] and Renaudin et al. [6] performed similarly since they can be rewritten to the

same model by employing substitution [5]. The model proposed by Do et al. [3] expectedly performed the worst since it does not contain any tuneable constants.

7. CONCLUSION

In this work we presented our research towards an enhanced inertial sensor-based step length estimation model. We based our model on the model proposed by Tian et al. [2] since we obtained the best evaluation results for it for universal sets of constants [5].

We eliminated user's height from the model and included mean absolute acceleration in walking direction instead. We tested the proposed model for one sensor position in hand and obtained promising evaluation results comparable to related models.

We will further improve the accuracy of the proposed model and test it for more sensor positions. We also plan to modify the proposed model, so it would require less time for tuning and thoroughly address the pre-processing of the sensor data. Moreover, we will conduct additional experiments using different IoT devices and test the proposed model for pedestrian-dead-reckoning-based indoor positioning.

Acknowledgments

M. V. received funding for doctoral studies from the University of Ljubljana – 2016 generation. Authors would like to thank all the volunteers who participated in the experiment.

8. REFERENCES

- [1] P. Zhang, X. Chen, X. Ma, Y. Wu, H. Jiang, D. Fang, Z. Tang, and Y. Ma, "SmartMTra: Robust Indoor Trajectory Tracing Using Smartphones," *IEEE Sensors Journal*, vol. 17, no. 12, pp. 3613–3624, 2017.
- [2] Q. Tian, Z. Salcic, K. I. K. Wang, and Y. Pan, "A Multi-Mode Dead Reckoning System for Pedestrian Tracking Using Smartphones," *IEEE Sensors Journal*, vol. 16, no. 7, pp. 2079–2093, 2016.
- [3] T. N. Do, R. Liu, C. Yuen, M. Zhang, and U. X. Tan, "Personal Dead Reckoning Using IMU Mounted on Upper Torso and Inverted Pendulum Model," *IEEE Sensors Journal*, vol. 16, no. 21, pp. 7600–7608, 2016.
- [4] A. Mikov, A. Moschevikin, A. Fedorov, and A. Sikora, "A localization system using inertial measurement units from wireless commercial hand-held devices," in *2013 International Conference on Indoor Positioning and Indoor Navigation (IPIN)*, 2013, pp. 1–7.
- [5] M. Vežočnik and M. B. Jurič, "Inertial Sensor-Based Step Length Estimation Models: A Review," *In Review Process*, 2018.
- [6] V. Renaudin, M. Susi, and G. Lachapelle, "Step Length Estimation Using Handheld Inertial Sensors," *Sensors*, vol. 12, no. 7, pp. 8507–8525, 2012.
- [7] H. Weinberg, "Using the ADXL202 in pedometer and personal navigation applications," *Analog Devices AN-602 application note*, vol. 2, no. 2, pp. 1–6, 2002.
- [8] E. M. Diaz and A. L. M. Gonzalez, "Step detector and step length estimator for an inertial pocket navigation system," in *2014 International Conference on Indoor Positioning and Indoor Navigation (IPIN)*, 2014, pp. 105–110.

- [9] I. Bylemans, M. Weyn, and M. Klepal, “Mobile phone-based displacement estimation for opportunistic localisation systems,” in *Third International Conference on Mobile Ubiquitous Computing, Systems, Services and Technologies, 2009. UBICOMM’09.*, 2009, pp. 113–118.

University of Primorska Press
www.hippocampus.si
ISBN 978-961-7055-26-9