TOWARD AN iMoD™ ECOSYSTEM

Mark W. Miles

QUALCOMM MEMS Technologies - USA

2581 Junction Ave., San Jose, CA 95134

www.qualcomm.com/qmt

ABSTRACT

The iMoD™ is the basis for a MEMS display that exploits optical interference. QUALCOMM MEMS Technologies (QMT) is engaged in a multi-front effort to commercialize iMoD. This paper will review the history of iMoD development to date, and discuss QMT's strategy, philosophy, and transformation as it addresses the array of issues it must face to succeed.

HISTORY OF iMoD DEVELOPMENT

The iMoD, or interferometric modulator, underwent a rather long gestation not unlike that experienced by similar devices such as the Digital Micromirror Device from Texas Instruments. The device was originally conceived as the "Resonant Membrane Spatial Light Modulator" (RMSLM) in 1989. This period coincided with research activities by a variety of organizations into different MEMS light modulators, exploring the uses of reflection, diffraction, and interference. In the case of the RMSLM, it was thought that interference could provide two very significant advantages. The first was the ability to process light with great efficiency, and the second was the ability to do so with a degree of finesse available only through thin film optics. Applications including optical computing, telecommunications, and adaptive optics were all candidates for ultimate commercialization. However it was flat panel displays that were the original and ongoing focus of the work. The attributes that MEMS brought to this application would become more apparent later in the development.

First funding for the development occurred via the Small Business Administration (SBIR) program that drove the efforts of the author's first company, Etalon Inc. From 1991 to 1997. These resources were used to gain experience with the materials that were suitable for creating MEMS structures, but whose traditional role was in the creation of thin film stacks for static optical devices. All these efforts occurred within a subset of the facilities of MIT's Department of Materials Research where Etalon was an industrial user. It was also during this period that the initial thin film design families, optimized for display applications, were modeled.

The end of this long research phase was marked by the actuation of the first functioning pixels. In typical fashion, these were glass fragments decorated with silver paint, long wires, and barely perceivable pixels. Additionally, a process by which large, full color, bright and vivid static displays could be built was developed. Ironically, or perhaps mercifully, it was conceived in one afternoon and realized the following evening with the help of a laser printer, transparencies, a thermal evaporator, and PECVD. Together, these two accomplishments provided a powerful validation of the technology's potential, and as "sales" tools they enabled significant new funding. It was also during this period that the term "iMoD" was coined, and Iridigm Display Corporation formed. Iridigm's purpose was the commercialization of iMoD technology for display applications. Subsequent efforts were focused in three main areas. The first

was the creation of a functioning macro-pixel array that could be addressed and driven to show basic graphic information. Second was the validation of a manufacturing strategy that would rely on the exploitation of existing TFT LCD facilities. The third was to extend and refine the iMoD family of optical designs.

Iridigm closed its first funding round in 2001, the height of the Internet boom. This process was especially hard-fought due to a combination of circumstances. Venture backed forays into domestic display production were riddled with recent and well publicized failures and technical obstacles. At the same time excitement around the Internet drove capital into web based startups, and startups aimed at fiber-optic infrastructure development. Many MEMS companies dove into the breach of the latter category. Iridigm subsisted with a lean approach that minimally expanded its engineering and management team, and built a small prototype fab. The fab was affectionately known as "New York," a more than passing reference to the song. Costing only \$3M and 10 months buildout, it was a completely integrated facility which took 4" glass wafers in, and produced packaged devices. Many similarly purposed facilities cost 10X as much.

A significant array of milestones was achieved. Usable hysteresis, one of the pillars of the iMoD's promise, was realized. This led directly to the fabrication of the first matrix addressable displays. Prototypical static and dynamic displays based on bi-chrome, black and white, and full color families emerged. The manufacturing strategy was also validated by the first successful use of an LCD fab to build iMoD displays.

Iridigm was acquired by QUALCOMM in October of 2004. QUALCOMM MEMS Technologies (QMT) was subsequently formed as fully owned subsidiary focused on the manufacture of displays for portable electronic devices, and the exploitation of iMoD related technology to MEMS in general.

iMoD THEORY AND OPERATION

The theoretical basis for iMoDs has been described in prior publications [1] [2] [3]. Optical interference occurs between the thin film stack and the metallic membrane reflector. Thus the iMoD is viewed through its transparent substrate. The thin film stack comprises a number of dielectrics and highly absorbing metals like chrome or tungsten. Changes in the optical state are produced by the reflection or absorption of light by the iMoD structure, depending on the position of the membrane element shown in Figure 1.

Figure 1. The iMoD architecture.

Figure 2. *iMoD in resonant mode.*

Fundamentally the device has a resonant state and an induced absorption state. As in many thin film stacks, a standing wave is produced whose peak position is determined by the position and properties of its constituent films. When the iMoD is in its resonant state, the metallic membrane is not actuated, and the overall design is such that the standing wave peak resides within the airgap. In this state the iMoD behaves as a resonant reflector, reflecting a color peak whose wavelength is determined by the size of the airgap. A diagram of this mode and a micrograph of a corresponding display is shown in Figure 2.

Figure 3. *iMoD in induced absorption mode.*

Actuation of the membrane into contact repositions the standing wave peak so that it coincides with the absorbing film in the thin film stack. The result is a phenomenon known as induced absorption. Light is consequently absorbed with great efficiency producing an effective black state as shown in Figure 3.

From a functional standpoint, the iMoD is very appealing as a display element for two reasons. The first concerns the efficiency of the device as a modulator. Reflective media, like a magazine or a newspaper, must be exceptionally bright to be readable in a variety of ambient conditions. The former generally have a brightness of around 80%, while the latter achieve on average 55%. iMoD pixels routinely achieve reflective peaks in excess of 85%, as shown in Figure 4. The result is an average brightness of 30%, a figure which makes them viewable even in exceptionally dim environments. Overall

this attribute minimizes, and in some cases eliminates, the need for some form of supplemental lighting.

Figure 4. *Typical iMoD reflective peaks.*

Hysteresis is another significant attribute as it allows the elimination of the Thin Film Transistor (TFT) array, a significant component in many matrix addressed displays. The function of the TFT array is to provide memory and a voltage threshold. The combination of memory and threshold allows for the generation of an addressing waveform that can be applied almost independently of the electro-optic behavior of the modulating medium. The downside of the bargain is that the TFT often constitutes one third of the overall cost of a display. Figure 5 illustrates a typical hysteresis curve attained with iMoD. Such curves are easily exploited for they are wide, and have very well defined transitions.

Figure 5 *Typical iMoD hysteresis curve.*

APPLICATIONS AND ECOSYSTEM

Display-centric portable electronic products are engaged in a constant struggle to provide increasing features against a backdrop of decreasing power, size, and cost budgets. The aforementioned qualities of high brightness and inherent hysteresis are two of the cornerstones upon which the iMoD's promise rests. Delivering in these two critical areas makes it an attractive solution for many of these products. However, a discussion of the iMoD's display architecture reveals a broader and more compelling implication.

A comparison between architectures derived from iMoD and LCD solutions is illustrated in Figures 6 and 7. These

figures show that the iMoD solution exhibits a higher degree of functional integration in at least three dimensions. Modulation in the LCD requires a combination of the LC material, and polarizing films vs. a single actuating membrane. LCD color selection relies on a separate color filter component, a component made unnecessary by the iMoD's predefined air gaps. The elimination of the TFT array speaks for itself. Thus it can be seen that the iMoD brings advantages on a broad system wide level as well.

Figure 6. Full-color iMoD architecture.

Figure 7. LCD display system architecture.

This exercise also serves to bring to light the challenging nature of displays or display subsystems compared to other components comprising a product's BOM (Bill of Materials). Challenging in the sense that the display must "integrate" and "interface" across a wider variety of axes than the other devices in the BOM. Put simply, and by example, IC design must consider standardized silicon layout/fab, packaging, and lead frame options. Display design by default must take equivalent issues into account. However this process is significantly burdened by the need to consider additional complexities. Complexities associated with the physical, electronic, mechanical, and optical coupling of the display to a dizzying array of components and materials. Not to mention that the resulting subsystem must serve as both a compelling visual and frequently tactile transducer. Successful design and deployment of off-the-shelf display technologies depends on the intimate coordination and collaboration between a host of seemingly unrelated industries and disciplines. To achieve a similar result with a technology that is yet to be established requires the almost spontaneous realization of a comparable infrastructure or "ecosystem."

ELEMENTS OF AN iMoD ECOSYSTEM

At last count the author has identified no less than ten separate "niches" which must be filled or otherwise addressed to achieve a functional iMoD ecosystem. Functional in the sense that viable products can result, and mechanisms exist to provide for the evolution and advancement of technology and its application. This is not necessarily an inclusive list. However it should be a fair representation of the general scope, and overlay

what QMT has and will establish as part of its larger commercialization strategy. A list and brief descriptions follow.

Basic materials R&D

Materials study and engineering, particularly as it relates to electromechanical behavior and the impact of different oxides.

iMoD architecture development

Fundamental structure design to improve performance and expand the range of iMoD functionality.

iMoD family specific materials R&D

Materials research as it relates to electro-optomechanical behavior. Designs for bi/monochrome, full-color, B&W, etc.

Array manufacturing

Manufacturing process design and toolset specification related to the fabrication of the iMoD array.

Array packaging

Process and tool development for encapsulation of the array, post array fabrication.

Electronic system development

Design and development of drive waveforms, drive/controller electronics, as well as lighting and touch systems.

Lighting system development

R&D of new iMoD specific supplemental lighting systems, and customization and deployment of existing solutions.

Optical film development

Development and customization of organic and inorganic films and coatings for optical performance enhancement.

Module assembly

Adaptation and customization of existing module assembly tools and processes. Development of cost reducing iMoD specific module assembly enhancements.

Advanced Development

iMoD and iMoD derived innovations to support roadmap, and alternative MEMS related opportunities.

CHALLENGES AND STRATEGIES

Each of these niches serves a different purpose or role and is therefore constrained or driven by varying issues or demands. Strategies must be established, or adapted if already existing, that are niche specific but "system aware" (analogous to "think globally, act locally"). In some cases the approach is driven by the availability of resources or the need to control IP. Others are a continuation of strategies put in place years ago, but are challenged by changes in corporate culture and personnel. Yet others must be agile and highly responsive to changing demands from customers and internal processes.

Materials R&D and architecture development represent two separate areas that have almost identical drivers and constraints. Both must respond to the need to continually improve the iMoD, functionally via architecture and electro-dynamically via materials R&D. Both are constrained as they lie at the core of the IP value proposition and as such represent high priority assets. Both have dedicated in-house engineering teams. In the case of materials, this occurs in the form of a relatively new

device physics group. Architecture development of course, has been a central process from the very beginning.

Additionally, one of the legacies of the iMoD's long gestation period is that there has been plenty of time to identify and document a myriad of evolutionary and revolutionary enhancements along material and architecture axes. This plethora of avenues comes with the pressure to explore the most promising ideas quickly, in some cases before another entity does. All these factors helped to drive the decision to establish comprehensive in-house facilities that are fully integrated and capable of small-scale prototyping, as well as exotic R&D. The expense of such a capability is justified by maintaining leadership and control over what is arguably the most critical asset of the company.

On the other hand, there are some areas of R&D that can be "safely" outsourced. One example is the exploration of iMoD family specific materials. Family, in this case, refers to an iMoD design that is defined by the incorporation of a particular material/s, and minor architecture changes. The consequence is that the family exhibits fundamentally different electro-optic behavior. An example of this is shown in Figure 8, where a photograph of a static B&W iMoD is shown.

This outsourcing strategy is palatable because the innovation occurs using software design tools, a resource which can be established and staffed for relatively low cost. The actual development activity involves the deposition of specific materials or materials combinations. The results are then characterized separately or in conjunction with in-house fabricated structures. Since the deposition function can be easily outsourced, burdens on in-house resources are decreased while maintaining control over IP.

Figure 8. Static display based on B&W design family.

The term "niche" is hardly a sufficient label for the resources and energies devoted to array manufacturing. iMoD array manufacturing will occur, in the near term, on existing/modified LCD factories and tools. This strategy was ingrained in the ecosystem at a time when the iMoD design families and associated materials had not been defined. Essentially that decision established a rather rigid catalog of materials that had to be mixed and matched to achieve the iMoD's goals, not the other way around. Figure 9 is one such catalog that derives from a specific LCD factory [4]. The overwhelming benefit has resulted in a relatively mature manufacturing process. The process is exceptionally well adapted to drop-in to an existing TFT LCD fab. This pool is large and increasing in size as existing fabs are supplanted by larger and more efficient replacements.

Material	Purpose
Al, Al:Nd	Gate metal, Gate bus line
Ta, Mo-W, MoCr, Mo	Gate metal
ITO	Pixel electrode
SiNx	Passivation, gate dielectric
a-Si	Channel

Figure 9. Sample "catalog" of materials for iMoD mfg.

The challenges to this strategy could easily be entitled "The Realities of a 'Drop-in' Process," "Evolution of Staffing From Development to Production," and "Line Balancing: The Act." At its core is the current relationship between QMT and PVI (Prime View International of Taiwan) that provides regular and exclusive foundry access for iMoD manufacture. The particular facility that QMT has access to is well suited for this purpose. Tools and materials can be easily reconfigured, and the production rates are compatible with a cross-section of introductory products. However despite the selection of materials that are already in use and well characterized, production tools rarely deliver the same performance as tools in a development environment. The result is that a technology transfer process begins to resemble a re-development effort. The development team must accept this fact early on and prepare accordingly. Advance sampling and characterization of materials is one approach that can be pursued in parallel [5].

Accepting the realities of this process can directly challenge the nature and composition of the development team. In all likelihood an "entire development staff, although well chosen for the creation of a new technology, may not be properly suited for the move to engineering and production" [5]. The necessary transformation can sometimes be complicated by "pride of ownership" and a lack of appreciation for the fact that some problems are often more efficiently solved on the manufacturing vs. development side.

From the standpoint of establishing a foundry in an existing factory, the issue of line balancing also emerges. In the case of iMoD, upwards of 90% of the equipment set already exists within a TFT AMLCD fab. However the sequence of process steps for which the factory layout was designed is such that the toolset is not optimized for efficient production. Figure 10 illustrates the iMoD sequence. TFT processes tend to be "heavy" in dielectrics and "light" on the metals side. The resolution of this circumstance is non-trivial for it involves tradeoffs between early incremental equipment changes with potentially large future expenses, versus initial large expenditures with growing savings in the future.

Figure 10. iMoD array manufacturing sequence.

Supplemental lighting systems is a niche whose complexity begins to encompass some of the aforementioned "integration and interfacing" issues. It is also subject to pressures which are variable in product space since some apps require lighting and some don't. Variations over time can also occur as the initial product mix along with customer priorities may change, sometimes quite rapidly.

The technical challenge is not unlike that of an LCD where the lighting system is a separately defined component. This is in

contrast to emissive displays, such as plasma, OLED, and FED where light emission is a consequence of the electro-optic effect. This similarity is beneficial in that it creates the potential for adapting existing LCD solutions for application to iMoD. Front lights, as they are called, have existed since the advent of commercially available reflective LCDs. However they have evolved specifically to complement the characteristics of LCDs. LCDs usually accommodate a narrow entry/exit cone, and have an affinity for polarized light.

A typical example is shown in Figure 11, which illustrates the major components and the associated optical path. The general design goal is to minimize losses at each interface, and produce a structure that is robust enough to maintain alignment during everyday use. Effectively homogenizing and coupling the incident light into the display, without producing undue visual artifacts, represents one of the more subtle and difficult design challenges. This approach is sub-optimal given the iMoD's wide viewing angle and polarization insensitivity. It also does not take into account iMoD specific color shift phenomena, as well as characteristics that enable reductions in total system size.

Figure 11 LCD Frontlight layout.

Overall, lighting system design must consider the complex interaction of a stack of organic and inorganic films, adhesives, micro structured films, and light sources from an optical, mechanical, visual, and thermal standpoint. Even existing solutions are born and evolve within the framework of yet another industrial infrastructure with different specialty niches. To bring together these resources in-house in a timely fashion is not conceivable. Thus, QMT has established a multi-faceted outsourcing model involving at least four vendors. This model combines both directed efforts to adapt existing solutions, and a “shotgun” approach which allows for a wide variety of advanced solutions to be quickly vetted and, if appropriate, positioned for more targeted development.

BROADER DEVELOPMENT AND APPLICATION

Most of the activities within the ecosystem are guided by a technology roadmap that takes its cues from a product roadmap. The resulting mechanism is highly responsive to customer requirements for introductory products, and for future products that exist along a well defined feature set hierarchy. What this mechanism lacks is the ability to anticipate or, in some cases, define new customer requirements. This is in addition to identifying opportunities that do not exist on the current product roadmap. Consequently QMT has created a Technology Planning Group (TPG) whose areas of responsibility include – a focus on non display applications that lie off the current

roadmap, an interest in things that could lie on the current roadmap in the future, and some support of the existing planned product developments.

Existing product development efforts include, for example, the incorporation of MEMS switch arrays to provide a waveform multiplexing function. By capturing this functionality within the array MEMS process, the pin-count and resulting driver cost/complexity is reduced. TPG will support such efforts if supplemental resources or expertise are required within the associated technology development program.

Advanced iMoD architectures illustrate one kind of project that TPG has an interest in. Possible variations include devices which can be addressed with simplified waveforms, and iMoDs which are tunable and therefore can achieve any color with a resulting 3X improvement in brightness. The speculative nature of these thrusts do not necessarily place them on the technology roadmap. TPG's purpose in this case is to drive further exploration of these technology options and their value in enabling future product opportunities. The objective for this work is to reduce uncertainty and fix new points on the technology roadmap for further development.

The iMoD is quite a versatile device in itself. Unlike many display entrants it has the potential to play a role in a more diverse array of display market segments than its competitors. The value and potential are equally manifested in other ways as well. In addition to the large area MEMS process, and manufacturing knowledge and capability, there is the experience being gained in bringing a MEMS based system into a high volume, cost competitive environment.

Thus TPG's third role, its focus, is to explore off-roadmap opportunities that are enabled by the iMoD's functionality, assess and vet non-display applications that are enabled by the growing process and manufacturing expertise, and pursue the development of capabilities that support and benefit all-the-above. Opportunities include television, and large area (kiosk or billboard), but also RF switches, variable capacitors, or telecommunications. Synergistic efforts in the area of ultra low-cost manufacturing range from pre-deposited “starter stacks” and plastic roll-to-roll substrates, to pre-form, or printing like approaches.

CONCLUSIONS

This paper is an attempt to provide insight into the context and intricacies of realizing a new MEMS display technology. It is by no means comprehensive. Commercialization has been and continues to be an exceptionally elaborate and complex undertaking. This is not to suggest that the same cannot be said of any new technology being driven toward the marketplace. However iMoD has come of age from within an industry (MEMS) still recovering from a “boom-bust” cycle and therefore not quite as mature as it might be. At the same time, emerging into an established industry with no precedent for the role of MEMS (flat panel displays). The legacy of Iridigm is a robust, wide IP portfolio, engineering team and manufacturing strategy. The challenge to QMT is broadly developing and commercializing this windfall, while keeping it intact and maintaining control over its future. The product in question is not an individual component to be developed in relative isolation. Rather it is an intricate system whose pieces derive from multiple and disparate industries and disciplines. Getting one's arms around such a project is helped by viewing it as a developing ecosystem. Like all of its natural equivalents, survival depends on the successful positioning and interdependence of the all elements within.

ACKNOWLEDGEMENTS

The author wishes to thank the team at Qualcomm MEMS Technologies for their unabashed enthusiasm and dedication to the pursuit of iMoD displays.

REFERENCES

- [1] M.W. Miles, “Digital Paper™ :Reflective Displays Using Interferometric Modulation”, SID 2000 Digest, p. 32 (2000)
- [2] M. Miles, E. Larson, C. Chui, M. Kothari, B. Gally, and J. Batey, “Digital Paper™ for Reflective Displays”, SID Symposium Digest 33, 115 (2002)
- [3] Brian J. Gally, “Wide-Gamut Color Reflective Displays Using iMoD™ Interference Technology”, SID Symposium Digest 35, 654 (2004)
- [4] P.D. Floyd, D. Heald, B. Arbuckle, et. al, “iMoD™ Display Manufacturing”, SID Symposium (2006)
- [5] J.B. Sampsell “Innovation to Production: A Continuum”, SID Symposium (2006)