Coordenadores:

Luciano Lourenço

António Vieira

Metodologia de Análise de Riscos através de Estudos de Casos

RISCOS

Associação Portuguesa de Riscos, Prevenção e Segurança
Coimbra, 2018

Como o próprio título sugere, esta não é uma obra exaustiva sobre os diferentes tipos de análise de riscos, pois reúne uma série de estudos sobre de diferentes casos de riscos, em que preocupa descrever com suficiente detalhe, para cada um deles, a metodologia usada para analisar cada tipo de risco.

Ainda que, do ponto de vista metodológico, haja muitos aspetos comuns na análise dos diferentes tipos de risco, tal não significa que quando entramos na análise das características concretas de determinado risco, não possam existir nuances próprias, intrínsecas à sua especificidade, que merecem um tratamento particular.

Por isso, estamos convictos de que a edição desta obra será de grande utilidade para todos os investigadores que se dediquem às temáticas nela tratadas, uma vez que aqui poderão encontrar a metodologia que os ajudará a desenvolver a sua pesquisa e que poderá servir de suporte ao trabalho que pretendam realizar.

RISCOS

ASSOCIAÇÃO PORTUGUESA
DE RISCOS, PREVENÇÃO
E SEGURANÇA

ESTRUTURAS EDITORIAIS
Estudos Cindínicos

DIRETOR PRINCIPAL | MAIN EDITOR
Luciano Lourenço

RISCOS - Associação Portuguesa de Riscos, Prevenção e Segurança

DIRETORES ADJUNTOS | ASSISTANT EDITORS
António Amaro, Adélia Nunes, António Vieira, Fátima Velez de Castro
RISCOS - Associação Portuguesa de Riscos, Prevenção e Segurança

ASSISTENTE EDITORIAL | EDITORIAL ASSISTANT
Fernando Félix
RISCOS - Associação Portuguesa de Riscos, Prevenção e Segurança

COMISSÃO CIENTÍFICA | EDITORIAL BOARD

Ana Meira e Castro
Universidade do Porto

António Betâmio de Almeida
Instituto Superior Técnico, Lisboa

Cristina Queirós
Universidade do Porto

José Simão Antunes do Carmo
Universidade de Coimbra

Manuel João Ribeiro
Instituto Superior de Educação e Ciências de Lisboa

Romero Bandeira
Instituto de Ciências Biomédicas Abel Salazar, Porto

Salvador Almeida
Universidade Lusófona do Porto

Carla Juscélia de Oliveira Souza
Universidade São João del Rei

Maria Augusta Fernández Moreno
Católica do Equador

Miguel Castillo Soto
Universidade do Chile

Purificación Flaño
Universidade de La Rioja

Rita Cássia de Souza
Universidade Federal de Uberlândia

Yolanda Hernandez Peña

Zeineddine Nouaceur
Universidade de Rouden

REVISORES CONVIDADOS | INVITED REVIEWERS

Airton Bodstein de Barro
Universidade Federal Fluminense

Albano Figueiredo
Universidade de Coimbra

Alecir Antônio Maciel Moreira
Universidade Federal de Minas Gerais

Anabela M. Ramos
MARE - Centro de Ciências do Mar e do Ambiente

Ana Monteiro de Sousa
Universidade do Porto

Angela Santos
Universidade de Lisboa

Franklin Trejo-Paredes
Univ. Nacional de Los Llanos Ezequiel Zamora

Helena Fernandez
Universidade do Algarve

Lais Nayara dos Reis
Universidade Estadual de Goiás

Lilian Moreira Bento
Universidade Federal de Uberlândia

Lúcio Cunha
Universidade de Coimbra

Marcelo Fragoso
Universidade de Lisboa

Maria José Roxo
Universidade Nova de Lisboa

Mario Talaia
Universidade de Aveiro

Maria Teresa Barral Silva
Universidade de Santiago de Compostela

Tomás Figueiredo
Universidade de Bragança

Ricardo A. C. Garcia
Universidade de Lisboa

Rui Ferreira Figueiredo
Universidade de Coimbra

LUCIANO LOURENÇO
ANTÓNIO VIEIRA
(COORDS.)

METODOLOGIA DE ANÁLISE DE RISCOS ATRAVÉS DE ESTUDOS DE CASOS

Edição

RISCOS - Associação Portuguesa de Riscos, Prevenção e Segurança

Email: riscos@riscos.pt

URL: <https://www.riscos.pt/publicacoes/sec/>

COORDENAÇÃO EDITORIAL

Luciano Lourenço e António Vieira

IMAGEM DA CAPA

Karine Nieman

PRÉ-IMPRESSÃO

Fernando Félix

EXECUÇÃO GRÁFICA

Simões & Linhares, Lda.

ISSN

2184-5727

DOI (Série)

<https://doi.org/10.34037/978-989-54295-1-6>

Depósito Legal

449620/18

ISBN

978-989-54295-6-1

ISBN Digital

978-989-54295-2-3

DOI

https://doi.org/10.34037/978-989-54295-2-3_3

SUMÁRIO

PREFÁCIO	7
INTRODUÇÃO	9
 Estratégias de gestão e mitigação do risco sísmico: da avaliação ao planejamento de emergência	
Rui Maio, Tiago M. Ferreira e Romeu Vicente	11
 Metodologias para a hierarquia de riscos de desastres: um estudo comparativo em Santos/SP, Brasil	
Carolina Iwane Hotta e Maria Isabel Castreghini de Freitas	51
 Metodologia para delimitação de áreas de instabilidade de vertentes	
Antônio Amílcar Moura Alves da Silva	85
 An early warning for soil moisture in Brazil, using radar data and normalized difference vegetation index	
Luciana Rossato Spatafora, Humberto Barbosa, Mercè Vall-llossera, Jojhy Sakuragi, Carlos Frederico de Angelis and José A. Marengo	117
 Monitoramento das condições climáticas e do uso da cobertura vegetal em uma bacia hidrográfica no semiárido brasileiro, utilizando imagens landsat	
Ronildo Alcântara Pereira, Clênia Rodrigues Alcântara e Luiton Pereira Rocha	139
 Aplicação da transformada de ondeletas a precipitação do estado do Maranhão - Brasil	
Adriana de Souza Costa, Célia Campos Braga, Wanessa Luana de Brito Costa e Edicarlo Pereira de Sousa	179
 Landslide & rainfalls: press inventory, conditioning factors characterization and precipitation thresholds for Gipuzkoa province (Basque country)	
Txomin Bornaetxea, Orbanxe Ormaetxea, Iñaki Antigüedad and Massimo Melillo	201
 O trabalho de campo e o levantamento da profundidade, cor e textura de solos em áreas de risco a escorregamentos - os casos de Ubatuba e Santos/SP, Brasil	
Carolina Verbicaro Perdomo, Estéfano Seneme Gobbi e Francisco Sérgio Bernardes Ladeira	223

SUMÁRIO

Métodos de bandas de controlo para avaliação de risco de exposição a nanopartículas fabricadas Ana C. Meira Castro, João Santos Baptista e Andréa Pereira	245
Levantamento de riscos ambientais para sistemas de drenagem alterados pelos canais derivados multifuncionais Renato Emanuel Silva e Silvio Carlos Rodrigues	261
Uma abordagem multidisciplinar para a aplicação de metodologias de padrões abertos e gestão de risco Mariza Ferreira da Silva	285
Análise e modelagem numérica da atmosfera na avaliação e prevenção de riscos decorrentes de eventos meteorológicos extremos: estudo de caso para Petrópolis, RJ - Brasil Marina Aires, Jorge Luiz Fernandes de Oliveira, José Maria de Castro Junior, Marília Mitidieri Fernandes de Oliveira e Nelson Francisco Favilla Ebecken	311
CONCLUSÃO	331

PREFÁCIO

O IV Congresso Internacional de Riscos, realizado na cidade de Coimbra, em maio de 2017, deu origem a uma série de trabalhos científicos, alguns dos quais foram publicados sob a forma de artigos na revista *Territorium*, n.º 25 (II), dedicado ao tema “Riscos e Educação”. Os restantes trabalhos, que foram submetidos e aceites para publicação, distribuem-se por quatro volumes da série de livros dedicada aos “Estudos Cindínicos” e que, como este tomo, versam sobre temas específicos.

A metodologia de “Análise de riscos” através de “Estudos de casos”, como o próprio nome indica, corresponde a uma obra de cariz didático, pois, através de doze diferentes estudos, dá conta de vários métodos de análise que, em função dos diversos tipos de risco abordados, podem ser usados não só para analisar o risco, mas também para gerir algumas das suas manifestações e, até, para mitigar as consequências destas.

Como o próprio título sugere, esta não é uma obra exaustiva sobre os diferentes tipos de análise de riscos, pois trata-se de uma série de estudos de diferentes casos de riscos, que se preocupa em descrever, com suficiente detalhe, a metodologia que foi usada para analisar cada um desses vários tipos de risco.

Ainda que, do ponto de vista metodológico, haja muitos aspetos comuns na análise dos diferentes tipos de risco, tal não significa que quando entramos na análise das características concretas de determinado risco, não possam existir nuances próprias, intrínsecas à sua especificidade, que mereçam um tratamento particular.

De facto, analisar riscos tão diferentes como o sísmico, ou o de movimentações em massa, ou aqueles que estão associados à vegetação, à precipitação e às condições climáticas ou, ainda, riscos industriais e ambientais, para referir apenas alguns dos que são abordados nesta obra, dá bem conta da diversidade dos aspetos que, como maior ou menor detalhe, podem ser tidos em conta na análise de riscos e, por conseguinte, da diversidade metodológica que será possível encontrar na sua análise, através dos exemplos apresentados neste volume.

Por isso, estamos convictos de que a edição desta obra será de grande utilidade para todos os investigadores que se dediquem às temáticas nela tratadas, uma vez

que aqui poderão encontrar a metodologia que os ajudará a desenvolver a sua pesquisa e que poderá servir de suporte ao trabalho que pretendem realizar.

Deste modo, por várias razões, justifica-se a publicação deste livro e a RISCOS sente-se orgulhosa de o poder incluir na sua Coleção sobre “Estudos Cindínicos”

Coimbra, 20 de julho de 2018

Luciano Lourenço

INTRODUÇÃO

Luciano Lourenço

Departamento Geografia e Turismo, CEGOT e RISCOs,
Universidade de Coimbra (Portugal)
ORCID: 0000-0002-2017-0854 luciano@uc.pt

Ainda que nem sempre os aspetos metodológicos sejam devidamente valorizados nos trabalhos científicos, o uso da metodologia adequada é fundamental não só para alcançar o objetivo proposto, mas também para o conseguir fazer com o mínimo dispêndio de tempo e de esforço, razões mais do que suficientes para que se lhe deva dedicar alguma atenção.

Ora, por essa razão e porque a metodologia para a análise de risco pode ser abordada sob várias perspetivas, nunca será por demais apresentar alguns exemplos desse tipo de abordagens.

Assim, nesta obra são divulgados vários exemplos de abordagens, através de diferentes estudos de casos, que, entre outros, passam pela proposição de diversa metodologia, a qual poderá ser usada para fins variados, designadamente para:

- i. Gestão e mitigação do risco sísmico, desde a avaliação até ao planeamento de emergência;
- ii. Hierarquização de riscos de catástrofes, tendo por base um estudo comparativo em Santos;
- iii. Delimitação de áreas de instabilidade em vertentes;
- iv. Emissão de alertas precoces para a humidade do solo no Brasil, usando dados de radar e de índices de vegetação;
- v. Verificação das condições climáticas e do uso da cobertura vegetal numa bacia hidrográfica no semiárido brasileiro, utilizando imagens *Landsat*;
- vi. Aplicação da transformada de ondeletas à precipitação do estado do Maranhão - Brasil;
- vii. Definição de limiares de precipitação responsáveis pela ocorrência deslizamentos na província de Gipuzkoa (País Basco);
- viii. Levantamento da profundidade, cor e textura de solos em áreas de risco a escorregamentos, com base no trabalho de campo em Ubatuba e Santos/SP, Brasil;

- ix. Avaliação de risco de exposição a nanopartículas fabricadas, através do método de bandas de controlo;
- x. Levantamento de riscos ambientais em sistemas de drenagem alterados pelos canais derivados multifuncionais;
- xi. Aplicação de padrões abertos à gestão de risco, através de uma abordagem multidisciplinar;
- xii. Avaliação e prevenção de riscos decorrentes de eventos meteorológicos extremos em Petrópolis, RJ - Brasil, através da análise e modelagem numérica da atmosfera.

A reunião deste conjunto de estudos permite mostrar a diversidade metodológica que pode ser aplicada à análise de riscos e, através dos estudos de casos apresentados, serve de exemplo para outros estudos que possam vir a ser desenvolvidos sobre os riscos aqui abordados.

Convicto de que este livro poderá ser útil a todos aqueles que se interessam pelos aspetos metodológicos que devem presidir à elaboração de estudos científicos, a RISCOS também não teve dúvidas em o incluir na sua série sobre “Estudos Cindínicos”, na expectativa de que ele possa contribuir para ajudar a aumentar o conhecimento de quem nele vier procurar informação.

Que seja útil não só aos investigadores, mas também aos decisores, são os nossos votos!

**LANDSLIDE & RAINFALLS: PRESS INVENTORY,
CONDITIONING FACTORS CHARACTERIZATION
AND PRECIPITATION THRESHOLDS FOR
GIPUZKOA PROVINCE (BASQUE COUNTRY)**
**MOVIMENTOS DE VERTENTE E CHUVAS:
INVENTÁRIO DE IMPRENSA, CARACTERIZAÇÃO
DE FATORES CONDICIONANTES E LIMIARES DE
PRECIPITAÇÃO PARA A PROVÍNCIA DE GIPUZKOA
(PAÍS BASCO)**

Txomin Bornaetxea

Department of Geography, Prehistory and Archaeology, Faculty of Arts
University of the Basque Country (UPV/EHU)
ORCID: 0000-0002-1540-3991 txomin.bornaetxea@ehu.eus

Orbange Ormaetxea

Department of Geography, Prehistory and Archaeology, Faculty
Arts of the University of the Basque Country (UPV/EHU)
ORCID: 0000-0001-8573-2806 orbange.ormaetxea@ehu.eus

Iñaki Antigüedad

Department of Geodynamic, Faculty of Science and Technology
University of the Basque Country (UPV/EHU)
ORCID: 0000-0001-8482-2156 inaki.antiguedad@ehu.eus

Massimo Melillo

Istituto di Ricerca per la Protezione Idrogeologica. CNR. (Italy)
ORCID: 0000-0001-7416-8138 massimo.melillo@irpi.cnr.it

Abstract: This article presents a landslide inventory based on press reports published between 2006 and 2015 for Gipuzkoa, a province in the Basque country. Based on this information and after analysing and characterizing the rainfall events that occurred in the same period, a

relationship was established between the inventoried instabilities and the rainfall events. Finally, a tool to define the objective precipitation thresholds responsible for landslides was applied.

Keywords: Landslides, rainfall conditions, empirical precipitation threshold, Gipuzkoa Province.

Resumo: Este artigo apresenta um inventário de movimentos de vertente feito com base em notícias de imprensa publicadas entre 2006 e 2015 para a província de Gipuzkoa (País Basco). Baseado nesta informação foi efetuada a análise e caracterização de eventos de precipitação durante o mesmo período, foi estabelecida a relação entre as instabilidades inventariados e eventos de precipitação. Finalmente, foi aplicada uma metodologia para a definição objetiva de limiares de precipitação responsáveis pela ocorrência de movimentos de vertente.

Palavras-chave: Movimentos de vertente, condições de chuva, Limiar de precipitação empírica, Província de Gipuzkoa.

Introduction

According to the United States Geological Survey (USGS), landslides can be defined by a wide variety of processes that result in the downward and outward movement of slope-forming materials including rock, soil, artificial fill or combination of these. This widespread phenomenon is usually influenced by the environmental conditions such as geology, morphology or factors associated with human activities that made the slope more likely to have failures. But together with these conditioning factors, it is because of a single event that finally a landslide is initiated, which is called the triggering factor.

Rainfall is one of the most usual landslide triggering factors which affects the terrain by building up of the water pressure into the ground and modifying the

balance of the slope (F. Guzzetti *et al.*, 2007), and there are several researchers that attempted to determine the amount of precipitation needed to the mobilization of the slopes (G.F. Wieczorek, 1987; J. Corominas and J. Moya, 1999; F. C. Dai and C. Lee, 2001; C. Li *et al.*, 2011; M.T. Brunetti *et al.*, 2010; A. M. Ramos-Cañón *et al.*, 2015; Zêzere *et al.*, 2015; L. Piciullo *et al.*, 2016; Valenzuela *et al.*, 2017). The problem is that precipitation thresholds can vary a lot depending on the study area conditions and also depending on the type of data used for its delineation (Zêzere *et al.*, 2015). Moreover, in the bibliography there are several different approaches to calculate it. In F. Guzzetti *et al.* (2007) it is more in depth discussed the variety of the possibilities that are available in order to empirically define a landslide initiation rainfall threshold.

Thereby, the objectives of this study are (i) to carry out an inventory of those mass movements that were reported in newspapers, as well as their localization and characterization considering their spatial conditioning factors and damage type that they have caused; (ii) to characterize the precipitation events occurred during the period of time considerate in this study for different rain gauges of the Meteorological Agency of the Basque Country belonging to Gipuzkoa Province; (iii) to detect qualitative relations between the inventoried instabilities and the mentioned rainfall events for the empirical calculation of a landslide precipitation threshold in Gipuzkoa Province.

So, in order to achieve the presented objectives, we have put in practice the approach proposed by M. Melillo *et al.* (2015) and M. Melillo *et al.* (2016) for automatically determining a landslide responsible precipitation threshold by means of an algorithm for the objective reconstruction of rainfall events responsible for landslides, created in the IRPI (Istituto di Ricerca per la Protezione Idrogeologica of Perugia). It is a tool programmed in R open-source software for advanced statistical computing and graphics, release 2.15.2 (<http://www.r-project.org>), which groups a continuous record of rainfall measurements considering a minimum dry period before and after each rainfall event, and then, each landslide in the temporal record can be associated to a single rainfall event.

The decision of applying such approach has two advantages: i) the relative facility to obtain the necessary data (only the landslide occurrence moment and the

precipitation data are needed), against other approaches such as the one proposed by Valenzuela *et al.*, 2017 that demands data from daily water balance models, and ii) the availability of a software with an open source code that automatically reconstructs the rainfall events as well as calculates the statistical relation between them and the landslide occurrence data.

The algorithm was applied in Gipuzkoa Province considering a temporal precipitation data set of 10 years and a landslide inventory based on press reports whose temporal information were available for the same period of time. Also spatial information about slope, lithology and land use was crossed with the landslide inventory, and the outputs of the software were also used to obtain an overview of the relation that exists between the precipitation patterns of Gipuzkoa Province and the occurrence of landslides.

Study Area

Gipuzkoa Province (fig. 1) is a 1980 km² territory located in the north part of the Iberian Peninsula predominantly covered by forest (63 %), mainly plantation forest (38.7 %), and meadow (19 %). With a population density of 354 hab/km², artificial surface comparatively limited (7 %) but very concentrated at the bottom of the main valleys, where the transportation infrastructure network is also dense. It is divided by six parallel principal watersheds with different sizes, all of them draining their water toward the Cantabrian Sea (fig. 1).

According to C.A. Múcher *et al.* (2010), Gipuzkoa Province corresponds to a hilly and mountainous Atlantic landscape, where an average annual precipitation of 1597 mm is registered (J.C. González-Hidalgo *et al.*, 2011) with two maximum periods (November-January: 34 % and April: 10 %) and with a persistent daily rain as a typical feature (P. Fdez-Arroyabe and J. Martín-Vide, 2012). So, precipitations are the main triggering factor of landslides, together with the anthropogenic slope modifications such as slope clearings or forest extraction activities (J. Corominas, 2006; A. Cendrero *et al.*, 2006).

Fig.1 - Gipuzkoa Province, location of landslides and rain gauges
(Source: Basque Meteorology Agency, Euskalmet and landslide inventory).

Fig.1 - Província Gipuzkoa, localização de movimentos em massa e de pluviômetros
(Fonte: Agência Basca de Meteorologia, Euskalmet e inventário de movimentos de vertente).

Methodology

The methodology used was diverse and sequential respect to the three objectives of the investigation.

Data collection

The landslide inventory was collected by means of the newspaper review. To do so, the most sold newspaper in the Province (El Diario Vasco) was chosen and was collected every report in which the key words “deslizamiento”, “desprendimiento”

or “derrumbe” (slide, landslide and crumble in Spanish, respectively) was cited. Because the digital newspaper library did not offer any information previous to 2006, the time lap covered by this review starts the first January of this year and finishes the thirty one December of 2015.

As a result, 2005 reports were obtained from the newspapers review. Later on, considering this information source, landslides that have occurred in Gipuzkoa Province were selected and the following information was summarized in a data base:

- Occurrence date: the date in which the landslide happened;
- Occurrence moment: the exact time at which the landslide occurred. If the exact time was not known, the approximated time was registered depending on the accuracy of the information (*night 6:00; morning 12:00; afternoon 18:00; evening 23:59*). And if only the date was known 23:59 time was registered;
- Occurrence moment accuracy: the accuracy of the information about the occurrence time of the landslide (*Exact time; Relative time; Only the day is known*). Notice that the time was transformed into Coordinated Universal Time (UTC);
- Location accuracy: the accuracy of the information about the location of the reported landslide. At least the municipality has to be known to accept the event in the inventory (*Exact location; Relative location with less than 1 km of error; Relative location with less than 10 km of error; Only the municipality is known*);
- Type of movement: when information about the characteristics of the movement was reported, or if the news was supported with pictures, the process was classified according to the D. J. Varnes (1958) classification (*Slide; Rock fall; Flow; Mixed movement*). If no information is provided on this regard, the generic word “*Landslide*” was assigned;
- Cause: if this information was reported on the news it was introduced in the database (*Rainfall; Human activity; Waves; Fluvial erosion; Wind; Unknown*);
- Damage type: if this information was reported on the news it was also introduced in the database the type of damage caused by the movement (*Buildings; Communication network; Parks; Personal; Undefined*).

It has to be pointed out the meaning of the landslide inventory. Each landslide refers to a single case of terrain instability occurred at a given moment and in a given place. Thus, it frequently happens that more than one landslide occurred very close in time and space, due to the same rainfall event.

Slope, Lithology and Land use digital layers (fig. 2) were provided by the Spatial Data Service of the Basque Country (www.geo.euskadi.eus). But, giving the large number of classes of the last two, some categories were grouped into the same class by expert criteria (see figs. 2b and 2c), while the slope was applied to the analysis keeping the original classification.

Rainfall data was collected from the Meteorological Agency of the Basque Country (www.euskalmet.euskadi.eus) which provided the precipitation records of each 10 minutes for 24 rain gauges located all along the study area (fig. 1).

Before starting to analyse the precipitation, the original 10 minutes records were verified to ensure the completeness of the data series, and they were transformed into hourly data for this study. On this regard, whenever a rain gauge presents more than one month of missing values, this rain gauge was removed from the analysis.

Algorithm for the objective reconstruction of rainfall events responsible for landslides

Once the data sets were checked, the reconstruction of the rainfall events that took place in Gipuzkoa Province between 2006 and 2015, as well as the calculation of the precipitation threshold responsible for landslides was carried out by means of the algorithm proposed in M. Melillo *et al.*, 2015. According to the same authors, a rainfall event was defined as a period of continuous rainfall or a chronological ensemble of periods of continuous rainfall, separated from preceding and successive rainfall events by periods with no rainfall.

For this case study, two seasonal periods were defined: (1) a “dry” period, when there is a generalized decrease of the precipitation, between the months of June and August (E. Ruiz and R. Galdos, 2008), and (2) a “wet” period, when frontal systems which traverse the study area are more frequent and precipitation prob-

ability higher, between September and May (A. Uriarte, 1996). Accordingly, the minimum dry period to differentiate between independent rainfall events for each season was set, by default, to 48 hours during “dry” season and 96 hours during “wet” season (M. Melillo *et al.*, 2015).

The algorithm gives the metrics for each of the detected rainfall event, including the rainfall duration D (h); the event total cumulated rainfall E (mm); the mean rainfall intensity I (mm/h); the peak hourly rainfall intensity I_p (mm/h) and the maximum precipitation in 24 hours $E_{\max 24}$ (mm) (M. Melillo *et al.*, 2015).

Additionally, as it is explained more in detail by M.T. Brunetti *et al.* (2010) and M. Melillo *et al.* (2016), an empirical definition approach was adopted for the landslide responsible precipitation threshold calculation. Each landslide from the inventory was linked to the closest rain gauge and the metrics of the rainfall event related to each instability are used for further calculations. Applying the Frequentist methodology (M. T. Brunetti *et al.*, 2010), the algorithm gives different precipitation threshold curves for different exceedance probability levels, which assuming that the catalogue of rainfall events is sufficiently complete and representative, it can be stated that the probability of experiencing a landslide triggered by rainfall below this threshold is less than the given exceedance value.

The Frequentist method consists in plotting the log-transformed values of accumulated precipitation amount (E) respect to the duration (D) for each known rainfall event that caused a landslide. On this regard, only the accumulated precipitation and the duration until the landslide occurrence exact time are considered. Thus, although more than one landslide could be related to the same rainfall event, they do not necessarily have to present the same E and D parameters, unless they happened at the same time. Later on, the distribution of the rainfall conditions, $\log(E)$ vs. $\log(D)$, that resulted in landslides is fitted (least square method) with a linear equation of the type (M. T. Brunetti *et al.*, 2010):

$$\text{Log}(E) = \log(\alpha) + \gamma * \log(D)$$

or which is equivalent:

$$E = \alpha * D^\gamma$$

Then, the precipitation threshold for a given exceedance level T_i corresponds to the parallel of the fitting curve in which the i % of the observations stay below the curve.

Finally, basing on the rainfall duration and the total cumulated precipitation for the landslide associated events, the definition of thresholds and their associated uncertainties for different exceedance probabilities are provided applying the bootstrapping statistical technique (S. Peruccacci *et al.*, 2012).

Landslides and rainfalls characterization

In order to check the features of the landslides that were reported on the newspaper the last ten years, the frequencies of slope movements belonging to each class of slope, lithology and land use were calculated using the Quantum GIS 2.14.7 software. At the same time, the frequencies of the damage types were also calculated.

For this analysis it was necessary to ensure the location accuracy of the landslides, thus, this characterization was carried out only taking into account those landslides where the exact location was known.

On the other hand, a descriptive analysis of the total reconstructed rainfall conditions was also carried out in order to compare them with the landslide associated rainfall conditions.

To begin, the rainfall events were classified in different typologies following two different approaches. The first one defines the type of rainfall depending on the maximum precipitation in 24 hours as it was proposed by P. Alpert *et al.* (2002), and the class thresholds are summarized in TABLE I. The second is a classification developed by the authors which considers the combination of different rainfall duration classes and different cumulated precipitation classes (E. Díaz *et al.*, 2012) (TABLE I). This alternative classification was proposed because it was considered interesting the characterization of the rainfall conditions taking into account the totality of each event and not only the maximum intensity. This way, complementary information was added for further analysis.

Then, the relative frequencies of each rainfall type were presented for the total rainfall events detected in Gipuzkoa Province during the studied period, and also for the rainfalls that cause landslides, in order to observe the differences.

TABLE I - Rainfall classification suggested by P. Alpert *et al.* (2002) and the authors' proposal.
TABELA I - Classificação de precipitação sugerida por P. Alpert *et al.* (2002) e proposta pelos autores.

P. Alpert's classification		Authors classification			
$E_{\max 24}$ (mm)	Class	D (h)	Class	E (mm)	Class
≤ 4	Light	≤ 24	a	≤ 15	A
4 to 16	Light - Moderate	24 to 71	b	15 to 30	B
16 to 32	Moderate	71 to 143	c	30 to 60	C
32 to 64	Moderate - Heavy	144 to 287	d	60 to 120	D
64 to 128	Heavy	287 to 431	e	120 to 180	E
128 to 256	Heavy - Torrential	431 to 719	f	≤ 180	F
≥ 256	Torrential	≥ 720	g		

* $E_{\max}$: the maximum precipitation in 24 hours in mm; **D**: Duration of the rainfall event in hours;

E: Cumulated precipitation in mm.

Results

Because of the above detailed methodology, a landslide inventory of 339 different single landslides was obtained from a press reports survey for a period of 10 years (TABLE II). Among all these terrain instabilities only in 326 landslides the trigger factor was defined as rainfall or unknown (80.7 % and 19.3 % respectively), and all the remaining cases were related to other triggering factors such as human activity, waves, fluvial erosion or wind. So, only this subset was used as input for the algorithm. On the other hand, only 137 landslides were localized with enough accuracy to carry out the landslides characterization (TABLE II). Concerning to the precipitation data, preliminary controls pointed out the lack of sufficient records in two of the 24 the rain gauges so, only the information from 22 rain gauges was used for this work (TABLE II).

During the analysis run by the algorithm, 23 landslides were discarded because they could hardly be related with any rainfall event, and other 5 were manually discarded by the authors because of their confusing information so, for the final analysis, only 298 landslides were related with the rain fall events (TABLE II).

TABLE II - Summary of the available data and the data used for each analysis.

TABELA II - Resumo dos dados disponíveis e os dados utilizados para cada análise.

Data types	Landslides	Rain gauges
Original data	339	24
Data used for landslide characterization	137	-
Data used for rainfall events analysis	-	22
Data input for the algorithm	326	22
Data used for precipitation threshold calculation	298	22

In order to answer the main objectives of this study, next we present the results following three sub-sections. First, the characterization of the landslides exactly localized will be shown. Then, the results of the rainfall typologies will be presented. And to finish, the landslides responsible precipitation threshold which is proposed by the algorithm software will be displayed.

Characterization of landslides

The following figures show the relative distribution frequencies of the areas covered by slope, lithology and land use classes along the territory, together with the relative distribution frequency of landslides in each class (fig. 2).

In fig. 2a we can see that most of the inventoried terrain instabilities happened in slopes with values between 30 % and 100 %. The most part of the Province (40.36 %) presents moderate slopes (30 % - 50 %) where landslides are frequent (35.62 %), but the biggest number of landslides (43.15 %) occurred in slopes with values between 50 % and 100 %, although this class takes less area than the former (27.35 %).

If we take under consideration the relation between landslides and lithological characteristics, landslides occurring in impure limestone or calcarenite (35.7 %) together with sandstone (12.4 %) largely overcome the spatial distribution of types of lithology in the study area (18 % and 6.5 % respectively), which suggests

Fig. 2 - Study area (Gipuzkoa) and relative distribution frequency of landslides per slope class (a), lithology (b) and land use (c).

Fig. 2 - Área de estudo (Gipuzkoa) e distribuição de frequência relativa de movimentos de vertente por classes de declive (a), litologia (b) e uso do solo (c).

an important susceptibility to landslide occurrence. In addition, alternation of detrital rock and marl also present a considerable number of landslides (19 % and 20.4 % respectively), but these are the most frequent lithologies along the study area (fig. 2b).

Concerning the land use distribution, it is highlighted the number of instabilities falling in artificial areas (36.7 %) though this class covers only the 6.5 % of the study area. Scrub land use shows also a greater relative frequency on landslides than in the entire area for the analysed inventory (16.5 % v.s. 7.3 %). Unlikely, cropland, pasture or meadow, forest and above all, forest plantation display a lower relative frequency in landslides, respect to the area covered by these classes (fig. 2c).

Fig. 3 shows the damages produced by the inventoried landslide. It can be observed that the most affected elements are the human infrastructures such as the communication network (56 %), buildings (33 %) or parks (6 %).

Fig. 3 - Relative distribution frequency of landslides per damage type.

Fig. 3 - Distribuição de frequência relativa de movimentos de vertente segundo tipos de danos.

Characterization of rainfalls

In this section the results of the comparison between the general rainfall characteristics in Gipuzkoa Province and the characteristics of the rainfalls that triggered

landslides are presented. First, for each of the 22 rain gauges the relative frequency of the rainfall event classes defined in Table I was calculated (an average of 275 rainfall events per rain gauge). Then, the average of the 22 results for each class were represented in figures 4 and 5.

Figure 4 shows the frequency distribution of the maximum 24 hours rainfall typologies according to the P. Alpert *et al.* (2002) classification for all the rainfall events and for rainfall events that trigger landslides. It can be observed that the most part of the total rainfall events (80 %) belong to typologies from Light to Moderate-Heavy which represent a maximum precipitation in 24 hours between 0 and 32 mm, being the Light-Moderate typology (4 - 16 mm) the most usual (37 %). Thus, it can be stated that the most common rainfall typologies for Gipuzkoa Province, according to this classification, is Light-Moderate. Nevertheless, if we consider only the rainfalls associated to landslides occurrence, then, the most frequent rainfall event typology is Heavy (45 %), which represents a maximum precipitation in 24 hours between 64 and 128 mm.

Fig. 4 - Rainfall types relative distribution according to the classification of P. Alpert et al., 2002, in Gipuzkoa Province (2006-2015).

Fig. 4 - Tipos de precipitação e distribuição relativa de acordo com a classificação de P. Alpert et al., 2002, na Província de Gipuzkoa (2006-2015).

A similar comparison is displayed in figure 5, where two contingency graphics show the most frequent rainfall typologies for the total rainfall events and for the landslide associated rainfall events considering their duration (D) and their total cumulated rain (E).

A clear difference can be observed between both figures 5a and 5b, and each one presents very clustered results. In figure 5a most rainfall events (33.4 %) present a typology with durations which can range between single minutes and 24 h where the precipitated rain does not exceed 15 mm (combination a-A). But in figure 5b the most frequent (22.8 %) rainfall type durations range between 24 h and 71 h where the cumulated rain can range between 60 mm and 120 mm (combination b-D). Notice that there are also high frequencies (16.8 %) in events of 71 h to 143 h of duration with cumulated rains between 60 mm and 120 mm (combination c-D). So, regarding this results, it can be stated that, in general, in Gipuzkoa Province rainfall events spent less than 24 h of time and they cumulate less than 15 mm, but in case that rainfalls become longer in time (1 to 5 days) and start to cumulate precipitation over 60 mm, then landslides start to trigger.

Fig. 5 - Contingency graphics - rainfall event relative distribution according to its duration and accumulated rain: a) in rainfall events; b) in landslide trigger rainfall events, in Gipuzkoa Province (2006-2015). The meaning of the letters (a-g; A-F) is summarized in TABLE I.

Fig. 5 - Gráficos de contingência - tipologias de eventos de precipitação segundo a sua duração e chuva acumulada: a) todos os eventos de precipitação; b) eventos de precipitação desencadeantes de movimentos de vertente, na Província de Gipuzkoa (2006-2015). O significado das letras (a-g; A-F) está resumido na TABELA I.

Landslides triggering rainfall threshold

We calculated objectively cumulated precipitation (E) and rainfall duration (D) based thresholds, for different exceedance probability levels, adopting the software described in M. Melillo *et al.* (2015). Each exceedance level represents the percentage of observations that stay below a given threshold, so it can be interpreted as the error probability of such threshold.

Below, we present the precipitation threshold equations proposed by the software considering the data obtained in the Gipuzko Province case study. These equations show the minimum threshold of cumulated precipitation (E) that is expected to produce landslides for a given period (D). In this case, T_5 represents the curve above which landslide occurrence is expected with a 95 % of probability, and T_1 represents so with a 99 % of probability (fig. 6).

$$T_5 : E = (4.4 \pm 0.7) D^{(0.47 \pm 0.04)}$$

$$T_1 : E = (3.0 \pm 0.5) D^{(0.47 \pm 0.04)}$$

Additionally, the uncertainty range of the thresholds (represented by the $\pm$ values), obtained by the bootstrap technique, is also provided (S. Peruccacci *et al.*, 2012). This shows the level of variability of the resulting curves respect to the introduced data (figs. 6b and 6c).

Conclusion

The case study presented in this article shows the application of an approach that permits the management of landslide occurrence data and precipitation data in order to obtain an overview of the real behaviour of the slope instabilities in a given territory respect to their triggering because of rainfalls. By using the approach proposed in M. Melillo *et al.*, 2015, all the analytical part of the procedure was done automatically. In addition, landslides characterization and rainfall events characterizations tests were carried out, and during these analyses some important aspects were highlighted, which are detailed as follow.

Fig. 6 - Landslide responsible rainfall thresholds for Gipuzkoa Province: a) All rainfall events in logarithmic scale; b) Only rainfall events that trigger landslides in logarithmic scale (The difference between light and dark blue dots is result of the overlapping); c) Only rainfall events that trigger landslide in decimal scale.

Fig. 6 - Limiares de precipitação responsável por desencadear movimentos de vertente na Província de Gipuzkoa: a) Todos os eventos de precipitação em escala logarítmica; b) Apenas eventos de precipitação que provocam deslizamento de terra (a diferença entre os pontos azul claro e azul escuro é resultado da sobreposição); c) Apenas eventos de precipitação que provocam deslizamento de terra em escala decimal.

First, it is highlighted the big number of landslides falling in artificial land use (fig. 2c). Considering that this class represents the spatial distribution of the most part of the human goods likely to be affected, it is logical to find that the entire inventory except the 3.73 % caused damages (fig. 3). Furthermore, these results suggest that being a landslide inventory based on press reports, the landslide inventory is probably biased, because landslides that appear on the newspapers are mainly those that have caused some kind of negative effect to the humans, or their goods.

So, the information provided by the landslide inventory cannot be considered as a representation of the general behaviour of landslides, but only of landslides which directly affects to humans or their activity.

Nevertheless, slope and lithology (figs. 2a and 2b) are less related to the human activity than land use. So, comparison of their relative distribution allowed to highlight if the presence of landslides in one or another class was given to the general presence of such class along the study area, or instead, the landslides are more likely to occur in one specific class than in others, concluding which are the most recurrent classes for the landslides with impact on humans. Thus, considering the limitation of the landslide inventory, the analysed data suggest that slopes with values of 30 % to 100 % and impure limestone and calcarenite or sandstone are the most likely to be affected by rainfall induced landslides. Apart from that, alternation of detrital rock and marl also present considerable number of landslides, but it could be due to the large territory that they occupy in the study area. Indeed, this behaviour agrees with the results of J. Remondo (2003) and J. Bonachea (2006), whose more detailed analysis in a smaller portion of our study area also reveals the importance of such materials respect to the landslide occurrence.

Referring to the rainfall data, the survey of the characterization tests (figs. 4 and 5) show that, for the studied 10 years, the most common rainfall event typology in Gipuzkoa Province and the typology responsible of landslide triggering are considerably different. This suggests that landslide occurrence is closely related to a concrete type of rainfall. Furthermore, the classification of the rainfall events has allowed the identification of precipitation types that are more likely to cause landslides in Gipuzkoa Province. According to the P. Alpert *et al.* (2002) classification, landslides in our study area are triggered mainly by rainfall events that contain a maximum cumulated precipitation in 24 hours of at least 64 mm and less than 128 mm (fig. 4). Likewise, the alternative classification which considers the duration of the whole rainfall event and its cumulated precipitation presents similar results. According to this classification, the events of 1 to 4 days that can cumulate between 60 mm and 120 mm are the most likely of causing slope failures (fig. 5).

The information provided by these classifications allows the responsible entities to obtain a general idea of the relation between rainfalls and landslide occurrence,

although this generalization would be better supported by a longer data set to consider this rainfall pattern as a reliable trend.

Apart from the above mentioned general relationships, basing in 298 landslide observations and their special and temporal information, the automatic software proposed a landslides responsible precipitation threshold for Gipuzkoa Province. The T_5 and T_1 equations presented in fig. 6 indicate the threshold above which the 95 % or 99 % of the inventoried landslides are placed and the range of uncertainty associated to the input data. So, it is considered reasonable to expect that, in the future and in this study area, the same kind of landslides will be mostly triggered once the threshold would be overcome. Thereby, this information could be considered as an approximation toward a future data supported early warning system design, as it is suggested in R. Fell *et al.* (2008).

On the other hand, the analysis followed in this work should be interpreted considering some important topics. To begin with, rainfall events were defined automatically according to user set up values, such as the minimum interval without precipitation (48 and 96 hours in this case). The rationale behind this option is the different rhythm of soils returning to under saturated state along the year (M. Melillo *et al.*, 2015; 2016), and though in this work these intervals were defined by expert criteria, we acknowledge that considering soil moisture data like in P. Valenzuela *et al.* (2017) uncertainties related to the antecedent soil conditions could be reduced, which can be important above all for medium and long duration landslide trigger rainfall events, as suggested by Zêzere *et al.* (2015). Furthermore, the empirical method applied by the software, presents several drawbacks. As it is more in depth discussed in S. Peruccacci *et al.* (2012), it has to be pointed out that the resulting threshold is highly dependent, not only from the quality and extension of the data, but also from its distribution, allowing the underestimation of large rainfall events with landslides. Thus, it has to be taken into account, that all the results are based on a given data set, and so we cannot do statistical inferences about the population outside the data set unless we know the relation between the data set (landslide inventoried) and the total population (the totality of occurred landslides). As we never know the totality of the occurred landslides, hence, we don't know how representative is our data set, and so, it is not possible in statistical terms to do a prediction. This threshold have to be considered as

a suggestion of occurrence of landslides based on a given data set. And, for the same reason, if it would be used in a landslide warning system, the thresholds may result in false positives, as it is illustrated in the considerable amount of rainfall events plotted above the thresholds in fig. 6a. Nevertheless, by means of the bootstrap approach, the statistical uncertainty associated with the data set was quantified.

To conclude, this study has put in practice a very powerful tool which contributes to the definition of the rainfall needed (in quantity and quality) to trigger landslides, an information that, together with an appropriate susceptibility map, could be used to develop landslides occurrence forecasts. At the same time, some basic spatial data were added to the procedure in order to complement this outcome with the information about some physiographic features, such as land use, lithology and slope, where landslides are most likely to occur. Additionally, the data about rainfall events produced by the software was profited to identify the most common rainfall typologies in Gipuzkoa Province for the studied period and based in two different classifications, as well as the particular type of rainfalls responsible of landslides.

Aknowledgement

This work was funded by the Cultural Landscape and Heritage UNESCO Chair of the University of the Basque Country (UPV/EHU), and the article could not be possible without the support of the IT1029-16 research group. The authors would also like to thank IRPI (Istituto di Ricerca per la Protezione Idrogeologica di Perugia) for providing us the algorithm software code.

Bibliographic references

- Alpert, P., Ben-Gai, T., Baharad, A., Benjamini, Y., Yekutieli, D., Colacino, M., Diodato, L., Ramis, C., Homar, V., Romero, R., Michaelides, S., Manes, A. (2002). The paradoxical increase of Mediterranean extreme daily rainfall in spite of decrease in total values. *Geophysical research letters*, 29, 1536 p
- Bonachea, J. (2006). *Desarrollo, aplicación y validación de procedimientos y modelos para la evaluación de amenazas, vulnerabilidad y riesgo debidos a procesos geomorfológicos*. PhD Thesis. Universidad de Cantabria, Santander, 380 p.

- Brunetti, M. T., Peruccacci, S., Rossi, M., Luciani, S., Valigi, D., & Guzzetti, F. (2010). Rainfall thresholds for the possible occurrence of landslides in Italy. *Natural Hazards and Earth System Sciences*, 10(3), 447-458.
- Cendrero, A., Remondo, J., Bonachea, J., Rivas, V., & Soto, J. (2006). Acción Humana y Procesos Geológicos Superficiales ¿Qué Le Estamos Haciendo A La Faz De La Tierra?. *Real Academia de las Ciencias Exactas Físicas y Naturales, España*, 100(1), 187-209.
- Corominas, J. (2006). El clima y sus consecuencias sobre la actividad de los movimientos de ladera en España. *Cuaternario y Geomorfología*, 20(3-4), 89-113.
- Corominas, J., & Moya, J. (1999). Reconstructing recent landslide activity in relation to rainfall in the Llobregat River basin, Eastern Pyrenees, Spain. *Geomorphology*, 30(1), 79-93.
- Dai, F. C., & Lee, C. F. (2001). Frequency-volume relation and prediction of rainfall-induced landslides. *Engineering geology*, 59(3), 253-266.
- Díaz, E., De Olazagoitia, A. S., Ormaetxea, O., & Ibasate, A. (2012). Análisis de factores de desestabilización de laderas en dos cuencas del ámbito atlántico: Sollube-mape (Bizkaia) y Ramaio (Alava). *Cuaternario y Geomorfología*, 26(1), 171-190.
- El Diario Vasco. <http://www.diariovasco.com/>
- Fdez-Arroyabe Hernández, P., & Martín-Vide, J. (2012). Regionalization of the probability of wet spells and rainfall persistence in the Basque Country (Northern Spain). *International Journal of Climatology*, 32(12), 1909-1920.
- Fell, R., Corominas, J., Bonnard, C., Cascini, L., Leroi, E., & Savage, W. Z. (2008). Guidelines for landslide susceptibility, hazard and risk zoning for land-use planning. *Engineering Geology*, 102(3), 99-111.
- González-Hidalgo, J. C., Brunetti, M., & de Luis, M. (2011). A new tool for monthly precipitation analysis in Spain: MOPREDAS database (monthly precipitation trends December 1945–November 2005). *International Journal of Climatology*, 31(5), 715-731.
- Guzzetti, F., Peruccacci, S., Rossi, M., & Stark, C. P. (2007). Rainfall thresholds for the initiation of landslides in central and southern Europe. *Meteorology and atmospheric physics*, 98(3), 239-267.
- Li, C., Ma, T., Zhu, X., & Li, W. (2011). The power-law relationship between landslide occurrence and rainfall level. *Geomorphology*, 130(3), 221-229.
- Melillo, M., Brunetti, M. T., Peruccacci, S., Gariano, S. L., & Guzzetti, F. (2015). An algorithm for the objective reconstruction of rainfall events responsible for landslides. *Landslides*, 12(2), 311-320.
- Melillo, M., Brunetti, M. T., Peruccacci, S., Gariano, S. L., & Guzzetti, F. (2016). Rainfall thresholds for the possible landslide occurrence in Sicily (Southern Italy) based on the automatic reconstruction of rainfall events. *Landslides*, 13(1), 165-172.
- Mücher, C. A., Klijn, J. A., Wascher, D. M., & Schaminée, J. H. (2010). A new European Landscape Classification (LANMAP): A transparent, flexible and user-oriented methodology to distinguish landscapes. *Ecological indicators*, 10(1), 87-103.
- Peruccacci, S., Brunetti, M. T., Luciani, S., Vennari, C., & Guzzetti, F. (2012). Lithological and seasonal control on rainfall thresholds for the possible initiation of landslides in central Italy. *Geomorphology*, 139, 79-90.
- Piciullo, L., Gariano, S. L., Melillo, M., Brunetti, M. T., Peruccacci, S., Guzzetti, F., & Calvello, M. (2016). Definition and performance of a threshold-based regional early warning model for rainfall-induced landslides. *Landslides*, 1-14.
- Ramos-Cañón, A. M., Trujillo-Vela, M. G., & Prada-Sarmiento, L. F. (2015). Niveles umbrales de lluvia que generan deslizamientos: Una revisión crítica. *Ciencia e Ingeniería Neogranadina*, 25(2), 61-80.

- Remondo, J., González-Díez, A., De Terán, J. R. D., & Cendrero, A. (2003). Landslide susceptibility models utilising spatial data analysis techniques. A case study from the lower Deba Valley, Guipúzcoa (Spain). *Natural Hazards*, 30(3), 267-279.
- Ruiz, E., Galdos, R. (2008). *Geografía del País Vasco*, Editorial Nerea, Donostia-San Sebastián, 364 p.
- USGS. United States Geological Survey. <https://www.usgs.gov/>
- Uriarte, A. (1996). *El clima de Euskal Herria*. In Meaza, G. & Ruíz, E. (Coord.). *Geografía de Euskal Herria. Tomo 3*. Editorial Ostoa, Lasarte-Oria, p. 8-83.
- Valenzuela, P., Domínguez-Cuesta, M. J., García, M. A. M., & Jiménez-Sánchez, M. (2017). Rainfall thresholds for the triggering of landslides considering previous soil moisture conditions (Asturias, NW Spain). *Landslides*, 1-10.
- Varnes, D. J. (1958). Landslide types and processes. *Landslides and engineering practice*, 24, 20-47.
- Wieczorek, G. F. (1987). Effect of rainfall intensity and duration on debris flows in central Santa Cruz Mountains, California. *Reviews in Engineering Geology*, 7, 93-104.
- Zêzere, J. L., Vaz, T., Pereira, S., Oliveira, S. C., Marques, R., & Garcia, R. A. C. (2015). Rainfall thresholds for landslide activity in Portugal: a state of the art. *Environmental Earth Sciences*, 73(6), 2917-2936.

CONCLUSÃO

Luciano Lourenço

Departamento Geografia e Turismo, CEGOT e RISCOs,
Universidade de Coimbra (Portugal)
ORCID: 0000-0002-2017-0854 luciano@uc.pt

A publicação desta obra, além de satisfazer as naturais expectativas dos autores que nela colaboraram, visou reunir e divulgar diferentes métodos de análise de riscos, através de estudos de caso, os quais, de uma forma genérica, passaram pela recolha de informação, pelo desenvolvimento de investigação científica, pela compilação de estratégias e, por vezes, pela emanação de orientações com vista à mitigação do risco estudado.

Ora, todos estes aspetos podem vir a ser de grande utilidade, tanto para os investigadores que queiram desenvolver trabalhos semelhantes, como, sobretudo, para as entidades governamentais e as autoridades de proteção civil que, em face do exposto, poderão sentir necessidade de, eventualmente, repensar e ajustar algumas linhas orientadoras das suas missões, bem como de reorganizar os seus planos de intervenção.

Por outro lado, os cidadãos comuns, porventura aqueles que estejam mais des-
pertos para a sua autoproteção, também poderão encontrar nesta obra informações úteis, que lhe permitem aprofundar os seus conhecimentos sobre diferentes aspetos da temática dos riscos.

De facto, esta obra contempla vários desses aspetos, de que nos permitimos destacar, entre outros, os seguintes:

- Metodologia de análise de riscos;
- Caracterização de diferentes tipos de risco;
- Diagnósticos, prognósticos e análises preventivas de catástrofes, enquanto plenas manifestações do risco;
- Aplicação dos sistemas de informação geográfica à análise espacial e cartografia de risco;
- Modelos e software para previsão de ocorrências;
- Planeamento de emergência;

- Educação para a redução do risco;
- Gestão participativa de segurança geradora de mudança de mentalidades;
- Atitudes de superação;
- Auxílio à tomada de decisão;
- Mecanismos de informação pública;
- Sistemas de pré-aviso à população;
- Conjugação da educação, do planeamento e da gestão de risco, como forma de tornar as sociedades mais resilientes às manifestações de risco.

Certamente que uma leitura atenta permitirá encontrar muitos outros aspetos, além destes que foram dados como exemplo, e que se revelarão preciosos para todos aqueles que pretendem aumentar os seus conhecimentos sobre os riscos e as suas manifestações.

SÉRIE
ESTUDOS CINDÍNICOS

Títulos Publicados:

- 1 *Incêndios em Estruturas. Aprender com o Passado;*
- 2 *Educação para a Redução dos Riscos;*
- 3 *Metodologia de Análise de Riscos através de Estudos de Casos;*

Volume em publicação:

- 4 *Riscos Hidrometeorológicos;*
- 5 *Pluralidade na Diversidade de Riscos;*

Tomos em preparação:

- 6 *Risco Sísmico - Aprender com o Passado;*
- 7 *Geografia dos Incêndios Florestais. 50 anos de Incêndios a queimar Portugal;*
- 8 *Efeitos dos Incêndios Florestais nos Solos de Portugal;*
- 9 *Floresta, Incêndios e Educação;*
- 10 *Redução do Risco e Educação.*

Luciano Lourenço é doutorado em Geografia Física, pela Universidade de Coimbra, onde é Professor Catedrático.

É Diretor do NICIF - Núcleo de Investigação Científica de Incêndios Florestais, da Faculdade de Letras da Universidade de Coimbra e Presidente da Direção da RISCOS - Associação Portuguesa de Riscos, Prevenção e Segurança.

Exerceu funções de Diretor-Geral da Agência para a Prevenção de Incêndios Florestais, Presidente do Conselho Geral da Escola Nacional de Bombeiros e Presidente da Direção da Escola Nacional de Bombeiros.

Consultor científico de vários organismos e de diversas revistas científicas, nacionais e estrangeiras, coordenou diversos projetos de investigação científica, nacionais e internacionais, e publicou mais de mais de três centenas de títulos, entre livros e capítulos de livro, artigos em revistas e atas de colóquios, nacionais e internacionais.

António Vieira é geógrafo, doutorado em Geografia pela Universidade de Coimbra. É Mestre em Geografia, área de especialização em Geografia Física e Estudos Ambientais e Licenciado em Geografia, especialização em Estudos Ambientais pela Faculdade de Letras da Universidade de Coimbra. É professor auxiliar no Departamento de Geografia da Universidade do Minho, desenvolvendo atividades de investigação como membro integrado do Centro de Estudos de Geografia e Ordenamento do Território (CEGOT – UM/UC/UP), do qual é Coordenador na Universidade do Minho.

É membro de diversas organizações científicas, nomeadamente a Associação Portuguesa de Geomorfólogos (APGeom, da qual é presidente desde 2017), e a Riscos – Associação Portuguesa de Riscos, Prevenção e Segurança, sendo seu vice-presidente. É também membro da FUEGORED (Red Temática Nacional Efectos de los Incendios Forestales sobre los Suelos) e colaborador do GRAM (Grup de Recerca Ambiental Mediterrània).

Durante a sua carreira desenvolveu investigação no âmbito da geomorfologia granítica, do património geomorfológico e das alterações do uso do solo, debruçando-se atualmente sobre temáticas relacionadas com sistemas de informação geográfica e deteção remota e sua aplicação ao ordenamento do território, geomorfologia glacial e periglacial, património geomorfológico, processos erosivos na sequência de incêndios florestais e medidas de mitigação, entre outras.

RISCOS

ASSOCIAÇÃO PORTUGUESA
DE RISCOS, PREVENÇÃO
E SEGURANÇA