GEOGRAFIA, RISCOS E PROTEÇÃO CIVIL

HOMENAGEM AO PROFESSOR DOUTOR
LUCIANO LOURENÇO

VOLUME 2

Coordenadores:
Adélia Nunes
António Amaro
António Vieira
Fátima Velez de Castro
Fernando Félix

RISCOS - ASSOCIAÇÃO PORTUGUESA DE RISCOS,
PREVENÇÃO E SEGURANÇA

GEOGRAFIA, RISCOS E PROTEÇÃO CIVIL

HOMENAGEM AO PROFESSOR DOUTOR
LUCIANO LOURENÇO

VOLUME 2

COORDENADORES:

Adélia Nunes

António Amaro

António Vieira

Fátima Velez de Castro

Fernando Félix

RISCOS - Associação Portuguesa de Riscos,
Prevenção e Segurança

FICHA TÉCNICA

Título: Geografia, Riscos e Proteção Civil.
Homenagem ao Professor Doutor Luciano Lourenço.
Volume 2

Edição: RISCOS - Associação Portuguesa de Riscos, Prevenção e Segurança

Coordenação: Adélia Nunes, António Amaro, António Vieira, Fátima Velez de Castro e Fernando Félix

Capa e contracapa: Fernando Félix

Concepção gráfica e paginação: Fernando Félix

Impressão: Simões & Linhares, Lda.

ISBN: 978-989-9053-05-2 **ISBN digital:** 978-989-9053-06-9

DOI: https://doi.org/10.34037/978-989-9053-06-9_1.2

Depósito Legal: 487457/21

1.ª Edição

Os trabalhos apresentados são da responsabilidade dos Autores.

PARCEIROS

FACULDADE DE LETRAS
UNIVERSIDADE DE
COIMBRA

DEPGEOTUR
DEPARTAMENTO
DE GEOGRAFIA
E TURISMO

REPÚBLICA
PORTUGUESA

Este trabalho é Financiado por Fundos Nacionais através da FCT – Fundação para a Ciência e a Tecnologia no âmbito do projeto “UIDB/GEO/04084/2020”.

This work is Financed by National Funds through the FCT - Foundation for Science and Technology under the project “UIDB/GEO/04084/2020”.

LUCIANO LOURENÇO NOS 25 ANOS DE ESCUTEIROS DA FUNDAÇÃO DO GRUPO DE ALBORAIA (VALÊNCIA),
COM A ESPOSA MARIA DA GRAÇA LOURENÇO, EM 08/02/1995.

FOTOGRAFIA CEDIDA POR MARIA DA GRAÇA LOURENÇO, 2021.

COMPANHEIROS DE JORNADAS DE INVESTIGAÇÃO,
O FILHO JOÃO NUNO LOURENÇO E O TIO AGOSTINHO, EM JUNHO DE 2000.

FOTOGRAFIA CEDIDA POR MARIA DA GRAÇA LOURENÇO, 2021.

LUCIANO LOURENÇO, NO CHILE, NA EXPOSIÇÃO DE MATERIAL DE COMBATE A INCÊNDIOS FLORESTAIS,
NA ABERTURA DE UMA FAIXA DE DEFESA DA FLORESTA CONTRA INCÊNDIOS FLORESTAIS E
VISITA A UMA CORPORAÇÃO DE BOMBEIROS, EM 12/11/1995.
FOTOGRAFIA CEDIDA POR MARIA DA GRAÇA LOURENÇO, 2021.

NUM ALMOÇO DO DIA DE CORPO DE BOMBEIROS DE MACAU, COM A RECEÇÃO DO ESCUDO DE ARMAS DO CB DE MACAU, ESTANDO REPRESENTADAS DELEGAÇÕES DE HONG KONG, PROVÍNCIA DE GUANGDONG (RPC), MACAU E A ESCOLA NACIONAL DE BOMBEIROS, PORTUGAL, A 2 DE MAIO DE 1998.

FOTOGRAFIA CEDIDA POR MARIA DA GRAÇA LOURENÇO, 2021.

LUCIANO LOURENÇO, EM REPRESENTAÇÃO DA ENB - ESCOLA NACIONAL DE BOMBEIROS, NA RECEÇÃO A DELEGAÇÃO DE BOMBEIROS DE MACAU, EM ABRIL DE 2000.

FOTOGRAFIA CEDIDA POR MARIA DA GRAÇA LOURENÇO, 2021.

LUCIANO LOURENÇO NA VISITA
DO PRESIDENTE DA REPÚBLICA
MÁRIO SOARES ÀS INSTALAÇÕES
DO NICIF, A 14/04/1994 E, AO
LADO, COM O MINISTRO DA
ADMINISTRAÇÃO INTERNA JORGE
COELHO E O PRESIDENTE DA
LIGA DOS BOMBEIROS
PORTUGUESES, LOURENÇO
BATISTA, EM 28/04/1997.

FOTOGRAFIA CEDIDA POR
MARIA DA GRAÇA LOURENÇO, 2021.

LUCIANO LOURENÇO NUMA ALOCUÇÃO
DURANTE UM EPRIF - ENCONTROS
PEDAGÓGICOS SOBRE RISCO DE INCÊNDIO
FLORESTAL, EM 20/11/1995.

FOTOGRAFIA CEDIDA POR
MARIA DA GRAÇA LOURENÇO, 2021.

LUCIANO LOURENÇO, NUMA DAS REUNIÕES DO PREFER - *SPACE-BASED INFORMATION SUPPORT FOR PREVENTION AND RECOVERY OF FOREST FIRES EMERGENCY*, DESENVOLVIDO POR UM CONSÓRCIO DE 8 INSTITUIÇÕES, ORIUNDAS DE 5 PAÍSES, EM 04/06/2015.

FOTOGRAFIA CEDIDA POR MARIA DA GRAÇA LOURENÇO, 2021.

LUCIANO LOURENÇO, NA SESSÃO DE ENCERRAMENTO DO III SIMPÓSIO IBERO-AFRO-AMERICANO DE RISCOS, A 20 DE JUNHO DE 2019, NO INSTITUTO DE GEOGRAFIA, CAMPUS SANTA MÔNICA, DA UNIVERSIDADE FEDERAL DA UBERLÂNDIA, MINAS GERAIS, BRASIL.

FOTOGRAFIA DOS ARQUIVOS DA RISCOS - ASSOCIAÇÃO PORTUGUESA DE RISCOS, PREVENÇÃO E SEGURANÇA, 2021.

PROTEÇÃO CIVIL E SEGURANÇA COMUNITÁRIA

Caminhos a percorrer

LUCIANO LOURENÇO, NUMA VISITA AO CIRCOSC - *CENTRE INTER REGIONAL COORDINATION SECURITE CIVILE*,
EM BORDEUS (FRANÇA), JUNHO DE 1987.

FOTOGRAFIA CEDIDA POR MARIA DA GRAÇA LOURENÇO, 2021.

Decision support systems and risk analysis for spatial planning

Nelson Mileu*

Margarida Queirós*

ORCID: 0000-0002-6677-0425 nmileu@campus.ul.pt ORCID: 0000-0001-6843-6861 margaridav@campus.ul.pt

*University of Lisboa, Center for Geographical Studies, Institute of Geography and Spatial Planning (Portugal)

Abstract

Risk amplification and spatial planning strategies are becoming increasingly intertwined, due to frequency and intensification of recurrent disasters, as a result of climate change. Promoted under the United Nations, the Sendai Framework for Disaster risk Reduction (2015-2030) set the priority of “investing in disaster risk reduction for resilience”, and therefore is committed with the mainstreaming of disaster risk assessment into land-use and spatial planning. In this research we present RiskOTe, a framework that aims at integrating the risk management component into municipal planning. RiskOTe is therefore a decision support system to assist spatial planning integrating the risk management components at the local level. RiskOTe tool is presented in order to explain its theoretical concepts, components (e.g., spatial database), and interface models. We use a case study to illustrate how the system operates.

Keywords: Risk, spatial planning, decision support system, webgis.

Resumo

Sistemas de apoio à decisão e análise de risco no ordenamento do território. A amplificação de riscos e as estratégias de ordenamento do território encontram-se cada vez mais interligadas, devido à frequência e intensificação recorrente de catástrofes naturais, como resultado das mudanças climáticas. Promovido pelas Nações Unidas, o Quadro de Sendai para Redução do Risco de Catástrofes (2015-2030) definiu a prioridade de “investir na redução do risco de desastres para a resiliência” e, portanto, está comprometido com a integração da avaliação do risco de catástrofes no uso do solo e no ordenamento do território. Nesta pesquisa, apresentamos o RiskOTe, uma plataforma que visa integrar a componente de gestão de risco no planeamento municipal. O RiskOTe é, portanto, um sistema de apoio à decisão desenvolvido para auxiliar o ordenamento do território integrando os componentes de gestão de risco à escala local. A ferramenta RiskOTe é apresentada, explicando-se os conceitos teóricos adotados, componentes (por exemplo a base de dados espacial) e interface da plataforma, demonstrando-se o seu funcionamento através de um caso de estudos.

Palavras-chave: Risco, ordenamento do território, sistema de suporte à decisão, webgis.

Introduction

According to the Sendai Framework for Disaster Risk Reduction 2015–2030, disaster risk reduction requires a multi hazard approach and inclusive risk informed decision making based on the open exchange and dissemination of disaggregated data (by sex, age and disability), and also on accessible, up to date, understandable, science based, non-sensitive risk information, and traditional knowledge (UN, 2015). At EU level, the Green Deal [COM(2019) 640 final, p.2] “[...] *aims to protect, conserve and enhance the EU’s natural capital, and protect the health and well-being of citizens from environment-related risks and impacts*”. To achieve the targets set out by Sendai Framework and the European Green Deal, it is of utmost importance to take risk informed choices based on Decision Support Systems.

Integrating concerns associated with risk analysis and risk governance, a spatial decision support system was developed, designed to provide support to spatial planning activities that integrate risk management, the RiskOTe framework. Recent definitions of a spatial decision support system (SDSS) include a combination of GIS functionalities, remote sensing techniques, mathematical models and other decision functionalities (Sugumaran & DeGroote, 2011; Eissa, 2013).

Newman *et al.* (2014), Belardo *et al.* (1984a), Belardo *et al.* (1984b) and Wallace and Debalogh (1985), paved the way for research decision support systems in risk management. Cioca and Cioca (2010) explored the use of decision support systems in disaster management, using a rapid flood alert system as case study. More recently Newman *et al.* (2017) presented a review of literature on decision support systems for natural hazard risk reduction where they present the current status and future research directions in this research area. In this work the authors claim that decision support systems (DSSs) for natural hazard risk reduction (NHRR) are becoming increasingly important.

In this chapter, we focus on the development of a decision support system for disaster management, taking into account its usefulness in spatial planning policies. Considering the most recent works in the body of literature about decision support systems, we confirm that it is a recurring theme which is used on several hazards and for different purposes in risk management (Newman *et al.*, 2017; Mileu, 2016; Cioca & Filip, 2015). However, the inclusion of risk-reduction measures, such as landuse planning is still one of the research areas that require greater focus (Newman *et al.*, 2017).

An example of the application of SDSS in risk management to structure decisions in spatial planning was the EU-funded research project “Applied Multi Risk Mapping

of Natural Hazards for Impact Assessment” (ARMONIA) project. Its overall aim was to develop an approach to produce integrated multi-risk maps to achieve more effective spatial planning actions in areas prone to natural disasters (ARMONIA, 2007). Using a similar rational, Menoni *et al.* (2006) established a methodology to ensure that planning policies can be entirely informed about the multiple risks affecting specific areas, the levels of vulnerability of different land uses and settlements, taking into account social factors and the options that are available to mitigate the risks.

Three major questions can be addressed when using the RiskOTe tool as an SDSS (hereinafter termed RiskOTe SDSS) in order to integrate risk mapping in spatial planning at the local level:

- i. How can a decision support model be useful in risk management to support spatial planning and land-use changes assessment?
- ii. Which components and their characteristics can a decision support system have to consider?
- iii. What scenarios can be developed by the decision support system and how can results be user-friendly?

The development of RiskOTe SDSS demonstrates the advantages associated with land-use decision-making, based on a rock-solid foundation of information and analysis of the different risks, consequences, and possible actions to be taken to mitigate and reduce them. The tool fills a gap among the existing ones, based on four principles: considers explicitly the risk concept in spatial planning decision-making (integrating hazard and vulnerability components); focuses the analysis on the municipal scale since different policies are reverted to the territory at this scale; integrates a system of semaphore signaling to land use changes, rather than using a prohibitive system; helps policies based on a multicriteria methodology where the weights are obtained from expert judgements.

This chapter describes the modelling framework about which RiskOTe SDSS was assembled, with a specific emphasis on a risk assessment approach. It then explains the SDSS technological framework and the tool functionalities. Additionally, the application of RiskOTe SDSS is clarified using the semi-quantitative and the qualitative approaches for one case study: the municipality of Oeiras (in Lisbon Metropolitan Area, Portugal). Lastly, the chapter recaps the use of RiskOTe SDSS in the context of spatial planning decision-making and discusses the limitations and future developments.

RiskOTe SDSS approach

The RiskOTe SDSS risk analysis is supported by the following risk definition: the probability of harmful consequences, or expected losses resulting from interactions between hazards and vulnerable conditions in a given area and time period (Julião *et al.*, 2009; UNISDR, 2004). Supported by this definition, the challenge was to apply the concept in the system to different hazards (floods, forest fires, landslides, tsunamis and seismic hazard), considering their importance to spatial planning. Although the system considers the seismic hazard, it was not analyzed because there are no seismic hazard data at the local scale, and it does not integrate the planning options of the Oeiras municipality. It was used different geospatial data in the development of RiskOTe SDSS for the cases studies (TABLE I). This list summarizes the data used in the case study of Oeiras, but the system allows the integration of data for other case studies, as long as they are in vector format, allowing their export to the spatial database.

TABLE I - List of the geospatial data used.

Name	Type	Source	Scale	Date	EPSG
Flood maps	Vector\Polygons	Hydrological / Hydraulic Study for the Delimitation of Oeiras Flood Zones according to Decree-Law Nº. 115/2010	1:2.000	2011	3763
Landslide susceptibility map	Raster (10m)	Oeiras Municipal Civil Protection Emergency Plan	1:10.000	2011	3763
Wildfire susceptibility map	Raster (10m)	Oeiras Municipal Civil Protection Emergency Plan	1:10.000	2011	3763
Tsunami map	PDF Vector\Polygons	Oeiras Master Plan	1:10.000	2013	3763
Exposed elements	Vector\Polygons\ Lines\Points	http://dadosabertos.cm-oeiras.pt	1:2.000	2011	3763
Census areas	Vector\Polygons	Nacional Statistics Institute	1:10.000	2011	3763
Land use maps	Vector\Polygons	Directorate-General for Territory	1:25.000	2015	3763
National Protected Areas Network	Vector\Polygons	ICNF/CEAP/ISA/ULisboa	1:25.000	2013	3763
Natura 2000 Network	Vector\Polygons	ICNF/CEAP/ISA/ULisboa	1:100000	2013	3763

Considering that the system was designed to support decisions about the transformation of land-use, the analysis process was organized in four phases: 1) Delimitation of the area to be transformed; 2) Risk Analysis (Semi-quantitative and/or qualitative models); 3) Obtaining results (maps, graphics, report); and 4) Land-use transformation decision.

The following points present the semi-quantitative and the qualitative risk analysis models implemented in RiskOTe SDSS.

Semi-quantitative approach

The semi-quantitative model expresses the risk in terms of indexes and can be described as a product of a hazard index (HI) by a consequence index (CI), applied to the different hazards that affect spatial planning (Eq. (1)).

$$Risk_n = Hazard\ Index_n \times Consequence\ Index_n \quad (1)$$

The development of the semi-quantitative model in RiskOTe is an adaptation of Lumbroso and Woolhouse (2007) model, where the risk index is obtained through the product of the hazard index by the consequence indexes for the components of physical, social, economic and environmental vulnerability.

In terms of weighting the different components of vulnerability, the chosen option was based on a multicriteria solution. For the initial default weights, the values were obtained from the MACBETH model (Bana e Costa *et al.*, 2015). This methodology was applied in the RiskOTe framework by weighting the four components of consequences (i.e., physical, social, economy, and environment) according to stakeholder preferences or other user-specified weights. Based on the concepts adopted in the development of the decision support system, the fundamental points of view for comparing alternatives for assessing vulnerability were defined. In this case, three risk minimization alternatives were considered through the different components of vulnerability. The first alternative (A1) corresponds to the non-interventionist alternative, that is, the development perspective according to the trend where there are no intervention measures related to risk minimization. The second alternative (A2), corresponds to urban development, conditioned to the integration of mitigating measures in the project that allow to demonstrate the reduction of the hazard or the vulnerability of the exposed elements. The third alternative (A3) corresponds to the prohibitionist perspective, where any and all urban development located in a hazard prone area is not allowed.

Using a hierarchical additive model formula, it was possible, through the weighting coefficients of each component, and the scores obtained through the application of the model, to obtain a general classification for the idealized alternatives. It is possible to observe the partial aggregation of values according to all points of view that are part of the vulnerability assessment model and subcomponents of physical vulnerability (TABLE II). In lines A1, A2 and A3, corresponding to the alternatives, the scores obtained from the judgments can be observed, by vulnerability component (PH_V, SO_V, EC_V and EN_V) and in the last line the resulting weights.

TABLE II - Vulnerability weights.

Vulnerability	Physical				Social	Economic	Environment
Alternative	Population	Buildings	Infrastructures	PH_V	SO_V	EC_V	EN_V
A1	70.59	71.43	60.0	70.59	86.87	87.5	92.86
A2	88.24	92.86	86.87	88.24	86.87	87.5	92.86
A3	100.0	92.86	100.0	100.0	100.0	100.0	92.86
Weights	0.57	0.29	0.14	0.46	0.15	0.08	0.31

An advantage of this approach is the possibility that any entity can apply the MACBETH method, thus obtaining weights adjusted to each case. Because the determination of the weights is subject to the different judgments provided, the weights that will be included in the decision support system, and which by default are those previously determined, can also be readjusted in the interface, by the user, either for the evaluation model qualitative risk, or for the semi-quantitative risk assessment model. The coping capacity does not directly integrate the risk function but has been considered as an additional and complementary information element to support the decision.

The hazard/susceptibility indexes calculation is supported by the classes described in the methodological guide for the production of municipal risk cartography and for the creation of municipal-based Geographic Information Systems (Julião *et al.*, 2009). With this methodological guide the assessment of the susceptibility to a certain hazard is carried out through the predisposition factors for the occurrence of dangerous processes or actions, in a qualitative way. The classification of the susceptibility expressed in the maps is established on a qualitative scale with four classes, having as reference the reality of the entire Portuguese territory: 1-High Susceptibility; 2- Moderate Susceptibility; 3- Low Susceptibility; 4- Susceptibility Null or Not Applicable. The main reason for using the classes described in the methodological guide as indexes lies in the fact that it is a national guide adopted by all Portuguese municipalities for producing municipal risk cartography.

The second component of the adopted risk definition are the consequence indexes. The consequence indexes are calculated for the different vulnerability components considered: i) Physical; ii) Social; iii) Economical; iv) Environmental, considering the value of the exposed elements. A detailed description of the indexes and respective mathematical formulae can be found in the works of Mileu (2016) and Mileu and Queirós (2018a).

Qualitative approach

For the case studies where risk maps are unavailable, a qualitative risk assessment model can be used. The qualitative risk model in RiskOTe uses a risk matrix, adapted from Saunders (2012) that relates consequences and likelihood.

The consequences are described in a matrix that expresses the severity of impact (Severe, Major, Moderate, Minor and Negligible) for health and safety; social; economic and environmental metrics. Different impact measures allow to obtain six consequence values (Saunders, 2012). In the RiskOTe SDSS workflow it is possible to define the consequence model weights by the user and establish an overall level of impact adapted to different case studies. By default, the system presents the following weights, adapted from SMG model (S = seriousness, M = manageability and G = growth), were adopted: People: 50%, Buildings: 25%, Economy: 15% and Environment: 10%.

For each hazard, the likelihood can be obtained from seven levels. The first level corresponds to a theoretically possible but not expected to occur event (one in 10,000 years). The second level corresponds to a possible but not expected event to occur, except in exceptional circumstances (one in 1000 years). The third level corresponds to a possible but not expected event to occur, except in exceptional circumstances (once every 100 years). The fourth level corresponds to an event that occurs somewhere from time to time (once every 30 years). The fifth level corresponds to an event that might occur once in your lifetime (up to once every ten years). The sixth level corresponds to an event that has occurred several times in your lifetime (once every three years). Finally, the seventh level corresponds to an event that occur on an annual basis (once a year or more frequently).

The qualitative model implemented in RiskOTe expresses the level of risk as a function of consequences multiplied by likelihood. For achieving risk, consequence levels are crossed with likelihood in a matrix that is classified in four colors (green, yellow, orange and red) that are used as descriptors for land use control.

RiskOTe SDSS implementation

The RiskOTe design and configuration is based on five system components, adapted from Sugumaran and DeGroote (2011). This components are: the knowledge component where the adopted risk concepts are described; the database management component,

where the data model is established; the management component of the model where the multicriteria risk approach and the land use transformation model is implemented; the interface component where all the model inputs and outputs are designed; and the last component dedicated to the actors/decision makers where the focus is the relation between the system and risk governance.

The technical architecture of RiskOTe is supported by three tiers (fig. 1): data, application and client tier. All the alphanumeric and vector data is stored in PostgreSQL/Postgis relational database. All the layers used in the system are provided through WMS services available in the local GIS server or in public WMS services.

Fig. 1 - RiskOTe technical architecture.

The system takes advantage of GeoServer as GIS server and the application developed to perform the risk assessment. This application was developed using the Visual Basic .NET programming language. One of the initial system requirements was that the application should work in a web environment. Considering this requirement, the development was based on HTML5, CSS and Javascript (JS). The development of the webgis interface included the following JS libraries: OpenLayers javascript library for displaying geographic data in browsers; the GeoExt javascript library, and other libraries such as Bootstrap and JQuery.

From the user's point of view, 8 steps are required for the system to obtain information and support decisions about the transformation of land-use (fig. 2): 1) RiskOTE SDSS home page; 2) Multicriteria weighting; 3) Scenario definitions; 4) Susceptibility analysis; 5) Exposed elements; 6) Analysis of the vulnerability/consequence indexes; 7) Coping capacity; 8) Results and comparison of scenarios.

Fig. 2 - RiskOTE SDSS initial page (Source: Mileu, 2016).

The home page of RiskOTE SDSS is the gateway to the system, presenting the concepts used and a user manual. The first step of the system consists of defining the weights for the semi-quantitative and qualitative risk assessment models, depending on the user's option. These weights are predefined, and the user can adjust them according to the case study. In the next step, the scenario is defined, namely the name,

layers that integrate mitigation measures or layers associated with climate change scenarios. In this phase, the user must draw a polygon with the limit of the area to be analysed or the area corresponding to the urbanistic intention. This polygon serves as a limit to perform the topological intersection with the hazard/susceptibility layers, vulnerability and exposed elements and to carry out the respective qualitative and \ or semi-quantitative risk analysis.

In the next step, corresponding to the susceptibility analysis, the results of the intersection of the polygon with the analysed hazards are presented. Taking into account the susceptibility classes and the intersected area, a weighted value, between 0 and 3, is calculated for each analysed hazard. The exposed elements are considered in the system as a support in the decision process, so in all analysis processes, a summary table is presented with the number and type of exposed elements that intersect the user defined polygon. The calculation and presentation of maps referring to the consequence indices for the different vulnerability components is the next step. For the different vulnerability components and for each hazard, a normalised value between 0 and 3 is calculated and presented to the user. Although the coping capacity does not integrate the risk analysis models, it is one of the steps of the system, as it is considered to be an element of added value in risk analysis. In this step, the firefighter's arrival times are calculated at the location corresponding to the user defined polygon, as well as the arrival time at the nearest hospital. In the last step, the user has access to the results of the risk analysis where he can check the guidelines provided for the transformation of land use. At this stage, the user can compare the results of the current scenario with other scenarios previously performed and thus inform and support the decision with all relevant information.

Applying RiskOTe to support spatial planning

Using the semi-quantitative and the qualitative approaches, implemented in RiskOTe SDSS, the two following use cases provide a global view on the interaction with the system. With these two use cases it is possible to show the spatial planning guidelines obtained by RiskOTe SDSS.

The municipality of Oeiras was used to test the applicability of the methodology at local level. Oeiras is a Portuguese urban municipality in the western part of Lisbon metropolitan area, with a population of 172,120 inhabitants.

3.1 – Semi-quantitative approach use case

For the semi-quantitative approach, the principles of land use transformation were structured according to the different risk classes following the matrix (fig. 3).

Risk		RURAL	URBAN
	HIGH	Forbidden to build	Construction prohibited (exceptionally permitted under strict conditions)
	MODERATE	Construction prohibited (exceptionally permitted under strict conditions)	The safety conditions should be demonstrated for new buildings and mitigation measures must be implemented
	LOW	Construction is conditionally authorised if specified conditions for hazards are provided	Construction is authorized Owners should be aware of the existing hazards and possible mitigation measures
NULL OR NON-APPLICABLE			

Fig. 3 - Land use transformation matrix (Source: Mileu, 2016).

In this matrix, three risk classes can be observed, obtained in the semi-quantitative approach from the product of the hazard index by the consequence index. In this way, the partial analysis of the susceptibility in the processes of transformation of land use integrates the vulnerability component. At the same time, this matrix analyzes the place where the urban planning operation is to be carried out in a dual way, differentiating between urban and rural locations. This differentiation works as an additional protection mechanism for rural areas, or areas with lower population densities.

The first step for calculating the semi-quantitative risk is setting the vulnerability weights. In this use case the weights were obtained from the application of the MACBETH method: 46% for the physical component; 15% for the social component; 8% for the economic component and 31% for the environmental component (fig. 4a). In the second step the scenario configuration is defined, selecting the hazards and the exposed elements to be analyzed (fig. 4b). In this use case, a small polygon was drawn near the locality of Porto Salvo (fig. 4c). The next step intersects the selected susceptibility layers with the previous drawn polygon (fig. 4d). The intersection between the polygon and the susceptibility layers

resulted in the identification of only two themes: forest fires and landslides. For the forest fires layer, a hazard index of 2.89 was calculated, while for the landslides an index of 0.04 was obtained. The fourth step lists the selected exposed elements that intersect the previous drawn polygon (fig. 4e). The fifth step presents the calculated consequence indexes (fig. 4f). In the case of forest fires, it resulted in a consequence index of 1.58, while for landslides a value of 1.98 was obtained. The sixth step corresponds to the coping capacity analyzes (fig. 4g). In the last step, the results are presented (fig. 4h).

In this use case, the risk analysis for forest fires and landslides resulted in a “Low” risk, becoming an indication for spatial planning “Construction is authorized. Owners should be aware of existing hazards and possible risk-minimization measures” (TABLE III). The results of this use case allow us to verify that it is possible to inform and provide indications to decision-makers about the possibility of transforming land use beyond the simple analyses, based on the intersection with the susceptibility.

TABLE III - Semi-quantitative approach use case results.

	Semi-quantitative model	
Hazards	Risk	Spatial planning guidance
Floods	Null	No restrictions on land use transformation
Forest fires	Low	Construction is authorized. Owners should be aware of existing hazards and possible risk-minimization measures
Landslides	Low	Construction is authorized. Owners should be aware of existing hazards and possible risk-minimization measures
Tsunami	Null	No restrictions on land use transformation
Seismic	-	-

Source: Mileu, 2016.

Qualitative approach use case

For the qualitative approach, the principles of land use transformation were structured according to the different risk classes following the matrix (TABLE IV).

TABLE IV - Qualitative levels of risk based.

Level of risk	Level of land use control
Acceptable	Permitted
Tolerable	Controlled
Tolerable with consent	Discretionary, restricted Discretionary
Intolerable	No complying, prohibited

Source: Adapted from Saunders, 2012.

Fig. 4 - RiskOTe SDSS analysis steps: (a) Multi-criteria weights; (b) Scenario definition; (c) Polygon drawing; (d) Susceptibility; (e) Exposed elements; (f) Vulnerability/consequence indexes; (g) Coping capacity; (h) Results (Source: Mileu, 2016).

The first step for calculating the qualitative risk is setting the criteria weights (fig. 5). The weights used in this use case are based on Saunders (2012) [19] methodology for assessing acceptability, tolerability, and intolerability of risk based on consequences on health, social, economic and environmental conditions: 50% for People; 25% for Buildings; 15% for Economy and 10% for Environment.

The second and last step for calculating the qualitative risk is the scenario configuration where the scenario name is defined, and the probability and the consequences are established. For the qualitative approach use case, the consequences were extracted from the report “Storms in revision” elaborated by the Municipality of Oeiras (CMO, 1996) regarding the storm of January 8, 1996, using an impact area near the mouth of the Laje river, located in the parish of Oeiras. This report contains detailed data about the asset identification and location, description of repairs and their cost and financing source.

Multi-criteria analysis

Step 2a | 7 from scenario **111**

2a.1 **Qualitative risk model weights**

The weightings of the qualitative approach are based on Saunders's (2013) methodology for assessing acceptability, tolerability and intolerability of risk based on consequences (C) on health (victims), social (edified), economic and environmental conditions using the SMG model (S = seriousness, M = manageability and G = growth): Victims 50%, Edified 25%, Economy 15% and Environment 10%, being able in each scenario to adapt the model weights.

Consequence	Weight (%)
Victims	50
Building	25
Economy	15
Environment	10
TOTAL	100

Scenario configuration.

Step 3 | 7 from scenario **112**

3.1 Select parish of **Bancarenha** for scenario definition.

3.2 Name: **Scenario 7** and description: **new urban development**

3.3. Select probability level for each hazard

	Chamas/Inundações (m-2m)	Inundações Florestais (>1000m)	Mar. Massa Várzea	Tsunami	Sismos (M>5)
Uma vez por ano ou mais	☒	☐	☐	☐	☐
Uma vez entre três anos	☐	☐	☐	☐	☐
Uma vez entre dez anos	☐	☐	☐	☐	☐
Uma vez entre trinta anos	☐	☐	☐	☐	☐
Uma vez entre cem anos	☐	☐	☐	☐	☐
Uma vez entre mil anos	☐	☐	☐	☐	☐
Uma vez entre mil anos	☐	☐	☐	☐	☐

3.4. Select consequence level for each hazard

	Chamas/Inundações (m-2m)	Inundações Florestais	Mar. Massa Várzea	Tsunami	Sismos
Saúde	Múltiplas fatalidades ou i	Múltiplas fatalidades ou i	Múltiplas fatalidades ou i	Múltiplas fatalidades ou i	Múltiplas fatalidades ou i
Social	Quantias sociais muito g	Quantias sociais muito g	Quantias sociais muito g	Quantias sociais muito g	Quantias sociais muito g
Economia	Severo ou mais de 50% c	Severo ou mais de 50% c	Severo ou mais de 50% c	Severo ou mais de 50% c	Severo ou mais de 50% c
Ambiente	Severo, prejuizos de long	Severo, prejuizos de long	Severo, prejuizos de long	Severo, prejuizos de long	Severo, prejuizos de long

Fig. 5 - RiskOTe SDSS qualitative scenario configuration (Source: Mileu, 2016).

The most serious consequences associated with this storm were associated with the floods that occurred in the final section of Laje River. Taking into account the consequences of this storm, the respective probability and consequences values were introduced into the system.

The qualitative risk assessment result for this scenario (TABLE V), show a “Tolerable with consent” risk, and an indication for land use planning where land use transformation should be subject to restrictions (Mileu and Queirós, 2018b)). The results of this use case allowed us to verify that for situations in which there are no risk maps, but it is possible to access the history of serious accidents or catastrophes, it is possible to provide indications to decision-makers about the possibility of transforming land use.

TABLE V - Qualitative approach use case results.

	Qualitative model	
Hazards	Risk	Spatial planning guidance
Floods	Tolerable with consent	Discretionary, restricted
Forest fires	-	-
Landslides	-	-
Tsunami	-	-
Seismic	-	-

Source: Mileu, 2016.

Conclusions

The integration of risk in the development strategies of the territories is currently an unavoidable issue. The integrated understanding of disaster risk in all its dimensions, as expressed in the first action priority of the Sendai Framework for Disaster Risk Reduction, only emphasizes the need to increase knowledge of pre disaster risk assessment, improving the capacity to preparedness and effective response to disasters. The adoption of these tools in Europe can also be an important boost in the European Green Deal development, facilitating evidence-based decisions and expanding the capacity to understand and tackle environmental challenges.

The implementation of RiskOTe SDSS is a contribution to the development of decision support tools in the field of spatial planning, integrating risk in its various dimensions in the process of land use transformation. With the development and use of RiskOTe SDSS, it was possible to verify, as previously stated by other authors (Menoni *et al.*, 2006; ARMONIA, 2007), that it is possible to achieve more effective spatial planning procedures in areas that are prone to natural disasters.

The development of RiskOTe SDSS enabled the integrated use of geographic data from various sources and the obtaining of information to support the political decision-making process at the municipal level. The use of the municipal scale to inform the process of transformation of land use is critical, as it is on this scale that all options for land management are taken, as well as emergency planning and immediate response to disasters.

The use cases provided a global view of the interaction with the system demonstrating the applicability of RiskOTe SDSS with a semi-quantitative and a qualitative model.

The implementation of the semi-quantitative and qualitative model of risk revealed the flexibility of the system in responding to the existence of different data realities. The semi-quantitative approach, based on the calculation of susceptibility indices and consequence indices, proved to be a complex task to implement, but with a high added value in the risk assessment process. Despite showing a strong dependence associated with the existence of risk mapping, it is the component of the system with the greatest potential for evolution. This evolution will necessarily involve the implementation of a quantitative risk model with all its known advantages and disadvantages. As demonstrated in the use case, the implementation of the qualitative approach proved to be useful in situations where there is a historical record of events and its geographical identification is possible.

The adoption of decision support systems like RiskOTe by the municipalities will be an evolution beyond the traditional binary management of the territory, where the possibility of transforming land use is authorized or not. The adoption of decision support systems such as RiskOTe makes it possible to support the decision-making process on the transformation of land use in a more comprehensive way, since it integrates various components of risk such as susceptibility, vulnerability or coping capacity, disconnecting from the prohibitionist view, focusing on prevention and obtaining guidelines for spatial planning.

Bibliographic references

- APPLIED MULTI RISK MAPPING OF NATURAL HAZARDS FOR IMPACT ASSESSMENT - ARMONIA (2007). *A Summary of the Research Undertaken by the ARMONIA Research Project*, Funded under the Sixth EU Framework Programme for Research and Technological Development; with Support of T6 Società Cooperativa; Lancaster University, Department of Geography: Lancaster, UK.
- Bana e Costa, C., Corte, J., Vansnick, J. (2015). M-MACBETH Versão 2.4.0 Guia do Utilizador. [Available from: <http://www.m-macbeth.com/help/pdf/M-MACBETH%202.4.0%20Guia%20do%20utilizador.pdf> [accessed on 2015-11-30].
- Belardo, S., Karwan, K., Wallace, W. (1984a). An investigation of system-design considerations for emergency management decision support. *IEEE Trans. Syst. Man Cybern.*, 14, 795–804.

- Belardo, S., Karwan, K., Wallace, W. (1984b). Managing the response to disasters using microcomputers. *Interfaces*, 14, 29-39.
- Cioca, M., Cioca, L. (2010). Decision Support Systems used in Disaster Management. In *Decision Support Systems*; Jao, S., Ed., Intech: Rijeka, Croatia; pp. 371–391. ISBN 978-953-7619-64-0.
- Cioca, M., Filip, F. (2015). *Decision Support Systems—A Bibliography 1947–2007*. Available from: <http://www.cif.ulsibiu.ro/mariusu/bibliographySSD.htm> [Accessed on 2015-11-30].
- CMO – CÂMARA MUNICIPAL DE OEIRAS (1996). *Intempéries em Revisão. Plano de Actividades. Relatório da Situação* [Storms under review. Activity Plan. Status Report], Oeiras.
- Eissa, A. (2013). *Spatial Decision Support System for Infrastructure Resource allocation (Master's Thesis)*. University of Twente, Enschede, The Netherlands.
- Julião, R., Nery, F., Ribeiro, J. L., Zêzere, J. L. (2009). *Guia Metodológico Para a Produção de Cartografia Municipal de Risco e Para a Criação de Sistemas de Informação Geográfica (SIG) de Base Municipal* [Methodological Guide for the Production of Municipal Risk Cartography and for the Creation of Geographic Information Systems (GIS) of Municipal Base]; Autoridade Nacional de Protecção Civil/Direcção Geral de Ordenamento do Território e Desenvolvimento Urbano/Instituto Geográfico Português: Lisboa, Portugal.
- Lumbroso, D. & Woolhouse, G. (2007). *Implementation of a Case Study Simulation, Armonia Project: Applied Multi-Risk Mapping of Natural Hazards for Impact Assessment*. Available online: https://forum.eionet.europa.eu/eionet-air-climate/library/public/2010_citiesproject/interchange/armonia_project/armonia_project_10/download/en/1/ARMONIA_PROJECT_Deliverable%206.1.pdf [Accessed on 2018-03-18]
- Menoni, S., Galderisi, A., Ceudech, A., Delmonaco, G., Margotinni, C. & Spizzichino, D. (2006). *Harmonised Hazard, Vulnerability and Risk Assessment Methods Informing Mitigation Strategies Addressing Land-use Planning and Management*. Available online: https://forum.eionet.europa.eu/eionet-air-climate/library/public/2010_citiesproject/interchange/armonia_project/armonia_project_8/download/en/1/ARMONIA_PROJECT_Deliverable%205.1.pdf [Accessed on 2018-03-20]
- Mileu, N. (2016). *Sistema de Apoio à Decisão na Gestão do Risco à Escala Municipal* (Ph.D. Thesis). University of Lisbon, Lisbon, Portugal.
- Mileu, N., Queirós, M. (2018a). Integrating Risk Assessment into Spatial Planning: RiskOTe Decision Support System; *International Journal of Geo-Information*, 7, 184. DOI: <https://doi.org/10.3390/ijgi7050184>
- Mileu, N., Queirós, M. (2018b). The qualitative risk assessment model of riskote decision support system, *Revista Brasileira de Planejamento e Desenvolvimento*, Curitiba, v. 7, n. 4, 479-494.
- Newman, J., Maier, H., Delden, H., Zecchin, A., Dandy, G., Riddell, G., Newland, C. (2014). Literature Review on Decision Support Systems for Optimising Long-Term Natural Hazard Mitigation Policy and Project Portfolios; Report 2014.009; Bushfire and Natural Hazards CRC: Melbourne, Australia.
- Newman, J., Maier, H., Riddell, G., Zecchin, A., Daniell, J., Schaefer, A., Delden, H., Khazai, B., O'Flaherty, M., Newland, C. (2017). Review of literature on decision support systems for natural hazard risk reduction: Current status and future research directions. *Environmental Modelling & Software* 96, 378-409.
- Saunders, W. (2012). *Innovative land-use planning for natural hazard risk in New Zealand (PhD Thesis)*. University of Massey, Manawatu.
- Sugumaran, R., DeGroote, J. (2011). *Spatial Decision Support Systems—Principles and Practices*; CRC Press, Taylor&Francis Group: Boca Raton, FL, USA.
- Sugumaran, R., DeGroote, J. (2011). *Spatial Decision Support Systems—Principles and Practices*; CRC Press, Taylor&Francis Group: Boca Raton, FL, USA.
- UN - UNITED NATIONS (2015). *Sendai Framework for Disaster Risk Reduction 2015-2030*. Available from: https://www.unisdr.org/files/43291_sendaiframeworkfordrren.pdf [Accessed on 2018-05-02]
- UNISDR (2004). *Living with Risk. A Global Review of Disaster Reduction Initiatives*; United Nations International Strategy for Disaster Reduction: Geneva, Switzerland; ISBN 9211010640.
- Wallace, W., Debalogh, F. (1985). *Decision support systems for disaster management*. *Public Adm. Rev.*, 45, 134-146.

ÍNDICE

PENSAR A FLORESTA NA PERSPETIVA DOS RISCOS	
DOS INCÊNDIOS FLORESTAIS À DIVERSIDADE ECOLÓGICA	19
 A investigação geográfica dos incêndios florestais em Portugal - Luciano Lourenço o grande impulsionador	
António Bento-Gonçalves e António Vieira	21
 Incêndios extremos em Portugal e na Grécia: reflexões sobre a importância da preparação e da comunicação do risco e da crise	
31	
Fantina Tedim, Vittorio Leone, Ângela Silva e Fernando Correia	
 A prevenção contra incêndios florestais em tempo de pandemia: A união entre experiência e inovação	
Adriana Aparecida Bianchi Azevedo e Fábio Pimentel Barcello	45
 Relações entre ocorrências de incêndios florestais e alteração no uso e cobertura do solo	
Fillipe Tamiozzo Pereira Torres	57
 Is native forest an alternative to prevent wildfire in the WUI in Central Portugal?	
Aline Silva de Oliveira, Joaquim Sande Silva, José Gaspar, Nuno R. G. Nunes Guiomar e Paulo M. Fernandes	67
 Avaliação de Risco de Incêndio Rural à escala local na região Centro de Portugal	
Sandra Oliveira, Rafaello Bergonse, Pedro Pinto Santos, Ana Gonçalves, Raquel Melo e José Luís Zêzere	79
 Identificação de unidades cartográficas de intervenção prioritária pós incêndio florestal na Serra de Monchique	
Filipe Pereira, Fernando Granja-Martins e Helena Maria Fernandez	91
 O estudo dos processos erosivos em áreas ardidas em Portugal: perspetiva geográfica	
António Vieira e António Bento-Gonçalves	103
 Dinâmica do armazenamento de carbono em áreas de matos de montanha: efeito do fogo controlado	
Felícia Fonseca, Diego Silva, Zulimar Hernández, Ana Caroline Royer, e Tomás de Figueiredo	115
 Sixty years of the development projects and combating the environment and natural resources degradation in arid and semi-arid areas in Rif mountains in Morocco	
Hanifa El Motaki, Abdelhak El-fengour and Aissa El Bouzidi	125

Grandes incendios forestales en España y alteraciones de su régimen en las últimas décadas

Xavier Úbeda, Jorge Mataix-Solera, Marcos Francos y Joaquim Farguell 147

Review of satellite based support to forest fire environmental impact assessment: the example of Arischia (Italy) forest fire

Giovanni Laneve, Valerio Pampanoni 163

Adaptaciones de los programas de prevención contra incendios forestales en Chile, ante un escenario cambio climático

Miguel Castillo Soto 179

Resiliência aos incêndios através da gestão da paisagem: perceção da população do Sabugal sobre o Programa de Transformação da Paisagem

Diogo Martinho, Pedro Saloio, Carlos Pinto e Adélia Nunes 199

Impacto de agentes de distúrbio nos serviços dos ecossistemas em povoamentos de pinheiro bravo na Serra da Lousã

Raúl Salas González e Beatriz Fidalgo 213

A Floresta no Município de Mortágua: serviços e riscos percecionados pela população residente

Lígia Mateus, Adélia Nunes, Albano Figueiredo e António Campar de Almeida 225

El eucalipto en la Península Ibérica y su impacto sobre los recursos hídricos

Francisco Díaz-Fierros Viqueira 239

Marketing Territorial na Sustentabilidade Económica e Ambiental: o caso da Mata do Buçaco

Paulo Simões 251

A Biogeografia da cor

Jorge Paiva 263

PROTEÇÃO CIVIL E SEGURANÇA COMUNITÁRIA

CAMINHOS A PERCORRER 275

2021: um tempo para revisitação da gestão do risco e de crises

António Betâmio de Almeida 277

Planos de Emergência de Proteção Civil

Antonio Duarte Amaro 301

Redução do risco de desastre em áreas urbanas: revisão conceptual e aplicação	
Tiago Miguel Ferreira	311
As operações de proteção civil nos territórios arquipelágicos nacionais: o emprego de recursos disponíveis e o reforço das capacidades	
Luis Neri	323
A Avaliação de Riscos Climáticos nos Planos Municipais de Emergência em Portugal: métodos e experiência	
António Lopes, Marcelo Fragoso e Ezequiel Correia	333
<i>Déficits</i> de governação de risco: uma leitura sobre a pandemia SARS-CoV-2	
Manuel Ribeiro	353
A problemática dos riscos costeiros no âmbito do Turismo Costeiro e Marítimo: o caso do município de Odemira	
Mónica Brito, e José Gouveia	367
Gestão territorial do risco na adaptação às alterações climáticas	
Alexandre O. Tavares e Neide P. Areia	387
Os observatórios sociais nos processos de redução dos riscos, desastres e catástrofes	
Antenora Maria da Mata Siqueira e Luana Fernandes dos Santos Azeredo	399
Compreensão dos riscos de desastres através de Banco de Dados e Sistema de Informação Geográfica na cidade de Natal, RN, Brasil	
Lutiane Queiroz de Almeida, Francisca Leiliane Sousa de Oliveira, Dyego Freitas Rocha, Ana Clara Celestino Belchior e Eduardo Sousa de Azevedo	411
A importância do uso da comunicação estratégica na proteção civil	
Albino Tavares	425
Segurança ocupacional em operações de colheita florestal	
Ana C. Meira Castro, João Santos Baptista e Killian S. Lima	435
Conceitos e terminologia em Medicina de Catástrofe. Sinopse	
Romero Bandeira e Sara Gandra	445
Estratégias de coping na gestão do stress associado à atividade profissional das forças policiais, bombeiros e emergência pré-hospitalar	
Cristina Queirós, Sílvia Monteiro Fonseca, Sara Faria, Sónia Cunha, Fernando Passos, Natália Vara e Rui Campos	463
Perturbação de stress pós-traumático em bombeiros: prevenção e intervenção	
Natália Vara, Sara Faria, Sílvia Monteiro Fonseca e Cristina Queirós	477
Emergency teams in their voice (PSP & GNR) factors of risk and resilience	
Carmen Diego Gonçalves	489

Como parâmetros que definem um Ambiente Térmico potenciam riscos:
estudo de casos

Mário Talaia 503

Segurança alimentar em Portugal e no Brasil: diferenças e equidades

Eurídice Alencastro, José Manuel Mendes e Ana Sancha Batista 517

Decision support systems and risk analysis for spatial planning

Nelson Mileu e Margarida Queirós 529

MENSAGENS PROSEPE 547

COORDENAÇÃO DISTRITAL 549

Mensagem da Coordenação Distrital dos Clubes da Floresta de Aveiro 550

Mensagem do Coordenador Distrital dos Clubes da Floresta de Braga 552

Mensagem do Coord. Distrital dos Clubes da Floresta de Castelo Branco 554

Mensagem do Coordenador Distrital dos Clubes da Floresta do Porto 555

Mensagem da Coord.^a Distrital dos Clubes da Floresta de Coimbra 558

Mensagem da Coordenadora Distrital dos Clubes da Floresta de Lisboa 560

Mensagem do Coord. Distrital dos Clubes da Floresta de Viana do Castelo ... 562

Mensagem da Coordenadora Distrital dos Clubes da Floresta de Viseu 564

CLUBES DA FLORESTA 567

Mensagem do Clube da Floresta os “Amigos dos Bacorinhos” 568

Mensagem do Clube da Floresta “Águia Real ” 570

Mensagem do Clube da Floresta “Borboleta e Amigos, Lda” 571

Mensagem do Clube da Floresta “*Canis lupus*” 572

Mensagem do Clube da Floresta os “Florestadores” 574

Mensagem do Clube da Floresta os “Laranjinhas de Amares” 576

Mensagem do Clube da Floresta “Marão Vida” 577

Mensagem do Clube da Floresta os “Micófilos” 578

Mensagem do Clube da Floresta os “Milhafrões” 580

Mensagem do Clube da Floresta “As Andorinhas” e “Ouriço” 582

Mensagem do Clube da Floresta “Ouriço” 584

Mensagem do Clube da Floresta “Pulmões do Mundo” 586

Mensagem do Clube da Floresta “Vamos Dar a Mão à Natureza” 587

LUCIANO LOURENÇO VIAJANDO PELO AMAZONAS AO PÔR DO SOL, EM 15/06/2012.

FOTOGRAFIA CEDIDA POR MARIA DA GRAÇA LOURENÇO, 2021.

Impressão:
Simões & Linhares, Lda.
Rua do Fetal, Lote 5
3020-923 Coimbra

Telefone: (0351) 239 084 200 | E-Mail: geral@simoeselinhares.pt
Web: <https://www.simoeselinhares.pt>

Setembro de 2021

RISCOS

ASSOCIAÇÃO PORTUGUESA
DE RISCOS, PREVENÇÃO
E SEGURANÇA

COIMBRA
2021