BIBLIOGRAPHIC INFORMATION SYSTEM

Journal Full Title: Journal of Biomedical Research & Environmental Sciences

Journal NLM Abbreviation: J Biomed Res Environ Sci

Journal Website Link: <https://www.jelsciences.com>

Journal ISSN: 2766-2276

Category: Multidisciplinary

Subject Areas: Medicine Group, Biology Group, General, Environmental Sciences

Topics Summation: 128

Issue Regularity: Monthly

Review Process type: Double Blind

Time to Publication: 7-14 Days

Indexing catalog: [Visit here](#)

Publication fee catalog: [Visit here](#)

DOI: 10.37871 ([CrossRef](#))

Plagiarism detection software: [iThenticate](#)

Managing entity: USA

Language: English

Research work collecting capability: Worldwide

Organized by: [SciRes Literature LLC](#)

License: Open Access by Journal of Biomedical Research & Environmental Sciences is licensed under a Creative Commons Attribution 4.0 International License. Based on a work at SciRes Literature LLC.

Manuscript should be submitted in Word Document (.doc or .docx) through **Online Submission** form or can be mailed to support@jelsciences.com

Vision

Journal of Biomedical Research & Environmental Sciences main aim is to enhance the importance of science and technology to the scientific community and also to provide an equal opportunity to seek and share ideas to all our researchers and scientists without any barriers to develop their career and helping in their development of discovering the world.

Modeling the Movement of Groundwater V_0D in a Rectangular Jumper with a Screen

Bereslavsky EN*

St. Petersburg State of Civil Aviation University, 38, Pilots Street, St. Petersburg, Russian Federation

LITERATURE REVIEW

Within the framework of planar steady-state filtration of incompressible fluid according to Darcy's law, an exact analytical solution of the problem of flow in a rectangular cofferdam with a screen in the presence of evaporation from the free surface of groundwater is given. The limiting cases of the considered motion – filtration in unconfined reservoir to imperfect gallery, as well as the flow in the absence of evaporation – are noted.

The solution of the problem of fluid inflow to an imperfect well with a flooded filter (i.e. axisymmetric problem) in the exact hydrodynamic formulation, is associated with great mathematical difficulties (especially for flows with a free surface) and so far does not exist [1–6] (numerous numerical and approximate solutions are not considered here). Therefore, as a first approximation to the solution of this problem, its flat analogues – problems about fluid flow to a rectangular cofferdam with a screen and to an imperfect rectilinear gallery – were considered [1,5–8], which give a certain qualitative insight into the possible dependence of filtration characteristics on the degree of well imperfection. Exact analytical solution of the problem of groundwater movement in unconfined reservoir to imperfect gallery in presence of evaporation from free surface is given in work [9]. As well as an approximate solution of the problem in the case when the flow area on the left is limited by some equipotential defined from the solution. It is shown that the flow pattern near the impermeable screen significantly depends not only on the imperfection of the gallery, but also on the presence of evaporation, which strongly affects the flow rate of the gallery and the ordinate of the exit point of the depression curve on the impermeable wall.

The presented work gives an exact solution of the filtration problem in a rectangular cofferdam with a screen in the presence of evaporation from the free surface of groundwater. In this case, as well as in [9] (unlike in [7,8]) in the area of the flow velocity hodograph appear not rectilinear, but circular polygons, which does not allow using the classical Christoffel-Schwarz formula. The effect of evaporation from the free surface is studied using the method of Polubarinova-Kochina PY [1–6]. Using the methods of conformal mapping of circular polygons developed for special form regions [10–12,13], the mixed multiparameter boundary value problem of the theory of analytic functions is solved. Taking into account the characteristic features of the flow under consideration makes it possible to obtain the solution through elementary functions, which makes their use the simplest and most convenient. The results of numerical calculations are given and hydrodynamic analysis of the influence of all physical parameters of the model on filtration characteristics is given. Obtained results of plane problem solution give at least

*Corresponding author

Bereslavskii EN, St. Petersburg State of Civil Aviation University, 38, Pilots street, St. Petersburg, Russian Federation, Russia

Tel: +7-812-301-0792

E-mail: eduber@mail.ru

DOI: 10.37871/jbres1191

Submitted: 15 February 2021

Accepted: 22 February 2021

Published: 23 February 2021

Copyright: © 2021 Bereslavsky EN. Distributed under Creative Commons CC-BY 4.0

OPEN ACCESS

Subject: Environmental Sciences

Topic & Subtopic(s): Ecotoxicology; Ecosystem Science

Figure 2 Area of the complex velocity w .

freshwater currents over resting saline waters, in problems of flowing of Zhukovsky sheet in presence of saline retaining waters (see, for example [11-15]).

Replacing the variables $\zeta = thzt$ translates the upper half-plane ζ into the horizontal half-plane $\text{Re } t > 0$, $0 < \text{Im } t < 0.5\pi$ of the parametric plane t when the points $t_A = \infty$, $t_D = 0$, $t_C = 0.5\pi$, $t_B = \text{arch}\sqrt{b} + 0.5\pi$, $t_{A1} = \text{arch}\sqrt{a_1} + 0.5\pi$ ($1 < a_1 < b < \infty$), and the Y integrals of equation (3), which are constructed by the method [13], transforms to the form

$$Y_1 = \frac{\text{ch}t\text{ch}\nu t + \text{Csh}t\text{sh}\nu t}{\text{ch}^{1+\nu}t}, \quad (4)$$

$$Y_2 = \frac{\text{ch}t\text{sh}\nu t + \text{Csh}t\text{ch}\nu t}{\text{ch}^{1+\nu}t}$$

where C ($C \neq 1$) is an unknown fitting constant.

Taking into account relation (2) and considering that $w = d\omega/dz$, we arrive at the required dependencies

$$\frac{d\omega}{dt} = iM \frac{\sqrt{\varepsilon}(\text{ch}t\text{ch}\nu t + \text{Csh}t\text{sh}\nu t) + i(\text{ch}t\text{sh}\nu t + \text{Csh}t\text{ch}\nu t)}{\Delta(t)},$$

$$\frac{dz}{dt} = -\frac{M}{\sqrt{\varepsilon}} \frac{\text{ch}t\text{ch}\nu t + \text{Csh}t\text{sh}\nu t - i\sqrt{\varepsilon}(\text{ch}t\text{sh}\nu t + \text{Csh}t\text{ch}\nu t)}{\Delta(t)}, \quad (5)$$

$$\Delta(t) = \sqrt{[(a_1 - 1)\text{sh}^2 t + a_1][(b - 1)\text{sh}^2 t + b]},$$

where $M > 0$ is the scale constant of the simulation.

One can check that the functions (5) satisfy the boundary conditions (1) reformulated in terms of the functions $d\omega/dt$ and dz/dt , and thus are the parametric solution of the original boundary value problem. Writing representations (5) for different parts of the half-band boundary followed by integration over the whole area of the parametric variable t leads to the closure of the flow area and thus serves as a computational control.

As a result, we get expressions for the following values: the width L of the cofferdam, the water levels in the upper H and lower H_2 pools, and the length H_1 of the filter

$$\int_0^\infty X_{DA}(t)dt = L, \quad \int_{\text{arch}\sqrt{a_1}}^\infty Y_{AA_1}(t)dt = H,$$

$$\int_0^{0.5\pi} [\Phi_{DC}(t) + Y_{DC}(t)]dt + H_1 = H_2, \quad (6)$$

$$\int_0^{\text{arch}\sqrt{b}} Y_{CB}(t)dt = H_1,$$

of the required coordinates of the free surface points AD

$$x(t) = -\int_0^t X_{DA}(t)dt, \quad y(t) = H_0 - \int_0^t Y_{DA}(t)dt \quad (7)$$

and expressions for the filtration flow rate Q and the free surface exit point ordinate

$$Q = \int_0^{\text{arch}\sqrt{b}} \Psi_{CB}(t)dt, \quad H_0 = H - \int_0^\infty \Phi_{DA}(t)dt. \quad (8)$$

Other expressions for Q , H_0 and L are used to control the calculations:

$$Q = -\varepsilon L + \int_{\text{arch}\sqrt{a_1}}^\infty \Psi_{AA_1}(t)dt,$$

$$H_0 = H_2 - \int_0^{0.5\pi} \Phi_{DC}(t)dt, \quad H_0 = H_1 + \int_0^{0.5\pi} Y_{DC}(t)dt, \quad (9)$$

$$L = \int_{\text{arch}\sqrt{b}}^{\text{arch}\sqrt{a_1}} X_{BA_1}(t)dt,$$

as well as the expression

$$\int_0^\infty \Phi_{DA}(t)dt - \int_0^{0.5\pi} \Phi_{DC}(t)dt - \int_{\text{arch}\sqrt{b}}^{\text{arch}\sqrt{a_1}} \Phi_{BA_1}(t)dt. \quad (10)$$

directly derived from the boundary conditions (1).

In formulas (5) - (10), the integrand functions are expressions of the right-hand sides of equations (3) on the corresponding parts of the contour of the auxiliary region t .

Limit cases.

- At $L \rightarrow \infty$, i.e. at the junction of points A_1 and A , in plane t , i.e. at $a_1 \rightarrow 1$ ($\text{arch } a_1 = \infty$) the cofferdam degenerates into a semi-infinite left-handed unconfined formation. Thus, the exact solution of groundwater flow to the imperfect gallery, studied earlier [9], is obtained.

At $\varepsilon \rightarrow 0$, i.e. at small values of evaporation intensity the results of works [7,8] are obtained.

Representations (5) - (10) contain four unknown constants M , C , a_1 and b . The parameters a_1 , b ($1 < a_1 < b < \infty$),

C (C1) ≠ are determined from equations (6) for the given values H_1 , H_2 ($H_1 \leq H_2 < H$) and L ; the simulation constant M is found from the second equation (6) fixing the water level H in the headwater of the cofferdam. After determination of the unknown constants the filtration flow rate Q and the ordinate H_0 of the outlet point of the depression curve on the impermeable section DC by formulas (8) and coordinates of points of free surface DA by formulas (7) are sequentially found.

On figure 1 the picture of flow, calculated at $\varepsilon = 0.5$, $H = 3$, $L = 2$, $H_1 = 1.0$, $H_2 = 1.4$ (the base case [9]) is shown. Results of calculations of influence of determining physical parameters ε , H , H_1 , H_2 and L on values Q and H_0 are given in tables 1, 2. On figure 3 and 4 dependences of flow Q (curves 1) and ordinate H_0 of a point of an exit of a depression curve on a screen (curves 2) from parameters H_1 and H_2 are submitted. Analysis of calculations of these tables and graphs allows us to draw the following conclusions:

- A decrease in the evaporation intensity ε and an increase in the head H accompany an increase in the flow rate Q and the ordinate H_0 of the exit point of the depression curve on the screen;
- Decrease of the screen depth H_1 and increase of the water level in the downstream H_2 are accompanied by a decrease of the flow Q and increase of the ordinate H_0 ;
- As the width of the cofferdam L increases, the flow rate Q and the ordinate H_0 of the free surface exit point to the screen decrease.

From table 2 and figures 3, 4 follows that decrease of parameters H_1 and H_2 by 1.5 and 1.3 times, respectively, leads to change of Q value by 16.8 % (at fixing H_1) and 12 % (at fixing H_2). The marked regularities lead to the conclusion that the cofferdam flow rate depends on the value of level

lowering to a somewhat greater extent than on the filter length (or on imperfection of a well or a well).

For the base case, almost all the dependences of Q and H_0 on the parameters ε , H , H_1 , H_2 , and L are close to linear.

Comparison of the exact values obtained for the base case $Q = 1.155$ and $H_0 = 1.776$ with the approximate values $Q = 1.141$ and $H_0 = 1.768$ for the base case [9] where the flow area to the left was limited by the equipotential shows that the relative error of the calculations is rather small and amounts to only 0.5 and 1.3% respectively.

Comparison of exact value of flow $Q = 1.16$, obtained for basic variant, with approximate value $Q = 1.26$, which follows at application of generalized formula of I.A. Charnyi [1,p.267] for usual rectangular cofferdam (without screen) in presence of evaporation

$$Q = -\frac{\varepsilon L}{2} + \frac{H^2 - H_2^2}{2L},$$

leads to an error of 8.3%.

For comparison with data $H = 1$, $H_1 = 0.05$, $H_2 = 0.238$, $L = 4$ work [7] at absence of evaporation, i.e. at $\varepsilon = 0$, for which values $Q = 0.118$, $H_0 = 0.29$ are received by the approximate formulas in semi-inverse formulation, we consider variant $\varepsilon = 0.1$, $H = 1$, $H_1 = 0.05$, $H_2 = 0.238$, $L = 4$, leading to exact values $Q = 0.42$, $H_0 = 0.75$. Here, relative calculation errors are 71 and 61%, respectively. Consequently, just as in [9], evaporation significantly affects the flow pattern.

A technique for constructing an exact analytical solution of the problem of fluid motion in a rectangular cofferdam with a screen in the presence of evaporation from the free surface of groundwater has been developed. The investigation shows that the filtration scheme in a rectangular cofferdam with impermeable screen, firstly, is very similar to the previously considered [9] problem about

Table 1: Results of calculations of Q and H_0 values when varying ε , H and L .

ε	Q	H_0	H	Q	H_0	L	Q	H_0
0.1	1.3937	2.3003	2.5	0.5624	1.4074	1.5	1.6261	2.1424
0.2	1.3423	2.1544	3.0	1.1554	1.7750	1.7	1.8970	1.3492
0.3	1.2839	2.0179	3.5	1.5715	2.0883	2.0	1.1554	1.7755
0.4	1.2218	1.8920	4.5	2.6811	3.3097	2.5	0.7585	1.5045
0.5	1.1554	1.7755	5.0	2.9726	3.7528	2.9	0.4863	1.3727

Table 2: Results of calculations of Q and H_0 values when varying H_1 and H_2 .

H_1	Q	H_0	H_2	Q	H_0
0.9	1.1120	1.8292	1.09	1.3965	1.5533
1.0	1.1554	1.7755	1.19	1.3627	1.5775
1.1	1.1928	1.7161	1.29	1.2425	1.7051
1.2	1.2235	1.6494	1.39	1.1598	1.7695
1.3	1.2460	1.5728	1.40	1.1634	1.7694

Figure 3 Dependence of the cofferdam flow rate Q and the ordinate H_0 of the free surface outlet point H_0 on the filter length H_1 .

Figure 4 Dependence of cofferdam flow rate Q and the ordinate H_0 of the free surface outlet point on the water level in the downstream reservoir H_2 .

movement of ground waters to the imperfect gallery, one of them being limiting with respect to the other. Secondly, the flow pattern near the screen essentially depends not only on the filter size, but also on the presence of evaporation, which strongly affects the flow rate value and the ordinate of the outlet point of the depression curve on the screen. The obtained results, announced in [16], give some idea (at least qualitatively) about possible dependence of motion characteristics when considering the filtration problem already to imperfect well or tubular well.

References

1. Polubarinova-Kochina PY. Theory of groundwater movement. Moscow: Gostekhizdat; 1952. p. 677. 2nd Ed. Moscow: Nauka; 1977. p. 664.
2. Numerov SN. Theory of motion of liquids and gases in a non-deformable porous medium. Moscow: Gostekhizdat; 1953. p. 616.
3. Polubarinova-Kochina PY. Development of Studies on Filtration Theory in the USSR (1917-1967). Ed. Moscow: Nauka; 1967. p. 545.
4. Mikhailov GK, Nikolaevsky VN. In: Mechanics in the USSR for 50 years. Moscow: Nauka; 1970. V(2). p. 585-648.
5. Polubarinova-Kochina PYa, Pryazhinskaya VG, Emikh VN. Mathematical methods in matters of irrigation. Moscow: Nauka; 1969. p. 414.
6. Kochina PYa. Selected Works. Hydrodynamics and Filtration Theory. Moscow: Nauka; 1991. p. 351.
7. Pryazhinskaya VG. Groundwater motion in a rectangular cofferdam with an impermeable vertical wall. Izv Mechanics and Engineering. 1964. №4. p. 41-49.
8. Polubarinova-Kochina PYa, Postnov VA, Emikh N, Emikh VN. The steady-state filtration to an imperfect gallery in an unpressurized reservoir. Izv MZHG. 1967. № 4. p. 97-100.
9. Bereslavsky EN, Dudina LM. On motion of ground waters to an imperfect gallery in the presence of evaporation from a free surface. Vestnik S.-Petersburg. Series 1. Mathematics. Mechanics. Astronomy. 2017. №4. T. 4(62). p. 654-663.
10. Bereslavsky EN, Kochina PYa. On some Fuchs class equations in hydro- and aeromechanics. Izvestiya RAN MJG. 1992. №5. p. 3-7.
11. Kochina PYa, Bereslavsky EN, Kochina NN. Analytic theory of Fuchs class linear differential equations and some problems of underground hydromechanics. Preprint No. 567. M, Institute of Mechanics Problems. MOSCOW : INSTITUTE FOR PROBLEMS OF MECHANICS OF THE RUSSIAN ACADEMY OF SCIENCES, 1996. Part 1. p. 122.
12. Bereslavsky EN, Kochina PY. On Fuchs class differential equations encountered in some problems of fluid and gas mechanics. Izv MJG. 1997. №5. C.9-17.
13. Bereslavsky EN. On the Integration in Closed Form of Some Fuchs Class Differential Equations Occurring in Hydro-Paeromechanics. DAN. 2009. T. 428. №4. p. 439-443.
14. Golubev VV. Lectures on the analytic theory of differential equations. Moscow: L. Gostekhizdat; 1950. p. 436.
15. Bereslavsky EN, Likhacheva NV. Mathematical modeling of filtration from canals and sprinklers. Vestnik S-Petersburg. Un-tat. Series 10. Appl Inform Proce management. 2012;V(3). p. 10-22.
16. Bereslavsky EN, Dalinger JM, Dudina LM. Modeling of groundwater motion a screen. Reports of RAS. Physics. Technical Sciences.2020. T. 490. № 1. C. 57-62.

How to cite this article: Bereslavsky EN. Modeling the Movement of Groundwater V_0D in a Rectangular Jumper with a Screen. J Biomed Res Environ Sci. 2021 Feb 23; 2(2): 069-073. doi: 10.37871/jbres1191, Article ID: JBRES1191