KLUNK, Marcos Antônio^{1*}; DASGUPTA, Sudipta²; DAS, Mohuli²; SHAH, Zeban³

¹ University of Vale do Rio dos Sinos, Graduation Program in Mechanical Engineering, Brazil

² Department of Earth Sciences, IIT Bombay, India Federation

³ Institute of Chemistry, Federal University of Rio Grande do Sul (UFRGS), Brazil

* Correspondence author
e-mail: marcosak@edu.unisinos.br

Received 12 May 2018; received in revised form 30 June 2018; accepted 14 August 2018

ABSTRACT

Carbon capture and storage (CCS) has been observed as an alternative measure to mitigate emissions from greenhouse gases. CCS systems separate CO₂ during the process of converting fuel and transport to the facilities where they are stored, e.g., under geological formation conditions. Capture and sequestration technologies are now widely used in different industries. CO₂ capture is currently a costly and energy-consuming technology. The costs obviously depend on the size of the plant and the type of fuel used. Generally, capture systems are categorized into three categories: pre-combustion, post-combustion, and oxy-fuel combustion. The saline aquifer, depleted oil, and gas fields are large-capacity storage sinks. The coalbeds also provide as a substitute to geological storage. One of the main advantages of coal storage is renewable methane fuel and coal desulfurization. The studied coal reserves are located in Candiota, State of Rio Grande do Sul, Brazil. These are the largest coal deposits in the country, with a reserve of 1 billion tons. This work will represent a study on CO₂ storage in Candiota coalbed system. The use of a synthetic CO₂ cylinder with a flow of 0.2 L /min varies the time of contact with the coalbed. The results from the volatile matter increase by 11%. The results of the ultimate analysis exhibited an 8% increase for carbon and oxygen after 60 minutes of CO₂ flow in the coalbed. On the other hand, there was a reduction of 32% for sulfur. The resultant phenomena occur due to the adsorption capacity of CO₂, where the compounds are released from the pores of coal.

Keywords: *Greenhouse Gases, Climate Change, Candiota Coalfield, Carbon Capture, and Storage.*

1. INTRODUCTION

The burning of fossil fuels emits a substantial amount of greenhouse gases (GHG), where carbon dioxide (CO₂) is most abundant (Chen *et al.*, 2017). The emission of this gas into the atmosphere causes the natural phenomenon of heat retention on Earth's surface to be aggravated, causing climatic changes (Fernández-Sánchez *et al.*, 2015). These changes in climate, in turn, activate a set of changes related to the operation of ecosystems (Kim and Kim, 2016; IPCC, 2014). As a procedure of mitigating environmental impacts, the geological, oceanic and biological storage of CO₂ are technological alternatives that have been discovered. Geological storage is the process which follows the capture and transport of CO₂ (Man *et al.*, 2018).

Capture and transport take place from the

source to reservoirs which are capable of retaining CO₂ for hundreds or thousands of years. This technology system is called Carbon Capture and Storage (CCS). Carbon capture and storage systems occur with separation of CO₂ during the process of energetic conversion of fossil fuel to different geological formations (IPCC, 2014). The reservoirs currently used are depleted oil and gas fields, saline aquifers and Carboniferous formations (Agartan *et al.*, 2018; Hosa *et al.*, 2011; Qi *et al.*, 2009; Hassanzadeh *et al.*, 2008). The use of carboniferous formations as a reservoir occurs when the coal is no longer operable and the extraction of methane (CH₄) adsorbed in the pores of the geological formation and desulfurization of the coal with high SO₂ contents due to the presence of pyrite is desired (Shogenov *et al.*, 2017; Xia and Xie, 2017; Borah and Baruah, 2001).

In order to achieve the storage of large volumes of CO₂, the geological formation requires to have adequate permeability (Jiskani *et al.*,

2018; Marcisz *et al.*, 2018). The logistics of CO₂ capture, transport, and storage are not trivial, and risks of leakage are involved at all stages (Deng *et al.*, 2014; Keller *et al.*, 2008). The characteristics of the reservoir and possible escape mechanisms of CO₂ must be carefully monitored to avoid catastrophe in the environment (Deng *et al.*, 2014).

This particular work aims to study a CO₂ adsorption system in coalbed in order to properly capture and store CO₂ in order to sustain for a long inactive period of time. The coals of Candiota, State of Rio Grande do Sul, Brazil, were utilized for this purpose. In a system simulating coalbeds, CO₂ could be stored. This is evident in the results of proximate and ultimate analyses where there was an increase of 11% in the volatile matter and a decrease of 32% in sulfur contents.

2. CO₂ CAPTURE, TRANSPORTATION AND STORAGE TECHNOLOGIES

Carbon is an essential chemical element of life. It occurs in nature as graphite and/or diamond, it is also associated with other atoms such as carbon dioxide, coal, methane, etc. (Reiter and Lindorfer, 2015). The development of modern society is based on activities which provoke an increase in carbon. In this context, we can mention: soil use (agriculture, forest burning); ii) industrial activities (petrochemical); iii) the burning of fossil fuels (coal, oil and natural gas) for generating power (Koytsoumpa *et al.*, 2018).

As there are no natural mechanisms to convert carbon at the same rate as it is transferred, CO₂ ends up concentrating on the atmosphere. This increase in CO₂ concentration causes the greenhouse effect in the atmosphere (Huaman and Lourenco, 2015). Other gases are also responsible for this disastrous effect on the atmosphere, which includes nitrous oxide (N₂O), methane (CH₄) and chlorofluorocarbons (CFC's). Among GHGs, CO₂ possesses the maximum concentration (approximately 75%) in the atmosphere (Deng *et al.*, 2014).

2.1. CO₂ capture

Generally, capture systems are classified into three categories: pre-combustion, post-combustion, and oxyfuel combustion.

2.1.1. Pre-combustion capture

The technology for pre-combustion is extensively applied for chemical, gaseous fuel (H₂ and CH₄), fertilizer, and also for power production

(Mantripragada and Rubin, 2017). In these particular cases, the fossil fuel is partially oxidized in a gasifier. CO from the derived syngas (CO and H₂) reacts with additional steam (H₂O) and is thereby converted into CO₂ and H₂ (Zheng *et al.*, 2017). The resultant CO₂ can be captured from a comparatively pure exhaust stream. H₂ can further be used as fuel, whereas, removal of CO₂ takes place before combustion. There are various advantages and disadvantages when this method is compared to conventional post-combustion carbon dioxide capture (Kanniche *et al.*, 2010). In this method, CO₂ is removed after combustion of fossil fuels, but before the expansion of flue gas in the atmospheric pressure. This method is applied to contemporary fossil fuel burning power plants, or to existing plants where re-powering is an alternative (Park *et al.*, 2015). The capture which occurs before expansion, i.e., from pressurized gas, is the standard in almost all the industrial CO₂ capture processes at the same scale as required for utility power plants.

Pre-combustion capture also has the advantage of excessive control of CO₂ emissions (90 to 95% of CO₂ is captured). It involves low technological risk and also has the possibility of becoming the most efficient method to mitigate CO₂ emissions (Ryu *et al.*, 2017).

2.1.2. Post-combustion capture

Post-combustion systems retain CO₂ capture after the burning of fossil fuel (Wu *et al.*, 2014). In this case, CO₂ is captured from flue gases at several power stations or other massive point sources. The technology is well comprehended and is presently used in distinct industrial applications, although at a different scale than required in a commercial scale power station (Moser *et al.*, 2013). Post-combustion capture is most accepted for research purpose since the existing fossil fuel power plants can be retrofitted for including CCS technology in this specific configuration (Singh, 2013). There are several methods which can be applied to capture CO₂ in post-combustion processes (Jin *et al.*, 2018). One significant method is the separation of the gases produced and emitted into the atmosphere through the absorption process (Plaza *et al.*, 2017). This includes a mass transfer between the gas (combustion gas) and liquid (solvent) phases, which exploits the differences in the gas-liquid solubility of distinct components of the treated mixture. Another post-combustion capture process is adsorption, which involves utilization of a solid surface, such as activated carbon or zeolites to adsorb CO₂ present in a

particular gas mixture (Moser *et al.*, 2013). Separation of CO₂ by membranes is another significant process associated with capture. The membranes cannot separate the CO₂ with the required efficiency in only one step. It is, therefore, necessary to repeat the process until a suitable degree of purity has been achieved. This is responsible for increasing the complexity associated with increasing energy consumption and costs in the system (Jin *et al.*, 2018).

2.1.3. Oxy-fuel combustion

In oxy-fuel combustion method, the fuel is burned in oxygen instead of air (Dwivedi *et al.*, 2018). The cooled flue gas is re-circulated and then injected into the combustion chamber to limit the resultant flame temperature up to the levels of conventional combustion (Hu *et al.*, 2018). The flue gas consists of mainly carbon dioxide and water vapor, where the latter is condensed through cooling (Leffler *et al.*, 2017). The outcome of the process is an almost pure carbon dioxide stream, which can be conveyed to the sequestration site and stored. Power plant processes associated with oxy-fuel combustion are frequently referred to as "zero emission" cycles. In these processes, the preserved CO₂ does not occur as a fraction removed from the flue gas stream (like in pre- and post-combustion capture methods), but the overall flue gas stream itself (Carrasco-Maldonado *et al.*, 2017). A certain fraction of the generated CO₂ during combustion will inevitably end up as a constituent of the condensed water. The water has to be treated or disposed of appropriately for authorization of the "zero emission" label. The oxy-fuel combustion technique is promising, but the initial step of air separation requires a lot of energy (Chen, 2018).

2.2. CO₂ transport

CO₂ transport is the least complicated process in the CCS chain, as it is an existing technology for which relevant costs can be estimated (Goldthorpe and Ahmad, 2017). The principal complication with CO₂ transport is that this compound behaves in different ways when subjected to variations in pressure and temperature (Jakobsen *et al.*, 2017). Thus, the transfer of CO₂ has to be carefully managed to prevent solidification and occurrence of blockages. There are two effective methods for transporting massive volumes of CO₂: pipeline transport and ship transport. Transportation is also possible through trucks with CO₂, usually in liquid form. However, these two solutions are not

feasible for substantial quantities (Engel and Kathe, 2017).

2.3. CO₂ storage

In several places of the world, CO₂ is trapped in carboniferous formations (He *et al.*, 2011). The idea of geological storage further seeks to reproduce such natural phenomenon which attests to the great potential that geological formations have for storage of gases (Shogenov *et al.*, 2017).

Several aspects need to be considered when it comes to CO₂ storage: (i) the storage period should be extensive, preferably hundreds or thousands of years; (ii) the cost of storage, including transport from the place of capture, injection, and monitoring, should be minimized; (iii) the applied methods may not violate any national or international law or regulation; (iv) the environmental impacts need to be carefully considered, and their minimization techniques should be assessed; (v) the probability of occurrence of accidents should be practically null (Zhao *et al.*, 2016). Coal is the sedimentary rock which results from the decomposition of organic matter and is generally found in veins or layers (Maphala and Wagner, 2012).

If CO₂ is injected into coal deposits, CO₂ will release the trapped CH₄ therein and fill the voids where it was located. Based on laboratory studies, it is estimated that a volume of CO₂ can be stored twice as large as that of CH₄ initially adsorbed (Chai and Shimada, 2011). Since this technique leads to an improvement in the yield of a deposit in terms of collected natural gas, it became popular as Enhanced Coalbed Methane Recovery (ECBMR) (Fan *et al.*, 2018). ECBMR is a more efficient method for capturing more than 90% gas than the traditional methods for CH₄ collection from coal which captures about 50% of the gas (Vishal *et al.*, 2018; Ma *et al.*, 2017).

3.2. MATERIALS AND METHODS

3.1. Coal geology

Coal is a biogenic sedimentary rock, which is easily combustible and is brown to black in color. It is derived from the decomposition of accumulated debris in a basin from the atmosphere, on which sediments were deposited (Wang *et al.*, 2018). The formation consisting of the coal goes through an initial phase of slow biodegradation of the accumulated material by anaerobic microorganisms (Fuertez *et al.*, 2017). Both biochemical and thermodynamic processes

occur with the successive deposition of inert gases on this organic sludge (Davis and Gerlach, 2018). Dehydration is accompanied by impoverishment in the volatile matter, along with loss of oxygen and hydrogen. The resulting mass, enriched in carbon, decreases in volume, and increases in density due to the combined action of pressure and temperature (Wang *et al.*, 2018).

The constituents of coal which can be distinguished microscopically are called macerals. The term "maceral" is analogous to the use of the term mineral while speaking of igneous or metamorphic rocks. However, unlike minerals, macerals have no characteristic crystalline form and are not constant in their chemical composition and physical properties. One of the most common macerals is vitrinite, which is derived from woody materials (Zieger *et al.*, 2018). Vitrinite is considered to be the most important maceral due to its extraordinary adsorption power of CO₂, causing a greater increase of volume of the same and, consequently reducing the permeability of coal (Zieger *et al.*, 2018).

The proportion in which the different macerals present themselves, as well as the level of their maturation, have consequences on the chemical, physical, and mechanical properties of the coal. Therefore, there occurred a requirement to classify the various types of coal. One of the most widely used concepts is the rank of coal. This is an important feature as it is widely used by coal-burning industries to infer the calorific value of the fuel (Fuertez *et al.*, 2017).

The degree of coal is estimated by a specific energy, evaluation of the water content, percentage of volatile matter or reflectance of vitrinite. A single parameter is not sufficient to classify the different grades of coal, and however, sometimes more parameters are used for one rank than others. The low-rank coals are generally characterized by the heat energy value and the water content, whereas the high-rank coals are distinguished using the reflectance values of vitrinite, the presence of fixed carbon and the percentages of volatile matter (Zieger *et al.*, 2018).

3.2. Location of the study area

The study area is located in the city of Candiota, at the southern end of the State of Rio Grande do Sul, Brazil. The Presidente Médici thermoelectric power plant belongs to Eletrobrás - Companhia de Geração Térmica de Energia Elétrica SA (CGTEE) and is provided by Companhia Riograndense de Mineração (CRM), which has reserves of 1,419.41x10⁶ tons (CRM,

2010) and a production of 1,600,000 tons per year of ore to meet the needs of the plant.

3.3. Preparation of coal samples and CO₂ injection system

The coal samples were inserted into a system (Figure 1) and connected to CO₂ gas (from Martins PRAXAIR INC. WHITE™) with a concentration of 5000 ppm packaged in the cylinder, with a purity of 99.95%. For the experiments, a flux of 0.2 L/min was used with contact intervals of 5, 10, 15, 30, 45, and 60 minutes in the coalbed. Proximate analysis and ultimate analysis were measured before the tests and after the contact intervals between the CO₂-Coal interactions.

4. RESULTS AND DISCUSSION

The results of proximate analysis (Table 1) reveal that CO₂ injected into the coal changes its properties. The moisture and ashes underwent an increase of 5% after 60 minutes of the reaction. Also, an overall increase of 11% was observed for the volatile matter and fixed carbon. The ability of coal to adhere CO₂ releasing hydrocarbons manifests such behavior. The greater amount of CO₂ in contact with the charcoal bed produces greater ash content. The volatile matter has increased in content as a consequence of the increased amount of CO₂.

The ultimate analysis (table 1) results in an 8% increase for carbon and oxygen after 60 minutes of CO₂ flow in the coalbed. For sulfur, a decrease of 32% has been observed. This is due to the displacement capacity of sulfur in porous layers of coal. There was coal desulfurization with the increase of CO₂ flow during 60 minutes of contact.

5. CONCLUSIONS

The present study addressed the characteristics of the CO₂ capture and storage technique. In this context, a CO₂ injection scheme was presented in coalbed, and the physicochemical properties were verified after the experiments. It was established that according to the time of contact with the CO₂ flow, there is an increment of 5% of moisture and ash content and 6% of carbon and oxygen, in the coal. Subsequently, for the volatile matter and fixed carbon, there is a decrease of 7 and 11% respectively. The desulfurization caused by the injection of CO₂ into the coal where there was a 32% decrease is another interesting discovery.

Therefore, the results indicate that the proposed coalbed system was efficient in the adsorption of CO₂ and might act as an alternative for the removal of SO₂ in the coal.

6. ACKNOWLEDGMENTS

The authors acknowledge the Brazilian agencies CNPq (National Council of Technological and Scientific Development – Brasília, DF, Brazil), CAPES (Coordination for the Improvement of Higher Education Personnel) for the research funding, and the generous assistance of all the people from the company who granted us access to their database and perception information.

7. REFERENCES

1. Chen, J., Zhao, F., Liu, Z., Ou, X., & Hao, H. Greenhouse gas emissions from road construction in China: A province-level analysis. *Journal of Cleaner Production*, **2017**, 168, 1039–1047.
2. Fernández-Sánchez, G., Berzosa, Á., Barandica, J. M., Cornejo, E., & Serrano, J. M. Opportunities for GHG emissions reduction in road projects: a comparative evaluation of emissions scenarios using CO₂ NSTRUCT. *Journal of Cleaner Production*, **2015**, 104, 156–167.
3. Kim, M.-K., & Kim, T. Estimating the impact of regional greenhouse gas initiative on coal to gas switching using synthetic control methods. *Energy Economics*, **2016**, 59, 328–335.
4. IPCC (Intergovernmental Panel on Climate Change), Physical Science Basis. Working Group I Contribution to the Fifth Assessment Report of the Intergovernmental Panel on Climate Change Cambridge University Press, Cambridge (United Kingdom) and New York (USA), **2014**.
5. Man, Y., Han, Y., Hu, Y., Yang, S., & Yang, S. Synthetic natural gas as an alternative to coal for power generation in China: Life cycle analysis of haze pollution, greenhouse gas emission, and resource consumption. *Journal of Cleaner Production*, **2018**, 172, 2503–2512.
6. Agartan, E., Gaddipati, M., Yip, Y., Savage, B., & Ozgen, C. CO₂ storage in depleted oil and gas fields in the Gulf of Mexico. *International Journal of Greenhouse Gas Control*, **2018**, 72, 38–48.
7. Hosa, A., Esentia, M., Stewart, J., & Haszeldine, S. Injection of CO₂ into saline formations: Benchmarking worldwide projects. *Chemical Engineering Research and Design*, **2011**, 89(9), 1855–1864.
8. Qi, R., Laforce, T., & Blunt, M. Design of carbon dioxide storage in aquifers. *International Journal of Greenhouse Gas Control*, **2009**, 3(2), 195–205.
9. Hassanzadeh, H., Pooladi-Darvish, M., Elsharkawy, A. M., Keith, D. W., & Leonenko, Y. Predicting PVT data for CO₂–brine mixtures for black-oil simulation of CO₂ geological storage. *International Journal of Greenhouse Gas Control*, **2008**, 2(1), 65–77.
10. Shogenov, K., Shogenova, A., Gei, D., & Forlin, E. Synergy of CO₂ Storage and Oil Recovery in Different Geological Formations: Case Study in the Baltic Sea. *Energy Procedia*, **2017**, 114, 7047–7054.
11. Xia, W., & Xie, G. A technological review of developments in chemical-related desulfurization of coal in the past decade. *International Journal of Mineral Processing*, **2017**, 161, 65–71.
12. Borah, D., & Baruah, M. K. Kinetic and thermodynamic studies on oxidative desulphurisation of organic sulphur from Indian coal at 50–150°C. *Fuel Processing Technology*, **2001**, 72(2), 83–101.
13. Jiskani, I. M., Siddiqui, F. I., & Pathan, A. G. Integrated 3D geological modeling of Sonda-Jherruck coal field, Pakistan. *Journal of Sustainable Mining*, **2018**, 17(3), 111–119.
14. Marcisz, M., Probiez, K., & Ostrowska-Łach, M. 3D representation of geological observations in underground mine workings of the Upper Silesian Coal Basin. *Journal of Sustainable Mining*, **2018**, 17(1), 34–39.
15. Deng, H., Bielicki, J. M., Oppenheimer, M., Fitts, J. P., & Peters, C. A. Policy implications of Monetized Leakage Risk from Geologic CO₂ Storage Reservoirs. *Energy Procedia*, **2014**, 63, 6852–6863.
16. Keller, K., McInerney, D., & Bradford, D. F. Carbon dioxide sequestration: how much and when? *Climatic Change*, **2008**, 88(3-4), 267–291.
17. Reiter, G., & Lindorfer, J. Evaluating CO₂ sources for power-to-gas applications – A case study for Austria. *Journal of CO₂ Utilization*, **2015**, 10, 40–49.
18. Koytsoumpa, E. I., Bergins, C., & Kakaras, E. The CO₂ economy: Review of CO₂

- capture and reuse technologies. The Journal of Supercritical Fluids, **2018**, 132, 3–16.
19. Huaman, R. N. E., & Lourenco, S. A. Review on: CO₂ Capture Technology on Fossil Fuel Power Plant. Journal of Fundamentals of Renewable Energy and Applications, **2015**, 5 (3), 164–175.
 20. Wu, X., Yu, Y., Qin, Z., & Zhang, Z. The Advances of Post-combustion CO₂ Capture with Chemical Solvents: Review and Guidelines. Energy Procedia, **2014**, 63, 1339–1346.
 21. Moser, P., Schmidt, S., Wallus, S., Ginsberg, T., Sieder, G., Clausen, I. Mihailowitsch, D. Enhancement and Long-Term Testing of Optimised Post-Combustion Capture Technology – Results of the Second Phase of the Testing Programme at the Niederaussem Pilot Plant. Energy Procedia, **2013**, 37, 2377–2388.
 22. Singh, P. Post combustion CO₂ capture technology: current status and future directions IEA Greenhouse Gas R&D Programme, Conference on Clean Coal and Carbon Capture and Storage Technologies, 3rd December **2013**, Trichy, India.
 23. Jin, H., Liu, P., & Li, Z. Energy-efficient process intensification for post-combustion CO₂ capture: A modeling approach. Energy, **2018**, 158, 471–483.
 24. Plaza, M. G., Durán, I., Rubiera, F., & Pevida, C. Adsorption-based Process Modelling for Post-combustion CO₂ Capture. Energy Procedia, **2017**, 114, 2353–2361.
 25. Mantripragada, H. C., & Rubin, E. S. Chemical Looping for Pre-combustion and Post-combustion CO₂ Capture. Energy Procedia, **2017**, 114, 6403–6410.
 26. Zheng, J., Zhang, P., & Linga, P. Semiclathrate hydrate process for pre-combustion capture of CO₂ at near ambient temperatures. Applied Energy, **2017**, 194, 267–278.
 27. Kanniche, M., Gros-Bonnivard, R., Jaud, P., Valle-Marcos, J., Amann, J.-M., & Bouallou, C. Pre-combustion, post-combustion and oxy-combustion in thermal power plant for CO₂ capture. Applied Thermal Engineering, **2010**, 30(1), 53–62.
 28. Park, S. H., Lee, S. J., Lee, J. W., Chun, S. N., & Lee, J. B. The quantitative evaluation of two-stage pre-combustion CO₂ capture processes using the physical solvents with various design parameters. Energy, **2015**, 81, 47–55.
 29. Ryu, H.-J., Bae, D.-H., Moon, J.-H., Jo, S.-H., & Jin, G.-T. Total Integrated Operation of Gasifier, Hot Gas Desulfurizer, and SEWGS Process for Pre-combustion CO₂ Capture Using Real Syngas from Coal. Energy Procedia, **2017**, 114, 2128–2135.
 30. Dwivedi, A., Gudi, R., & Biswas, P. Oxy-fuel combustion based enhancement of the tri-reforming coupled methanol production process for CO₂ valorization. Journal of CO₂ Utilization, **2018**, 24, 376–385.
 31. Hu, F., Li, P., Guo, J., Wang, K., Liu, Z., & Zheng, C. Evaluation, development, and validation of a new reduced mechanism for methane oxy-fuel combustion. International Journal of Greenhouse Gas Control, **2018**, 78, 327–340.
 32. Leffler, T., Brackmann, C., Berg, M., Aldén, M., & Li, Z. Online Alkali Measurement during Oxy-fuel Combustion. Energy Procedia, **2017**, 120, 365–372.
 33. Carrasco-Maldonado, F., Bakken, J., Ditaranto, M., Haugen, N. E. L., Langørgen, Ø., Grathwohl, S., & Maier, J. Oxy-fuel burner investigations for CO₂ capture in cement plants. Energy Procedia, **2017**, 120, 120–125.
 34. Chen, S. Fundamentals of Oxy-fuel Combustion. Oxy-Fuel Combustion, **2018**, 13–30.
 35. Goldthorpe, W., & Ahmad, S. Policy Innovation for Offshore CO₂ Transport and Storage Deployment. Energy Procedia, **2017**, 114, 7540–7549.
 36. Jakobsen, J., Bysveen, M., Vågenes, E., Eickhoff, C., Mikunda, T., Neele, F., Hanstock, D. Developing a Pilot Case and Modelling the Development of a Large European CO₂ Transport Infrastructure - The GATEWAY H2020 (Horizon 2020) Project. Energy Procedia, **2017**, 114, 6835–6843.
 37. Engel, F., & Kather, A. Conditioning of a Pipeline CO₂ Stream for Ship Transport from Various CO₂ Sources. Energy Procedia, **2017**, 114, 6741–6751.
 38. He, M., Luis, S., Rita, S., Ana, G., Euripedes, V., & Zhang, N. Risk assessment of CO₂ injection processes and storage in carboniferous formations: a review. Journal of Rock Mechanics and Geotechnical Engineering, **2011**, 3(1),

- 39–56.
39. Zhao, X., Liao, X., & He, L. The evaluation methods for CO₂ storage in coal beds, in China. *Journal of the Energy Institute*, **2016**, 89(3), 389–399.
 40. Maphala, T., & Wagner, N. J. Effects of CO₂ storage in coal on coal properties. *Energy Procedia*, **2012**, 23, 426–438.
 41. Chai, Z., & Shimada, S. CO₂ storage in coal-bearing formation. *Energy Procedia*, **2011**, 4, 3103–3111.
 42. Fan, Y., Deng, C., Zhang, X., Li, F., Wang, X., & Qiao, L. Numerical study of CO₂ - enhanced coalbed methane recovery. *International Journal of Greenhouse Gas Control*, **2018**, 76, 12–23.
 43. Vishal, V., Mahanta, B., Pradhan, S. P., Singh, T. N., & Ranjith, P. G. Simulation of CO₂ enhanced coalbed methane recovery in Jharia coalfields, India. *Energy*, **2018**, 159, 1185–1194.
 44. Ma, T., Rutqvist, J., Oldenburg, C. M., & Liu, W. Coupled thermal–hydrological–mechanical modeling of CO₂ enhanced coalbed methane recovery. *International Journal of Coal Geology*, **2017**, 179, 81–91.
 45. Wang, A., Shao, P., Lan, F., & Jin, H. Organic chemicals in coal available to microbes to produce biogenic coalbed methane: A review of current knowledge. *Journal of Natural Gas Science and Engineering*, **2018**, 60, 40–48.
 46. Fuertez, J., Nguyen, V., McLennan, J. D., Adams, D. J., Han, K.-B., & Sparks, T. D. Optimization of biogenic methane production from coal. *International Journal of Coal Geology*, **2017**, 183, 14–24.
 47. Davis, K. J., & Gerlach, R. Transition of biogenic coal-to-methane conversion from the laboratory to the field: A review of important parameters and studies. *International Journal of Coal Geology*, **2018**, 185, 33–43.
 48. Zieger, L., Littke, R., & Schwarzbauer, J. Chemical and structural changes in vitrinites and megaspores from Carboniferous coals during maturation. *International Journal of Coal Geology*, **2018**, 185, 91–102.
 49. CRM, 2010. Companhia Riograndense de Mineração. Disponível em: <<http://www.crm.rs.gov.br>>. Acesso em set de **2017**.

Figure 1. Schematic system of capture CO_2 in coalbed

Table 1: Properties of the coal before and after interaction with carbon dioxide.

Proximate analysis - Weight (%) on dry basis					
Samples	Moisture	Ash	Volatile matter	Fixed carbon	
CF	8.4	52.9	51.2	24.9	
C-5	8.7	53.4	51.7	25.7	
C-10	8.8	53.8	52.4	25.9	
C-15	8.8	54.2	52.6	26.3	
C-30	8.9	54.9	53.1	26.7	
C-45	9.1	55.3	55.9	27.5	
C-60	9.4	55.8	56.8	27.9	
Ultimate analysis - Weight (%) on wet basis					
Samples	Carbon	Hydrogen	Nitrogen	Oxygen	Sulfur
CF	25.4	4.9	0.9	14.9	2.5
C-5	25.7	5.0	0.9	15.1	2.3
C-10	26.0	5.2	0.8	15.3	2.0
C-15	26.3	5.2	0.8	15.4	1.8
C-30	26.8	5.3	0.8	15.7	1.6
C-45	26.9	5.3	0.8	15.9	1.4
C-60	27.3	5.3	0.8	16.1	1.1

The SOUTHERN BRAZILIAN JOURNAL OF CHEMISTRY (ISSN: 2674-6891; 0104-5431) is an open-access journal since 1993. Journal DOI: 10.48141/SBJCHEM. <http://www.sbjchem.com>. This text was introduced in this file in 2021 for compliance reasons.

© The Author(s)
OPEN ACCESS. This article is licensed under a Creative Commons Attribution 4.0 (CC BY 4.0) International License, which permits use, sharing, adaptation, distribution, and reproduction in any medium or format, as long as you give appropriate credit to the original author(s) and the source, provide a link to the Creative Commons license, and indicate if changes were made. The images or other third-party material in this article are included in the article's Creative Commons license unless indicated otherwise in a credit line to the material. If material is not included in the article's Creative Commons license and your intended use is not permitted by statutory regulation or exceeds the permitted use, you will need to obtain permission directly from the copyright holder. To view a copy of this license, visit <http://creativecommons.org/licenses/by/4.0/>.

CF (Coal free of CO_2 flux); C-5 (CO_2 flux in coalbed of 5 min); C-10 (CO_2 flux in coalbed of 10 min); C-15 (CO_2 flux in coalbed of 15 min); C-30 (CO_2 flux in coalbed of 30 min); C-45 (CO_2 flux in coalbed of 45 min); C-60 (CO_2 flux in coalbed of 60 min).