

NISTIR 8183

Cybersecurity Framework Manufacturing Profile

Keith Stouffer
Timothy Zimmerman
CheeYee Tang
Joshua Lubell
Jeffrey Cichonski
John McCarthy

This publication is available free of charge from:
<https://doi.org/10.6028/NIST.IR.8183>

NIST
**National Institute of
Standards and Technology**
U.S. Department of Commerce

NISTIR 8183

Cybersecurity Framework Manufacturing Profile

Keith Stouffer
Timothy Zimmerman
CheeYee Tang
*Intelligent Systems Division
Engineering Laboratory*

Joshua Lubell
*Systems Integration Division
Engineering Laboratory*

Jeffrey Cichonski
*Applied Cybersecurity Division
Information Technology Laboratory*

John McCarthy
*Dakota Consulting, Inc.
Silver Spring, Maryland*

This publication is available free of charge from:
<https://doi.org/10.6028/NIST.IR.8183>

September 2017
INCLUDES UPDATES AS OF 05-20-2019; SEE PAGE v



U.S. Department of Commerce
Wilbur L. Ross, Jr., Secretary

National Institute of Standards and Technology
Walter Copan, NIST Director and Under Secretary of Commerce for Standards and Technology

National Institute of Standards and Technology Internal Report 8183
57 pages (September 2017)

This publication is available free of charge from:
<https://doi.org/10.6028/NIST.IR.8183>

Certain commercial entities, equipment, or materials may be identified in this document in order to describe an experimental procedure or concept adequately. Such identification is not intended to imply recommendation or endorsement by NIST, nor is it intended to imply that the entities, materials, or equipment are necessarily the best available for the purpose.

There may be references in this publication to other publications currently under development by NIST in accordance with its assigned statutory responsibilities. The information in this publication, including concepts and methodologies, may be used by federal agencies even before the completion of such companion publications. Thus, until each publication is completed, current requirements, guidelines, and procedures, where they exist, remain operative. For planning and transition purposes, federal agencies may wish to closely follow the development of these new publications by NIST.

Organizations are encouraged to review all draft publications during public comment periods and provide feedback to NIST. All NIST Computer Security Division publications, other than the ones noted above, are available at <http://csrc.nist.gov/publications>.

Comments on this publication may be submitted to:

National Institute of Standards and Technology
Attn: Applied Cybersecurity Division, Information Technology Laboratory
100 Bureau Drive (Mail Stop 2000) Gaithersburg, MD 20899-2000
Electronic Mail: CSF_Manufacturing_Profile@nist.gov

All comments are subject to release under the Freedom of Information Act (FOIA).

Abstract

This document provides the Cybersecurity Framework (CSF) implementation details developed for the manufacturing environment. The “Manufacturing Profile” of the Cybersecurity Framework can be used as a roadmap for reducing cybersecurity risk for manufacturers that is aligned with manufacturing sector goals and industry best practices. This Manufacturing Profile provides a voluntary, risk-based approach for managing cybersecurity activities and reducing cyber risk to manufacturing systems. The Manufacturing Profile is meant to enhance but not replace current cybersecurity standards and industry guidelines that the manufacturer is embracing.

Keywords

Computer security; Cybersecurity Framework (CSF); distributed control systems (DCS); industrial control systems (ICS); information security; manufacturing; network security; programmable logic controllers (PLC); risk management; security controls; supervisory control and data acquisition (SCADA) systems

Acknowledgments

The authors gratefully acknowledge and appreciate the significant contributions from individuals and organizations in the public and private sectors, whose thoughtful and constructive comments improved the overall quality, thoroughness, and usefulness of this publication. A special acknowledgement to the members of the Department of Homeland Security Industrial Control System Joint Working Group (ICSJWG) for their exceptional contributions to this publication.

Table of Contents

Executive Summary iv

1. Introduction 1

 1.1 Purpose & Scope 1

 1.2 Audience 2

 1.3 Document Structure 2

2. Overview of Manufacturing Systems 3

3. Overview of the Cybersecurity Framework 4

 3.1 Framework Core 4

4. Manufacturing Profile Development Approach 7

5. Manufacturing Business/Mission Objectives 8

 5.1 Alignment of Subcategories to Meet Mission Objectives 8

6. Manufacturing System Categorization and Risk Management 13

 6.1 Categorization Process 13

 6.2 Profile’s Hierarchical Supporting Structure 15

 6.3 Risk Management 15

7. Manufacturing Profile Subcategory Guidance 16

Appendix A - Acronyms and Abbreviations 45

Appendix B - Glossary 46

Appendix C - References 50

This publication is available free of charge from: <https://doi.org/10.6028/NIST.IR.8183>

Executive Summary

This document provides the Cybersecurity Framework implementation details developed for the manufacturing environment. The “Manufacturing Profile” of the Cybersecurity Framework can be used as a roadmap for reducing cybersecurity risk for manufacturers that is aligned with manufacturing sector goals and industry best practices.

The Profile gives manufacturers:

- A method to identify opportunities for improving the current cybersecurity posture of the manufacturing system
- An evaluation of their ability to operate the control environment at their acceptable risk level
- A standardized approach to preparing the cybersecurity plan for ongoing assurance of the manufacturing system’s security

The Profile is built around the primary functional areas of the Cybersecurity Framework which enumerate the most basic functions of cybersecurity activities. The five primary functional areas are: Identify, Protect, Detect, Respond, and Recover. There are 98 distinct security objectives within the primary functional areas. These 98 objectives comprise a starting point from which to develop a manufacturer-specific or sector-specific Profile at the defined risk levels of Low, Moderate and High.

This Manufacturing “Target” Profile focuses on desired cybersecurity outcomes and can be used as a roadmap to identify opportunities for improving the current cybersecurity posture of the manufacturing system. The Manufacturing Profile provides a prioritization of security activities to meet specific business/mission goals. Relevant and actionable security practices that can be implemented to support key business/mission goals are then identified.

This Manufacturing Profile provides a voluntary, risk-based approach for managing cybersecurity activities and reducing cyber risk to manufacturing systems. The Manufacturing Profile is meant to enhance but not replace current cybersecurity standards and industry guidelines that the manufacturer is embracing.

Errata

This table contains changes that have been incorporated into NISTIR 8183. Errata updates can include corrections, clarifications, or other minor changes in the publication that are either *editorial* or *substantive* in nature.

DATE	TYPE	CHANGE	PAGE
05-20-2019	Editorial	Corrected contact information to indicate "Applied Cybersecurity Division."	i
05-20-2019	Editorial	General formatting	All
05-20-2019	Substantive	Changed "\$1000" to "Tens of thousands" in Table 7	14
05-20-2019	Substantive	Changed "\$100,000" to "Hundreds of thousands" in Table 7	14
05-20-2019	Substantive	Changed "Minutes" to "Hours" in Table 7	14
05-20-2019	Substantive	Deleted "Military Contractors" in Table 8	14
05-20-2019	Substantive	Deleted "Address the security of protected information in its third-party relationships." from ID.AM-5.	17
05-20-2019	Substantive	Deleted "and devices" from PR.AC-1 Low security level and Added "Establish and manage identification mechanisms and credentials for users and devices of the manufacturing system." to the PR.AC-1 Moderate security level.	22
05-20-2019	Substantive	Changed "Protect network integrity of the manufacturing system, incorporating network segregation where appropriate." to "Protect network integrity of the manufacturing system, incorporating network segmentation and segregation where appropriate." in PR.AC-5 Low security level.	24
05-20-2019	Substantive	Moved "Protect the manufacturing system against, or limit the effects of, denial of service attacks." from the PR.DS-4 Low security level to the PR.DS-4 Moderate and High security levels.	26
05-20-2019	Substantive	Moved "Heighten system monitoring activity whenever there is an indication of increased risk to manufacturing operations and assets." from the PR.DS-5 Low security to the PR.DS-5 Moderate and High security levels.	26
05-20-2019	Substantive	Deleted "Manufacturing systems are often connected to business systems or interconnected. Any single system can be an attack vector for all systems. It is therefore necessary to provide a uniform defense encompassing all baselines." from PR.IP-8.	31
05-20-2019	Substantive	Changed "Test response and recovery plans to determine the effectiveness of the plans, and the readiness to execute the plans." to "Review response and recovery plans to determine the effectiveness of the plans, and the readiness to execute the plans." in PR.IP-10 Low security level.	31
05-20-2019	Substantive	Added "Test response and recovery plans to determine the effectiveness of the plans, and the readiness to execute the plans." to PR.IP-10 Moderate and High security level.	31
05-20-2019	Substantive	Moved "Ensure that audit processing failures on the manufacturing system generate alerts and trigger defined responses." from PR.PT-1 Low security level to the PR.PT-1 Moderate security level.	33
05-20-2019	Substantive	Deleted "technical" from PR.PT-2 Low security level	34
05-20-2019	Substantive	Deleted "Employ technical safeguards to control access to the manufacturing system and assets." From PR.PT-3 Low security level and added "Configure the manufacturing system to provide only essential capabilities." to PR.PT-3 Low security level.	34
05-20-2019	Substantive	Changed "attacks" to "defined cybersecurity events" in DE.CM-1	36
05-20-2019	Substantive	Moved "Manage for false positives during malicious code detection and eradication." from DE.CM-4 Low security level to DE.CM-4 Moderate and High security level.	37
05-20-2019	Substantive	Changed "attacks" to "defined cybersecurity events" in DE.CM-6.	37
05-20-2019	Substantive	Moved "Deploy monitoring devices strategically within the manufacturing system to collect essential information to detect specific events of interest." from DE.CM-7 Low security to DE.CM-7 Moderate and High security level.	38

1. Introduction

The Executive Order 13636, “Improving Critical Infrastructure Cybersecurity,” [1] directed the development of the voluntary Cybersecurity Framework that provides a prioritized, flexible, repeatable, performance-based, and cost-effective approach to manage cybersecurity risk [1] for those processes, information, and systems directly involved in the delivery of critical infrastructure services.

The Cybersecurity Framework is a voluntary risk-based assemblage of industry standards and best practices designed to help organizations manage cybersecurity risks [2]. The Framework, created through collaboration between government and the private sector, uses a common language to address and manage cybersecurity risk in a cost-effective way based on business needs without imposing additional regulatory requirements.

The Profile defines specific cybersecurity activities and outcomes for the protection of the manufacturing system, its components, facility, and environment. Through use of the Profile, the manufacturer can align cybersecurity activities with business requirements, risk tolerances, and resources. The Profile provides a manufacturing sector-specific approach to cybersecurity from standards, guidelines, and industry best practices.

1.1 Purpose & Scope

This document represents a “Target” Profile that focuses on the desired cybersecurity outcomes and provides an approach to the desired state of cybersecurity posture of the manufacturing system. It can be used to identify opportunities for improving cybersecurity posture by comparing the current state with the desired (Target) state. Creating a Target Profile is Step 5 of Section 3.2 Establishing or Improving a Cybersecurity Program of the Cybersecurity Framework, Version 1.0 [2]. The Target Profile can also be used for comparison with the current state to influence process improvement priorities for the organization. The manufacturing system’s “Current” Profile represents the outcomes from the Framework Core that are currently being achieved.

The Manufacturing “Target” Profile focuses on desired cybersecurity outcomes and can be used as a guideline to identify opportunities for improving the current cybersecurity posture of the manufacturing system. The Manufacturing Profile provides a prioritization of security activities to meet specific business/mission goals. Relevant and actionable security practices that can be implemented to support key business/mission goals are then identified.

Comparison of Profiles (e.g., the Current Profile and Target Profile) may reveal gaps to be addressed to meet cybersecurity risk management objectives. Prioritization of gap mitigation is driven by the organization’s business needs and risk management processes. This risk-based approach enables an organization to gauge resource estimates (e.g., staffing, funding) to achieve cybersecurity goals in a cost-effective, prioritized manner. The following are examples of how the Target Profile may be used:

- A manufacturer may utilize the Target Profile to express cybersecurity risk management requirements to an external service provider.

- A manufacturer may express a system’s cybersecurity state through a Current Profile to report results relative to the Target Profile, or to compare with acquisition requirements.
- A critical infrastructure owner/operator, having identified an external partner upon whom that infrastructure depends, may use the Target Profile to convey required cybersecurity outcomes.
- A critical infrastructure sector may establish a baseline that can be used among its constituents as a sector-specific starting point from which to build tailored Target Profiles.

The Manufacturing Profile provides a voluntary, risk-based approach for managing cybersecurity activities and reducing cyber risk to manufacturing systems.

1.2 Audience

This document covers details specific to manufacturing systems. Readers of this document should be acquainted with operational technology, general computer security concepts, and communication protocols such as those used in networking. The intended audience is varied and includes the following:

- Control engineers, integrators, and architects who design or implement secure manufacturing systems.
- System administrators, engineers, and other information technology (IT) professionals who administer, patch, or secure manufacturing systems.
- Managers who are responsible for manufacturing systems.
- Senior management who are trying to understand implications and consequences as they justify and implement a manufacturing systems cybersecurity program to help mitigate impacts to business functionality.
- Researchers, academic institutions and analysts who are trying to understand the unique security needs of manufacturing systems.

1.3 Document Structure

The remainder of this guide is divided into the following major sections:

- Section 2 provides an overview of manufacturing systems.
- Section 3 provides an overview of the *Framework for Improving Critical Infrastructure Cybersecurity* (Cybersecurity Framework).
- Section 4 discusses the manufacturing profile development approach.
- Section 5 provides rationale for integrating cybersecurity into manufacturing Business/mission objectives.
- Section 6 discusses cyber risk management and the risk categorization of the manufacturing system.
- Section 7 provides the manufacturing implementation of the CSF subcategories.
- Appendix A— provides a list of acronyms and abbreviations used in this document.
- Appendix B— provides a glossary of terms used in this document.
- Appendix C— provides a list of references used in the development of this document.

2. Overview of Manufacturing Systems

Manufacturing is a large and diverse industrial sector. Manufacturing industries can be categorized as either *process-based*, *discrete-based*, or a combination of both [3].

Process-based manufacturing industries typically utilize two main process types:

- **Continuous Manufacturing Processes.** These processes run continuously, often with phases to make different grades of a product. Typical continuous manufacturing processes include fuel or steam flow in a power plant, petroleum in a refinery, and distillation in a chemical plant.
- **Batch Manufacturing Processes.** These processes have distinct processing steps, conducted on a quantity of material. There is a distinct start and end to a batch process with the possibility of brief steady state operations during intermediate steps. Typical batch manufacturing processes include food, beverage, and biotech manufacturing.

Discrete-based manufacturing industries typically conduct a series of operations on a product to create the distinct end product. Electronic and mechanical parts assembly and parts machining are typical examples of this type of industry. Both process-based and discrete-based industries utilize similar types of control systems, sensors, and networks. Some facilities are a hybrid of discrete and process-based manufacturing.

Manufacturing industries are usually located within a confined factory or plant-centric area. Communications in manufacturing industries are typically performed using fieldbus and local area network (LAN) technologies that are reliable and high speed. Wireless networking technologies are gaining popularity in manufacturing industries. Fieldbus includes, for example, DeviceNet, Modbus, and Controller Area Network (CAN) bus.

The Manufacturing sector of the critical infrastructure community includes public and private owners and operators, along with other entities operating in the manufacturing domain. Members of the distinct critical infrastructure sector perform functions that are supported by industrial control systems (ICS) and by information technology (IT). This reliance on technology, communication, and the interconnectivity of ICS and IT has changed and expanded the potential vulnerabilities and increased potential risk to manufacturing system operations.

3. Overview of the Cybersecurity Framework

The Profile defines specific practices to address the Framework Core. It is the next layer of detail for implementing cybersecurity best practices for each category expressed in the Framework.

3.1 Framework Core

The Framework Core is a set of cybersecurity activities and desired outcomes determined to be essential across critical infrastructure sectors [2]. The Core presents industry standards, guidelines, and practices in a manner that allows for communication of cybersecurity activities and outcomes across the organization from the executive level to the implementation/operations level. The Framework Core consists of five concurrent and continuous Functions—Identify, Protect, Detect, Respond, Recover. When considered together, these Functions provide a high-level, strategic view of the organization’s management of cybersecurity risk. The Framework Core then identifies underlying key Categories and Subcategories for each Function, and matches them with example Informative References such as existing standards, guidelines, and practices for each Subcategory [2].

The five Framework Functions can be performed concurrently and continuously to form an operational culture that addresses the dynamic cybersecurity risk.

Table 1 Cybersecurity Framework Functions and Categories

Function Unique Identifier	Function	Category Unique Identifier	Category
ID	Identify	ID.AM	Asset Management
		ID.BE	Business Environment
		ID.GV	Governance
		ID.RA	Risk Assessment
		ID.RM	Risk Management Strategy
PR	Protect	PR.AC	Access Control
		PR.AT	Awareness and Training
		PR.DS	Data Security
		PR.IP	Information Protection Processes and Procedures
		PR.MA	Maintenance
		PR.PT	Protective Technology
DE	Detect	DE.AE	Anomalies and Events
		DE.CM	Security Continuous Monitoring
		DE.DP	Detection Processes
RS	Respond	RS.RP	Response Planning
		RS.CO	Communications
		RS.AN	Analysis
		RS.MI	Mitigation
		RS.IM	Improvements
RC	Recover	RC.RP	Recovery Planning
		RC.IM	Improvements
		RC.CO	Communications

This publication is available free of charge from: <https://doi.org/10.6028/NIST.IR.8183>

The five “functions” of the Framework Core are:

Identify – Develop the organizational understanding to manage cybersecurity risk to systems, assets, data, and capabilities. The activities in the Identify Function are foundational for effective use of the Framework. Understanding the business context, the resources that support critical functions and the related cybersecurity risks enables an organization to focus and prioritize its efforts, consistent with its risk management strategy and business needs. Examples of outcome Categories within this Function include: Asset Management; Business Environment; Governance; Risk Assessment; and Risk Management Strategy.

Protect – Develop and implement the appropriate safeguards to ensure delivery of critical infrastructure services. The activities in the Protect Function support the ability to limit or contain the impact of a potential cybersecurity event. Examples of outcome Categories within this Function include: Access Control; Awareness and Training; Data Security; Information Protection Processes and Procedures; Maintenance; and Protective Technology.

Detect – Develop and implement the appropriate activities to identify the occurrence of a cybersecurity event. The activities in the Detect Function enable timely discovery of cybersecurity events. Examples of outcome Categories within this Function include: Anomalies and Events; Security Continuous Monitoring; and Detection Processes.

Respond – Develop and implement the appropriate activities to take action regarding a detected cybersecurity event. The activities in the Respond Function support the ability to contain the impact of a potential cybersecurity event. Examples of outcome Categories within this Function include: Response Planning; Communications; Analysis; Mitigation; and Improvements.

Recover – Develop and implement the appropriate activities to maintain plans for resilience and to restore any capabilities or services that were impaired due to a cybersecurity event. The activities in the Recover Function support timely recovery to normal operations to reduce the impact from a cybersecurity event. Examples of outcome Categories within this Function include: Recovery Planning; Improvements; and Communications.

The Manufacturing Profile for the Cybersecurity Framework presents detailed implementation language for the cybersecurity standards expressed in the Framework categories and subcategories. The Profile is intended to support cybersecurity outcomes based on business needs that the manufacturer has selected from the Framework Categories and Subcategories [2]. The Profile can be characterized as the alignment of standards, guidelines, and practices to the Framework Core in a practical implementation scenario.

4. Manufacturing Profile Development Approach

The manufacturing profile was developed to be an actionable approach for implementing cybersecurity controls into a manufacturing system and its environment. The specific statements in the subcategories in Section 7 are derived from the security controls of the NIST SP 800-53 Rev.4 [4], and are customized to the manufacturing domain using relevant informative references. The general informative references of ISA/IEC 62443 [5] from the Framework are also listed in the References column. COBIT 5 is sourced for subcategories that have no corresponding 800-53 references. Additional input came from NIST SP 800-82, Rev. 2, both in section 6.2 (Guidance on the Application of Security Controls to ICS) and in Appendix G (ICS Overlay) [3]. For informative references to an entire control family, or set of controls (such as subcategory ID.GV-1's informative reference to all "policy and procedures" controls), the approach took a holistic view of the controls comprising the family/set.

Section 7 provides the customized CSF subcategory language developed using informative references relevant to the manufacturing domain. In the Reference column in Section 7, hyperlinks are provided to the specific and relevant source influences for the subcategory statements.

The Profile expresses tailored values for cybersecurity controls for the manufacturing system environment. These represent the application of the Categories and Subcategories from the Framework based on domain-specific relevance, business drivers, risk assessment, and the manufacturer's priorities. Users of the Profile can also add Categories and Subcategories as needed to address unique and specific risks.

5. Manufacturing Business/Mission Objectives

The development of the Manufacturing Profile included the identification of common business/mission objectives to the manufacturing sector. These business/mission objectives provide the necessary context for identifying and managing applicable cybersecurity risk mitigation pursuits [2]. Five common business/mission objectives for the manufacturing sector were initially identified: *Maintain Human Safety*, *Maintain Environmental Safety*, *Maintain Quality of Product*, *Maintain Production Goals*, and *Maintain Trade Secrets*. Other business/mission objectives were identified for the manufacturing sector but not included in this initial profile. Key cybersecurity practices are identified for supporting each business/mission objective, allowing users to better prioritize actions and resources according to the user's defined needs.

These Business/Mission Objectives Are Not Listed in Prioritized Order.

Maintain Human Safety

Manage cybersecurity risks that could potentially impact human safety. Cybersecurity risk on the manufacturing system could potentially adversely affect human safety. Personnel should understand cybersecurity and safety interdependencies.

Maintain Environmental Safety

Manage cybersecurity risks that could adversely affect the environment, including both accidental and deliberate damage. Cybersecurity risk on the manufacturing system could potentially adversely affect environmental safety. Personnel should understand cybersecurity and environmental safety interdependencies.

Maintain Quality of Product

Manage cybersecurity risks that could adversely affect the quality of product. Protect against compromise of integrity of the manufacturing process and associated data.

Maintain Production Goals

Manage cybersecurity risks that could adversely affect production goals. Cybersecurity risk on the manufacturing system, including asset damage, could potentially adversely affect production goals. Personnel should understand cybersecurity and production goal interdependencies.

Maintain Trade Secrets

Manage cybersecurity risks that could lead to the loss or compromise of the organization's intellectual property and sensitive business data.

5.1 Alignment of Subcategories to Meet Mission Objectives

To align cybersecurity goals with overall mission success, the Profile subcategories are prioritized in order to support specific business/mission objectives. This allows the manufacturer to focus on implementing those cybersecurity measures against threats that could severely compromise their ability to perform their essential mission.

For each business/mission objective, the most critical Subcategories initially determined to support the objective are highlighted in the tables under each Function. The selection of Subcategories to business/mission objectives was based on a broad range of manufacturing sectors and operations. The most critical Subcategories may differ for individual manufacturers.

***Identify** - The Identify Function is critical in the development of the foundation for cybersecurity management, and in the understanding of cyber risk to systems, assets, data, and capabilities.*

Table 2 IDENTIFY Business Mission Objectives

		Maintain Human Safety	Maintain Environmental Safety	Maintain Quality of Product	Maintain Production Goals	Maintain Trade Secrets
Category	Subcategories					
ID	Asset Management	ID.AM-1	ID.AM-1	ID.AM-1	ID.AM-1	ID.AM-1
		ID.AM-2	ID.AM-2	ID.AM-2	ID.AM-2	ID.AM-2
		ID.AM-3	ID.AM-3	ID.AM-3	ID.AM-3	ID.AM-3
		ID.AM-4	ID.AM-4	ID.AM-4	ID.AM-4	ID.AM-4
		ID.AM-5	ID.AM-5	ID.AM-5	ID.AM-5	ID.AM-5
		ID.AM-6	ID.AM-6	ID.AM-6	ID.AM-6	ID.AM-6
	Business Environment	ID.BE-1	ID.BE-1	ID.BE-1	ID.BE-1	ID.BE-1
		ID.BE-2	ID.BE-2	ID.BE-2	ID.BE-2	ID.BE-2
		ID.BE-3	ID.BE-3	ID.BE-3	ID.BE-3	ID.BE-3
		ID.BE-4	ID.BE-4	ID.BE-4	ID.BE-4	ID.BE-4
		ID.BE-5	ID.BE-5	ID.BE-5	ID.BE-5	ID.BE-5
	Governance	ID.GV-1	ID.GV-1	ID.GV-1	ID.GV-1	ID.GV-1
		ID.GV-2	ID.GV-2	ID.GV-2	ID.GV-2	ID.GV-2
		ID.GV-3	ID.GV-3	ID.GV-3	ID.GV-3	ID.GV-3
		ID.GV-4	ID.GV-4	ID.GV-4	ID.GV-4	ID.GV-4
	Risk Assessment	ID.RA-1	ID.RA-1	ID.RA-1	ID.RA-1	ID.RA-1
		ID.RA-2	ID.RA-2	ID.RA-2	ID.RA-2	ID.RA-2
		ID.RA-3	ID.RA-3	ID.RA-3	ID.RA-3	ID.RA-3
		ID.RA-4	ID.RA-4	ID.RA-4	ID.RA-4	ID.RA-4
		ID.RA-5	ID.RA-5	ID.RA-5	ID.RA-5	ID.RA-5
		ID.RA-6	ID.RA-6	ID.RA-6	ID.RA-6	ID.RA-6
	Risk Management Strategy	ID.RM-1	ID.RM-1	ID.RM-1	ID.RM-1	ID.RM-1
		ID.RM-2	ID.RM-2	ID.RM-2	ID.RM-2	ID.RM-2
		ID.RM-3	ID.RM-3	ID.RM-3	ID.RM-3	ID.RM-3

This publication is available free of charge from: <https://doi.org/10.6028/NIST.IR.8183>

Protect – The Protect Function is critical to limit the impact of a potential cybersecurity event.

Table 3 PROTECT Business Mission Objectives

	Maintain Human Safety	Maintain Environmental Safety	Maintain Quality of Product	Maintain Production Goals	Maintain Trade Secrets	
Category	Subcategories					
PR	Access Control	PR.AC-1	PR.AC-1	PR.AC-1	PR.AC-1	PR.AC-1
		PR.AC-2	PR.AC-2	PR.AC-2	PR.AC-2	PR.AC-2
		PR.AC-3	PR.AC-3	PR.AC-3	PR.AC-3	PR.AC-3
		PR.AC-4	PR.AC-4	PR.AC-4	PR.AC-4	PR.AC-4
		PR.AC-5	PR.AC-5	PR.AC-5	PR.AC-5	PR.AC-5
	Awareness and Training	PR.AT-1	PR.AT-1	PR.AT-1	PR.AT-1	PR.AT-1
		PR.AT-2	PR.AT-2	PR.AT-2	PR.AT-2	PR.AT-2
		PR.AT-3	PR.AT-3	PR.AT-3	PR.AT-3	PR.AT-3
		PR.AT-4	PR.AT-4	PR.AT-4	PR.AT-4	PR.AT-4
		PR.AT-5	PR.AT-5	PR.AT-5	PR.AT-5	PR.AT-5
	Data Security	PR.DS-1	PR.DS-1	PR.DS-1	PR.DS-1	PR.DS-1
		PR.DS-2	PR.DS-2	PR.DS-2	PR.DS-2	PR.DS-2
		PR.DS-3	PR.DS-3	PR.DS-3	PR.DS-3	PR.DS-3
		PR.DS-4	PR.DS-4	PR.DS-4	PR.DS-4	PR.DS-4
		PR.DS-5	PR.DS-5	PR.DS-5	PR.DS-5	PR.DS-5
		PR.DS-6	PR.DS-6	PR.DS-6	PR.DS-6	PR.DS-6
		PR.DS-7	PR.DS-7	PR.DS-7	PR.DS-7	PR.DS-7
	Information Protection Processes and Procedures	PR.IP-1	PR.IP-1	PR.IP-1	PR.IP-1	PR.IP-1
		PR.IP-2	PR.IP-2	PR.IP-2	PR.IP-2	PR.IP-2
		PR.IP-3	PR.IP-3	PR.IP-3	PR.IP-3	PR.IP-3
		PR.IP-4	PR.IP-4	PR.IP-4	PR.IP-4	PR.IP-4
		PR.IP-5	PR.IP-5	PR.IP-5	PR.IP-5	PR.IP-5
		PR.IP-6	PR.IP-6	PR.IP-6	PR.IP-6	PR.IP-6
		PR.IP-7	PR.IP-7	PR.IP-7	PR.IP-7	PR.IP-7
		PR.IP-8	PR.IP-8	PR.IP-8	PR.IP-8	PR.IP-8
		PR.IP-9	PR.IP-9	PR.IP-9	PR.IP-9	PR.IP-9
		PR.IP-10	PR.IP-10	PR.IP-10	PR.IP-10	PR.IP-10
		PR.IP-11	PR.IP-11	PR.IP-11	PR.IP-11	PR.IP-11
		PR.IP-12	PR.IP-12	PR.IP-12	PR.IP-12	PR.IP-12
	Maintenance	PR.MA-1	PR.MA-1	PR.MA-1	PR.MA-1	PR.MA-1
		PR.MA-2	PR.MA-2	PR.MA-2	PR.MA-2	PR.MA-2
	Protective Technology	PR.PT-1	PR.PT-1	PR.PT-1	PR.PT-1	PR.PT-1
		PR.PT-2	PR.PT-2	PR.PT-2	PR.PT-2	PR.PT-2
		PR.PT-3	PR.PT-3	PR.PT-3	PR.PT-3	PR.PT-3
		PR.PT-4	PR.PT-4	PR.PT-4	PR.PT-4	PR.PT-4

This publication is available free of charge from: <https://doi.org/10.6028/NIST.IR.8183>

***Detect** – The Detect Function enables timely discovery of cybersecurity events. Real time awareness and continuous monitoring of the systems is critical to detect cybersecurity events.*

Table 4 DETECT Business Mission Objectives

		Maintain Human Safety	Maintain Environmental Safety	Maintain Quality of Product	Maintain Production Goals	Maintain Trade Secrets
Category		Subcategories				
DE	Anomalies and Events	DE.AE-1	DE.AE-1	DE.AE-1	DE.AE-1	DE.AE-1
		DE.AE-2	DE.AE-2	DE.AE-2	DE.AE-2	DE.AE-2
		DE.AE-3	DE.AE-3	DE.AE-3	DE.AE-3	DE.AE-3
		DE.AE-4	DE.AE-4	DE.AE-4	DE.AE-4	DE.AE-4
		DE.AE-5	DE.AE-5	DE.AE-5	DE.AE-5	DE.AE-5
	Security Continuous Monitoring	DE.CM-1	DE.CM-1	DE.CM-1	DE.CM-1	DE.CM-1
		DE.CM-2	DE.CM-2	DE.CM-2	DE.CM-2	DE.CM-2
		DE.CM-3	DE.CM-3	DE.CM-3	DE.CM-3	DE.CM-3
		DE.CM-4	DE.CM-4	DE.CM-4	DE.CM-4	DE.CM-4
		DE.CM-5	DE.CM-5	DE.CM-5	DE.CM-5	DE.CM-5
		DE.CM-6	DE.CM-6	DE.CM-6	DE.CM-6	DE.CM-6
		DE.CM-7	DE.CM-7	DE.CM-7	DE.CM-7	DE.CM-7
		DE.CM-8	DE.CM-8	DE.CM-8	DE.CM-8	DE.CM-8
	Detection Processes	DE.DP-1	DE.DP-1	DE.DP-1	DE.DP-1	DE.DP-1
		DE.DP-2	DE.DP-2	DE.DP-2	DE.DP-2	DE.DP-2
		DE.DP-3	DE.DP-3	DE.DP-3	DE.DP-3	DE.DP-3
		DE.DP-4	DE.DP-4	DE.DP-4	DE.DP-4	DE.DP-4
		DE.DP-5	DE.DP-5	DE.DP-5	DE.DP-5	DE.DP-5

This publication is available free of charge from: <https://doi.org/10.6028/NIST.IR.8183>

Respond – The Respond Function supports the ability to contain the impact of a potential cybersecurity event.

Table 5 RESPOND Business Mission Objectives

		Maintain Human Safety	Maintain Environmental Safety	Maintain Quality of Product	Maintain Production Goals	Maintain Trade Secrets
Category	Subcategories					
RS	Response Planning	RS.RP-1	RS.RP-1	RS.RP-1	RS.RP-1	RS.RP-1
	Communications	RS.CO-1	RS.CO-1	RS.CO-1	RS.CO-1	RS.CO-1
		RS.CO-2	RS.CO-2	RS.CO-2	RS.CO-2	RS.CO-2
		RS.CO-3	RS.CO-3	RS.CO-3	RS.CO-3	RS.CO-3
		RS.CO-4	RS.CO-4	RS.CO-4	RS.CO-4	RS.CO-4
		RS.CO-5	RS.CO-5	RS.CO-5	RS.CO-5	RS.CO-5
	Analysis	RS.AN-1	RS.AN-1	RS.AN-1	RS.AN-1	RS.AN-1
		RS.AN-2	RS.AN-2	RS.AN-2	RS.AN-2	RS.AN-2
		RS.AN-3	RS.AN-3	RS.AN-3	RS.AN-3	RS.AN-3
		RS.AN-4	RS.AN-4	RS.AN-4	RS.AN-4	RS.AN-4
	Mitigation	RS.MI-1	RS.MI-1	RS.MI-1	RS.MI-1	RS.MI-1
		RS.MI-2	RS.MI-2	RS.MI-2	RS.MI-2	RS.MI-2
		RS.MI-3	RS.MI-3	RS.MI-3	RS.MI-3	RS.MI-3
	Improvements	RS.IM-1	RS.IM-1	RS.IM-1	RS.IM-1	RS.IM-1
		RS.IM-2	RS.IM-2	RS.IM-2	RS.IM-2	RS.IM-2

Recover – The Recover Function supports timely recovery to normal operations to reduce the impact from a cybersecurity event. Defined Recovery objectives are needed when recovering from disruptions.

Table 6 RECOVER Business Mission Objectives

		Maintain Human Safety	Maintain Environmental Safety	Maintain Quality of Product	Maintain Production Goals	Maintain Trade Secrets
Category	Subcategories					
RC	Recovery Planning	RC.RP-1	RC.RP-1	RC.RP-1	RC.RP-1	RC.RP-1
	Improvements	RC.IM-1	RC.IM-1	RC.IM-1	RC.IM-1	RC.IM-1
		RC.IM-2	RC.IM-2	RC.IM-2	RC.IM-2	RC.IM-2
	Communications	RC.CO-1	RC.CO-1	RC.CO-1	RC.CO-1	RC.CO-1
		RC.CO-2	RC.CO-2	RC.CO-2	RC.CO-2	RC.CO-2
	RC.CO-3	RC.CO-3	RC.CO-3	RC.CO-3	RC.CO-3	

This publication is available free of charge from: <https://doi.org/10.6028/NIST.IR.8183>

6. Manufacturing System Categorization and Risk Management

In addition to the Business/Mission Objectives for aligning a focused set of cybersecurity controls to support critical business goals, the Manufacturing Profile is also structured into three levels of security to be applied to a manufacturing system according to its categorization of Low, Moderate, or High.

6.1 Categorization Process

The Profile guidance is provided at three security levels: Low, Moderate, and High. These designations identify the security capability, functionality, and specificity for a defined risk level. A manufacturer or industry sector applies the Profile to a manufacturing system by categorizing its system or component(s) to a security level of Low, Moderate, or High.

The categorization is based on the potential impact if a security breach jeopardizes the manufacturing system or components, operational assets, individuals, or the organization. Security categorizations are to be used in conjunction with vulnerability and threat information in assessing the risk to an organization. FIPS 199, for example, defines three levels of potential impact on systems should there be a breach of security (i.e., a loss of integrity, availability, or confidentiality). The application of these definitions must take place within the context of the organization, facility, and manufacturing system.

The Profile defines the three security levels as follows:

1. The *potential impact* is **LOW** if the loss of integrity, availability, or confidentiality could be expected to have a **limited** adverse effect on manufacturing operations, manufactured product, assets, brand image, finances, personnel, the general public, or the environment.
2. The *potential impact* is **MODERATE** if the loss of integrity, availability, or confidentiality could be expected to have a **serious** adverse effect on manufacturing operations, manufactured product, assets, brand image, finances, personnel, the general public, or the environment.
3. The *potential impact* is **HIGH** if the loss of integrity, availability, or confidentiality could be expected to have a **severe or catastrophic** adverse effect on manufacturing operations, manufactured product, assets, brand image, finances, personnel, the general public, or the environment.

The security categorization process influences the level of effort expended when implementing the Profile. Manufacturing systems supporting the most critical and/or sensitive operations and assets demand the greatest level of attention and effort to ensure that appropriate operational security and risk mitigation are achieved.

The tables below provide examples of mission-based rationale for selecting the security categorization of the manufacturing system:

Table 7 Manufacturing System Impact Levels [3]

Impact Category	Low-Impact	Moderate-Impact	High-Impact
Injury	Cuts, bruises requiring first aid	Requires hospitalization	Loss of life or limb
Financial Loss (\$)	Tens of thousands	Hundreds of thousands	Millions
Environmental Release	Temporary damage	Lasting damage	Permanent damage, off-site damage
Interruption of Production	Hours	Days	Weeks
Public Image	Temporary damage	Lasting damage	Permanent damage

Table 8 Manufacturing System Impact Levels Based on Product Produced and Industry Concerns [3]

Category	Low-Impact	Moderate-Impact	High-Impact
Product Produced	Non-hazardous materials or products Non-ingested consumer products	Some hazardous products or steps during production High amount of proprietary information	Critical infrastructure (e.g., electricity) Hazardous materials Ingested products
Industry Examples	Plastic injection molding Warehousing	Automotive metal stamping Pulp and paper Semiconductors Automotive production	Utilities Petrochemical Food and beverage Pharmaceutical

A limited adverse effect means that, for example, the loss of integrity, availability, or confidentiality might:

- cause a degradation in mission capability to an extent and duration that the system is able to perform its primary functions, but the effectiveness of the functions is noticeably reduced;
- result in minor damage to operational assets;
- result in minor financial loss;
- result in minor harm to individuals.

A serious adverse effect means that, for example, the loss of integrity, availability, or confidentiality might:

- cause a significant degradation in mission capability to an extent and duration that the system is able to perform its primary functions, but the effectiveness of the functions is significantly reduced;
- result in significant damage to operational assets;
- result in significant financial loss;
- result in significant harm to individuals but does not involve loss of life or serious life threatening injuries.

A severe or catastrophic adverse effect means that, for example, the loss of integrity, availability, or confidentiality might:

- cause a severe degradation in or loss of mission capability to an extent and duration that the system is not able to perform one or more of its primary functions;
- result in major damage to operational assets;
- result in major financial loss;
- result in severe or catastrophic harm to individuals involving loss of life or serious life threatening injuries.

6.2 Profile's Hierarchical Supporting Structure

The Profile guidance is scalable and supports intensifying security protections where needed, while maintaining a conventional baseline. Each higher security level builds from the baseline starting with the Low designation. The Moderate and High each include all of the stipulations from the levels below.

- A Moderate categorization includes all Moderate and Low security implementations
- A High categorization includes all High, Moderate, and Low security implementations

Each security level is positioned as the platform to support the next higher security level implementation, or categorization. The security level implementation starts with Low and increases in rigor through the Moderate and High implementations. The Low security level represents the starting baseline for all manufacturing systems. The Moderate security level will implement the Low security guidance as well as the Moderate. The High security level will implement all of the Low and Moderate guidance as well as the High inputs. Section 7 provides CSF subcategory language for each security level customized to the manufacturing domain.

6.3 Risk Management

The Profile relies on the manufacturer's risk management processes to inform and prioritize decisions regarding cybersecurity. It supports recurring risk assessments and validation of business drivers to help manufacturers select target states for cybersecurity activities that reflect desired outcomes.

To manage cybersecurity risks, a clear understanding of the business drivers and security considerations specific to the Manufacturing system and its environment is required. Each organization's risk is unique, along with its use of ICS and IT, thus the implementation of the profile will vary.

The Manufacturing Profile is meant to enhance but not replace current cybersecurity standards and industry guidelines that the manufacturer is currently embracing. Manufacturers can determine activities that are important to critical service delivery and can prioritize investments to maximize the impact of each dollar spent. Ultimately, the Profile is aimed at reducing and better managing cybersecurity risks. The Profile, along with the Cybersecurity Framework, are not one-size-fits-all approaches to managing cybersecurity risk for critical infrastructure. Manufacturers will continue to have unique risks – different threats, different vulnerabilities, different risk tolerances – and how they implement security practices will vary.

7. Manufacturing Profile Subcategory Guidance

Function	Category	Subcategory	Manufacturing Profile	Reference			
IDENTIFY	Asset Management (ID.AM)	ID.AM-1	Low	Document an inventory of manufacturing system components that reflects the current system. Manufacturing system components include for example PLCs, sensors, actuators, robots, machine tools, firmware, network switches, routers, power supplies, and other networked components or devices. System component inventory is reviewed and updated as defined by the organization. Information deemed necessary for effective accountability of manufacturing system components includes, for example, hardware inventory specifications, component owners, networked components or devices, machine names and network addresses. Inventory specifications include, for example, manufacturer, device type, model, serial number, and physical location.	62443-2-1:2009 4.2.3.4 62443-3-3:2013 SR 7.8 CM-8		
			Moderate			Identify individuals who are both responsible and accountable for administering manufacturing system components.	CM-8 (1)(4)(5)
			High				
			Low			Document an inventory of manufacturing system software components that reflects the current system. Manufacturing system software components include for example software license information, software version numbers, HMI and other ICS component applications, software, operating systems. System software inventory is reviewed and updated as defined by the organization.	62443-2-1:2009 4.2.3.4 62443-3-3:2013 SR 7.8 CM-8
		Moderate	Update the inventory of manufacturing system software as an integral part of component installations, removals, and system updates. Identify individuals who are both responsible and accountable for administering manufacturing system software.	CM-8 (1)(4)(5)			
		High			Employ automated mechanisms where safe and feasible to detect the presence of unauthorized software within the system.		

Function	Category	Subcategory	Manufacturing Profile	Reference
IDENTIFY	Asset Management (ID.AM)	ID.AM-3	<p>Low</p> <p>Document all connections within the manufacturing system, and between the manufacturing system and other systems. All connections are documented, authorized, and reviewed.</p> <p>Connection information includes, for example, the interface characteristics, data characteristics, ports, protocols, addresses, description of the data, security requirements, and the nature of the connection.</p>	62443-2-1:2009 4.2.3.4 CA-3
			<p>Moderate and High</p> <p>Map the flow of information within the manufacturing system and to external systems.</p>	AC-4
		ID.AM-4	<p>Low</p> <p>Identify and document all external connections for the manufacturing system.</p> <p>Examples of external systems include engineering design services, and those that are controlled under separate authority, personal devices, and other hosted services.</p>	AC-20
			<p>Moderate and High</p> <p>Require external providers to identify the functions, ports, protocols, and other services required for use with the manufacturing system.</p>	SA-9(2)
ID.AM-5	<p>Low, Moderate and High</p> <p>Identify and prioritize manufacturing system components and functions based on their classification, criticality, and business value.</p> <p>Identify the types of information in possession, custody, or control for which security safeguards are needed (e.g. sensitive or protected information).</p>	62443-2-1:2009 4.2.3.6 CP-2		
	ID.AM-6	<p>Low, Moderate and High</p> <p>Establish and maintain personnel cybersecurity roles and responsibilities for the manufacturing system. Include cybersecurity roles and responsibilities for third-party providers.</p> <p>Third-party providers are required to notify the organization of any personnel transition (including transfers or terminations) involving personnel with physical or logical access to the manufacturing system components.</p> <p>Third-party providers include, for example, service providers, contractors, and other organizations providing manufacturing system development, technology services, outsourced applications, or network and security management.</p>	62443-2-1:2009 4.3.2.3.3 CP-2 PS-7	

Function	Category	Subcategory	Manufacturing Profile	Reference
IDENTIFY	Business Environment (ID.BE)	<u>ID.BE-1</u>	<p style="text-align: center;">Low and Moderate</p> <p>Define and communicate the organization’s role in the supply chain. Identify the upstream and downstream supply channels that are outside of the organization's operations. Identify the overall mission supported by the manufacturing system.</p> <p style="text-align: center;">High</p> <p>Protect against supply chain threats to the manufacturing system, system components, or system services by employing security safeguards as part of a comprehensive, defense-in-depth security strategy.</p>	<p><u>CP-2(1)(3)(8)</u></p> <p><u>SA-12</u></p>
		<u>ID.BE-2</u>	<p style="text-align: center;">Low, Moderate and High</p> <p>Define and communicate the manufacturer's place in critical infrastructure and its industry sector. Define and communicate critical infrastructure and key resources relevant to the manufacturing system. Develop, document, and maintain a critical infrastructure and key resources protection plan.</p>	<p><u>PM-8</u></p>
		<u>ID.BE-3</u>	<p style="text-align: center;">Low, Moderate and High</p> <p>Establish and communicate priorities for manufacturing missions, objectives, and activities with consideration for security and the resulting risk to manufacturing operations, components, and individuals. Identify critical manufacturing system components and functions by performing a criticality analysis.</p>	<p>62443-2-1:2009 4.2.2.1</p> <p><u>PM-11</u></p> <p><u>SA-14</u></p>
		<u>ID.BE-4</u>	<p style="text-align: center;">Low</p> <p>Identify and prioritize supporting services for critical manufacturing system processes and components. Provide an uninterruptable power supply for identified critical manufacturing system components to facilitate the transition of the manufacturing system to long-term alternate power in the event of a primary power source loss.</p> <p style="text-align: center;">Moderate and High</p> <p>Identify alternate and redundant supporting services for critical manufacturing system processes and components.</p>	<p><u>PM-8,SA-14</u></p> <p><u>PE-11</u></p> <p><u>PE-9(1)</u></p>

Function	Category	Subcategory	Manufacturing Profile	Reference	
IDENTIFY	Business Environment (ID.BE)	<u>ID.BE-5</u>	Low	<u>CP-2</u> <u>CP-2(3)</u> <u>CP-2(8)</u> <u>CP-2(2)</u> <u>CP-2(4)(5)</u>	
			Establish resilience requirements for the manufacturing system to support delivery of critical services.		
			Moderate		
			Define recovery time objective and recovery point objective for the resumption of essential manufacturing system processes. Identify critical manufacturing system assets that support essential manufacturing system processes.		
	High	Conduct capacity planning for manufacturing system processing, telecommunications, and environmental support as required during contingency operations. Conduct contingency planning for the continuance of essential manufacturing functions and services with little or no loss of operational continuity, and sustain that continuity until full system restoration.			
	Governance (ID.GV)		<u>ID.GV-1</u>	Low, Moderate and High	62443-2-1:2009 4.3.2.6 <u>800-53 Security Policies-1</u>
			Develop and disseminate a security policy that provides an overview of the security requirements for the manufacturing system. The policy includes, for example, the identification and assignment of roles, responsibilities, management commitment, coordination among organizational entities, and compliance. It also reflects coordination among organizational entities responsible for the different aspects of security (i.e., technical, physical, personnel, cyber-physical, access control, media protection, vulnerability management, maintenance, monitoring), and covers the full life cycle of the manufacturing system. Review and update the security policy as determined necessary. Ensure the security policy is approved by a senior official with responsibility and accountability for the risk being incurred by manufacturing operations.		
<u>ID.GV-2</u>			Low, Moderate and High	62443-2-1:2009 4.3.2.3.3 <u>PM-1, PS-7</u>	
Develop and disseminate a security program for the manufacturing system that includes, for example, the identification of personnel security roles and assignment of responsibilities, management commitment, coordination among organizational entities, and compliance. This includes security requirements, roles and responsibilities for third-party providers. Review and update the security program as determined necessary.					
<u>ID.GV-3</u>	Low, Moderate and High	62443-2-1:2009 4.4.3.7 <u>800-53 Security Policies-1</u>			
Ensure that legal and regulatory requirements affecting the manufacturing operations regarding cybersecurity are understood and managed.					

Function	Category	Subcategory	Manufacturing Profile	Reference
IDENTIFY	Governance (ID.GV)	<u>ID.GV-4</u>	<p style="text-align: center;">Low, Moderate and High</p> <p>Develop a comprehensive strategy to manage risk to manufacturing operations. Include cybersecurity considerations in the risk management strategy. Review and update the risk management strategy as determined necessary. Determine and allocate required resources to protect the manufacturing system.</p>	<p>62443-2-1:2009 4.2.3.1, 4.2.3.3, 4.2.3.8, 4.2.3.9</p> <p><u>PM-9</u>, <u>PM-11</u></p>
	Risk Assessment (ID.RA)	<u>ID.RA-1</u>	<p style="text-align: center;">Low and Moderate</p> <p>Develop a plan to identify, document, and report vulnerabilities that exist on the manufacturing system. Include the use of vulnerability scanning where safe and feasible on the manufacturing system, its components, or a representative system.</p> <p>Develop a plan for continuous monitoring of the security posture of the manufacturing system to facilitate ongoing awareness of vulnerabilities.</p> <p>Conduct risk assessments on the manufacturing system that take into account vulnerabilities and potential impact to manufacturing operations and assets.</p> <p style="text-align: center;">High</p> <p>Conduct performance/load testing and penetration testing on the manufacturing system with care to ensure that manufacturing operations are not adversely impacted by the testing process.</p> <p>Identify where manufacturing system vulnerabilities may be exposed to adversaries.</p> <p>Production systems may need to be taken off-line before testing can be conducted. If the manufacturing system is taken off-line for testing, tests are scheduled to occur during planned manufacturing outages whenever possible. If penetration testing is performed on non-manufacturing networks, extra care is taken to ensure that tests do not propagate into the manufacturing network.</p>	<p>62443-2-1:2009 4.2.3, 4.2.3.7, 4.2.3.9, 4.2.3.12</p> <p><u>CA-2</u></p> <p><u>CA-7</u></p> <p><u>RA-3</u></p> <p><u>CA-2(2)</u>,</p> <p><u>RA-5(4)</u></p>
		<u>ID.RA-2</u>	<p style="text-align: center;">Low and Moderate</p> <p>Establish and maintain ongoing contact with security groups and associations, and receive security alerts and advisories. Security groups and associations include, for example, special interest groups, forums, professional associations, news groups, and/or peer groups of security professionals in similar organizations. Implement a threat awareness program that includes a cross-organization information-sharing capability. Organizations should consider having both an unclassified and classified information sharing capability.</p>	<p>62443-2-1:2009 4.2.3, 4.2.3.9, 4.2.3.12</p> <p><u>PM-15</u></p>

Function	Category	Subcategory	Manufacturing Profile	Reference
IDENTIFY	Risk Assessment (ID.RA)		<p>Collaborate and share information about potential vulnerabilities and incidents on a timely basis. The DHS National Cybersecurity & Communications Integration Center (NCCIC) [6] serves as a centralized location where operational elements involved in cybersecurity and communications reliance are coordinated and integrated. The Industrial Control Systems Cyber Emergency Response Team (ICS-CERT) [7] collaborates with international and private sector Computer Emergency Response Teams (CERTs) to share control systems-related security incidents and mitigation measures.</p> <p style="text-align: center;">High</p> <p>Employ automated mechanisms where technically feasible to make security alert and advisory information available throughout the organization.</p>	<p>PM-16</p> <p>SI-5(1)</p>
		ID.RA-3	<p style="text-align: center;">Low, Moderate and High</p> <p>Conduct and document periodic assessment of risk to the manufacturing system that takes into account threats and likelihood of impact to manufacturing operations and assets. The risk assessment includes threats from insiders and external parties.</p>	<p>62443-2-1:2009 4.2.3, 4.2.3.9, 4.2.3.12</p> <p>RA-3</p>
		ID.RA-4	<p style="text-align: center;">Low, Moderate and High</p> <p>Conduct criticality reviews of the manufacturing system that define the potential adverse impacts to manufacturing operations, assets, and individuals if compromised or disabled.</p>	<p>62443-2-1:2009 4.2.3, 4.2.3.9, 4.2.3.12</p> <p>RA-2</p>
		ID.RA-5	<p style="text-align: center;">Low, Moderate and High</p> <p>Conduct risk assessments of the manufacturing system incorporating threats, vulnerabilities, likelihood, and impact to manufacturing operations, assets, and individuals. Disseminate risk assessment results to relevant stakeholders.</p>	<p>RA-3, PM-16</p>
		ID.RA-6	<p style="text-align: center;">Low, Moderate and High</p> <p>Develop and implement a comprehensive strategy to manage risk to the manufacturing system that includes the identification and prioritization of risk responses.</p>	<p>PM-9</p>
		Risk Management Strategy (ID.RM)	ID.RM-1	<p style="text-align: center;">Low, Moderate and High</p> <p>Establish a risk management process for the manufacturing system that effectively identifies, communicates, and facilitates addressing risk-related issues and information among key stakeholders internally and externally.</p>

Function	Category	Subcategory	Manufacturing Profile	Reference
IDENTIFY	Risk Management Strategy (ID.RM)	ID.RM-2	<p>Low, Moderate and High</p> <p>Define the risk tolerance for the manufacturing system.</p>	62443-2-1:2009 4.3.2.6.5 PM-9
		ID.RM-3	<p>Low, Moderate and High</p> <p>Ensure the risk tolerance for the manufacturing system is informed by the organization's role in critical infrastructure and sector-specific risk analysis.</p>	PM-9, PM-8
PROTECT	Access Control (PR.AC)	PR.AC-1	<p>Low</p> <p>Establish and manage identification mechanisms and credentials for users of the manufacturing system.</p>	62443-2-1:2009 4.3.3.5.1; SR 1.1, 1.2, 1.3, 1.4, 1.5,1.7 IA-Family AC-2(1)
			<p>Moderate</p> <p>Establish and manage identification mechanisms and credentials for users and devices of the manufacturing system. Employ automated mechanisms where feasible to support the management and auditing of information system credentials.</p>	AC-2(5)
			<p>High</p> <p>Deactivate system credentials after a specified time period of inactivity, unless this would result in a compromise to safe operation of the process. Monitor the manufacturing system for atypical use of system credentials. Credentials associated with significant risk are disabled.</p>	AC-2(12)(13)
			PR.AC-2	<p>Low</p> <p>Protect physical access to the manufacturing facility. Determine access requirements during emergency situations. Maintain and review visitor access records to the facility where the manufacturing system resides. Physical access controls may include, for example, lists of authorized individuals, identity credentials, escort requirements, guards, fences, turnstiles, locks, monitoring of facility access.</p>
<p>Moderate</p> <p>Protect power equipment, power cabling, network cabling, and network access interfaces for the manufacturing system from accidental damage, disruption, and physical tampering. Ensure availability and integrity of wireless systems, especially safety related systems. Employ redundant and physically separated power systems for critical manufacturing operations.</p>	PE-9 (1)			
<p>High</p> <p>Control physical access to the manufacturing system in addition to the physical access for the facility.</p>	PE-3 (1)			

Function	Category	Subcategory	Manufacturing Profile	Reference
PROTECT	Access Control (PR.AC)	<u>PR.AC-3</u>	<p style="text-align: center;">Low</p> <p>Establish usage restrictions, connection requirements, implementation guidance, and authorizations for remote access to the manufacturing system. Provide an explicit indication of active remote access connections to users physically present at the devices. Remote access methods include, for example, wireless, dial-up, broadband, VPN connections, mobile device connections, and communications through external networks.</p> <p style="text-align: center;">Moderate and High</p> <p>Allow remote access only through approved and managed access points. Monitor remote access to the manufacturing system, and employ cryptographic mechanisms where determined necessary. Allow only authorized use of privileged functions from remote access. Establish agreements and verify security for connections with external systems.</p>	<p>62443-2-1:2009 4.3.3.6.6 62443-3-3:2013 SR 1.13,2.6 AC-17,19,20 SC-15</p> <p>AC-17(1)(2)(3)(4) AC-20(1)(2)</p>
		<u>PR.AC-4</u>	<p style="text-align: center;">Low</p> <p>Define and manage access permissions for users of the manufacturing system. Identify and document user actions that can be performed on the manufacturing system without identification or authentication (e.g. during emergencies).</p> <p style="text-align: center;">Moderate</p> <p>Employ automated mechanisms where feasible to support the management of manufacturing system user accounts, including the disabling, auditing, notification, and removal of user accounts. Implement separation of duties for manufacturing system users. Limit, document, and explicitly authorize privileged user access to the manufacturing system. Audit the execution of privileged functions on the manufacturing system. Separation of duties includes, for example: dividing operational functions and system support functions among different roles; conducting system support functions with different individuals; and ensuring security personnel administering access control functions do not also administer audit functions.</p> <p style="text-align: center;">High</p> <p>Enforce account usage restrictions for specific time periods and locality. Monitor manufacturing system usage for atypical use. Disable accounts of users posing a significant risk. Specific restrictions can include, for example, restricting usage to certain days of the week, time of day, or specific durations of time. Privileged user access through non-local connections to the manufacturing system is restricted and managed.</p>	<p>62443-2-1:2009 4.3.3.7.3; 62443-3-3:2013 SR 2.1 AC-Controls AC-14</p> <p>AC-2(1)(3) AC-5 AC-6(1)(2)(5)(9)</p> <p>AC-2(11)(12)(13)</p>

This publication is available free of charge from: <https://doi.org/10.6028/NIST.IR.8183>

Function	Category	Subcategory	Manufacturing Profile	Reference
PROTECT	Access Control (PR.AC)	PR.AC-5	<p style="text-align: center;">Low</p> <p>Protect network integrity of the manufacturing system, incorporating network segmentation and segregation where appropriate. Identify and control connections between system components. Monitor and control connections and communications at the external boundary and at key internal boundaries within the manufacturing system. Employ boundary protection devices.</p> <p>Boundary protection mechanisms include, for example, routers, gateways, unidirectional gateways, data diodes, and firewalls separating system components into logically separate networks or subnetworks.</p>	<p>62443-2-1:2009 4.3.3.4 62443-3-3:2013 SR 3.1, 3.8</p> <p>SC-7</p>
			<p style="text-align: center;">Moderate</p> <p>Limit external connections to the manufacturing system. Monitor and use managed interfaces to conduct external system connections. Deny by default connections to the managed interface. Disable split tunneling and covert channel options in conjunction with remote devices. Ensure the manufacturing system fails securely in the event of the operational failure of a boundary protection device.</p>	<p>AC-4</p>
			<p style="text-align: center;">High</p> <p>Employ, where feasible, authenticated proxy servers for defined communications traffic between the manufacturing system and external networks.</p> <p>Isolate manufacturing system components performing different missions.</p>	<p>SC-7(8) SC-7(21)</p>
	Awareness and Training (PR.AT)	PR.AT-1	<p style="text-align: center;">Low</p> <p>Provide security awareness training for all manufacturing system users and managers.</p> <p>Training could include, for example, a basic understanding of the protections and user actions needed to maintain security of the system, responding to suspected cybersecurity incidents, and awareness of operational security.</p>	<p>62443-2-1:2009 4.3.2.4.2</p> <p>AT-2</p>
			<p style="text-align: center;">Moderate and High</p> <p>Incorporate insider threat recognition and reporting into security awareness training.</p>	<p>AT-2(2)</p>
		PR.AT-2	<p style="text-align: center;">Low, Moderate and High</p> <p>Ensure that users with privileged access to the manufacturing system understand the requirements and responsibilities of their assignments.</p> <p>Establish standards for measuring, building, and validating individual qualifications for privileged users.</p>	<p>62443-2-1:2009 4.3.2.4.2</p> <p>AT-3 PM-13</p>

Function	Category	Subcategory	Manufacturing Profile	Reference
PROTECT	Awareness and Training (PR.AT)	<u>PR.AT-3</u>	<p align="center">Low</p> <p>Establish and enforce security requirements for third-party providers and users. Ensure that third-party providers understand their responsibilities regarding the security of the manufacturing system and the responsibilities of their assignments. Require notifications be given for any personnel transfers, termination, or transition involving personnel with physical or logical access to the manufacturing system components.</p> <p>Ensure that providers of external system services comply with defined security requirements. Monitor and audit external service providers for security compliance.</p>	<p>ISA 62443-2-1:2009 4.3.2.4.2</p> <p><u>PS-7</u></p> <p><u>SA-9</u></p>
			<p align="center">Moderate and High</p> <p>Require external service providers to identify the functions, ports, protocols, and services necessary for the connection services.</p>	<p><u>SA-9(2)</u></p>
			<p align="center">Low, Moderate and High</p> <p>Ensure that senior executives understand the requirements for the security and protection of the manufacturing system, and their responsibilities for achieving them.</p>	<p>62443-2-1:2009 4.3.2.4.2</p> <p><u>AT-3</u></p>
	Data Security (PR.DS)	<u>PR.DS-1</u>	<p align="center">Low</p> <p>None</p>	<p>62443-3-3:2013 SR 3.4, 4.1</p>
			<p align="center">Moderate and High</p> <p>Protect while at rest manufacturing system information determined to be critical.</p>	<p><u>SC-28</u></p>
			<p align="center">Low</p> <p>None</p>	<p>62443-3-3:SR 3.1,3.8,4.1</p>
Data Security (PR.DS)	<u>PR.DS-2</u>	<p align="center">Moderate and High</p> <p>Protect manufacturing system information when in transit.</p>	<p><u>SC-8</u></p>	
		<p>Implement cryptographic mechanisms where determined necessary to prevent unauthorized access, distortion, or modification of system data and audit records.</p>	<p><u>SC-8(1)</u></p>	

Function	Category	Subcategory	Manufacturing Profile	Reference
PROTECT	Data Security (PR.DS)	<u>PR.DS-3</u>	Low	62443-2-1:2009 4. 4.3.3.3.9
			Enforce accountability for all manufacturing system components throughout the system lifecycle, including removal, transfers, and disposition.	62443-3-3:2013 SR 4.2
			Sanitize portable media prior to disposal, release, or reuse. All system components entering and exiting the facility are authorized, monitored, and controlled, and records are maintained of those items.	<u>PE-16</u> <u>MP-6</u>
			Moderate	
		Update the inventory of manufacturing system components as an integral part of component installations, removals, and system updates.	<u>CM-8(1)</u>	
		High		
Employ automated mechanisms where safe and feasible to maintain an up-to-date, complete, accurate, and readily available inventory of manufacturing system components. Ensure that disposal actions are approved, tracked, documented, and verified.	<u>CM-8(2)</u> <u>MP-6(1)</u>			
		<u>PR.DS-4</u>	Low	62443-3-3:2013 SR 7.1, 7.2
Ensure that adequate resources are maintained for manufacturing system information processing, networking, telecommunications, and data storage.	<u>CP-2(a).1.4.5</u>			
Off-load audit records from the manufacturing system for processing to an alternate system.				
Moderate and High	<u>AU-4(1)</u>			
Protect the manufacturing system against, or limit the effects of, denial of service attacks.	<u>SC-5</u>			
		<u>PR.DS-5</u>	Low	62443-3-3:2013 SR 5.2
Protect the manufacturing system against data leaks. Monitor the manufacturing system at the external boundary and at key internal points to detect unauthorized access and use.	<u>SI-4</u> <u>SC-7</u>			
Develop and document access agreements for all users of the manufacturing system.	<u>PS-6</u>			
Moderate and High				
Regulate the information flow within the manufacturing system and to outside systems. Enforce controls restricting connections to only authorized interfaces. Heighten system monitoring activity whenever there is an indication of increased risk to manufacturing operations and assets.	<u>AC-4</u> <u>SC-7(3)(4)</u> <u>SI-4(4)</u>			
Protect the system from information leakage due to electromagnetic signals emanations.	<u>PE-19</u>			

Function	Category	Subcategory	Manufacturing Profile	Reference
PROTECT	Data Security (PR.DS)	<u>PR.DS-6</u>	Low	62443-3-3:SR 3.1, 3.3, 3.4,
			Moderate	
			<p data-bbox="678 287 1696 375">Employ software, firmware, and information integrity checks to detect unauthorized changes to manufacturing system components during storage, transport, startup and when determined necessary.</p> <p data-bbox="678 394 1696 451">Incorporate the detection of unauthorized changes to the manufacturing system into the system's incident response capability.</p>	<p data-bbox="1759 295 1822 319"><u>SI-7(1)</u></p> <p data-bbox="1759 394 1822 418"><u>SI-7(7)</u></p>
			High	<p data-bbox="1759 576 1822 600"><u>SI-7(2)</u></p> <p data-bbox="1759 657 1822 682"><u>SI-7(5)</u></p>
		<u>PR.DS-7</u>	Low, Moderate and High	
			<p data-bbox="678 760 1696 816">Utilize an off-line development and testing system for implementing and testing changes to the manufacturing system.</p>	<u>CM-2</u>
	Information Protection Processes and Procedures (PR.IP)	<u>PR.IP-1</u>	<p data-bbox="667 889 1745 930" style="text-align: center;">Low</p> <p data-bbox="678 933 1623 958">Develop, document, and maintain a baseline configuration for the manufacturing system.</p> <p data-bbox="678 990 1728 1144">Baseline configurations include for example, information about manufacturing system components (e.g. software license information, software version numbers, HMI and other ICS component applications, software, operating systems), current version numbers and patch information on operating systems and applications; and configuration settings/parameters), network topology, and the logical placement of those components within the system architecture.</p> <p data-bbox="678 1177 1470 1234">Configure the manufacturing system to provide only essential capabilities. Review the baseline configuration and disable unnecessary capabilities.</p>	<p data-bbox="1759 889 1990 930">62443-2-1:2009 4.3.4.3.2, 62443-3-3:2013 SR 7.6</p> <p data-bbox="1759 963 1822 987"><u>CM-2</u></p> <p data-bbox="1759 987 1822 1011"><u>CM-6</u></p> <p data-bbox="1759 1144 1822 1169"><u>CM-7</u></p> <p data-bbox="1759 1169 1843 1193"><u>CM-7(1)</u></p>

Function	Category	Subcategory	Manufacturing Profile	Reference
<p style="text-align: center;">PROTECT</p>	<p style="text-align: center;">Information Protection Processes and Procedures (PR.IP)</p>	<p style="text-align: center;"><u>PR.IP-1</u></p>	<p style="text-align: center;">Moderate</p> <p>Review and update the baseline configuration of the manufacturing system as an integral part of system component installations and upgrades. Retain previous versions of the baseline configuration to support rollback. Employ software program usage restrictions.</p> <p>Develop a configuration management plan for the manufacturing system. The plan includes, for example, configuration processes, roles, lifecycle definition, configuration items, and control methods.</p> <p>Define configuration parameters, capabilities, and fail-to-known-state procedures such that, upon a system failure (or failure conditions), assets revert to a state that achieves a predetermined mode of operation.</p> <p>Employ a deny-all, permit-by-exception policy to allow the execution of only authorized software programs.</p> <p style="text-align: center;">High</p> <p>Employ automated mechanisms where feasible to maintain an up-to-date, complete, accurate, and readily available baseline configuration of the manufacturing system. Automated system support includes for example, documentation, notification, and management of the change control process on the manufacturing system.</p> <p>Review system changes to determine whether unauthorized changes have occurred.</p>	<p>CM-2(1)(3)</p> <p>CM-7(2)</p> <p>CM-9</p> <p>SC-24</p> <p>CM-7(5)</p> <p>CM-2(2)</p> <p>CM-3(1)</p> <p>CM-5(1)(2)</p>
		<p style="text-align: center;"><u>PR.IP-2</u></p>	<p style="text-align: center;">Low</p> <p>Manage the manufacturing system using a system development life cycle that includes security considerations.</p> <p>Include security requirements into the acquisition process of the manufacturing system and its components.</p> <p style="text-align: center;">Moderate and High</p> <p>Require the developer of the manufacturing system and system components to provide a description of the functional properties of security controls, and design and implementation information for security-relevant system interfaces.</p> <p>Apply security engineering principles into the specification, design, development, implementation, and modification of the manufacturing system.</p> <p>Employ configuration management and change control during the development of the manufacturing system and its components, and include flaw tracking and resolution, and security testing.</p>	<p>62443-2-1:2009 4.3.4.3.3</p> <p>SA-3</p> <p>SA-4</p> <p>SA-4(1)(2)</p> <p>SA-8</p> <p>SA-10</p>

This publication is available free of charge from: https://doi.org/10.6028/NIST.IR.8183

Function	Category	Subcategory	Manufacturing Profile	Reference
PROTECT	Information Protection Processes and Procedures (PR.IP)	<u>PR.IP-3</u>	Low	62443-2-1:2009 4.3.4.3.2 62443-3-3:2013 SR 7.6 CM-3 CM-4
			Employ configuration change control for the manufacturing system and its components. Conduct security impact analyses in connection with change control reviews.	
			Moderate	Test, validate, and document changes to the manufacturing system before implementing the changes on the operational system. CM-3(2)
			Review and authorize proposed configuration-controlled changes prior to implementing them on the manufacturing system.	
			High	Employ automated mechanisms where feasible to support the change control process. CM-3(1) CM-4(1)
		Conduct security impact analysis in a separate test environment before implementation into an operational environment for planned changes to the manufacturing system.		
		<u>PR.IP-4</u>	Low	62443-2-1:2009 4.3.4.3.9 62443-3-3:2013 SR 7.3, 7.4 CP-9 CP-4
			Conduct and maintain backups for manufacturing system data. Manufacturing system data includes for example software, configurations and settings, documentation, system configuration data including computer configuration backups, application configuration backups, operational control limits, control bands and set points for pre-incident operation for all ICS programmable equipment	
			Moderate	Verify the reliability and integrity of backups. CP-9(1)
			Coordinate backup testing with organizational elements responsible for related plans. CP-4(1)	
Establish a separate alternate storage site for system backups and ensure the same security safeguards are employed. CP-6				
High	Include into contingency plan testing the conducting of restorations from backup data. CP-9(2) CP-9(3)			
Store critical manufacturing system backup information separately.				

Function	Category	Subcategory	Manufacturing Profile	Reference	
PROTECT	Information Protection Processes and Procedures (PR.IP)	<u>PR.IP-5</u>	Low and Moderate	62443-2-1:2009 4.3.3.3.1	
			Define, implement, and enforce policy and regulations regarding emergency and safety systems, fire protection systems, and environment controls for the manufacturing system.	<u>PE-Family</u> [10,12,13,14,15,18] <u>PE-13(3)</u>	
			Fire suppression mechanisms should take the manufacturing environment into account (e.g., water sprinkler systems could be hazardous in specific environments).		
				High	
		Employ fire detection devices that activate and notify key personnel automatically in the event of a fire.	<u>PE-13(1)(2)</u>		
			Low and Moderate	62443-2-1:4.3.3.3.1 62443-3-3:2013 SR 4.2	
		Ensure that manufacturing system data is destroyed according to policy.	<u>MP-6</u>		
			High		
		Ensure that media sanitization actions are approved, tracked, documented, and verified. Test sanitization equipment and procedures.	<u>MP-6(1)(2)(3)</u>		
Apply nondestructive sanitization techniques to portable storage devices connecting to the manufacturing system.					
		Low	62443-2-1:2009 4.4.3.1, 4.4.3.2, 4.4.3.3, 4.4.3.4,		
Incorporate improvements derived from the monitoring, measurements, assessments, and lessons learned into protection process revisions.	<u>PM-6</u> <u>CA-2</u> <u>CA-7</u> <u>SI-4</u>				
Ensure that the security plan for the manufacturing system facilitates the review, testing, and continual improvement of the security protection processes.	<u>PL-2</u> , <u>PM-14</u>				
	Moderate and High				
Employ independent teams to assess the protection process.	<u>CA-2(1)</u> , <u>CA-7(1)</u>				
Independent teams, for example, may include internal or external impartial personnel. Impartiality implies that assessors are free from any perceived or actual conflicts of interest with regard to the development, operation, or management of the manufacturing system under assessment or to the determination of security control effectiveness.					

Function	Category	Subcategory	Manufacturing Profile	Reference
PROTECT	Information Protection Processes and Procedures (PR.IP)	<u>PR.IP-8</u>	Low, Moderate and High	<u>AC-21</u> <u>AC-21(1)</u>
			Collaborate and share information about manufacturing system related security incidents and mitigation measures with designated sharing partners.	
		<u>PR.IP-9</u>	Low	62443-2-1:2009 4.3.2.5.3, <u>CP-2</u> <u>IR-8</u>
			Develop and maintain response and recovery plans that identify essential functions and associated contingency requirements, as well as providing a roadmap for implementing incident response. Plans should incorporate recovery objectives, restoration priorities, metrics, contingency roles, personnel assignments and contact information. Address maintaining essential functions despite system disruption, and the eventual restoration of the manufacturing system.	
			Define incident types, resources and management support needed to effectively maintain and mature the incident response and contingency capabilities.	
		<u>PR.IP-10</u>	Moderate and High	<u>CP-2(1)</u>
Coordinate contingency plan development with stakeholders responsible for related plans.				
<u>PR.IP-10</u>	Low	162443-2-1:2009 4.3.2.5.7 62443-3-3:2013 SR 3.3 <u>CP-4</u> , <u>PM-14</u>		
	Review response and recovery plans to determine the effectiveness of the plans, and the readiness to execute the plans.			
	Moderate and High			
Test response and recovery plans to determine the effectiveness of the plans, and the readiness to execute the plans.	<u>CP-4(1)</u> <u>IR-3(2)</u>			
Coordinate testing of response and recovery plans with relevant stakeholders.				
Related plans include, for example, Business Continuity Plans, Disaster Recovery Plans, Continuity of Operations Plans, Crisis Communications Plans, Critical Infrastructure Plans, Cyber Incident Response Plans, and Occupant Emergency Plans.				

Function	Category	Subcategory	Manufacturing Profile	Reference
PROTECT	Information Protection Processes and Procedures (PR.IP)	<u>PR.IP-11</u>	<p style="text-align: center;">Low, Moderate and High</p> <p>Develop and maintain a personnel security program for the manufacturing system. Personnel security program should include policy, position risk designations, personnel screening, terminations and transfers, access agreements, third-party roles and responsibilities, and personnel sanctions.</p>	<p>62443-2-1:2009 4.3.3.2.1</p> <p><u>PS- Family</u></p>
		<u>PR.IP-12</u>	<p style="text-align: center;">Low</p> <p>Establish and maintain a process that allows continuous review of vulnerabilities, and defines strategies to mitigate them.</p> <p style="text-align: center;">Moderate</p> <p>Restrict access to privileged vulnerability data.</p> <p style="text-align: center;">High</p> <p>Identify where manufacturing system vulnerabilities may be exposed to adversaries.</p>	<p><u>RA-3, SI-2</u></p> <p><u>RA-5(5)</u></p> <p><u>RA-5(4)</u></p>
		<u>PR.MA-1</u>	<p style="text-align: center;">Low</p> <p>Schedule, perform, document and review records of maintenance and repairs on manufacturing system components.</p> <p>Establish a process for maintenance personnel authorization, and escort non-authorized maintenance personnel.</p> <p>Verify impacted security controls following maintenance or repairs.</p> <p style="text-align: center;">Moderate</p> <p>Enforce approval requirements, control, and monitoring of maintenance tools for use on the manufacturing system.</p> <p>Maintenance tools can include, for example, hardware/software diagnostic test equipment, hardware/software packet sniffers and laptops.</p> <p>Perform preventative maintenance at defined intervals. Inspect maintenance tools brought into the facility.</p> <p>Scan maintenance tools and portable storage devices for malicious code before they are used on the manufacturing system.</p>	<p>62443-2-1:2009 4.3.3.3.7</p> <p><u>MA-2</u></p> <p><u>MA-5</u></p> <p><u>MA-2</u></p> <p><u>MA-3</u></p> <p><u>MA-6</u> <u>MA-3(1)</u></p> <p><u>MA-3(2)</u></p>

Function	Category	Subcategory	Manufacturing Profile	Reference
PROTECT	Maintenance (PR.MA)	<u>PR.MA-1</u>	High	<u>MA-2(2)</u> <u>MA-3(3)</u>
			Employ automated mechanisms where feasible to schedule, conduct, and document maintenance and repairs; and to produce records of maintenance activity. Prevent the unauthorized removal of maintenance equipment containing manufacturing system information.	
	Protective Technology (PR.PT)	<u>PR.PT-1</u>	Low and Moderate	62443-2-1:2009 4.3.3.6.5 <u>MA-4</u> Require that diagnostic services pertaining to remote maintenance be performed from a system that implements a security capability comparable to the capability implemented on the manufacturing system. <u>MA-4(3)</u>
			High	
	Protective Technology (PR.PT)	<u>PR.PT-1</u>	Low	62443-2-1:2009 4.3.3.3.9, 62443-3-3:2013 SR 2.8, <u>AU-3</u> <u>AU-5</u> <u>AU-8</u> Generate audit records containing information that establishes what type of event occurred, when the event occurred, where the event occurred, the source of the event, the outcome of the event, and the identity of any individuals or manufacturing components associated with the event. Generate time stamps from an internal system clock that is mapped to Coordinated Universal Time (UTC) or Greenwich Mean Time (GMT). Ensure that audit processing failures on the manufacturing system generate alerts and trigger defined responses. Review and update audit events. Employ automated mechanisms to integrate audit review, analysis, and reporting. Compare and synchronize the internal system clocks to an authoritative time source. Authoritative time sources include for example, an internal NTP server, radio clock, atomic clock, GPS time source. Integrate analysis of audit records with physical access monitoring. Conduct time correlation of audit records. Enable authorized individuals to extend audit capabilities when required by events.
Moderate				
High				
			High	<u>AU-5</u> <u>AU-2(3)</u> <u>AU-6(1)</u> <u>AU-7(1)</u> <u>AU-6(6)</u> <u>AU-12(1)</u> <u>AU-12(3)</u>

Function	Category	Subcategory	Manufacturing Profile	Reference
PROTECT	Protective Technology (PR.PT)	<u>PR.PT-2</u>	Low	62443-3-3:2013 SR 2.3
			Employ safeguards to restrict the use of portable storage devices.	<u>MP-2</u>
		Moderate and High		
		Protect and control portable storage devices containing manufacturing system data while in transit and in storage. Scan all portable storage devices for malicious code before they are used on the manufacturing system	<u>MP-4</u> <u>MP-7</u>	
		<u>PR.PT-3</u>	Low	62443-2-1:2009 4.3.3.5.1, 62443-3-3:2013 SR 1.1, SR
			Configure the manufacturing system to provide only essential capabilities.	<u>AC-3</u>
		Moderate and High		
		Disable defined functions, ports, protocols, and services within the manufacturing system deemed to be unnecessary. Employ technical safeguards to enforce a deny-all, permit-by-exception policy to only allow the execution of authorized software programs.	<u>CM-7(1)</u> <u>CM-7(5)</u>	
		<u>PR.PT-4</u>	Low	62443-3-3:2013 SR 3.1, SR
			Monitor and control communications at the external boundary and at key internal boundaries within the manufacturing system.	<u>SC-7</u>
			Moderate and High	
			Control the flow of information within the manufacturing system and between interconnected systems. Information flow may be supported, for example, by labeling or coloring physical connectors as an aid to manual hookup. Inspection of message content may enforce information flow policy. For example, a message containing a command to an actuator may not be permitted to flow between the control network and any other network. Physical addresses (e.g., a serial port) may be implicitly or explicitly associated with labels or attributes (e.g., hardware I/O address). Manual methods are typically static. Label or attribute policy mechanisms may be implemented in hardware, firmware, and software that controls or has device access, such as device drivers and communications controllers.	<u>AC-4</u>
Limit external connections to the system.	<u>SC-7(3)</u>			
Manage the interface for external telecommunication services by establishing a traffic flow policy, protecting the confidentiality and integrity of the information being transmitted, reviewing and documenting each exception to the traffic flow policy.	<u>SC-7(4)</u>			

Function	Category	Subcategory	Manufacturing Profile	Reference
DETECT	Anomalies and Events (DE.AE)	<u>DE.AE-1</u>	<p>Low, Moderate and High</p> <p>Ensure that a baseline of network operations and expected data flows for the manufacturing system is developed, documented, and maintained to detect events.</p>	<p>62443-2-1:2009 4.4.3.3</p> <p><u>CM-2</u></p>
		<u>DE.AE-2</u>	<p>Low</p> <p>Review and analyze detected events within the manufacturing system to understand attack targets and methods.</p> <p>Moderate and High</p> <p>Employ automated mechanisms where feasible to review and analyze detected events within the manufacturing system.</p>	<p>62443-2-1:2009 4.3.4.5.6, 62443-3-3:2013 SR 2.8, 2.9</p> <p><u>AU-6</u>, <u>IR-4</u></p> <p><u>AU-6(1)</u> <u>IR-4(1)</u></p>
		<u>DE.AE-3</u>	<p>Low and Moderate</p> <p>Ensure that event data is compiled and correlated across the manufacturing system using various sources such as event reports, audit monitoring, network monitoring, physical access monitoring, and user/administrator reports.</p> <p>High</p> <p>Integrate analysis of events where feasible with the analysis of vulnerability scanning information; performance data; manufacturing system monitoring, and facility monitoring to further enhance the ability to identify inappropriate or unusual activity.</p>	<p>62443-3-3:2013 SR 6.1</p> <p><u>IR-5</u></p> <p><u>AU-6(5)(6)</u>, <u>AU-12(1)</u></p>
		<u>DE.AE-4</u>	<p>Low</p> <p>Determine negative impacts to manufacturing operations, assets, and individuals resulting from detected events, and correlate with risk assessment outcomes.</p> <p>Moderate</p> <p>Employ automated mechanisms to support impact analysis.</p> <p>High</p> <p>Correlate detected event information and responses to achieve perspective on event impact across the organization.</p>	<p><u>RA-3</u></p> <p><u>IR-4(1)</u>, <u>SI-4(2)</u></p> <p><u>IR-4(4)</u></p>

Function	Category	Subcategory	Manufacturing Profile	Reference
DETECT	Anomalies and Events (DE.AE)	DE.AE-5	<p>Low</p> <p>Define incident alert thresholds for the manufacturing system.</p>	62443-2-1:2009 4.2.3.10 IR-4 , IR-5 , AU-2 , AU-3 , IR-8
			<p>Moderate and High</p> <p>Employ automated mechanisms where feasible to assist in the identification of security alert thresholds.</p>	IR-4(1) IR-5(1)
	Security Continuous Monitoring (DE.CM)	DE.CM-1	<p>Low</p> <p>Conduct ongoing security status monitoring of the manufacturing system network to detect defined cybersecurity events and indicators of potential cybersecurity events.</p> <p>Detect unauthorized local, network, and remote connections, and identify unauthorized use of the manufacturing system.</p> <p>Generate audit records for defined cybersecurity events.</p> <p>Monitor network communications at the external boundary of the system and at key internal boundaries within the system.</p> <p>Heighten system monitoring activity whenever there is an indication of increased risk.</p>	62443-3-3:2013 SR 6.2 CA-7d AC-2g , SI-4b AU-12c SC-7 , SI-4(4) SI-4e
			<p>Moderate</p> <p>Employ automated mechanisms to support detection of cybersecurity events.</p> <p>Generate system alerts when indications of compromise or potential compromise occur.</p>	AC-2 (1)(2)(3)(4) , SI-4(2) SI-4(5)
			<p>High</p> <p>Monitor for and report atypical usage of the manufacturing system.</p>	AC-2(12)
			<p>Low</p> <p>Conduct ongoing security status monitoring of the manufacturing system facility to detect physical security incidents.</p>	62443-2-1:2009 4.3.3.3.8 CA-7d , PE-6 , PE-3
DE.CM-2	<p>Moderate and High</p> <p>Employ independent teams to monitor the security of the physical environment.</p>	CA-7(1)		
	<p>Monitor physical intrusion alarms and surveillance equipment.</p> <p>Monitor physical access to the manufacturing system and devices in addition to the facility.</p>	PE-6(1) PE-6(4) PE-3(1)		

Function	Category	Subcategory	Manufacturing Profile	Reference
DETECT	Security Continuous Monitoring (DE.CM)	<u>DE.CM-3</u>	<p style="text-align: center;">Low, Moderate and High</p> <p>Conduct security status monitoring of personnel activity associated with the manufacturing system. Enforce software usage and installation restrictions.</p>	<p>62443-3-3:2013 SR 6.2</p> <p><u>CA-7d</u> <u>CM-10</u>, <u>CM-11</u></p>
		<u>DE.CM-4</u>	<p style="text-align: center;">Low</p> <p>Deploy malicious code protection mechanisms throughout the manufacturing system where safe and feasible to detect and eradicate malicious code. Update malicious code protection mechanisms whenever new releases are available in accordance with the configuration management policy and procedures for the manufacturing system.</p> <p style="text-align: center;">Moderate and High</p> <p>Manage for false positives during malicious code detection and eradication. Automatically update malicious code protection mechanisms where safe and feasible.</p>	<p>62443-2-1:2009 4.3.4.3.8 62443-3-3:2013 SR 3.2</p> <p><u>SI-3</u></p> <p><u>SI-3d</u> <u>SI-3(2)</u></p>
		<u>DE.CM-5</u>	<p style="text-align: center;">Low</p> <p>None</p> <p style="text-align: center;">Moderate and High</p> <p>Define acceptable and detect unacceptable mobile code and mobile code technologies. Mobile code technologies include, for example, Java, JavaScript, ActiveX, Postscript, PDF, Shockwave movies, Flash animations, and VBScript. Enforce usage restrictions and establish implementation guidance for acceptable mobile code and mobile code technologies for use with the manufacturing system. The use of mobile code technologies is determined after careful consideration and after verification that it does not adversely impact the operational performance of the manufacturing system.</p>	<p>62443-3-3:2013 SR 2.4</p> <p><u>SC-18</u></p>
		<u>DE.CM-6</u>	<p style="text-align: center;">Low Moderate and High</p> <p>Conduct ongoing security status monitoring of external service provider activity on the manufacturing system. Detect defined cybersecurity events and indicators of potential cybersecurity events from external service providers. Monitor compliance of external providers with personnel security policies and procedures, and contract security requirements.</p>	<p><u>CA-7d</u> <u>SI-4</u> <u>PS-7</u>, <u>SA-4</u>, <u>SA-9</u>, <u>MA-5</u></p>

Function	Category	Subcategory	Manufacturing Profile	Reference
DETECT	Security Continuous Monitoring (DE.CM)	<u>DE.CM-7</u>	Low	<u>CA-7d</u> <u>CM-8</u>
			<p>Conduct ongoing security status monitoring on the manufacturing system for unauthorized personnel, connections, devices, access points, and software.</p> <p>Monitor for system inventory discrepancies.</p>	
		<u>DE.CM-8</u>	Moderate and High	<u>SI-4</u> <u>CM-3</u>
			<p>Deploy monitoring devices strategically within the manufacturing system to collect essential information to detect specific events of interest.</p> <p>Monitor for unauthorized configuration changes to the manufacturing system.</p>	
	Detection Processes (DE.DP)	<u>DE.DP-1</u>	Low, Moderate and High	62443-2-1:2009 4.2.3.1 <u>RA-5</u>
			<p>Conduct vulnerability scans on the manufacturing system where safe and feasible. Include analysis, remediation, and information sharing in the vulnerability scanning process.</p> <p>Employ control system-specific vulnerability scanning tools and techniques where safe and feasible.</p> <p>Active vulnerability scanning, which introduces network traffic, is used with care on manufacturing systems to ensure that system functions are not adversely impacted by the scanning process.</p>	
Detection Processes (DE.DP)	<u>DE.DP-2</u>	Low, Moderate and High	62443-2-1:2009 4.4.3.1 <u>CA-2</u> , <u>CA-7</u> , <u>PM-14</u>	
		<p>Define roles and responsibilities for detection activities on the manufacturing system and ensure accountability.</p>		
Detection Processes (DE.DP)	<u>DE.DP-2</u>	Low, Moderate and High	62443-2-1:2009 4.4.3.2 <u>CA-2</u>	
		<p>Conduct detection activities in accordance with applicable federal and state laws, industry regulations and standards, policies, and other applicable requirements.</p>		

Function	Category	Subcategory	Manufacturing Profile	Reference
DETECT	Detection Processes (DE.DP)	DE.DP-3	Low, Moderate and High	62443-2-1:2009 4.4.3.2 62443-3-3:2013 SR 3.3
			Validate that event detection processes are operating as intended.	PM-14
		DE.DP-4	Low	62443-2-1:2009 4.3.4.5.9 62443-3-3:2013 SR 6.1
			Communicate event detection information to defined personnel. Event detection information includes for example, alerts on atypical account usage, unauthorized remote access, wireless connectivity, mobile device connection, altered configuration settings, contrasting system component inventory, use of maintenance tools and nonlocal maintenance, physical access, temperature and humidity, equipment delivery and removal, communications at the information system boundaries, use of mobile code, use of VoIP, and malware disclosure.	AU-6 SI-4
			Moderate and High	Employ automated mechanisms and system generated alerts to support event detection communication.
		DE.DP-5	Low	62443-2-1:2009 4.4.3.4
			Incorporate improvements derived from the monitoring, measurements, assessments, and lessons learned into detection process revisions.	CA-2 , CA-7 , SI-4
			Ensure the security plan for the manufacturing system provides for the review, testing, and continual improvement of the security detection processes.	PL-2 , PM-14
			Moderate	Employ independent teams to assess the detection process.
High	Conduct specialized assessments including in-depth monitoring, vulnerability scanning, malicious user testing, insider threat assessment, performance/load testing, and verification and validation testing on the manufacturing system.	CA-2(7)		

Function	Category	Subcategory	Manufacturing Profile	Reference
RESPOND	Response Planning (RS.RP)	<u>RS.RP-1</u>	<p>Low, Moderate and High</p> <p>Execute the response plan during or after a cybersecurity event on the manufacturing system.</p>	<p>62443-2-1:2009 4.3.4.5.1</p> <p><u>IR-8</u>, <u>IR-4</u></p>
	Communications (RS.CO)	<u>RS.CO-1</u>	<p>Low, Moderate and High</p> <p>Ensure personnel understand objectives, restoration priorities, task sequences and assignment responsibilities for event response.</p>	<p>62443-2-1:2009 4.3.4.5.2</p> <p><u>CP-2</u>, <u>CP-3</u>, <u>IR-8</u></p>
		<u>RS.CO-2</u>	<p>Low</p> <p>Employ prompt reporting to appropriate stakeholders for cybersecurity events on the manufacturing system.</p> <p>Ensure that cybersecurity events on the manufacturing system are reported consistent with the response plan.</p>	<p>62443-2-1:2009 4.3.4.5.5</p> <p><u>IR-6</u>,</p> <p><u>AU-6</u></p>
			<p>Moderate and High</p> <p>Employ automated mechanisms to assist in the reporting of cybersecurity events.</p>	<p><u>IR-6(1)</u></p>
			<p>Low, Moderate and High</p> <p>Share cybersecurity incident information with relevant stakeholders per the response plan.</p>	<p>62443-2-1:2009 4.3.4.5.2</p> <p><u>CA-2d</u>, <u>CA-7g</u>, <u>CP-2f</u></p>
		<u>RS.CO-4</u>	<p>Low</p> <p>Coordinate cybersecurity incident response actions with all relevant stakeholders.</p> <p>Stakeholders for incident response include for example, mission/business owners, manufacturing system owners, integrators, vendors, human resources offices, physical and personnel security offices, legal departments, operations personnel, and procurement offices.</p>	<p>62443-2-1:2009 4.3.4.5.5</p> <p><u>CP-2</u>, <u>CP-2(1)</u>, <u>IR-4</u></p>
	<p>Moderate and High</p> <p>Employ automated mechanisms to support stakeholder coordination.</p>		<p><u>IR-4(1)</u></p>	

Function	Category	Subcategory	Manufacturing Profile	Reference
RESPOND	Communications (RS.CO)	<u>RS.CO-5</u>	<p>Low, Moderate and High</p> <p>Share cybersecurity event information voluntarily, as appropriate, with industry security groups to achieve broader cybersecurity situational awareness.</p>	<u>PM-15</u> , <u>SI-5</u>
			<p>For example, the DHS National Cybersecurity & Communications Integration Center (NCCIC) [6] serves as a centralized location where operational elements involved in cybersecurity and communications reliance are coordinated and integrated. The Industrial Control Systems Cyber Emergency Response Team (ICS-CERT) [7] collaborates with international and private sector Computer Emergency Response Teams (CERTs) to share control systems-related cybersecurity incidents and mitigation measures.</p>	
	Analysis (RS.AN)	<u>RS.AN-1</u>	<p>Low</p> <p>Investigate cybersecurity-related notifications generated from detection systems.</p>	62443-2-1:2009 4.3.4.5.6 62443-3-3:2013 SR 6.1
			<p>Moderate and High</p> <p>Employ automated mechanisms to assist in the investigation and analysis of cybersecurity-related notifications.</p>	<u>IR-4</u> , <u>CA-7</u> , <u>AU-6</u>
			<p>Low</p> <p>Understand the full implication of the cybersecurity incident based on thorough investigation and analysis results.</p>	62443-2-1:2009 4.3.4.5.6
			<p>Moderate and High</p> <p>Employ automated mechanisms to support incident impact analysis.</p>	<u>IR-4(4)</u>
		<u>RS.AN-2</u>	<p>Moderate and High</p> <p>Correlate detected event information and incident responses with risk assessment outcomes to achieve perspective on incident impact across the organization.</p>	<u>IR-5(1)</u> , <u>SI-4(2)</u>
			<p>Low</p> <p>Conduct forensic analysis on collected cybersecurity event information to determine root cause.</p>	62443-2-1:2009 4.3.4.5.6
			<p>Moderate and High</p> <p>Employ automated mechanisms to support incident impact analysis.</p>	<u>IR-4(1)</u> , <u>SI-4(2)</u>
			<p>Low</p> <p>Conduct forensic analysis on collected cybersecurity event information to determine root cause.</p>	62443-3-3:SR 2.8, 2.9, 2.10
<u>RS.AN-3</u>	<p>Moderate and High</p> <p>Provide on-demand audit review, analysis, and reporting for after-the-fact investigations of cybersecurity incidents.</p>	<u>IR-4</u>		
	<p>Low, Moderate and High</p> <p>Categorize cybersecurity incidents according to level of severity and impact consistent with the response plan.</p>	<u>AU-7(1)</u>		
<u>RS.AN-4</u>	<p>Low, Moderate and High</p> <p>Categorize cybersecurity incidents according to level of severity and impact consistent with the response plan.</p>	62443-2-1:2009 4.3.4.5.6		
			<p>Low, Moderate and High</p> <p>Categorize cybersecurity incidents according to level of severity and impact consistent with the response plan.</p>	<u>RA-3</u> , <u>PM-9</u> , <u>IR-4</u>

Function	Category	Subcategory	Manufacturing Profile	Reference
RESPOND	Mitigation (RS.MI)	<u>RS.MI-1</u>	<p>Low, Moderate and High</p> <p>Contain cybersecurity incidents to minimize impact on the manufacturing system.</p>	62443-2-1:2009 4.3.4.5.6 62443-3-3:2013 SR 5.1, SR <u>IR-4</u> , <u>IR-4(1)</u>
		<u>RS.MI-2</u>	<p>Low</p> <p>Mitigate cybersecurity incidents occurring on the manufacturing system.</p>	62443-2-1:2009 4.3.4.5.6, <u>IR-4</u>
			<p>Moderate and High</p> <p>Employ automated mechanisms to support the cybersecurity incident mitigation process.</p>	<u>IR-4(1)</u>
	<u>RS.MI-3</u>	<p>Low, Moderate and High</p> <p>Ensure that vulnerabilities identified while responding to a cybersecurity incident are mitigated or documented as accepted risks.</p>	<u>RA-5</u> , <u>RA-3</u>	
	Improvements (RS.IM)	<u>RS.IM-1</u>	<p>Low, Moderate and High</p> <p>Incorporate lessons learned from ongoing incident handling activities into incident response procedures, training, and testing, and implement the resulting changes accordingly.</p>	62443-2-1:2009 4.3.4.5.10 <u>IR-4</u>
		<u>RS.IM-2</u>	<p>Low, Moderate and High</p> <p>Update the response plans to address changes to the organization, manufacturing system, attack vectors, or environment of operation and problems encountered during plan implementation, execution, or testing.</p> <p>Updates may include, for example, responses to disruptions or failures, and predetermined procedures.</p> <p>Enable a process for the response plan to evolve to reflect new threats, improved technology, and lessons learned.</p>	<u>CP-2</u>

Function	Category	Subcategory	Manufacturing Profile	Reference
RECOVER	Recovery Planning (RC.RP)	RC.RP-1	<p>Low and Moderate</p> <p>Execute the recovery plan during or after a cybersecurity incident on the manufacturing system.</p> <p>Restore the manufacturing system within a predefined time-period from configuration-controlled and integrity-protected information representing a known, operational state for the components.</p>	<p>IR-8, CP-10</p> <p>CP-10(4)</p>
			<p>High</p> <p>Continue essential manufacturing functions and services with little or no loss of operational continuity, and sustain continuity until full system restoration.</p>	<p>CP-2(5)</p>
			<p>Low, Moderate and High</p> <p>Incorporate lessons learned from ongoing recovery activities into system recovery procedures, training, and testing, and implement the resulting changes accordingly.</p>	<p>62443-2-1 4.4.3.4</p> <p>IR-4</p>
	Improvements (RC.IM)	RC.IM-2	<p>Low, Moderate and High</p> <p>Update the recovery plan to address changes to the organization, manufacturing system, or environment of operation and problems encountered during plan implementation, execution, or testing.</p> <p>Ensure that updates are integrated into the recovery plans.</p>	<p>CP-2, IR-8</p>
			<p>Low</p> <p>Centralize and coordinate information distribution, and manage the public facing representation of the organization.</p> <p>Public relations management may include, for example, managing media interactions, coordinating and logging all requests for interviews, handling and ‘triaging’ phone calls and e-mail requests, matching media requests with appropriate and available internal experts who are ready to be interviewed, screening all of information provided to the media, ensuring personnel are familiar with public relations and privacy policies.</p>	<p>COBIT 5 EDM03.02</p>
	Communications (RC.CO)	RC.CO-1	<p>Moderate</p> <p>Assign a Public Relations Officer.</p>	
<p>High</p> <p>Pre-establish media contacts.</p> <p>Utilize external assets to manage public relations.</p>				

Function	Category	Subcategory	Manufacturing Profile	Reference
RECOVER	Communications (RC.CO)	RC.CO-2	<p style="text-align: center;">Low, Moderate and High</p> <p>Employ a crisis response strategy to protect against negative impact and repair organizational reputation.</p> <p>Crisis response strategies include, for example, actions to shape attributions of the crisis, change perceptions of the organization in crisis, and reduce the negative effect generated by the crisis.</p>	COBIT 5 EDM03.02
		RC.CO-3	<p style="text-align: center;">Low, Moderate and High</p> <p>Communicate recovery activities to all relevant stakeholders, and executive and management teams.</p>	CP-2 IR-4

Appendix A - Acronyms and Abbreviations

Selected acronyms and abbreviations used in the Manufacturing Profile are defined below.

CAN	Controller Area Network
CSF	Cybersecurity Framework
FIPS	Federal Information Processing Standards
HMI	Human Machine Interface
ICS	Industrial Control System
ICS-CERT	Industrial Control Systems Cyber Emergency Response Team
IEC	International Electrotechnical Commission
ISA	The International Society of Automation
IT	Information Technology
LAN	Local Area Network
NCCIC	National Cybersecurity & Communications Integration Center
NIST	National Institute of Standards and Technology
NVD	National Vulnerability Database
OT	Operational Technology
PLC	Programmable Logic Controller
RF	Radio Frequency
RTU	Remote Terminal Unit
US-CERT	United States Computer Emergency Readiness Team
VPN	Virtual Private Network

Appendix B - Glossary

Selected terms used in the Manufacturing Profile are defined below.

Actuator - A device for moving or controlling a mechanism or system. It is operated by a source of energy, typically electric current, hydraulic fluid pressure, or pneumatic pressure, and converts that energy into motion. An actuator is the mechanism by which a control system acts upon an environment. The control system can be simple (a fixed mechanical or electronic system), software-based (e.g. a printer driver, robot control system), or a human or other agent. [800-82]

Business/Mission Objectives - Broad expression of business goals. Specified target outcome for business operations.

Capacity Planning - Systematic determination of resource requirements for the projected output, over a specific period. [businessdictionary.com]

Category - The subdivision of a Function into groups of cybersecurity outcomes closely tied to programmatic needs and particular activities.

Critical Infrastructure - Essential services and related assets that underpin American society and serve as the backbone of the nation's economy, security, and health. [DHS]

Criticality Reviews - A determination of the ranking and priority of manufacturing system components, services, processes, and inputs in order to establish operational thresholds and recovery objectives.

Critical Services - The subset of mission essential services required to conduct manufacturing operations. Function or capability that is required to maintain health, safety, the environment and availability for the equipment under control. [62443]

Cyber Risk - Risk of financial loss, operational disruption, or damage, from the failure of the digital technologies employed for informational and/or operational functions introduced to a manufacturing system via electronic means from the unauthorized access, use, disclosure, disruption, modification, or destruction of the manufacturing system.

Cybersecurity - The process of protecting information by preventing, detecting, and responding to attacks. [CSF]

Defense-in-depth - The application of multiple countermeasures in a layered or stepwise manner to achieve security objectives. The methodology involves layering heterogeneous security technologies in the common attack vectors to ensure that attacks missed by one technology are caught by another. [62443 1-1]

Environmental Support – Any environmental factor for which the organization determines that it needs to continue to provide support in a contingency situation, even if in a degraded state.

This could include factors such as power, air conditioning, humidity control, fire protection, lighting, etc.

For example, while developing the contingency plan, the organization may determine that it is necessary to continue to ensure the appropriate temperature and humidity during a contingency situation so they would plan for the capacity to support that via supplemental/mobile air conditioning units, backup power, etc. and the associated procedures to ensure cutover operations. Such determinations are based on an assessment of risk, system categorization (impact level), and organizational risk tolerance.

Event - Any observable occurrence on a manufacturing system. Events can include cybersecurity changes that may have an impact on manufacturing operations (including mission, capabilities, or reputation). [CSF]

Fail to Known State – Upon a disruption event that causes the system to fail, it fails to a pre-determined state. Failure in a known safe state helps to prevent systems from failing to a state that may cause injury to individuals or destruction to property. Preserving manufacturing system state information facilitates system restart and return to the operational mode of organizations with less disruption of mission/business processes. [NVD.NIST]

Firmware - Software program or set of instructions programmed on the flash ROM of a hardware device. It provides the necessary instructions for how the device communicates with the other computer hardware. [Techterms.com]

Framework - The Cybersecurity Framework developed for defining protection of critical infrastructure. It provides a common language for understanding, managing, and expressing cybersecurity risk both internally and externally. Includes activities to achieve specific cybersecurity outcomes, and references examples of guidance to achieve those outcomes.

Function - Primary unit within the Cybersecurity Framework. Exhibits basic cybersecurity activities at their highest level.

Incident - An occurrence that actually or potentially jeopardizes the confidentiality, integrity, or availability of an information system or the information the system processes, stores, or transmits or that constitutes a violation or imminent threat of violation of security policies, security procedures, or acceptable use policies. [CSF]

Informative References - Specific sections of standards, guidelines, and practices common among critical infrastructure sectors that illustrate a method to achieve the outcomes associated with each Subcategory in the Cybersecurity Framework.

Integrator - A value-added engineering organization that focuses on industrial control and information systems, manufacturing execution systems, and plant automation, that has application knowledge and technical expertise, and provides an integrated solution to an engineering problem. This solution includes final project engineering, documentation, procurement of hardware, development of custom software, installation, testing, and commissioning. [CSIA.com]

Manufacturing Operations - Activities concerning the facility operation, system processes, materials input/output, maintenance, supply and distribution, health, and safety, emergency response, human resources, security, information technology and other contributing measures to the manufacturing enterprise.

Network Access - any access across a network connection in lieu of local access (i.e., user being physically present at the device).

Non-local Connection - A connection to the manufacturing system affording the user access to system resources and system functionality while physically not present.

Overlay - A fully specified set of security controls, control enhancements, and supplemental guidance derived from tailoring a security baseline to fit the user's specific environment and mission. [800-53]

Operational technology - Hardware and software that detects or causes a change through the direct monitoring and/or control of physical devices, processes and events in the enterprise. [Gartner.com]

Programmable Logic Controller - A solid-state control system that has a user-programmable memory for storing instructions for the purpose of implementing specific functions such as I/O control, logic, timing, counting, three mode (PID) control, communication, arithmetic, and data and file processing. [800-82]

Port - The entry or exit point from a computer for connecting communications or peripheral devices. [800-82]

Profile - A representation of the outcomes that a particular system or organization has selected from the Framework Categories and Subcategories. [CSF]

- Target Profile - the desired outcome or 'to be' state of cybersecurity implementation
- Current Profile – the 'as is' state of system cybersecurity

Protocol - A set of rules (i.e., formats and procedures) to implement and control some type of association (e.g., communication) between systems. [800-82]

Remote Access - Access by users (or information systems) communicating external to an information system security perimeter. Network access is any access across a network connection in lieu of local access (i.e., user being physically present at the device). [800-53]

Resilience Requirements - The business-driven availability and reliability characteristics for the manufacturing system that specify recovery tolerances from disruptions and major incidents.

Risk Assessment - The process of identifying risks to agency operations (including mission, functions, image, or reputation), agency assets, or individuals by determining the probability of occurrence, the resulting impact, and additional security controls that would mitigate this impact.

Part of risk management, synonymous with risk analysis. Incorporates threat and vulnerability analyses. [800-82]

Risk Tolerance - The level of risk that the Manufacturer is willing to accept in pursuit of strategic goals and objectives. [800-53]

Router - A computer that is a gateway between two networks at OSI layer 3 and that relays and directs data packets through that inter-network. The most common form of router operates on IP packets. [800-82]

Security Control - The management, operational, and technical controls (i.e., safeguards or countermeasures) prescribed for a system to protect the confidentiality, integrity, and availability of the system, its components, processes, and data. [800-82]

Subcategory - The subdivision of a Category into specific outcomes of technical and/or management activities. Examples of Subcategories include “External information systems are catalogued,” “Data-at-rest is protected,” and “Notifications from detection systems are investigated.” [CSF]

Supporting Services - Providers of external system services to the manufacturer through a variety of consumer-producer relationships including but not limited to: joint ventures; business partnerships; outsourcing arrangements (i.e., through contracts, interagency agreements, lines of business arrangements); licensing agreements; and/or supply chain exchanges. Supporting services include, for example, Telecommunications, engineering services, power, water, software, tech support, and security. [800-53]

Switch - A device that channels incoming data from any of multiple input ports to the specific output port that will take the data toward its intended destination. [Whatis.com]

System Categorization - The characterization of a manufacturing system, its components, and operations, based on an assessment of the potential impact that a loss of availability, integrity, or confidentiality would have on organizational operations, organizational assets, or individuals. [FIPS 199]

Third-Party Relationships - relationships with external entities. External entities may include, for example, service providers, vendors, supply-side partners, demand-side partners, alliances, consortiums, and investors, and may include both contractual and non-contractual parties. [DHS]

Third-party Providers - Service providers, integrators, vendors, telecommunications, and infrastructure support that are external to the organization that operates the manufacturing system.

Thresholds - Values used to establish concrete decision points and operational control limits to trigger management action and response escalation.

Appendix C - References

1. Executive Order 13636, *Improving Critical Infrastructure Cybersecurity*, February 12, 2013, <https://www.federalregister.gov/d/2013-03915> [accessed 9/5/17].
2. National Institute of Standards and Technology, *Framework for Improving Critical Infrastructure Cybersecurity, version 1.0*, February 12, 2014, <https://www.nist.gov/document-3766>.
3. National Institute of Standards and Technology, Special Publication (SP) 800-82 Revision 2, *Guide to Industrial Control Systems (ICS) Security*, National Institute of Standards and Technology, Gaithersburg, Maryland, May 2015, 247pp. <https://doi.org/10.6028/NIST.SP.800-82r2>.
4. National Institute of Standards and Technology, Special Publication (SP) 800-53 Revision 4, *Security and Privacy Controls for Federal Information Systems and Organizations*, National Institute of Standards and Technology, Gaithersburg, Maryland, April 2013 (including updates as of January 22, 2015), 462pp. <https://doi.org/10.6028/NIST.SP.800-53r4>.
5. ISA/IEC 62443 Series of Standards on Industrial Automation and Control Systems (IACS) Security. <http://isa99.isa.org/ISA99%20Wiki/Home.aspx> [accessed 9/5/17].
6. National Cybersecurity & Communications Integration Center (NCCIC) - <https://www.dhs.gov/national-cybersecurity-and-communications-integration-center> [accessed 9/5/17].
7. Industrial Control Systems Cyber Emergency Response Team (ICS-CERT) - <https://ics-cert.us-cert.gov/> [accessed 9/5/17].